

# MC74VHC157

## Quad 2-Channel Multiplexer

The MC74VHC157 is an advanced high-speed CMOS quad 2-channel multiplexer, fabricated with silicon gate CMOS technology. It achieves high-speed operation similar to equivalent Bipolar-Schottky TTL, while maintaining CMOS low-power dissipation.

It consists of four 2-input digital multiplexers with common select (S) and enable ( $\bar{E}$ ) inputs. When  $\bar{E}$  is held High, selection of data is inhibited and all the outputs go Low.

The select decoding determines whether the A or B inputs get routed to the corresponding Y outputs.

The internal circuit is composed of three stages, including a buffer output which provides high noise immunity and stable output. The inputs tolerate voltages up to 7 V, allowing the interface of 5 V systems to 3 V systems.

- High Speed:  $t_{PD} = 4.1 \text{ ns}$  (Typ) at  $V_{CC} = 5 \text{ V}$
- Low Power Dissipation:  $I_{CC} = 4 \mu\text{A}$  (Max) at  $T_A = 25^\circ\text{C}$
- High Noise Immunity:  $V_{NIH} = V_{NIL} = 28\% V_{CC}$
- Power Down Protection Provided on Inputs
- Balanced Propagation Delays
- Designed for 2 V to 5.5 V Operating Range
- Low Noise:  $V_{OLP} = 0.8 \text{ V}$  (Max)
- Pin and Function Compatible with Other Standard Logic Families
- Latchup Performance Exceeds 300 mA
- ESD Performance: HBM > 2000 V; Machine Model > 200 V
- Chip Complexity: 82 FETs
- These Devices are Pb-Free and are RoHS Compliant





Figure 1. Pin Assignment



**ON Semiconductor**

<http://onsemi.com>


### MARKING DIAGRAMS



**SOIC-16  
D SUFFIX  
CASE 751B**



**TSSOP-16  
DT SUFFIX  
CASE 948F**



VHC157 = Specific Device Code  
A = Assembly Location  
WL, L = Wafer Lot  
Y = Year  
WW, W = Work Week  
G or ■ = Pb-Free Package

### ORDERING INFORMATION

| Device          | Package  | Shipping        |
|-----------------|----------|-----------------|
| MC74VHC157DR2G  | SOIC-16  | 2500 Units/Reel |
| MC74VHC157DTR2G | TSSOP-16 | 2500 Units/Reel |

## MC74VHC157




Figure 2. Expanded Logic Diagram




Figure 3. IEC Logic Symbol

### FUNCTION TABLE

| Inputs |   | Outputs |
|--------|---|---------|
| E      | S | Y0 – Y3 |
| H      | X | L       |
| L      | L | A0 – A3 |
| L      | H | B0 – B3 |

A0 – A3, B0 – B3 = the levels of the respective Data-Word Inputs.

# MC74VHC157

## MAXIMUM RATINGS (Note 1)

| Symbol                | Parameter                                                                                                     | Value                          | Unit |
|-----------------------|---------------------------------------------------------------------------------------------------------------|--------------------------------|------|
| V <sub>CC</sub>       | DC Supply Voltage                                                                                             | − 0.5 to +7.0                  | V    |
| V <sub>I</sub>        | DC Input Voltage                                                                                              | − 0.5 to V <sub>CC</sub> + 7.0 | V    |
| V <sub>O</sub>        | DC Output Voltage                                                                                             | − 0.5 to V <sub>CC</sub> + 7.0 | V    |
| I <sub>IK</sub>       | DC Input Diode Current<br>V <sub>I</sub> < GND                                                                | − 20                           | mA   |
| I <sub>OK</sub>       | DC Output Diode Current<br>V <sub>O</sub> < GND                                                               | ± 20                           | mA   |
| I <sub>O</sub>        | DC Output Sink Current                                                                                        | ± 25                           | mA   |
| I <sub>CC</sub>       | DC Supply Current per Supply Pin                                                                              | ± 100                          | mA   |
| T <sub>STG</sub>      | Storage Temperature Range                                                                                     | − 65 to + 150                  | °C   |
| T <sub>L</sub>        | Lead Temperature, 1 mm from Case for 10 Seconds                                                               | 260                            | °C   |
| T <sub>J</sub>        | Junction Temperature under Bias                                                                               | + 150                          | °C   |
| θ <sub>JA</sub>       | Thermal Resistance                                                                                            | 250                            | °C/W |
| P <sub>D</sub>        | Power Dissipation in Still Air at 85°C                                                                        | 250                            | mW   |
| MSL                   | Moisture Sensitivity                                                                                          | Level 1                        |      |
| F <sub>R</sub>        | Flammability Rating<br>Oxygen Index: 30% – 35%                                                                | UL–94–VO (0.125 in)            |      |
| V <sub>ESD</sub>      | ESD Withstand Voltage<br>Human Body Model (Note 2)<br>Machine Model (Note 3)<br>Charged Device Model (Note 4) | >2000<br>>200<br>N/A           | V    |
| I <sub>Latch-Up</sub> | Latch-Up Performance<br>Above V <sub>CC</sub> and Below GND at 85°C (Note 5)                                  | ± 500                          | mA   |

1. Absolute maximum continuous ratings are those values beyond which damage to the device may occur. Extended exposure to these conditions or conditions beyond those indicated may adversely affect device reliability. Functional operation under absolute maximum-rated conditions is not implied.
2. Tested to EIA/JESD22–A114–A.
3. Tested to EIA/JESD22–A115–A.
4. Tested to JESD22–C101–A.
5. Tested to EIA/JESD78.

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Characteristics                                                                               | Min    | Max             | Unit |
|---------------------------------|-----------------------------------------------------------------------------------------------|--------|-----------------|------|
| V <sub>CC</sub>                 | DC Supply Voltage                                                                             | 2.0    | 5.5             | V    |
| V <sub>IN</sub>                 | DC Input Voltage<br>(Note 6)                                                                  | 0      | 5.5             | V    |
| V <sub>OUT</sub>                | DC Output Voltage                                                                             | 0      | V <sub>CC</sub> | V    |
| T <sub>A</sub>                  | Operating Temperature Range, all Package Types                                                | − 55   | 125             | °C   |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise or Fall Time<br>V <sub>CC</sub> = 3.3 V ± 0.3 V<br>V <sub>CC</sub> = 5.0 V ± 0.5 V | 0<br>0 | 100<br>20       | ns/V |

6. Unused inputs may not be left open. All inputs must be tied to a high-logic voltage level or a low-logic input voltage level.

## DEVICE JUNCTION TEMPERATURE VERSUS TIME TO 0.1% BOND FAILURES

| Junction Temperature °C | Time, Hours | Time, Years |
|-------------------------|-------------|-------------|
| 80                      | 1,032,200   | 117.8       |
| 90                      | 419,300     | 47.9        |
| 100                     | 178,700     | 20.4        |
| 110                     | 79,600      | 9.4         |
| 120                     | 37,000      | 4.2         |
| 130                     | 17,800      | 2.0         |
| 140                     | 8,900       | 1.0         |




Figure 4. Failure Rate vs. Time Junction Temperature

# MC74VHC157

## DC CHARACTERISTICS (Voltages Referenced to GND)

| Symbol          | Parameter                 | Condition                                                                                                  | V <sub>CC</sub><br>(V) | T <sub>A</sub> = 25°C      |                   |                            | T <sub>A</sub> ≤ 85°C      |                            | -55°C ≤ T <sub>A</sub> ≤ 125°C |                            | Unit |
|-----------------|---------------------------|------------------------------------------------------------------------------------------------------------|------------------------|----------------------------|-------------------|----------------------------|----------------------------|----------------------------|--------------------------------|----------------------------|------|
|                 |                           |                                                                                                            |                        | Min                        | Typ               | Max                        | Min                        | Max                        | Min                            | Max                        |      |
| V <sub>IH</sub> | High-Level Input Voltage  |                                                                                                            | 2.0<br>3.0 to 5.5      | 1.5<br>0.7 V <sub>CC</sub> |                   |                            | 1.5<br>0.7 V <sub>CC</sub> |                            | 1.5<br>0.7 V <sub>CC</sub>     |                            | V    |
| V <sub>IL</sub> | Low-Level Input Voltage   |                                                                                                            | 2.0<br>3.0 to 5.5      |                            |                   | 0.5<br>0.3 V <sub>CC</sub> |                            | 0.5<br>0.3 V <sub>CC</sub> |                                | 0.5<br>0.3 V <sub>CC</sub> | V    |
| V <sub>OH</sub> | High-Level Output Voltage | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> = -50 μA                           | 2.0<br>3.0<br>4.5      | 1.9<br>2.9<br>4.4          | 2.0<br>3.0<br>4.5 |                            | 1.9<br>2.9<br>4.4          |                            | 1.9<br>2.9<br>4.4              |                            | V    |
|                 |                           | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> = -4 mA<br>I <sub>OH</sub> = -8 mA | 3.0<br>4.5             | 2.58<br>3.94               |                   |                            | 2.48<br>3.8                |                            | 2.34<br>3.66                   |                            |      |
| V <sub>OL</sub> | Low-Level Output Voltage  | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OL</sub> = 50 μA                            | 2.0<br>3.0<br>4.5      |                            | 0.0<br>0.0<br>0.0 | 0.1<br>0.1<br>0.1          |                            | 0.1<br>0.1<br>0.1          |                                | 0.1<br>0.1<br>0.1          | V    |
|                 |                           | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> = 4 mA<br>I <sub>OH</sub> = 8 mA   | 3.0<br>4.5             |                            |                   | 0.36<br>0.36               |                            | 0.44<br>0.44               |                                | 0.52<br>0.52               |      |
| I <sub>IN</sub> | Input Leakage Current     | V <sub>IN</sub> = 5.5 V or GND                                                                             | 0 to 5.5               |                            |                   | ± 0.1                      |                            | ± 1.0                      |                                | ± 1.0                      | μA   |
| I <sub>CC</sub> | Quiescent Supply Current  | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                   | 5.5                    |                            |                   | 4.0                        |                            | 40.0                       |                                | 40.0                       | μA   |

## AC ELECTRICAL CHARACTERISTICS (Input t<sub>r</sub> = t<sub>f</sub> = 3.0 ns)

| Symbol                                 | Characteristic                    | Test Conditions                                                                   | T <sub>A</sub> = 25°C |             |              | T <sub>A</sub> ≤ 85°C |              | -55°C ≤ T <sub>A</sub> ≤ 125°C |              | Unit |
|----------------------------------------|-----------------------------------|-----------------------------------------------------------------------------------|-----------------------|-------------|--------------|-----------------------|--------------|--------------------------------|--------------|------|
|                                        |                                   |                                                                                   | Min                   | Typ         | Max          | Typ                   | Max          | Typ                            | Max          |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Propagation Delay,<br>A to B to Y | V <sub>CC</sub> = 3.3 ± 0.3 V    C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF |                       | 6.2<br>8.7  | 9.7<br>13.2  | 1.0<br>1.0            | 11.5<br>15.0 | 1.0<br>1.0                     | 11.5<br>15.0 | ns   |
|                                        |                                   | V <sub>CC</sub> = 5.0 ± 0.5 V    C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF |                       | 4.1<br>5.6  | 6.4<br>8.4   | 1.0<br>1.0            | 7.5<br>9.5   | 1.0<br>1.0                     | 7.5<br>9.5   |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Propagation Delay,<br>S to Y      | V <sub>CC</sub> = 3.3 ± 0.3 V    C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF |                       | 8.4<br>10.9 | 13.2<br>16.7 | 1.0<br>1.0            | 15.5<br>19.0 | 1.0<br>1.0                     | 15.5<br>19.0 | ns   |
|                                        |                                   | V <sub>CC</sub> = 5.0 ± 0.5 V    C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF |                       | 5.3<br>6.8  | 8.1<br>10.1  | 1.0<br>1.0            | 9.5<br>11.5  | 1.0<br>1.0                     | 9.5<br>11.5  |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Propagation Delay,<br>E to Y      | V <sub>CC</sub> = 3.3 ± 0.3 V    C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF |                       | 8.7<br>11.2 | 13.6<br>17.1 | 1.0<br>1.0            | 16.0<br>19.5 | 1.0<br>1.0                     | 16.0<br>19.5 | ns   |
|                                        |                                   | V <sub>CC</sub> = 5.0 ± 0.5 V    C <sub>L</sub> = 15 pF<br>C <sub>L</sub> = 50 pF |                       | 5.6<br>7.1  | 8.6<br>10.6  | 1.0<br>1.0            | 10.0<br>12.0 | 1.0<br>1.0                     | 10.0<br>12.0 |      |
| C <sub>IN</sub>                        | Input Capacitance                 |                                                                                   |                       | 4           | 10           |                       | 10           |                                | 10           | pF   |

|                 |                                        |                                         |    |
|-----------------|----------------------------------------|-----------------------------------------|----|
| C <sub>PD</sub> | Power Dissipation Capacitance (Note 7) | Typical @ 25°C, V <sub>CC</sub> = 5.0 V | pF |
|                 |                                        | 20                                      |    |

7. C<sub>PD</sub> is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: I<sub>CC(OPR)</sub> = C<sub>PD</sub> • V<sub>CC</sub> • f<sub>in</sub> + I<sub>CC</sub>. C<sub>PD</sub> is used to determine the no-load dynamic power consumption: P<sub>D</sub> = C<sub>PD</sub> • V<sub>CC</sub><sup>2</sup> • f<sub>in</sub> + I<sub>CC</sub> • V<sub>CC</sub>.

MC74VHC157

NOISE CHARACTERISTICS (Input  $t_r = t_f = 3.0\text{ ns}$ ;  $C_L = 50\text{ pF}$ ;  $V_{CC} = 5.0\text{ V}$ )

| Symbol    | Characteristic                           | $T_A = 25^\circ\text{C}$ |      | Unit |
|-----------|------------------------------------------|--------------------------|------|------|
|           |                                          | Typ                      | Max  |      |
| $V_{OLP}$ | Quiet Output Maximum Dynamic $V_{OL}$    | 0.3                      | 0.8  | V    |
| $V_{OLV}$ | Quiet Output Minimum Dynamic $V_{OL}$    | -0.3                     | -0.8 | V    |
| $V_{IHD}$ | Minimum High Level Dynamic Input Voltage |                          | 3.5  | V    |
| $V_{ILD}$ | Maximum Low Level Dynamic Input Voltage  |                          | 1.5  | V    |




Figure 5. Switching Waveform





Figure 6. Inverting Switching



\*Includes all probe and jig capacitance.

Figure 7. Test Circuit





Figure 8. Input Equivalent Circuit


# MC74VHC157

## PACKAGE DIMENSIONS

SOIC-16  
CASE 751B-05  
ISSUE K




## SOLDERING FOOTPRINT



# MC74VHC157

## PACKAGE DIMENSIONS

### TSSOP-16 CASE 948F-01 ISSUE B




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.18        | 0.28 | 0.007     | 0.011 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |

### SOLDERING FOOTPRINT



ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А