

# Type MLS 125 °C Stainless Flatpack, Ultra-Long Life, Aluminum

## Type MLS 125 °C



The Type MLS extends the super performance of the MLP from a maximum operating temperature of 85 °C to 125 °C. While the MLP is inherently capable of operation at 125 °C, its flat aluminum case can't withstand the higher temperature without inflating from internal pressure. The MLS incorporates a rugged, stainless steel case which assures flatness to beyond 125 °C. The MLS is perfect for hi-rel military systems and applications operating above 85 °C.

### Highlights

- Near-hermetic welded seal
- Stainless-steel case
- 100 years expected operating life
- New 2 inch case size

### Specifications

**Operating Temperature:**

-55 °C to +125 °C

**Rated Voltage:**

5.0 to 250 Vdc

**Capacitance:**

220 to 47,000 µF ±20%

**Load Life:**

2,000 h @ +125 °C

**Leakage Current:**

0.002 CV µA @ 25 °C and 5 min

**Cold Impedance:**

-55 °C multiple of 25 °C Z is ≤ 10 for up to 20 V, 2 for 25 V to 250 V

**Ripple Current Multipliers:**

**Case Temperature**

| 45 °C | 55 °C | 65 °C | 75 °C | 85 °C | 95 °C | 105 °C | 115 °C | 125 °C |
|-------|-------|-------|-------|-------|-------|--------|--------|--------|
| 1.41  | 1.32  | 1.22  | 1.12  | 1.00  | 0.87  | 0.71   | 0.50   | 0.00   |

**Ambient Temperature, No Heatsink**

| 45 °C | 55 °C | 65 °C | 75 °C | 85 °C | 95 °C | 105 °C | 115 °C | 125 °C |
|-------|-------|-------|-------|-------|-------|--------|--------|--------|
| 0.63  | 0.58  | 0.54  | 0.49  | 0.44  | 0.38  | 0.31   | 0.22   | 0.00   |

**Frequency**

|             | 50 Hz | 60 Hz | 120 Hz | 360 Hz | 1 kHz | 5 kHz | 10 kHz & up |
|-------------|-------|-------|--------|--------|-------|-------|-------------|
| 5 to 40 V   | 0.95  | 0.96  | 1.00   | 1.03   | 1.04  | 1.04  | 1.04        |
| 60 to 250 V | 0.80  | 0.84  | 1.00   | 1.18   | 1.25  | 1.30  | 1.30        |

**EIA Ripple Life:**

10,000 h full load at 85 C per EIA IS-749

Δ capacitance ±10%

ESR 200% of limit

DCL 100% of limit

**Shelf Life:**  
**Thermal Resistance:**

500 h at 125 °C, capacitance, ESR & DCL, initial requirements

| Large Sides Heatsinked | Case Length | 1.5" | 2.0" | 3.0" |
|------------------------|-------------|------|------|------|
|                        | Insulation  | °C/W | °C/W | °C/W |
| one                    | None        | 3.3  | 2.6  | 1.3  |
|                        | Polyester   | 4.5  | 3.6  | 1.8  |
| both                   | None        | 2.8  | 2.2  | 1.1  |
|                        | Polyester   | 4    | 3.2  | 1.6  |

**Vibration:**

10 Hz to 2 kHz 0.06" pp max and 10 g, MIL-STD-202, Meth. 204

**ESL:**

< 30 nH measured 1/4" from case at 1 MHz

**Weight:**

Case EK 43 g typical

Case EA 76 g typical

Case EB 92 g typical

**Terminals:**

18 AWG copper wire with 60/40 tin-lead electroplate



#### RoHS-5 Compliant

Has more than 1000 ppm lead in some homogenous material but otherwise complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).

# Type MLS 125 °C Stainless Flatpack, Ultra-Long Life, Aluminum

## Specifications

**Ripple Current Capability** is set by the maximum permissible internal core temperature, 125 °C.

**Air Cooled.** The ripple currents in the ratings tables are for 85 °C case temperatures. For air temperatures without a heatsink use the Ambient Temperature, No Heatsink multipliers.

**Heatsink Cooled.** Temperature rise from the internal hottest spot, the core, to ambient air is:

$$\Delta T = I^2(ESR)(\Theta_{cc} + \Theta_{ca})$$

where  $\Theta_{cc}$  is the thermal resistance from core to case and  $\Theta_{ca}$  from case to ambient. To calculate maximum ripple capability with the MLP attached to a heatsink use the maximum core temperature and the values for  $\Theta_{cc}$ .

As an illustration, suppose you operate an MLS332M060EB1C in 65 °C air and attach it to a commercial heatsink with a free-air thermal resistance of 2.7 °C/W. Use a good thermal grease between the MLS and the heatsink, and the total thermal resistance is 2.7 + 1.8 or 4.5 °C/W. The power which would heat the core to 125 °C is (125-65)/4.5 or 13.3 W. For an ESR of 31 mΩ, 13.3 W equates to a ripple current of 20.7A, however, the wire leads are rated for only 20 A.

## Outline Drawings

Style A: Mounting Tabs



| Case Code | Length L (in) | Weight (g) |
|-----------|---------------|------------|
| EK        | 1.5           | 43         |
| EA        | 2.0           | 76         |
| EB        | 3.0           | 92         |

Style C: Two Leads, No Tabs



Style D: Hook Leads



Note: The mounting tabs are at case potential and the negative lead connects to the case through the electrolyte.

## Part Numbering System

|            |                             |           |               |   |                               |   |
|------------|-----------------------------|-----------|---------------|---|-------------------------------|---|
| <b>MLS</b> | <b>821</b>                  | <b>M</b>  | <b>200</b>    | <b>EB</b>                                       | <b>0</b>                      | <b>A</b>  |
| Type       | Capacitance                 | Tolerance | Rated Voltage | Case Code                                       | Insulation                    | Mounting Style  |
| MLS        | 821=820 μF<br>102 = 1000 μF | M=±20%    | Vdc           | EK, L=1.5 in.<br>EA, L=2.0 in.<br>EB, L=3.0 in. | 0 = bare can<br>1 = polyester | A = mounting tabs<br>C = two leads/no tabs<br>D = hook leads/tabs |

# Type MLS 125 °C Stainless Flatpack, Ultra-Long Life, Aluminum



## MLS102M150EB0D Life Test at 125 °C, 150 V



# Type MLS 125 °C Stainless Flatpack, Ultra-Long Life, Aluminum

## Typical Performance Curves



### Ratings

| Cap (µF)  | Catalog Part Number | ESR max 25 °C (mΩ) |        | Ripple (A) Case @ 85°C |        | Length (inches) |
|---|---------------------|--------------------|--------|------------------------|--------|-----------------|
|   |                     | 120 Hz             | 20 kHz | 120 Hz                 | 20 kHz |                 |
| <b>5 Vdc (7.5 Vdc Surge) [105 °C: 7.5 Vdc (10 Vdc Surge)]</b> |                     |                    |        |                        |        |                 |
| 19,000  | MLS193M5R0EK0C      | 76                 | 66     | 12.6                   | 13.6   | 1.5             |
| 28,000  | MLS283M5R0EA0C      | 50                 | 44     | 19.9                   | 21.4   | 2.0             |
| 47,000  | MLS473M5R0EB0C      | 30                 | 26     | 32.0                   | 34.4   | 3.0             |
| <b>7.5 Vdc (10 Vdc Surge) [105 °C: 10 Vdc (13 Vdc Surge)]</b> |                     |                    |        |                        |        |                 |
| 17,000  | MLS173M7R5EK0C      | 77                 | 67     | 12.5                   | 13.5   | 1.5             |
| 26,000  | MLS263M7R5EA0C      | 51                 | 45     | 19.8                   | 21.1   | 2.0             |
| 43,000  | MLS433M7R5EB0C      | 31                 | 27     | 31.5                   | 33.8   | 3.0             |
| <b>10 Vdc (15 Vdc Surge) [105 °C: 16 Vdc (20 Vdc Surge)]</b>  |                     |                    |        |                        |        |                 |
| 13,000  | MLS133M010EK0C      | 81                 | 69     | 12.2                   | 13.3   | 1.5             |
| 23,000  | MLS233M010EA0C      | 51                 | 45     | 19.8                   | 21.1   | 2.0             |
| 38,000  | MLS383M010EB0C      | 31                 | 27     | 31.5                   | 33.8   | 3.0             |
| <b>20 Vdc (30 Vdc Surge) [105 °C: 30 Vdc (40 Vdc Surge)]</b>  |                     |                    |        |                        |        |                 |
| 6,800   | MLS682M020EK0C      | 84                 | 69     | 11.0                   | 12.2   | 1.5             |
| 10,000  | MLS103M020EA0C      | 56                 | 46     | 13.6                   | 15.0   | 2.0             |
| 17,000  | MLS173M020EB0C      | 33                 | 27     | 17.6                   | 19.5   | 3.0             |
| <b>40 Vdc (50 Vdc Surge) [105 °C: 50 Vdc (63 Vdc Surge)]</b>  |                     |                    |        |                        |        |                 |
| 4,400   | MLS442M040EK0C      | 97                 | 70     | 10.3                   | 12.1   | 1.5             |
| 6,600   | MLS662M040EA0C      | 62                 | 46     | 12.9                   | 15.0   | 2.0             |
| 11,000  | MLS113M040EB0C      | 36                 | 27     | 16.9                   | 19.5   | 3.0             |
| <b>60 Vdc (75 Vdc Surge) [105 °C: 80 Vdc (100 Vdc Surge)]</b> |                     |                    |        |                        |        |                 |
| 1,500   | MLS152M060EK0C      | 106                | 77     | 9.8                    | 11.5   | 1.5             |

| Cap (µF)   | Catalog Part Number | ESR max 25 °C (mΩ) |        | Ripple (A) Case @ 85°C |        | Length (inches) |
|--|---------------------|--------------------|--------|------------------------|--------|-----------------|
|  |                     | 120 Hz             | 20 kHz | 120 Hz                 | 20 kHz |                 |
| 2,100  | MLS212M060EA0C      | 72                 | 52     | 11.9                   | 14.1   | 2.0             |
| 3,300  | MLS332M060EB0C      | 44                 | 31     | 15.3                   | 18.2   | 3.0             |
| <b>75 Vdc (100 Vdc Surge) [105 °C: 100 Vdc (125 Vdc Surge)]</b>  |                     |                    |        |                        |        |                 |
| 1,100  | MLS112M075EK0C      | 112                | 78     | 9.6                    | 11.5   | 1.5             |
| 1,600  | MLS162M075EA0C      | 76                 | 54     | 11.6                   | 13.8   | 2.0             |
| 2,700  | MLS272M075EB0C      | 46                 | 33     | 14.9                   | 17.6   | 3.0             |
| <b>100 Vdc (125 Vdc Surge) [105 °C: 150 Vdc (180 Vdc Surge)]</b> |                     |                    |        |                        |        |                 |
| 500  | MLS501M100EK0C      | 355                | 248    | 5.4                    | 6.4    | 1.5             |
| 770  | MLS771M100EA0C      | 238                | 166    | 6.6                    | 7.8    | 2.0             |
| 1,300  | MLS132M100EB0C      | 143                | 100    | 8.5                    | 10.1   | 3.0             |
| <b>150 Vdc (175 Vdc Surge) [105 °C: 200 Vdc (250 Vdc Surge)]</b> |                     |                    |        |                        |        |                 |
| 400  | MLS401M150EK0C      | 388                | 253    | 5.1                    | 6.4    | 1.5             |
| 600  | MLS601M150EA0C      | 261                | 168    | 6.3                    | 7.8    | 2.0             |
| 1,000  | MLS102M150EB0C      | 158                | 100    | 8.1                    | 10.1   | 3.0             |
| <b>200 Vdc (225 Vdc Surge) [105 °C: 250 Vdc (300 Vdc Surge)]</b> |                     |                    |        |                        |        |                 |
| 330  | MLS331M200EK0C      | 426                | 258    | 4.9                    | 6.2    | 1.5             |
| 490  | MLS491M200EA0C      | 285                | 172    | 6.0                    | 7.7    | 2.0             |
| 820  | MLS821M200EB0C      | 172                | 103    | 7.7                    | 10.0   | 3.0             |
| <b>250 Vdc (275 Vdc Surge) [105 °C: 250 Vdc (300 Vdc Surge)]</b> |                     |                    |        |                        |        |                 |
| 220  | MLS221M250EK0C      | 597                | 393    | 4.1                    | 5.1    | 1.5             |
| 330  | MLS331M250EA0C      | 399                | 262    | 5.0                    | 6.3    | 2.0             |
| 560  | MLS561M250EB0C      | 240                | 157    | 6.5                    | 8.1    | 3.0             |



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А