

## High Pulse Load Carbon Film Leaded Resistors



CBB 0207 leaded resistors with advanced pulse load capability, are the perfect choice for circuitries exposed to high levels of electromagnetic interference or electrostatic discharge. The resistors can also be used to protect the circuitry of signal and mains input lines from surge pulses. Applications are in all fields of automotive, telecommunication and industrial equipment.

| METRIC SIZE |      |
|-------------|------|
| DIN         | 0207 |
| CECC        | B    |

### FEATURES

- Speciality product for EMC sensitive applications
- Special carbon film technology for maximum heat stress capability
- Up to 6 kV or 140 W pulse load capability
- Resistance range: 10 Ω to 1.5 MΩ
- Lead (Pb)-free solder contacts
- Pure tin plating provides compatibility with lead (Pb)-free and lead containing soldering processes
- Compliant to RoHS directive 2002/95/EC




### APPLICATIONS

- Automotive
- Telecommunication
- Industrial equipment

| TECHNICAL SPECIFICATIONS   |  |             |
|--|--|-------------|
| DESCRIPTION  | CBB 0207                               |             |
| CECC Size  | B                                      |             |
| Resistance Range   | 10 Ω to 1.5 MΩ                         |             |
| Resistance Tolerance   | ± 2 %                                  |             |
| Temperature Coefficient  | Refer to Temperature Coefficient graph |             |
| Operation Mode   | Long term                              | Standard    |
| Climatic Category (LCT/UCT/Days)   | 55/125/56                              | 55/155/56   |
| Rated Dissipation, $P_{70}$  | 0.4 W                                  | 0.6 W       |
| Operating Voltage, $U_{max}$ . AC/DC   | 350 V                                  |             |
| Film Temperature   | 125 °C                                 | 155 °C      |
| Max. Resistance Change at $P_{70}$ for Resistance Range, $\Delta R/R$ max., after: | 10 Ω to 100 kΩ                         |             |
|  | ± 1 %                                  | ± 2 %       |
|  | + 3 %/- 1 %                            | + 5 %/- 2 % |
| Permissible Voltage Against Ambient:   | 500 V                                  |             |
|  | 75 V                                   |             |
| Failure Rate: FIT <sub>observed</sub>  | ≤ 0.1 x 10 <sup>-9</sup> /h            |             |

#### Note


- These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.

**DIMENSIONS**

**DIMENSIONS** - Leaded resistor types, mass and relevant physical dimensions

| TYPE     | D <sub>max.</sub> (mm) | L <sub>max.</sub> (mm) | d <sub>nom.</sub> (mm) | l <sub>min.</sub> (mm) | M <sub>min.</sub> (mm) | MASS (mg) |
|----------|------------------------|------------------------|------------------------|------------------------|------------------------|-----------|
| CBB 0207 | 2.5                    | 6.3                    | 0.6                    | 28.0                   | 10.0                   | 220       |

**PART NUMBER AND PRODUCT DESCRIPTION**

PART NUMBER: CBB0207001501GC1



| MODEL/SIZE | VARIANT     | TCR                           | VALUE  | TOLERANCE | PACKAGING <sup>(1)</sup> | SPECIAL                         |
|------------|-------------|-------------------------------|--|-----------|--------------------------|---------------------------------|
| CBB0207    | 0 = Neutral | 0 = Standard<br>See TCR graph | <b>3 digit value</b><br><b>1 digit multiplier</b><br><b>MULTIPLIER</b><br>7 = *10 <sup>-3</sup> 2 = *10 <sup>2</sup><br>8 = *10 <sup>-2</sup> 3 = *10 <sup>3</sup><br>9 = *10 <sup>-1</sup> 4 = *10 <sup>4</sup><br>0 = *10 <sup>0</sup> 5 = *10 <sup>5</sup><br>1 = *10 <sup>1</sup> 6 = *10 <sup>6</sup> | G = ± 2 % | CT<br>C1                 | Up to 2 digits<br>00 = Standard |

PRODUCT DESCRIPTION: CBB 0207 2 % C1 1K5

|            |             |            |                          |                              |
|------------|-------------|------------|--------------------------|------------------------------|
| <b>CBB</b> | <b>0207</b> | <b>2 %</b> | <b>C1</b>                | <b>1K5</b>                   |
| MODEL      | SIZE        | TOLERANCE  | PACKAGING <sup>(1)</sup> | RESISTANCE VALUE             |
| CBB        | 0207        | ± 2 %      | CT<br>C1                 | 47K = 47 kΩ<br>51R1 = 51.1 Ω |

**Notes**
<sup>(1)</sup>Please refer to table PACKAGING

- The PART NUMBER is shown to facilitate the introduction of the unified part numbering system for ordering products

**PACKAGING**

| MODEL    | BOX          |          |
|----------|--------------|----------|
|          | PIECES/BOX   | CODE     |
| CBB 0207 | 1000<br>5000 | C1<br>CT |

**TOLERANCE AND RESISTANCE RANGE**

| TOLERANCE | RESISTANCE VALUE <sup>(1)</sup> |
|-----------|---------------------------------|
|           | CBB 0207                        |
| ± 2 %     | 10 Ω to 1.5 MΩ                  |

**Note**
<sup>(1)</sup>Resistance values to be selected from E24 series

## DESCRIPTION

Production is strictly controlled and follows an extensive set of instructions established for reproducibility. A homogeneous and dense carbon film is deposited on a high grade ceramic body (85 %  $Al_2O_3$ ) and conditioned to achieve the desired temperature coefficient. Nickel plated steel termination caps are firmly pressed on the rods. A special laser is used to achieve the target value by smoothly cutting a helical groove in the resistive layer without damaging the ceramics. Connecting wires of electrolytic copper plated with 100 % pure tin are welded to the termination caps. The resistors are covered by protective coating designed for electrical, mechanical and climatic protection. Five color code rings designate the resistance value and tolerance in accordance with **IEC 60062**.

The result of the determined production is verified by an extensive testing procedure performed on 100 % of the individual resistors. Only accepted products are stuck directly on the adhesive tapes in accordance with **IEC 60286-1**.

## ASSEMBLY

The resistors are suitable for processing on automatic insertion equipment and cutting and bending machines. Excellent solderability is proven, even after extended storage. They are suitable for automatic soldering using wave or dipping. The encapsulation is resistant to all cleaning solvents commonly used in the electronics industry, including alcohols, esters and aqueous solutions. The suitability of conformal coatings, if applied, shall be qualified

### Notes

(1) Global Automotive Declarable Substance List, see [www.gadsl.org](http://www.gadsl.org)

(2) CEFIC (European Chemical Industry Council), EECA (European Electronic Component Manufacturers Association), EICTA (European trade organisation representing the information and communications technology and consumer electronics), see [www.eicta.org/index.php?id=1053&id\\_article=340](http://www.eicta.org/index.php?id=1053&id_article=340)

by appropriate means to ensure the long-term stability of the whole system. The resistors are completely lead (Pb)-free, the pure tin plating provides compatibility with lead (Pb)-free and lead-containing soldering processes. The immunity of the plating against tin whisker growth has been proven under extensive testing. All products comply with **GADSL** <sup>(1)</sup> and the **CEFIC-EECA-EICTA** <sup>(2)</sup> list of legal restrictions on hazardous substances. This includes full compliance with the following directives:


- 2000/53/EC End of Vehicle Life Directive (ELV) and Annex II (ELVII)
- 2002/95/EC Restriction of the use of Hazardous Substances Directive (RoHS)
- 2002/96/EC Waste Electrical and Electrical Equipment Directive (WEEE)

## APPROVALS




Where applicable, the resistors are tested in accordance with **EN 140101-806 (successor of CECC 40101-806)** which refers to **EN 60115-1** and **EN 140100**.

Vishay Beyschlag has achieved “**Approval of Manufacturer**” in accordance with **IEC QC 001002-3, clause 2**. The release certificate for “**Technology Approval Schedule**” in accordance with **CECC 240001** based on **IEC QC 001002-3, clause 6** is granted for the Vishay Beyschlag manufacturing process.

## FUNCTIONAL DESCRIPTION




Derating - Standard Operation


**Derating - Long Term Operating**

**Temperature Rise**



Maximum pulse load, single pulse; for permissible resistance change equivalent to 8000 h operation.

**Single Pulse**




Maximum pulse load, continuous pulses; for permissible resistance change equivalent to 8000 h operation.

**Continuous Pulse**




Maximum pulse voltage, single and continuous pulses; for permissible resistance change equivalent to 8000 h operation.

**Pulse Voltage**





Pulse load rating in accordance with IEC 60115-1, 4.27; 1.2  $\mu$ s/50  $\mu$ s; 5 pulses at 12 s intervals; for permissible resistance change 0.5 %.

**1.2/50 Pulse**



Pulse load rating in accordance with IEC 60115-1, 4.27; 10  $\mu$ s/ 700  $\mu$ s; 10 pulses at 1 minute intervals; for permissible resistance change 0.5 %.

**10/700 Pulse**

**Temperature Coefficient (TCR)**

**Current Noise -  $A_1$  in accordance with IEC 60195**

**TESTS AND REQUIREMENTS**

Essentially all tests are carried out in accordance with the following specifications:

EN 60115-1, generic specification (includes tests)

EN 140100, sectional specification (includes schedule for qualification approval)

EN 140101-806 (successor of CECC 40101-806), detail specification (includes schedule for conformance inspection)

The following table contains the applicable tests selected from the documents listed above.

The tests are carried out in accordance with IEC 60068-2-xx test method and under standard atmospheric conditions in accordance with IEC 60068-1, 5.3. climatic category LCT/UCT/56 (rated temperature range: Lower category

temperature, upper category temperature; damp heat, long term, 56 days) is valid.

Unless otherwise specified the following values apply:

Temperature: 15 °C to 35 °C

Relative humidity: 45 % to 75 %

Air pressure: 86 kPa to 106 kPa (860 mbar to 1060 mbar).

In the Test Procedures and Requirements table only the tests and requirements are listed with reference to the relevant clauses of IEC 60115-1 and IEC 60068-2-xx test methods. A short description of the test procedure is also given.

| TEST PROCEDURES AND REQUIREMENTS |                            |  |   |  |
|----------------------------------|----------------------------|--|---|--|
| IEC 60115-1 CLAUSE               | IEC 60068-2-xx TEST METHOD | TEST   | PROCEDURE   | REQUIREMENTS PERMISSIBLE CHANGE ( $\Delta R$ )               |
|                                  |                            |  | Stability for product types:<br><b>CBB 0207</b>   | 10 $\Omega$ to 1.5 M $\Omega$                                |
| 4.5                              | -                          | Resistance                                   |   | $\pm 2 \%$   |
| 4.8                              | -                          | Temperature coefficient                      | At (20/LCT/20) °C and (20/UCT/20) °C  | -  |
| 4.25.1                           | -                          | Endurance at 70 °C: standard operation mode  | $U = \sqrt{P_{70} \times R}$ or $U = U_{max.}$ ;<br>1.5 h ON; 0.5 h OFF<br>70 °C; 1000 h<br>70 °C; 8000 h | $\pm (2 \% R + 0.05 \Omega)$<br>$\pm (4 \% R + 0.05 \Omega)$ |
| 4.25.1                           | -                          | Endurance at 70 °C: long term operation mode | $U = \sqrt{P_{70} \times R}$ or $U = U_{max.}$ ;<br>1.5 h ON; 0.5 h OFF<br>70 °C; 1000 h<br>70 °C; 8000 h | $\pm (1 \% R + 0.05 \Omega)$<br>$\pm (2 \% R + 0.05 \Omega)$ |
| 4.25.3                           | -                          | Endurance at upper category temperature      | 125 °C; 1000 h<br>155 °C; 1000 h  | $\pm (2 \% R + 0.05 \Omega)$<br>$\pm (4 \% R + 0.1 \Omega)$  |
| 4.24                             | 78 (Cab)                   | Damp heat, steady state                      | (40 $\pm$ 2) °C; 56 days;<br>(93 $\pm$ 3) % RH  | $\pm (1 \% R + 0.1 \Omega)$                                  |
| 4.23                             |                            | Climatic sequence:                           |   |  |
| 4.23.2                           | 2 (Ba)                     | Dry heat                                     | 155 °C; 16 h  |  |
| 4.23.3                           | 30 (Db)                    | Damp heat, cyclic                            | 55 °C; 24 h;<br>90 % to 100 % RH;<br>1 cycle  |  |
| 4.23.4                           | 1 (Aa)                     | Cold   | - 55 °C; 2 h  |  |
| 4.23.5                           | 13 (M)                     | Low air pressure                             | 8.5 kPa; 2 h; 15 °C to 35 °C  |  |
| 4.23.6                           | 30 (Db)                    | Damp heat, cyclic                            | 55 °C; 5 days;<br>95 % to 100 % RH;<br>5 cycles   | $\pm (1 \% R + 0.1 \Omega)$<br>no visible damage             |
| -                                | 1 (Aa)                     | Cold   | - 55 °C; 2 h  | $\pm (0.5 \% R + 0.1 \Omega)$                                |
| 4.13                             | -                          | Short time overload                          | Room temperature;<br>$U = 2.5 \times \sqrt{P_{70} \times R}$ or<br>$U = 2 \times U_{max.}$ ; 5 s          | $\pm (0.5 \% R + 0.1 \Omega)$<br>no visible damage           |

| TEST PROCEDURES AND REQUIREMENTS |   |  |  |   |
|----------------------------------|---|--|--|---|
| IEC 60115-1 CLAUSE               | IEC 60068-2-xx TEST METHOD                  | TEST                                       | PROCEDURE  | REQUIREMENTS PERMISSIBLE CHANGE ( $\Delta R$ )            |
|                                  |   |  | Stability for product types:<br><b>CBB 0207</b>                      | 10 $\Omega$ to 1.5 M $\Omega$                             |
| 4.19                             | 14 (Na)                                     | Rapid change of temperature                | 30 min at LCT = - 55 °C and<br>30 min at UCT = 155 °C;<br>200 cycles | $\pm (0.5 \% R + 0.05 \Omega)$<br>no visible damage       |
| 4.29                             | 45 (XA)                                     | Component solvent resistance               | Isopropyl alcohol + 23 °C;<br>toothbrush method                      | marking legible;<br>no visible damage                     |
| 4.18.2                           | 20 (Tb)                                     | Resistance to soldering heat               | Unmounted components;<br>(260 $\pm$ 3) °C; (10 $\pm$ 1) s            | $\pm (0.5 \% R + 0.05 \Omega)$<br>no visible damage       |
| 4.17                             | 20 (Ta)                                     | Solderability                              | + 235 °C; 2 s<br>solder bath method<br>SnPb40                        | Good tinning ( $\geq$ 95 % covered,<br>no visible damage) |
|                                  |   |  | + 245 °C; 3 s<br>solder bath method<br>SnAg3Cu0.5                    |   |
| 4.22                             | 6 (B4)                                      | Vibration                                  | 6 h;<br>10 Hz to 2000 Hz<br>1.5 mm or 196 m/s <sup>2</sup>           | $\pm (0.5 \% R + 0.05 \Omega)$                            |
| 4.16                             | 21 (Ua <sub>1</sub> )<br>21 (Ub)<br>21 (Uc) | Robustness of terminations                 | Tensile, bending and torsion   | $\pm (0.5 \% R + 0.05 \Omega)$                            |
| 4.7                              | -   | Voltage proof                              | $U_{RMS} = U_{ins}$ ; 60 s   | No flashover or breakdown                                 |
| 4.40                             | -   | Electrostatic discharge (human body model) | IEC 61340-3-1;<br>3 pos. + 3 neg.<br>16 kV                           | $\pm (0.5 \% R + 0.05 \Omega)$                            |

### HISTORICAL 12NC INFORMATION

- The resistors had a 12-digit numeric code starting with 2312.
- The subsequent 4 digits indicated the resistor type, specification and packaging; see the 12NC table.
- The remaining 4 digits indicated the resistance value:
  - The first 3 digits indicated the resistance value.
  - The last digit indicated the resistance decade in accordance with the Resistance Decade table.

### Resistance Decade

| RESISTANCE DECADE                | LAST DIGIT |
|----------------------------------|------------|
| 10 $\Omega$ to 99.9 $\Omega$     | 9          |
| 100 $\Omega$ to 999 $\Omega$     | 1          |
| 1 k $\Omega$ to 9.99 k $\Omega$  | 2          |
| 10 k $\Omega$ to 99.9 k $\Omega$ | 3          |
| 100 k $\Omega$ to 999 k $\Omega$ | 4          |
| 1 M $\Omega$ to 9.99 M $\Omega$  | 5          |

### 12NC Example

The 12NC of a CBB 0207 resistor, value 47 k $\Omega$  with  $\pm 2\%$  tolerance, supplied on bandolier in a box of 5000 units was: 2312 955 24703.

| HISTORICAL 12NC - Resistor type and packaging |           |                  |               |
|---|-----------|------------------|---------------|
| DESCRIPTION                                   |           | 2312 ... ..      |               |
|   |           | BANDOLIER IN BOX |               |
| TYPE  | TOL.      | C1 1000 units    | CT 5000 units |
| CBB 0207                                      | $\pm 2\%$ | 950 2....        | 955 2....     |





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А