

Type 460M

Metallized Polyester Film Capacitors

Type 460M Axial Lead Round Profile Metallized Polyester Film Capacitors



Specifications

Capacitance Range:

0.022 to 100.0 μ F

Capacitance Tolerance:

+5% and +10%, standard
(other tolerances available)

Voltage Ratings:

63 to 400 VDC
40 to 200 VAC

Operating Temperature:

Units may be operated at full-rated
voltage from -55°C to +85°C.

Voltage De-rating above +85 °C:

Units may be operated up to a
maximum of 125°C provided the
voltage is de-rated linearly to 50%
of rated voltage of +125°C.

Dissipation Factor:

1.0% maximum @ 1 KHz, +25°C

Insulation Resistance:

At +25°C: 10,000 M Ω for $C \leq 1.0 \mu$ F
10,000 M Ω - μ F for $C > 1.0 \mu$ F
At +85°C: 1,000 M Ω for $C \leq 1.0 \mu$ F
1,000 M Ω - μ F for $C > 1.0 \mu$ F

Encapsulation:

Wrapped with flame retardant polyester
tape (meets UL510 specifications) and
potted with flame retardant epoxy (meets
UL94V-0 specifications).

Lead Wire:

Tinned copper-clad steel for wire sizes:
0.020 (0.5) diameter (#24 AWG)
0.025 (0.6) diameter (#22 AWG)
0.032 (0.8) diameter (#20 AWG)

Tinned copper for wire sizes:
0.040 (1.0) diameter (#18 AWG)

Dielectric/Construction:

Metallized polyester film, single section
design. Non-inductively wound.

In addition to the information provided here, CDE also offers complete design and manufacturing
of specific capacitance values, custom form factors, special lead terminations, etc.

Dimensions are in inches, millimeters are in parenthesis.

Type 460M

Metallized Polyester Film Capacitors

General Specifications

The 460M series is designed and manufactured for use in many demanding applications. They are non-inductively wound using some of the most reliable metallized polyester film available today. A wide range of capacitance values, voltage ratings, lead terminations and sizes offer the designer an array of options to best meet the form, fit and function requirements specified.

Operating Temperature Range:

Standard operating temperature range is -55°C to $+85^{\circ}\text{C}$. Units may be operated at the full rated voltage within this temperature range.

The 460M series may be operated up to a maximum temperature of $+125^{\circ}\text{C}$, however the voltage must be linearly de-rated to 50% of the full rated voltage at $+125^{\circ}\text{C}$.

Dielectric Withstanding Voltage:

Units shall withstand a DC potential of 150% of rated voltage applied between terminals for not more than 2 minutes.

Lead Bend Test:

After 3 consecutive 180° bends. No damage.

Lead Pull Test:

5 pounds (2.3 Kg) for one minute on lead axis. No damage.

Humidity Testing:

Units subjected to 95% relative humidity for 250 hours with no voltage applied at $+40^{\circ}\text{C}$. After 4 hours of drying, minimum product of insulation resistance and capacitance shall be $5,000\text{ M}\Omega\text{-}\mu\text{F}$, but need not exceed $5,000\text{ M}\Omega$.

DC Voltage Life Test:

500 hours at $+85^{\circ}\text{C}$ at 125% of rated voltage. After test; capacitance shall not have changed by more than $\pm 10\%$ of initial value, insulation resistance shall not have decreased by more than 50% of initial value and dissipation factor shall not have increased to more than 1.25%. In addition, there shall be no open or short circuits, and no sign of visible damage.


Dielectric Material/Construction:

The 460M series is manufactured using metallized polyester film as the dielectric. The capacitor element is non-inductively wound in a single section design.

Metallized polyester film utilizes a base film of polyester with a thin layer of aluminum vacuum deposited directly on the film as the electrode.


Metallized film exhibits a characteristic called “self-healing” or “self-clearing”, which is the ability to remove a fault or short circuit in the dielectric film by vaporizing (from high current density) the metallization near the defect. The metallization is so thin that negligible film damage occurs during the clearing process. The vaporized metal oxidizes over time, aiding in the isolation of a fault area.

Typical Temperature Characteristics:



Metallized Polyester Film Capacitors

460M 106 9 2 C - XXX



Sample Marking on unit

CDE460M[C]
106K 250V
0824

Description

CDE	-	CDE Identification
460M	-	Type Number. 460MC indicates compact design.
250V	-	DC Voltage Rating
106K	-	Capacitance and Tolerance Code
0824	-	Weekly Date Code (i.e. 24th week of 2008)


Tolerance codes per EIA standards

J	$\pm 5\%$
K	$\pm 10\%$

Type 460M

Metallized Polyester Film Capacitors

Dimension Outline



Lead Length Table

L MAX dimension	Lead Length (Typical)
0.61 (15.5)	2.00 (50.8)
0.79 (20.1)	1.90 (48.3)
0.99 (25.1)	1.80 (45.7)
1.25 (31.8)	1.65 (41.9)
1.50 (38.1)	1.50 (38.1)
1.74 (44.2)	1.40 (35.6)
2.21 (56.1)	1.25 (31.8)

In all cases a MINIMUM lead length of 1.25 (31.8) will be met.

Lead Wire Size and Additional Termination Options

Standard lead wire sizes used in manufacturing range from 0.020 (0.5) diameter (#24 AWG) to 0.040 (1.0) diameter (#18 AWG). We can also provide a variety of other wire sizes and material (i.e. heavier gauges, insulated wire, tinned copper in smaller gauges, etc.). If the wire size or material listed on our standard items doesn't meet your requirements please contact us. We can accommodate your needs. We can also provide lug/tab terminations upon request. Please contact us with your specific requirements.

Type 460M

Metallized Polyester Film Capacitors

Type 460M Sizes and Ratings – 63 VDC/40 VAC

Cap μ F	Base Part #	Standard Dimensions			Compact Dimensions ¹		
		L MAX	DIA MAX	Wire (d)	L MAX	DIA MAX	Wire (d)
0.22	460M2249R6	0.61 (15.5)	0.21 (5.3)	0.020 (0.5)			
0.27	460M2749R6	0.61 (15.5)	0.23 (5.8)	0.020 (0.5)			
0.33	460M3349R6	0.61 (15.5)	0.24 (6.1)	0.020 (0.5)			
0.39	460M3949R6	0.61 (15.5)	0.26 (6.6)	0.025 (0.6)			
0.47	460M4749R6	0.79 (20.1)	0.23 (5.8)	0.020 (0.5)	0.61 (15.5)	0.28 (7.1)	0.025 (0.6)
0.5	460M5049R6	0.79 (20.1)	0.23 (5.8)	0.020 (0.5)	0.61 (15.5)	0.29 (7.4)	0.025 (0.6)
0.56	460M5649R6	0.79 (20.1)	0.24 (6.1)	0.020 (0.5)	0.61 (15.5)	0.30 (7.6)	0.025 (0.6)
0.6	460M6049R6	0.79 (20.1)	0.25 (6.4)	0.020 (0.5)	0.61 (15.5)	0.31 (7.9)	0.025 (0.6)
0.68	460M6849R6	0.79 (20.1)	0.26 (6.6)	0.025 (0.6)	0.61 (15.5)	0.33 (8.4)	0.025 (0.6)
0.75	460M7549R6	0.79 (20.1)	0.27 (6.9)	0.025 (0.6)	0.61 (15.5)	0.34 (8.6)	0.025 (0.6)
0.82	460M8249R6	0.99 (25.1)	0.24 (6.1)	0.020 (0.5)	0.79 (20.1)	0.29 (7.4)	0.025 (0.6)
0.9	460M9049R6	0.99 (25.1)	0.25 (6.4)	0.020 (0.5)	0.79 (20.1)	0.30 (7.6)	0.025 (0.6)
1.0	460M1059R6	0.99 (25.1)	0.26 (6.6)	0.025 (0.6)	0.79 (20.1)	0.31 (7.9)	0.025 (0.6)
1.2	460M1259R6	0.99 (25.1)	0.28 (7.1)	0.025 (0.6)	0.79 (20.1)	0.33 (8.4)	0.025 (0.6)
1.5	460M1559R6	0.99 (25.1)	0.31 (7.9)	0.025 (0.6)	0.79 (20.1)	0.37 (9.4)	0.025 (0.6)
1.8	460M1859R6	0.99 (25.1)	0.34 (8.6)	0.025 (0.6)	0.79 (20.1)	0.40 (10.2)	0.032 (0.8)
2.0	460M2059R6	0.99 (25.1)	0.36 (9.1)	0.025 (0.6)	0.79 (20.1)	0.42 (10.7)	0.032 (0.8)
2.2	460M2259R6	0.99 (25.1)	0.37 (9.4)	0.025 (0.6)	0.79 (20.1)	0.44 (11.2)	0.032 (0.8)
2.5	460M2559R6	0.99 (25.1)	0.39 (9.9)	0.032 (0.8)	0.79 (20.1)	0.47 (11.9)	0.032 (0.8)
2.7	460M2759R6	0.99 (25.1)	0.41 (10.4)	0.032 (0.8)	0.79 (20.1)	0.48 (12.2)	0.032 (0.8)
3.0	460M3059R6	1.25 (31.8)	0.37 (9.4)	0.025 (0.6)	0.99 (25.1)	0.43 (10.9)	0.032 (0.8)
3.3	460M3359R6	1.25 (31.8)	0.39 (9.9)	0.032 (0.8)	0.99 (25.1)	0.45 (11.4)	0.032 (0.8)
3.6	460M3659R6	1.25 (31.8)	0.41 (10.4)	0.032 (0.8)	0.99 (25.1)	0.47 (11.9)	0.032 (0.8)
3.9	460M3959R6	1.25 (31.8)	0.42 (10.7)	0.032 (0.8)	0.99 (25.1)	0.48 (12.2)	0.032 (0.8)
4.0	460M4059R6	1.50 (38.1)	0.39 (9.9)	0.032 (0.8)	0.99 (25.1)	0.49 (12.4)	0.032 (0.8)
4.7	460M4759R6	1.50 (38.1)	0.42 (10.7)	0.032 (0.8)	0.99 (25.1)	0.53 (13.5)	0.032 (0.8)
5.0	460M5059R6	1.50 (38.1)	0.43 (10.9)	0.032 (0.8)	0.99 (25.1)	0.54 (13.7)	0.032 (0.8)
5.6	460M5659R6	1.50 (38.1)	0.45 (11.4)	0.032 (0.8)	0.99 (25.1)	0.57 (14.5)	0.032 (0.8)
6.0	460M6059R6	1.50 (38.1)	0.47 (11.9)	0.032 (0.8)	0.99 (25.1)	0.59 (15.0)	0.032 (0.8)
6.8	460M6859R6	1.50 (38.1)	0.49 (12.4)	0.032 (0.8)	0.99 (25.1)	0.63 (16.0)	0.032 (0.8)
7.0	460M7059R6	1.50 (38.1)	0.50 (12.7)	0.032 (0.8)	0.99 (25.1)	0.64 (16.3)	0.032 (0.8)
7.5	460M7559R6	1.50 (38.1)	0.52 (13.2)	0.032 (0.8)	0.99 (25.1)	0.66 (16.8)	0.032 (0.8)
8.0	460M8059R6	1.50 (38.1)	0.53 (13.5)	0.032 (0.8)	1.25 (31.8)	0.59 (15.0)	0.032 (0.8)
9.0	460M9059R6	1.50 (38.1)	0.56 (14.2)	0.032 (0.8)	1.25 (31.8)	0.62 (15.7)	0.032 (0.8)
10.0	460M1069R6	1.50 (38.1)	0.59 (15.0)	0.032 (0.8)	1.25 (31.8)	0.66 (16.8)	0.032 (0.8)
12.0	460M1269R6	1.50 (38.1)	0.64 (16.3)	0.032 (0.8)	1.25 (31.8)	0.72 (18.3)	0.032 (0.8)
15.0	460M1569R6	1.50 (38.1)	0.71 (18.0)	0.032 (0.8)	1.25 (31.8)	0.80 (20.3)	0.040 (1.0)
20.0	460M2069R6	1.50 (38.1)	0.82 (20.8)	0.040 (1.0)			
25.0	460M2569R6	1.50 (38.1)	0.91 (23.1)	0.040 (1.0)			
30.0	460M3069R6	1.50 (38.1)	0.99 (25.1)	0.040 (1.0)			
35.0	460M3569R6	1.50 (38.1)	1.07 (27.2)	0.040 (1.0)			
40.0	460M4069R6	1.50 (38.1)	1.14 (29.0)	0.040 (1.0)			
45.0	460M4569R6	1.50 (38.1)	1.21 (30.7)	0.040 (1.0)			
50.0	460M5069R6	1.50 (38.1)	1.27 (32.3)	0.040 (1.0)			
55.0	460M5569R6	1.50 (38.1)	1.34 (34.0)	0.040 (1.0)			
60.0	460M6069R6	1.50 (38.1)	1.39 (35.3)	0.040 (1.0)			
65.0	460M6569R6	1.50 (38.1)	1.45 (36.8)	0.040 (1.0)			
70.0	460M7069R6	1.50 (38.1)	1.50 (38.1)	0.040 (1.0)			
75.0	460M7569R6	1.50 (38.1)	1.55 (39.4)	0.040 (1.0)			
80.0	460M8069R6	1.50 (38.1)	1.60 (40.6)	0.040 (1.0)			
85.0	460M8569R6	1.50 (38.1)	1.65 (41.9)	0.040 (1.0)			

¹ Please refer to Ordering/Part Number page for specific part numbering details.

Type 460M

Metallized Polyester Film Capacitors

Type 460M Sizes and Ratings - 100 VDC/63 VAC

Cap μ F	Base Part #	Standard Dimensions			Compact Dimensions ¹		
		L MAX	DIA MAX	Wire (d)	L MAX	DIA MAX	Wire (d)
0.15	460M15491	0.61 (15.5)	0.20 (5.1)	0.020 (0.5)			
0.18	460M18491	0.61 (15.5)	0.21 (5.3)	0.020 (0.5)			
0.22	460M22491	0.61 (15.5)	0.23 (5.8)	0.020 (0.5)			
0.27	460M27491	0.79 (20.1)	0.20 (5.1)	0.020 (0.5)	0.61 (15.5)	0.25 (6.4)	0.020 (0.5)
0.33	460M33491	0.79 (20.1)	0.22 (5.6)	0.020 (0.5)	0.61 (15.5)	0.27 (6.9)	0.025 (0.6)
0.39	460M39491	0.79 (20.1)	0.23 (5.8)	0.020 (0.5)	0.61 (15.5)	0.29 (7.4)	0.025 (0.6)
0.47	460M47491	0.99 (25.1)	0.22 (5.6)	0.020 (0.5)	0.61 (15.5)	0.31 (7.9)	0.025 (0.6)
0.5	460M50491	0.99 (25.1)	0.22 (5.6)	0.020 (0.5)	0.61 (15.5)	0.32 (8.1)	0.025 (0.6)
0.56	460M56491	0.99 (25.1)	0.23 (5.8)	0.020 (0.5)	0.61 (15.5)	0.34 (8.6)	0.025 (0.6)
0.6	460M60491	0.99 (25.1)	0.24 (6.1)	0.020 (0.5)	0.79 (20.1)	0.28 (7.1)	0.025 (0.6)
0.68	460M68491	0.99 (25.1)	0.25 (6.4)	0.020 (0.5)	0.79 (20.1)	0.29 (7.4)	0.025 (0.6)
0.75	460M75491	0.99 (25.1)	0.26 (6.6)	0.025 (0.6)	0.79 (20.1)	0.31 (7.9)	0.025 (0.6)
0.82	460M82491	0.99 (25.1)	0.27 (6.9)	0.025 (0.6)	0.79 (20.1)	0.32 (8.1)	0.025 (0.6)
0.9	460M90491	0.99 (25.1)	0.28 (7.1)	0.025 (0.6)	0.79 (20.1)	0.33 (8.4)	0.025 (0.6)
1.0	460M10591	1.25 (31.8)	0.26 (6.6)	0.025 (0.6)	0.79 (20.1)	0.35 (8.9)	0.025 (0.6)
1.2	460M12591	1.25 (31.8)	0.28 (7.1)	0.025 (0.6)	0.79 (20.1)	0.38 (9.7)	0.025 (0.6)
1.5	460M15591	1.25 (31.8)	0.31 (7.9)	0.025 (0.6)	0.79 (20.1)	0.42 (10.7)	0.032 (0.8)
1.8	460M18591	1.25 (31.8)	0.33 (8.4)	0.025 (0.6)	0.79 (20.1)	0.45 (11.4)	0.032 (0.8)
2.0	460M20591	1.25 (31.8)	0.35 (8.9)	0.025 (0.6)	0.79 (20.1)	0.47 (11.9)	0.032 (0.8)
2.2	460M22591	1.25 (31.8)	0.36 (9.1)	0.025 (0.6)	0.99 (25.1)	0.42 (10.7)	0.032 (0.8)
2.5	460M25591	1.25 (31.8)	0.39 (9.9)	0.032 (0.8)	0.99 (25.1)	0.44 (11.2)	0.032 (0.8)
2.7	460M27591	1.25 (31.8)	0.40 (10.2)	0.032 (0.8)	0.99 (25.1)	0.46 (11.7)	0.032 (0.8)
3.0	460M30591	1.25 (31.8)	0.42 (10.7)	0.032 (0.8)	0.99 (25.1)	0.48 (12.2)	0.032 (0.8)
3.3	460M33591	1.25 (31.8)	0.44 (11.2)	0.032 (0.8)	0.99 (25.1)	0.50 (12.7)	0.032 (0.8)
3.6	460M36591	1.25 (31.8)	0.46 (11.7)	0.032 (0.8)	0.99 (25.1)	0.52 (13.2)	0.032 (0.8)
3.9	460M39591	1.25 (31.8)	0.47 (11.9)	0.032 (0.8)	0.99 (25.1)	0.54 (13.7)	0.032 (0.8)
4.0	460M40591	1.50 (38.1)	0.44 (11.2)	0.032 (0.8)	0.99 (25.1)	0.55 (14.0)	0.032 (0.8)
4.7	460M47591	1.50 (38.1)	0.47 (11.9)	0.032 (0.8)	0.99 (25.1)	0.59 (15.0)	0.032 (0.8)
5.0	460M50591	1.50 (38.1)	0.48 (12.2)	0.032 (0.8)	0.99 (25.1)	0.61 (15.5)	0.032 (0.8)
5.6	460M56591	1.50 (38.1)	0.51 (13.0)	0.032 (0.8)	0.99 (25.1)	0.65 (16.5)	0.032 (0.8)
6.0	460M60591	1.50 (38.1)	0.52 (13.2)	0.032 (0.8)	1.25 (31.8)	0.58 (14.7)	0.032 (0.8)
6.8	460M68591	1.50 (38.1)	0.55 (14.0)	0.032 (0.8)	1.25 (31.8)	0.62 (15.7)	0.032 (0.8)
7.0	460M70591	1.50 (38.1)	0.56 (14.2)	0.032 (0.8)	1.25 (31.8)	0.62 (15.7)	0.032 (0.8)
7.5	460M75591	1.50 (38.1)	0.58 (14.7)	0.032 (0.8)	1.25 (31.8)	0.64 (16.3)	0.032 (0.8)
8.0	460M80591	1.50 (38.1)	0.60 (15.2)	0.032 (0.8)	1.25 (31.8)	0.66 (16.8)	0.032 (0.8)
9.0	460M90591	1.50 (38.1)	0.63 (16.0)	0.032 (0.8)	1.25 (31.8)	0.70 (17.8)	0.032 (0.8)
10.0	460M10691	1.74 (44.2)	0.60 (15.2)	0.032 (0.8)	1.50 (38.1)	0.66 (16.8)	0.032 (0.8)
12.0	460M12691	1.74 (44.2)	0.66 (16.8)	0.032 (0.8)	1.50 (38.1)	0.72 (18.3)	0.032 (0.8)
15.0	460M15691	1.74 (44.2)	0.73 (18.5)	0.032 (0.8)	1.50 (38.1)	0.80 (20.3)	0.040 (1.0)
20.0	460M20691	2.21 (56.1)	0.72 (18.3)	0.032 (0.8)	1.74 (44.2)	0.84 (21.3)	0.040 (1.0)
25.0	460M25691	2.21 (56.1)	0.81 (20.6)	0.040 (1.0)	1.74 (44.2)	0.93 (23.6)	0.040 (1.0)
30.0	460M30691	2.21 (56.1)	0.88 (22.4)	0.040 (1.0)	1.74 (44.2)	1.02 (25.9)	0.040 (1.0)
35.0	460M35691	2.21 (56.1)	0.95 (24.1)	0.040 (1.0)	1.74 (44.2)	1.10 (27.9)	0.040 (1.0)
40.0	460M40691	2.21 (56.1)	1.01 (25.7)	0.040 (1.0)	1.74 (44.2)	1.17 (29.7)	0.040 (1.0)
45.0	460M45691	2.21 (56.1)	1.07 (27.2)	0.040 (1.0)	1.74 (44.2)	1.24 (31.5)	0.040 (1.0)
50.0	460M50691	2.21 (56.1)	1.13 (28.7)	0.040 (1.0)			
55.0	460M55691	2.21 (56.1)	1.18 (30.0)	0.040 (1.0)			
60.0	460M60691	2.21 (56.1)	1.23 (31.2)	0.040 (1.0)			
65.0	460M65691	2.21 (56.1)	1.28 (32.5)	0.040 (1.0)			
70.0	460M70691	2.21 (56.1)	1.33 (33.8)	0.040 (1.0)			
75.0	460M75691	2.21 (56.1)	1.37 (34.8)	0.040 (1.0)			
80.0	460M80691	2.21 (56.1)	1.42 (36.1)	0.040 (1.0)			
85.0	460M85691	2.21 (56.1)	1.46 (37.1)	0.040 (1.0)			
90.0	460M90691	2.21 (56.1)	1.50 (38.1)	0.040 (1.0)			
95.0	460M95691	2.21 (56.1)	1.54 (39.1)	0.040 (1.0)			
100.0	460M10791	2.21 (56.1)	1.58 (40.1)	0.040 (1.0)			

¹ Please refer to Ordering/Part Number page for specific part numbering details.

Type 460M

Metallized Polyester Film Capacitors

Type 460M Sizes and Ratings - 250 VDC/160 VAC

Cap μ F	Base Part #	Standard Dimensions			Compact Dimensions ¹		
		L MAX	DIA MAX	Wire (d)	L MAX	DIA MAX	Wire (d)
0.068	460M68392	0.61 (15.5)	0.19 (4.8)	0.020 (0.5)			
0.075	460M75392	0.61 (15.5)	0.20 (5.1)	0.020 (0.5)			
0.082	460M82392	0.61 (15.5)	0.20 (5.1)	0.020 (0.5)			
0.1	460M10492	0.61 (15.5)	0.22 (5.6)	0.020 (0.5)			
0.12	460M12492	0.61 (15.5)	0.24 (6.1)	0.020 (0.5)			
0.15	460M15492	0.79 (20.1)	0.21 (5.3)	0.020 (0.5)	0.61 (15.5)	0.26 (6.6)	0.025 (0.6)
0.18	460M18492	0.79 (20.1)	0.22 (5.6)	0.020 (0.5)	0.61 (15.5)	0.28 (7.1)	0.025 (0.6)
0.22	460M22492	0.79 (20.1)	0.24 (6.1)	0.020 (0.5)	0.61 (15.5)	0.30 (7.6)	0.025 (0.6)
0.27	460M27492	0.79 (20.1)	0.26 (6.6)	0.025 (0.6)	0.61 (15.5)	0.33 (8.4)	0.025 (0.6)
0.33	460M33492	0.99 (25.1)	0.25 (6.4)	0.020 (0.5)	0.79 (20.1)	0.29 (7.4)	0.025 (0.6)
0.39	460M39492	0.99 (25.1)	0.26 (6.6)	0.025 (0.6)	0.79 (20.1)	0.31 (7.9)	0.025 (0.6)
0.47	460M47492	0.99 (25.1)	0.28 (7.1)	0.025 (0.6)	0.79 (20.1)	0.33 (8.4)	0.025 (0.6)
0.5	460M50492	0.99 (25.1)	0.29 (7.4)	0.025 (0.6)	0.79 (20.1)	0.34 (8.6)	0.025 (0.6)
0.56	460M56492	0.99 (25.1)	0.31 (7.9)	0.025 (0.6)	0.79 (20.1)	0.36 (9.1)	0.025 (0.6)
0.6	460M60492	0.99 (25.1)	0.32 (8.1)	0.025 (0.6)	0.79 (20.1)	0.37 (9.4)	0.025 (0.6)
0.68	460M68492	0.99 (25.1)	0.33 (8.4)	0.025 (0.6)	0.79 (20.1)	0.39 (9.9)	0.032 (0.8)
0.75	460M75492	0.99 (25.1)	0.35 (8.9)	0.025 (0.6)	0.79 (20.1)	0.41 (10.4)	0.032 (0.8)
0.82	460M82492	0.99 (25.1)	0.36 (9.1)	0.025 (0.6)	0.79 (20.1)	0.43 (10.9)	0.032 (0.8)
0.9	460M90492	0.99 (25.1)	0.38 (9.7)	0.025 (0.6)	0.79 (20.1)	0.45 (11.4)	0.032 (0.8)
1.0	460M10592	1.25 (31.8)	0.35 (8.9)	0.025 (0.6)	0.99 (25.1)	0.40 (10.2)	0.032 (0.8)
1.2	460M12592	1.25 (31.8)	0.38 (9.7)	0.025 (0.6)	0.99 (25.1)	0.43 (10.9)	0.032 (0.8)
1.5	460M15592	1.25 (31.8)	0.42 (10.7)	0.032 (0.8)	0.99 (25.1)	0.48 (12.2)	0.032 (0.8)
1.8	460M18592	1.25 (31.8)	0.45 (11.4)	0.032 (0.8)	0.99 (25.1)	0.52 (13.2)	0.032 (0.8)
2.0	460M20592	1.50 (38.1)	0.43 (10.9)	0.032 (0.8)	0.99 (25.1)	0.55 (14.0)	0.032 (0.8)
2.2	460M22592	1.50 (38.1)	0.45 (11.4)	0.032 (0.8)	0.99 (25.1)	0.57 (14.5)	0.032 (0.8)
2.5	460M25592	1.50 (38.1)	0.48 (12.2)	0.032 (0.8)	0.99 (25.1)	0.61 (15.5)	0.032 (0.8)
2.7	460M27592	1.50 (38.1)	0.50 (12.7)	0.032 (0.8)	0.99 (25.1)	0.63 (16.0)	0.032 (0.8)
3.0	460M30592	1.50 (38.1)	0.52 (13.2)	0.032 (0.8)	1.25 (31.8)	0.58 (14.7)	0.032 (0.8)
3.3	460M33592	1.50 (38.1)	0.54 (13.7)	0.032 (0.8)	1.25 (31.8)	0.60 (15.2)	0.032 (0.8)
3.6	460M36592	1.50 (38.1)	0.57 (14.5)	0.032 (0.8)	1.25 (31.8)	0.63 (16.0)	0.032 (0.8)
3.9	460M39592	1.50 (38.1)	0.59 (15.0)	0.032 (0.8)	1.25 (31.8)	0.65 (16.5)	0.032 (0.8)
4.0	460M40592	1.74 (44.2)	0.54 (13.7)	0.032 (0.8)	1.25 (31.8)	0.66 (16.8)	0.032 (0.8)
4.7	460M47592	1.74 (44.2)	0.58 (14.7)	0.032 (0.8)	1.25 (31.8)	0.71 (18.0)	0.032 (0.8)
5.0	460M50592	1.74 (44.2)	0.60 (15.2)	0.032 (0.8)	1.25 (31.8)	0.74 (18.8)	0.032 (0.8)
5.6	460M56592	1.74 (44.2)	0.63 (16.0)	0.032 (0.8)	1.25 (31.8)	0.78 (19.8)	0.040 (1.0)
6.0	460M60592	1.74 (44.2)	0.65 (16.5)	0.032 (0.8)	1.25 (31.8)	0.81 (20.6)	0.040 (1.0)
6.8	460M68592	1.74 (44.2)	0.69 (17.5)	0.032 (0.8)	1.50 (38.1)	0.76 (19.3)	0.040 (1.0)
7.0	460M70592	1.74 (44.2)	0.70 (17.8)	0.032 (0.8)	1.50 (38.1)	0.77 (19.6)	0.040 (1.0)
7.5	460M75592	1.74 (44.2)	0.73 (18.5)	0.032 (0.8)	1.50 (38.1)	0.80 (20.3)	0.040 (1.0)
8.0	460M80592	1.74 (44.2)	0.75 (19.1)	0.032 (0.8)	1.50 (38.1)	0.82 (20.8)	0.040 (1.0)
9.0	460M90592	1.74 (44.2)	0.79 (20.1)	0.040 (1.0)	1.50 (38.1)	0.87 (22.1)	0.040 (1.0)
10.0	460M10692	1.74 (44.2)	0.83 (21.1)	0.040 (1.0)	1.50 (38.1)	0.92 (23.4)	0.040 (1.0)
12.0	460M12692	2.21 (56.1)	0.79 (20.1)	0.040 (1.0)	1.74 (44.2)	0.91 (23.1)	0.040 (1.0)
15.0	460M15692	2.21 (56.1)	0.87 (22.1)	0.040 (1.0)	1.74 (44.2)	1.01 (25.7)	0.040 (1.0)
20.0	460M20692	2.21 (56.1)	1.00 (25.4)	0.040 (1.0)	1.74 (44.2)	1.17 (29.7)	0.040 (1.0)
25.0	460M25692	2.21 (56.1)	1.12 (28.4)	0.040 (1.0)			
30.0	460M30692	2.21 (56.1)	1.22 (31.0)	0.040 (1.0)			
35.0	460M35692	2.21 (56.1)	1.32 (33.5)	0.040 (1.0)			
40.0	460M40692	2.21 (56.1)	1.41 (35.8)	0.040 (1.0)			
45.0	460M45692	2.21 (56.1)	1.49 (37.8)	0.040 (1.0)			
50.0	460M50692	2.21 (56.1)	1.57 (39.9)	0.040 (1.0)			
55.0	460M55692	2.21 (56.1)	1.65 (41.9)	0.040 (1.0)			

¹ Please refer to Ordering/Part Number page for specific part numbering details.

Type 460M

Metallized Polyester Film Capacitors

Type 460M Sizes and Ratings - 400 VDC/200 VAC

Cap μ F	Base Part #	Standard Dimensions			Compact Dimensions ¹		
		L MAX	DIA MAX	Wire (d)	L MAX	DIA MAX	Wire (d)
0.022	460M22394	0.61 (15.5)	0.19 (4.8)	0.020 (0.5)			
0.027	460M27394	0.61 (15.5)	0.20 (5.1)	0.020 (0.5)			
0.033	460M33394	0.61 (15.5)	0.22 (5.6)	0.020 (0.5)			
0.039	460M39394	0.61 (15.5)	0.23 (5.8)	0.020 (0.5)			
0.047	460M47394	0.61 (15.5)	0.25 (6.4)	0.020 (0.5)			
0.05	460M50394	0.61 (15.5)	0.26 (6.6)	0.025 (0.6)			
0.056	460M56394	0.61 (15.5)	0.27 (6.9)	0.025 (0.6)			
0.062	460M62394	0.79 (20.1)	0.22 (5.6)	0.020 (0.5)	0.61 (15.5)	0.28 (7.1)	0.025 (0.6)
0.068	460M68394	0.79 (20.1)	0.23 (5.8)	0.020 (0.5)	0.61 (15.5)	0.29 (7.4)	0.025 (0.6)
0.075	460M75394	0.79 (20.1)	0.24 (6.1)	0.020 (0.5)	0.61 (15.5)	0.31 (7.9)	0.025 (0.6)
0.082	460M82394	0.79 (20.1)	0.25 (6.4)	0.020 (0.5)	0.61 (15.5)	0.32 (8.1)	0.025 (0.6)
0.1	460M10494	0.79 (20.1)	0.27 (6.9)	0.025 (0.6)	0.61 (15.5)	0.35 (8.9)	0.025 (0.6)
0.12	460M12494	0.99 (25.1)	0.25 (6.4)	0.020 (0.5)	0.79 (20.1)	0.29 (7.4)	0.025 (0.6)
0.15	460M15494	0.99 (25.1)	0.27 (6.9)	0.025 (0.6)	0.79 (20.1)	0.32 (8.1)	0.025 (0.6)
0.18	460M18494	0.99 (25.1)	0.29 (7.4)	0.025 (0.6)	0.79 (20.1)	0.35 (8.9)	0.025 (0.6)
0.22	460M22494	0.99 (25.1)	0.32 (8.1)	0.025 (0.6)	0.79 (20.1)	0.38 (9.7)	0.025 (0.6)
0.27	460M27494	0.99 (25.1)	0.35 (8.9)	0.025 (0.6)	0.79 (20.1)	0.42 (10.7)	0.032 (0.8)
0.33	460M33494	1.25 (31.8)	0.33 (8.4)	0.025 (0.6)	0.99 (25.1)	0.38 (9.7)	0.025 (0.6)
0.39	460M39494	1.25 (31.8)	0.36 (9.1)	0.025 (0.6)	0.99 (25.1)	0.41 (10.4)	0.032 (0.8)
0.47	460M47494	1.50 (38.1)	0.36 (9.1)	0.025 (0.6)	0.99 (25.1)	0.45 (11.4)	0.032 (0.8)
0.5	460M50494	1.50 (38.1)	0.37 (9.4)	0.025 (0.6)	0.99 (25.1)	0.46 (11.7)	0.032 (0.8)
0.56	460M56494	1.50 (38.1)	0.38 (9.7)	0.032 (0.8)	0.99 (25.1)	0.48 (12.2)	0.032 (0.8)
0.6	460M60494	1.50 (38.1)	0.39 (9.9)	0.032 (0.8)	0.99 (25.1)	0.50 (12.7)	0.032 (0.8)
0.68	460M68494	1.74 (44.2)	0.38 (9.7)	0.032 (0.8)	0.99 (25.1)	0.53 (13.5)	0.032 (0.8)
0.75	460M75494	1.74 (44.2)	0.40 (10.2)	0.032 (0.8)	0.99 (25.1)	0.55 (14.0)	0.032 (0.8)
0.82	460M82494	1.74 (44.2)	0.41 (10.4)	0.032 (0.8)	0.99 (25.1)	0.58 (14.7)	0.032 (0.8)
0.9	460M90494	1.74 (44.2)	0.43 (10.9)	0.032 (0.8)	0.99 (25.1)	0.60 (15.2)	0.032 (0.8)
1.0	460M10594	1.74 (44.2)	0.45 (11.4)	0.032 (0.8)	0.99 (25.1)	0.63 (16.0)	0.032 (0.8)
1.2	460M12594	1.74 (44.2)	0.49 (12.4)	0.032 (0.8)	1.25 (31.8)	0.60 (15.2)	0.032 (0.8)
1.5	460M15594	1.74 (44.2)	0.54 (13.7)	0.032 (0.8)	1.25 (31.8)	0.66 (16.8)	0.032 (0.8)
1.8	460M18594	1.74 (44.2)	0.59 (15.0)	0.032 (0.8)	1.25 (31.8)	0.72 (18.3)	0.032 (0.8)
2.0	460M20594	1.74 (44.2)	0.62 (15.7)	0.032 (0.8)	1.25 (31.8)	0.77 (19.6)	0.040 (1.0)
2.2	460M22594	1.74 (44.2)	0.64 (16.3)	0.032 (0.8)	1.25 (31.8)	0.80 (20.3)	0.040 (1.0)
2.5	460M25594	1.74 (44.2)	0.68 (17.3)	0.032 (0.8)	1.50 (38.1)	0.75 (19.1)	0.032 (0.8)
2.7	460M27594	1.74 (44.2)	0.71 (18.0)	0.032 (0.8)	1.50 (38.1)	0.78 (19.8)	0.040 (1.0)
3.0	460M30594	1.74 (44.2)	0.75 (19.1)	0.032 (0.8)	1.50 (38.1)	0.82 (20.8)	0.040 (1.0)
3.3	460M33594	1.74 (44.2)	0.78 (19.8)	0.040 (1.0)	1.50 (38.1)	0.86 (21.8)	0.040 (1.0)
3.6	460M36594	2.21 (56.1)	0.70 (17.8)	0.032 (0.8)	1.50 (38.1)	0.90 (22.9)	0.040 (1.0)
3.9	460M39594	2.21 (56.1)	0.73 (18.5)	0.032 (0.8)	1.50 (38.1)	0.93 (23.6)	0.040 (1.0)
4.0	460M40594	2.21 (56.1)	0.74 (18.8)	0.032 (0.8)	1.50 (38.1)	0.94 (23.9)	0.040 (1.0)
4.7	460M47594	2.21 (56.1)	0.80 (20.3)	0.040 (1.0)	1.50 (38.1)	1.02 (25.9)	0.040 (1.0)
5.0	460M50594	2.21 (56.1)	0.82 (20.8)	0.040 (1.0)	1.74 (44.2)	0.95 (24.1)	0.040 (1.0)
5.6	460M56594	2.21 (56.1)	0.87 (22.1)	0.040 (1.0)	1.74 (44.2)	1.01 (25.7)	0.040 (1.0)
6.0	460M60594	2.21 (56.1)	0.89 (22.6)	0.040 (1.0)	1.74 (44.2)	1.04 (26.4)	0.040 (1.0)
6.8	460M68594	2.21 (56.1)	0.95 (24.1)	0.040 (1.0)	1.74 (44.2)	1.11 (28.2)	0.040 (1.0)
7.0	460M70594	2.21 (56.1)	0.96 (24.4)	0.040 (1.0)	1.74 (44.2)	1.12 (28.4)	0.040 (1.0)
7.5	460M75594	2.21 (56.1)	1.00 (25.4)	0.040 (1.0)	1.74 (44.2)	1.16 (29.5)	0.040 (1.0)
8.0	460M80594	2.21 (56.1)	1.03 (26.2)	0.040 (1.0)	1.74 (44.2)	1.20 (30.5)	0.040 (1.0)
9.0	460M90594	2.21 (56.1)	1.09 (27.7)	0.040 (1.0)			
10.0	460M10694	2.21 (56.1)	1.14 (29.0)	0.040 (1.0)			
12.0	460M12694	2.21 (56.1)	1.25 (31.8)	0.040 (1.0)			
15.0	460M15694	2.21 (56.1)	1.40 (35.6)	0.040 (1.0)			
18.0	460M18694	2.21 (56.1)	1.53 (38.9)	0.040 (1.0)			
20.0	460M20694	2.21 (56.1)	1.61 (40.9)	0.040 (1.0)			

¹ Please refer to Ordering/Part Number page for specific part numbering details.

Type 460M

Metallized Polyester Film Capacitors

Maximum dV/dt Ratings (Volts/μsec)

Refer to the tabulated data below for the maximum allowable pulse rise time (dV/dt) based on voltage rating and length/diameter dimensions. In addition, further detailed notes regarding pulse applications may be found on page 13.

63 VDC

L MAX Dimension

Diameter Range	0.61	0.79	0.99	1.25	1.50	1.74	2.21
< 0.28	7	6	5				
0.28-0.39	15	9	6	5	4		
0.40-0.49		13	8	6	5		
0.50-0.75			9	7	6		
> 0.75				7	6		

100 VDC

L MAX Dimension

Diameter Range	0.61	0.79	0.99	1.25	1.50	1.74	2.21
< 0.28	7	6	5	4			
0.28-0.39	17	11	7	5			
0.40-0.49		13	9	7	6		
0.50-0.75			12	8	6	5	4
> 0.75					6	5	4

250 VDC

L MAX Dimension

Diameter Range	0.61	0.79	0.99	1.25	1.50	1.74	2.21
< 0.28	15	9	8	8			
0.28-0.39	23	14	9	9			
0.40-0.49		19	13	10	8		
0.50-0.75			14	11	8	7	
> 0.75				11	8	7	5

400 VDC

L MAX Dimension

Diameter Range	0.61	0.79	0.99	1.25	1.50	1.74	2.21
< 0.28	28	16	13				
0.28-0.39	43	25	16	14	11	9	
0.40-0.49		34	22	18		10	
0.50-0.75			23	18	14		8
> 0.75				18	14	11	8

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А