

| Parameter              | Rating | Units                |
|------------------------|--------|----------------------|
| Blocking Voltage       | 60     | $V_P$                |
| Load Current           | 75     | $mA_{rms} / mA_{DC}$ |
| On-Resistance (max)    | 10     | $\Omega$             |
| LED Current to operate | 0.5    | mA                   |

## Features

- Designed for EN50130-4 Compliant Security Systems
- 1500V<sub>rms</sub> Input/Output Isolation
- Only 0.5mA of LED Current Required to Operate
- Small 4-Pin SOP Package
- TTL/CMOS Compatible Input
- No Moving Parts
- High Reliability
- Arc-Free With No Snubbing Circuits
- No EMI/RFI Generation
- Immune to Radiated EM Fields
- SMD Pick & Place, Wave Solderable
- Tape & Reel Version Available

## Applications

- Security
  - Passive Infrared Detectors (PIR)
  - Data Signalling
  - Sensor Circuitry
- Instrumentation
  - Multiplexers
  - Data Acquisition
  - Electronic Switching
  - I/O Subsystems
- Meters (Watt-Hour, Water, Gas)
- Medical Equipment—Patient/Equipment Isolation
- Aerospace
- Industrial Controls

## Description

The CPC1006N is a miniature single-pole, normally open (1-Form-A) solid state relay in a 4-pin SOP package that employs optically coupled MOSFET technology to provide 1500V<sub>rms</sub> of input to output isolation.

The relay outputs are constructed with efficient MOSFET switches and photovoltaic die that use IXYS Integrated Circuits Division's patented OptoMOS architecture while the input, a highly efficient GaAlAs infrared LED, provides the optically coupled control.

Using IXYS Integrated Circuits Division's state of the art double-molded vertical construction packaging to produce one of the world's smallest relays, the CPC1006N offers board space savings of at least 20% over the competitor's larger 4-pin SOP relay.


## Approvals

- UL Recognized Component: File E76270
- CSA Certified Component: Certificate 1175739
- EN/IEC 60950-1 Certified Component:  
TUV Certificate B 09 07 49410 004


## Ordering Information

| Part #     | Description           |
|------------|-----------------------|
| CPC1006N   | 4-Pin SOP (100/tube)  |
| CPC1006NTR | 4-Pin SOP (2000/reel) |

## Pin Configuration



## Switching Characteristics of Normally Open Devices



### Absolute Maximum Ratings @ 25°C

| Parameter                            | Ratings     | Units            |
|--------------------------------------|-------------|------------------|
| Blocking Voltage                     | 60          | V <sub>P</sub>   |
| Reverse Input Voltage                | 5           | V                |
| Input Control Current                | 50          | mA               |
| Peak (10ms)                          | 1           | A                |
| Input Power Dissipation              | 70          | mW               |
| Total Power Dissipation <sup>1</sup> | 400         | mW               |
| Isolation Voltage Input to Output    | 1500        | V <sub>rms</sub> |
| ESD Rating, Human Body Model         | 4           | kV               |
| Operational Temperature              | -40 to +85  | °C               |
| Storage Temperature                  | -40 to +125 | °C               |

<sup>1</sup> Derate linearly 3.33 mW / °C

*Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at conditions beyond those indicated in the operational sections of this data sheet is not implied.*













### Electrical Characteristics @ 25°C

| Parameter                                      | Conditions  | Symbol            | Min  | Typ | Max  | Units                                |
|--|---|-------------------|------|-----|------|--------------------------------------|
| <b>Output Characteristics</b>                  |   |                   |      |     |      |                                      |
| Load Current                                   |   |                   |      |     |      |                                      |
| Continuous                                     | I <sub>F</sub> =0.5mA                                 | I <sub>L</sub>    | -    | -   | 75   | mA <sub>rms</sub> / mA <sub>DC</sub> |
| Peak   | t=10ms  | I <sub>LPK</sub>  | -    | -   | ±350 | mA <sub>P</sub>                      |
| On-Resistance <sup>1</sup>                     | I <sub>F</sub> =0.5mA, I <sub>L</sub> =75mA           | R <sub>ON</sub>   | -    | 7   | 10   | Ω                                    |
| Off-State Leakage Current                      | I <sub>F</sub> =0mA, V <sub>L</sub> =60V <sub>P</sub> | I <sub>LEAK</sub> | -    | -   | 1    | μA                                   |
| Switching Speeds                               |   |                   |      |     |      |                                      |
| Turn-On  | I <sub>F</sub> =2mA, V <sub>L</sub> =10V              | t <sub>on</sub>   | -    | -   | 10   | ms                                   |
| Turn-Off                                       |   | t <sub>off</sub>  | -    | -   | 10   | ms                                   |
| Output Capacitance                             | I <sub>F</sub> =0mA, V <sub>L</sub> =50V, f=1MHz      | C <sub>OUT</sub>  | -    | 5   | -    | pF                                   |
| <b>Input Characteristics</b>                   |   |                   |      |     |      |                                      |
| Input Control Current to Activate <sup>2</sup> | I <sub>L</sub> =75mA                                  | I <sub>F</sub>    | -    | 0.1 | 0.5  | mA                                   |
| Input Control Current to Deactivate            | -   | I <sub>F</sub>    | 0.05 | -   | -    | mA                                   |
| Input Voltage Drop                             | I <sub>F</sub> =5mA                                   | V <sub>F</sub>    | 0.9  | 1.2 | 1.4  | V                                    |
| Reverse Input Current                          | V <sub>R</sub> =5V                                    | I <sub>R</sub>    | -    | -   | 10   | μA                                   |
| <b>Common Characteristics</b>                  |   |                   |      |     |      |                                      |
| Capacitance Input to Output                    | -   | C <sub>I/O</sub>  | -    | 1   | -    | pF                                   |

<sup>1</sup> Measurement taken within 1 second of on-time.

<sup>2</sup> For applications requiring high temperature operation (greater than 60°C) a LED drive current of 2mA is recommended.


**PERFORMANCE DATA \***




\*The Performance Data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

**PERFORMANCE DATA \***


**Typical On-Resistance vs. Temperature**  
( $I_F=1\text{mA}$ ,  $I_L=50\text{mA}$ )




**Typical Load Current vs. Load Voltage**  
( $I_F=0.5\text{mA}$ ,  $T_A=25^\circ\text{C}$ )




**Maximum Load Current vs. Temperature**  
( $I_F=1\text{mA}$ )




**Typical Blocking Voltage vs. Temperature**




**Typical Leakage vs. Temperature Measured Across Pins 3&4**  
( $V_L=60\text{V}$ )



**Output Capacitance vs. Load Voltage**  
( $I_F=0\text{mA}$ )



**Energy Rating Curve**  
( $I_F=0.5\text{mA}$ )



\*The Performance Data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

## Manufacturing Information

### Moisture Sensitivity



All plastic encapsulated semiconductor packages are susceptible to moisture ingress. IXYS Integrated Circuits Division classified all of its plastic encapsulated devices for moisture sensitivity according to the latest version of the joint industry standard, **IPC/JEDEC J-STD-020**, in force at the time of product evaluation. We test all of our products to the maximum conditions set forth in the standard, and guarantee proper operation of our devices when handled according to the limitations and information in that standard as well as to any limitations set forth in the information or standards referenced below.

Failure to adhere to the warnings or limitations as established by the listed specifications could result in reduced product performance, reduction of operable life, and/or reduction of overall reliability.

This product carries a **Moisture Sensitivity Level (MSL) rating** as shown below, and should be handled according to the requirements of the latest version of the joint industry standard **IPC/JEDEC J-STD-033**.

| Device   | Moisture Sensitivity Level (MSL) Rating |
|----------|---|
| CPC1006N | MSL 3                                   |

### ESD Sensitivity



This product is **ESD Sensitive**, and should be handled according to the industry standard **JESD-625**.

### Reflow Profile

This product has a maximum body temperature and time rating as shown below. All other guidelines of **J-STD-020** must be observed.

| Device   | Maximum Temperature x Time |
|----------|----------------------------|
| CPC1006N | 260°C for 30 seconds       |



### Board Wash

IXYS Integrated Circuits Division recommends the use of no-clean flux formulations. However, board washing to remove flux residue is acceptable. Since IXYS Integrated Circuits Division employs the use of silicone coating as an optical waveguide in many of its optically isolated products, the use of a short drying bake could be necessary if a wash is used after solder reflow processes. Chlorine- or Fluorine-based solvents or fluxes should not be used. Cleaning methods that employ ultrasonic energy should not be used.




**MECHANICAL DIMENSIONS**

**CPC1006N**




**Recommended PCB Land Pattern**



Dimensions  
mm  
(inches)

**CPC1006NTR Tape & Reel**



For additional information please visit our website at: [www.ixysic.com](http://www.ixysic.com)

IXYS Integrated Circuits Division makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in IXYS Integrated Circuits Division's Standard Terms and Conditions of Sale, IXYS Integrated Circuits Division assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of IXYS Integrated Circuits Division's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. IXYS Integrated Circuits Division reserves the right to discontinue or make changes to its products at any time without notice.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А