




1

2


3

4

FCI P/N (SEE NOTE 10)	AWG	L(Meter)	NOTE
10124176-3010LF	28	1.0	NON-HALOGEN FREE
10124176-3030LF	28	3.0	
10124176-4050LF	26	5.0	
10124176-5070LF	24	7.0	



dr	Tonny Lin	2013/01/24	projection  	size	A3	scale	3:10
eng	Tonny Lin	2013/01/24		ecn no	rel level		
chr	Tonny Lin	2013/01/24					
appr	Roger Cheng	2013/01/24	product family	QSFP PLUG			
	title	QSFP+ (PASSIVE) ASSEMBLY		no	10124176	rev	A
www.fci.com	cat. no.	-	Product - Customer Drw			sheet 1 of 3	



LOW SPEED SIGNALS	
P1 & P2	
POSITION	SYMBOL
8	ModSelL
9	ResetL
10	VccRx
11	SCL
12	SDA
27	ModPrsL
28	IntL
29	VccTx
30	Vcc1
31	LPMode

TABLE 1

WIRING LIST (SEE NOTE 6)					
END P1			END P2		
POSITION	SYMBOL		POSITION	SYMBOL	
1	GND (TX)	---	20	GND (RX)	
2	TX2n	---	21	RX2n	
3	TX2p	---	22	RX2p	
4	GND (TX)	---	23	GND (RX)	
5	TX4n	---	24	RX4n	
6	TX4p	---	25	RX4p	
7	GND (TX)	---	26	GND (RX)	
13	GND (RX)	⚡	32	GND (TX)	
14	RX3p	⚡	33	TX3p	
15	RX3n	⚡	34	TX3n	
16	GND (RX)	⚡	35	GND (TX)	
17	RX1p	⚡	36	TX1p	
18	RX1n	⚡	37	TX1n	
19	GND (RX)	⚡	38	GND (TX)	
20	GND (RX)	⚡	1	GND (TX)	
21	RX2n	⚡	2	TX2n	
22	RX2p	⚡	3	TX2p	
23	GND (RX)	⚡	4	GND (TX)	
24	RX4n	⚡	5	TX4n	
25	RX4p	⚡	6	TX4p	
26	GND (RX)	⚡	7	GND (TX)	
32	GND (TX)	---	13	GND (RX)	
33	TX3p	---	14	RX3p	
34	TX3n	---	15	RX3p	
35	GND (TX)	---	16	GND (RX)	
36	TX1p	---	17	RX1p	
37	TX1n	---	18	RX1n	
38	GND (TX)	---	19	GND (RX)	
SHIELD		-----	SHIELD		

TABLE 2

dr	Tonny Lin	2013/01/24	projection	mm	size	A3	scale	3:10		
eng	Tonny Lin	2013/01/24			ecn no					
chr	Tonny Lin	2013/01/24								
appr	Roger Cheng	2013/01/24	product family		QSFP PLUG	rel level				
		title			QSFP+ (PASSIVE) ASSEMBLY	dwg no		10124176	rev	A
www.fci.com		cat. no.		-	Product - Customer Drw			sheet 2 of 3		



Copyright FCI.

NOTES:

1- MATERIAL:

CASTINGS: ZINC ALLOY/ COPPER UNDERPLATE/ NICKEL OVERPLATE
PULL TAB: THERMOPLASTIC POLYMER
LATCH RELEASE: ZINC DIECAST, NICKEL OVERPLATE
DRIVE SCREWS: STAINLESS STEEL
STRAIN RELIEF COLLAR: BRASS
SPRING: STAINLESS STEEL
LOCTITE
PADDLE CARD: PRINTED CIRCUIT SUBSTRATE

2- THIS PRODUCT MEETS THE RESTRICTION OF HAZARDOUS SUBSTANCES IN ELECTRICAL AND ELECTRONIC EQUIPMENT (RoHS) "Directive 2011/65/EU" .

3- THIS DIMENSION 'L' IS A FINISHED PRODUCT LENGTH.

4- UNLESS OTHERWISE SPECIFIED ASSEMBLED LENGTH TOLERANCE IS:

L	TOLERANCE
=< 1M	± 25mm
1M-10M	± %2L
>= 10M	+ 0/- %4L

5- ALL CABLE ASSEMBLIES SHALL BE 100% TESTED FOR CONTINUITY AS DEFINED IN WIRING LIST.

6- IMPEDANCE: 100 Ω DIFFERENTIAL.

7- OTHER TESTING PERFORMED AS REQUIRED BY PRODUCT SPECIFICATION: GS-12-622.

8- PACKAGING OF LEAD FREE PRODUCTS MEETS LABELING AND PACKAGING PER SPECIFICATION GS-14-920.
PACKAGE CABLE ASSEMBLIES PER GS-14-1272. DUST CAPS ARE TO BE ASSEMBLED PRIOR TO PACKAGING.
FCI PACKAGE TRACKING BAG LABEL IS NOLY FOR REFERENCE.

9- A "△" SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW, OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION. THE CURRENT REVISION WILL BE SHOWN IN THE SYMBOL.

10- HALOGEN FREE RAW CABLE CAN BE USED AS A SUBSTITUTE ON NON-HF PRODUCT NUMBERS.

11- LONGER LENGTH APPLICATIONS REQUIRE HOST SYSTEM PREMPHASIS AND/OR EQUALIZATION.

12- EACH CABLE WILL BE PACKAGED IN A ESD BAG INDIVIDUALLY.

13- LABEL FOR CABLE CONTENTS AS BELOW.

FCI, MADE IN CHINA
FCI P/N
REVISION
SERIAL NUMBER

EXAMPLE

FCI, MADE IN CHINA
10124176-3010LF
REV.A
CN1323QP103L0001

FONT SHALL BE CLEARLY VISIBLE AND BLACK IN COLOR.

SERIAL NUMBER IS ONLY USED FOR TRACKING PRODUCT :

CN1323QP103L0001

CN PRESENT MADE IN CHINA

YYWW(YEAR AND WEEK)

PRESENT PRODUCT BASE NUMBER(USE "QP")

SEQUENCE NUMBER(0001~9999)

L IS NON-HALOGEN FREE TYPE

CABLE AWG(3 IS 28AWG; 4 IS 26AWG; 5 IS 24AWG)

LENGTH(10 IS 1.0 METER,30 IS 3.0 METERS,ETC)

dr	Tommy Lin	2013/01/24	projection 	mm 	size	A3	scale	3:10
eng	Tommy Lin	2013/01/24			ecn no			
chr	Tommy Lin	2013/01/24			rel level			
appr	Roger Cheng	2013/01/24	product family		QSFP PLUG			
	title	QSFP+ (PASSIVE) ASSEMBLY			dwg no	10124176		rev
								A
www.fci.com	cat. no.	-	Product - Customer Drw				sheet 3 of 3	

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А