



Molded, 25 mil or 50 mil Pitch, Dual-In-Line Thin Film Resistor, Surface Mount Network




Vishay Dale Thin Film resistor networks are designed to be used in either analog or digital circuits. The use of thin film resistive elements within the network allows you to achieve an infinite number of very low noise and high stability circuits for industrial, medical and scientific instrumentation. Vishay Dale Thin Film resistor networks are packaged in molded plastic packages with sizes that are recognized throughout the world. The rugged packaging offers superior environmental protection and consistent dimensions for ease of placement with automatic SMT equipment. Vishay Dale Thin Film stocks many designs and values for off-the-shelf convenience. With Vishay Dale Thin Film you can depend on quality products delivered on time with service backing the product.

SCHEMATICS

01 SCHEMATIC

Resistance Range:
10 Ω to 47 kΩ



FEATURES

- Reduces total assembly costs
- Compatible with automatic surface mounting equipment
- UL 94 V-0 flame resistant
- Thin film tantalum nitride on silicon
- Choice of package sizes: VTSR (TSSOP) JEDEC MC-153, VSSR (SSOP or QSOP) JEDEC MS-137, VSOR (SOIC narrow) JEDEC MS-012
- Moisture sensitivity level 1 (per IPC/JEDEC STD-20C)
- Isolated/bussed/dual terminator/differential terminator circuits
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS COMPLIANT
HALOGEN FREE

TYPICAL PERFORMANCE

| | ABSOLUTE | TRACKING |
|------|----------|----------|
| TCR | 100 | NA |
| | ABSOLUTE | RATIO |
| TOL. | 5, 2, 1 | NA |

RESISTORS WITH ONE PIN COMMON

The 01 circuit provides nominally equal resistors connected between a common pin and a discrete PC board pin.

Commonly used in the following applications:

- MOS/ROM pull-up/-down
- Open collector pull-up
- "Wired OR" pull-up
- Power driven pull-up
- TTL input pull-down
- Digital pulse squaring
- TTL unused gate pull-up
- High speed parallels pull-up

Broad selection of standard values available

03 SCHEMATIC

Resistance Range:
10 Ω to 47 kΩ



ISOLATED RESISTORS

The 03 circuit provides nominally equal resistors isolated from all others and wired directly across.

Commonly used in the following applications:

- "Wired OR" pull-up
- Power driven pull-up
- Powergate pull-up
- Line termination
- Long-line impedance balancing
- LED current limiting
- ECL output pull-down
- TTL input pull-down

Broad selection of standard values available

05 SCHEMATIC



DUAL-LINE TERMINATOR; PULSE SQUARING


The 05 circuit contains pairs of resistors connected between ground and a common line. The junctions of these resistor pairs are connected to the input leads. The 05 circuits are designed for dual-line termination and pulse squaring.

Standard values are:

VSSR1605:
R₁ = 220 Ω, R₂ = 330 Ω
R₁ = 330 Ω, R₂ = 470 Ω

VSSR2005:
R₁ = 220 Ω, R₂ = 330 Ω
R₁ = 220 Ω, R₂ = 1.8 kΩ
R₁ = 1.5 kΩ, R₂ = 3.3 kΩ

47 SCHEMATIC



DIFFERENTIAL TERMINATOR

The 47 schematic consists of series resistor sections connected between V_{CC} and ground. Each contains 3 resistors of 2 different resistance values.

Standard values are:


VSSR20 and VTSR20:
R₁ = 270 Ω, R₂ = 120 Ω

VSSR16 and VTSR16:
R₁ = 330 Ω, R₂ = 150 Ω
R₁ = 330 Ω, R₂ = 220 Ω



| STANDARD ELECTRICAL SPECIFICATIONS | | |
|------------------------------------|--|----------------------------------|
| TEST | SPECIFICATIONS | CONDITIONS |
| Material | Tantalum nitride | - |
| Pin/Lead Number | 16, 20, 24 | - |
| Resistance Range | 10 Ω to 47 kΩ | Per E-24 table |
| TCR: Absolute | ± 100 ppm/°C | -55 °C to + 125 °C |
| TCR: Tracking | n/a | - |
| Tolerance: Absolute | ± 5 % standard (± 2 % available) ± 1 % standard (check factory) | Per E-24 table Per E-96 table |
| Tolerance: Ratio | NA | - |
| Power Rating: Resistor | 100 mW max. | At + 70 °C |
| Power Rating: Package | 16 = 1.0 W, 20 = 1.2 W, 24 = 1.4 W | 0 °C to + 70 °C |
| Stability: Absolute | - | - |
| Stability: Ratio | - | - |
| Voltage Coefficient | 5 ppm/V (typical) | - |
| Working Voltage | 50 V _{DC} | - |
| Operating Temperature Range | - 55 °C to + 125 °C | - |
| Storage Temperature Range | - 55 °C to + 150 °C | - |
| Noise | < - 35 dB | - |
| Thermal EMF | - | - |
| Shelf Life Stability: Absolute | - | - |
| Shelf Life Stability: Ratio | - | - |

DIMENSIONS AND IMPRINTING in inches (millimeters)



| DIMENSION | VTSR-xxxx | VSSR-xxxx | VSOR-xxxx |
|------------|-----------------------------|------------------------------|-----------------------------|
| A - 16 PIN | 0.206 ± 0.003 (5.23 ± 0.08) | 0.193 ± 0.004 (4.90 ± 0.010) | 0.390 ± 0.010 (9.91 ± 0.25) |
| A - 20 PIN | 0.256 ± 0.003 (6.50 ± 0.08) | 0.341 ± 0.003 (8.66 ± 0.08) | NA |
| A - 24 PIN | 0.306 ± 0.003 (7.77 ± 0.08) | 0.341 ± 0.003 (8.66 ± 0.08) | NA |
| B (Ref.) | 0.0256 (0.65) | 0.025 (0.64) | 0.050 (1.27) |
| C (Ref.) | 0.0087 (0.22) | 0.010 (0.25) | 0.016 (0.41) |
| D | 0.004 (0.10) | 0.006 (0.15) | 0.008 (0.20) |
| E (Typ.) | 0.024 (0.61) | 0.025 (0.64) | 0.030 (0.76) |
| F | 0.173 ± 0.003 (4.39 ± 0.08) | 0.154 ± 0.003 (3.91 ± 0.08) | 0.152 ± 0.003 (3.86 ± 0.08) |
| G | 0.015 × 45° (0.38) | 0.015 × 45° (0.38) | 0.015 × 45° (0.38) |
| H | 0.252 ± 0.005 (6.40 ± 0.13) | 0.236 ± 0.008 (5.99 ± 0.20) | 0.236 ± 0.005 (5.99 ± 0.13) |
| J (Ref.) | 0.005 (0.13) | 0.010 (0.25) | 0.008 (0.20) |
| W | 0.043 ± 0.005 (1.09 ± 0.13) | 0.064 ± 0.005 (1.63 ± 0.13) | 0.064 ± 0.005 (1.63 ± 0.13) |

MARKING

| MODEL | PIN COUNT (Optional) | SCHEMATIC | RESISTANCE | RESISTANCE | DATE CODE |
|-------|----------------------|-----------|---|---|-----------|
| VXXX | XX | XX | XXXX | XXX | XXXX |
| VSOR | 16 | 01, 03, | 1 % RESISTANCE | OR 1 %, 2 %, 5 % RESISTANCE e.g.: 103 = 10K The first 2 digits are significant figures, the last digit specifies the number of zeros to follow. | |
| VSSR | 20 | 05 or 47 | e.g.: 43R2 | | |
| VTSR | 24 | | 4 digits are used to express ohmic values only less than 100 Ω. R is used to designate the decimal position | | |



| MECHANICAL SPECIFICATIONS | |
|--------------------------------|--|
| Resistive Element | Tantalum nitride |
| Substrate Material | Silicon |
| Body | Molded epoxy |
| Terminals | Copper alloy |
| Plating | 100 % matte tin |
| Lead Coplanarity | 0.0005" |
| Marking Resistance to Solvents | Permanency testing per MIL-STD-202, method 215 |

| PACKAGING INFORMATION | | | |
|-----------------------|-------|---------------|-------|
| MODEL | LEADS | TAPE AND REEL | TUBES |
| VTSR (TSSOP) | 16 | 2500 | 94 |
| | 20 | 2500 | 74 |
| | 24 | 2500 | 62 |
| VSSR (QSOP) | 16 | 2500 | 98 |
| | 20 | 2500 | 55 |
| | 24 | 2500 | 55 |
| VSOR (SOIC) | 16 | 2500 | 48 |



GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: **VTSR1601103JTF**



| GLOBAL MODEL | PIN COUNT | SCHEMATIC | RESISTANCE (3, 4 or 6 digits) | TOLERANCE | PACKAGING |
|--|--|--|--|--|---|
| VTSR VSSR VSOR Lead (Pb)-free (e3) date code > 2705 | 20 (not VSOR) 24 (not VSOR) | 01 (bussed) 03 (isolated) | XXX: ≥ 100R and all 1 %, 2 % and 5 % First 2 digits are significant figures. Last digit specifies number of zeros to follow. XXXX: < 100R 1 % First 3 digits are significant figures. Last digit specifies number of zeros to follow. | F = 1.0 % G = 2.0 % J = 5.0 % | TAPE AND REEL TF = Full reel 2500 UF = Tubed |
| | 16 (not VTSR) 20 (not VSOR) | 05 (terminator) 47 (terminator) | xxx xxx First 2 digits are significant figures. Last digit specifies number of zeros. | G = 2.0 % J = 5.0 % | |

Historical Part Number example: **VSSR2001102GT/R** (for reference purposes only)

| | | | | | |
|-------|-----------|-----------|------------|-----------|-----------|
| VSSR | 20 | 01 | 102 | G | T/R |
| MODEL | PIN COUNT | SCHEMATIC | RESISTANCE | TOLERANCE | PACKAGING |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А