

# MC74HC151A

## 8-Input Data Selector/Multiplexer

### High-Performance Silicon-Gate CMOS

The MC74HC151 is identical in pinout to the LS151. The device inputs are compatible with standard CMOS outputs; with pullup resistors, they are compatible with LSTTL outputs.

This device selects one of the eight binary Data Inputs, as determined by the Address Inputs. The Strobe pin must be at a low level for the selected data to appear at the outputs. If Strobe is high, the Y output is forced to a low level and the  $\bar{Y}$  output is forced to a high level.

The HC151 is similar in function to the HC251 which has 3-state outputs.

#### Features

- Output Drive Capability: 10 LSTTL Loads
- Outputs Directly Interface to CMOS, NMOS, and TTL
- Operating Voltage Range: 2 to 6 V
- Low Input Current: 1  $\mu$ A
- High Noise Immunity Characteristic of CMOS Devices
- These are Pb-Free Devices





Figure 1. Logic Diagram



ON Semiconductor®


<http://onsemi.com>



A = Assembly Location  
WL, L = Wafer Lot  
YY, Y = Year  
WW, W = Work Week  
G or ■ = Pb-Free Package

(Note: Microdot may be in either location)

#### PIN ASSIGNMENT



#### FUNCTION TABLE

| Inputs |    |    |        | Outputs |            |
|--------|----|----|--------|---------|------------|
| A2     | A1 | A0 | Strobe | Y       | $\bar{Y}$  |
| X      | X  | X  | H      | L       | H          |
| L      | L  | L  | L      | D0      | $\bar{D0}$ |
| L      | L  | H  | L      | D1      | $\bar{D1}$ |
| L      | H  | L  | L      | D2      | $\bar{D2}$ |
| L      | H  | H  | L      | D3      | $\bar{D3}$ |
| H      | L  | L  | L      | D4      | $\bar{D4}$ |
| H      | L  | H  | L      | D5      | $\bar{D5}$ |
| H      | H  | L  | L      | D6      | $\bar{D6}$ |
| H      | H  | H  | L      | D7      | $\bar{D7}$ |

D0, D1, ..., D7 = the level of the respective D input.

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

# MC74HC151A

## MAXIMUM RATINGS

| Symbol    | Parameter                                                       | Value                  | Unit |
|-----------|-----------------------------------------------------------------|------------------------|------|
| $V_{CC}$  | DC Supply Voltage (Referenced to GND)                           | -0.5 to +7.0           | V    |
| $V_{in}$  | DC Input Voltage (Referenced to GND)                            | -1.5 to $V_{CC} + 1.5$ | V    |
| $V_{out}$ | DC Output Voltage (Referenced to GND)                           | -0.5 to $V_{CC} + 0.5$ | V    |
| $I_{in}$  | DC Input Current, per Pin                                       | $\pm 20$               | mA   |
| $I_{out}$ | DC Output Current, per Pin                                      | $\pm 25$               | mA   |
| $I_{CC}$  | DC Supply Current, $V_{CC}$ and GND Pins                        | $\pm 50$               | mA   |
| $P_D$     | Power Dissipation in Still Air<br>SOIC Package<br>TSSOP Package | 500<br>TBD             | mW   |
| $T_{stg}$ | Storage Temperature                                             | -65 to +150            | °C   |

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{in}$  and  $V_{out}$  should be constrained to the range  $GND \leq (V_{in} \text{ or } V_{out}) \leq V_{CC}$ . Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

## RECOMMENDED OPERATING CONDITIONS

| Symbol                             | Parameter                                            | Min                     | Max             | Unit |
|------------------------------------|------------------------------------------------------|-------------------------|-----------------|------|
| V <sub>CC</sub>                    | DC Supply Voltage (Referenced to GND)                | 2.0                     | 6.0             | V    |
| V <sub>in</sub> , V <sub>out</sub> | DC Input Voltage, Output Voltage (Referenced to GND) | 0                       | V <sub>CC</sub> | V    |
| T <sub>A</sub>                     | Operating Temperature, All Package Types             | −55                     | +125            | °C   |
| t <sub>r</sub> , t <sub>f</sub>    | Input Rise and Fall Time                             | V <sub>CC</sub> = 2.0 V | 0               | ns   |
|                                    | (Figure 2)                                           | V <sub>CC</sub> = 4.5 V | 0               |      |
|                                    |                                                      | V <sub>CC</sub> = 6.0 V | 0               |      |

## DC ELECTRICAL CHARACTERISTICS (Voltages Referenced to GND)

| Symbol   | Parameter                                      | Test Conditions                                                                                            | $V_{CC}$<br>V     | Guaranteed Limit   |                         |                          | Unit          |
|----------|------------------------------------------------|------------------------------------------------------------------------------------------------------------|-------------------|--------------------|-------------------------|--------------------------|---------------|
|          |                                                |                                                                                                            |                   | - 55 to<br>25°C    | $\leq 85^\circ\text{C}$ | $\leq 125^\circ\text{C}$ |               |
| $V_{IH}$ | Minimum High-Level Input Voltage               | $V_{out} = 0.1 \text{ V or } V_{CC} - 0.1 \text{ V}$<br>$ I_{out}  \leq 20 \mu\text{A}$                    | 2.0<br>4.5<br>6.0 | 1.5<br>3.15<br>4.2 | 1.5<br>3.15<br>4.2      | 1.5<br>3.15<br>4.2       | V             |
| $V_{IL}$ | Maximum Low-Level Input Voltage                | $V_{out} = 0.1 \text{ V or } V_{CC} - 0.1 \text{ V}$<br>$ I_{out}  \leq 20 \mu\text{A}$                    | 2.0<br>4.5<br>6.0 | 0.3<br>0.9<br>1.2  | 0.3<br>0.9<br>1.2       | 0.3<br>0.9<br>1.2        | V             |
| $V_{OH}$ | Minimum High-Level Output Voltage              | $V_{in} = V_{IH} \text{ or } V_{IL}$<br>$ I_{out}  \leq 20 \mu\text{A}$                                    | 2.0<br>4.5<br>6.0 | 1.9<br>4.4<br>5.9  | 1.9<br>4.4<br>5.9       | 1.9<br>4.4<br>5.9        | V             |
|          |                                                | $V_{in} = V_{IH}$<br>$ I_{out}  \leq 4.0 \text{ mA}$<br>$ I_{out}  \leq 5.2 \text{ mA}$                    | 4.5<br>6.0        | 3.98<br>5.48       | 3.84<br>5.34            | 3.70<br>5.20             |               |
| $V_{OL}$ | Maximum Low-Level Output Voltage               | $V_{in} = V_{IH} \text{ or } V_{IL}$<br>$ I_{out}  \leq 20 \mu\text{A}$                                    | 2.0<br>4.5<br>6.0 | 0.1<br>0.1<br>0.1  | 0.1<br>0.1<br>0.1       | 0.1<br>0.1<br>0.1        | V             |
|          |                                                | $V_{in} = V_{IH} \text{ or } V_{IL}$<br>$ I_{out}  \leq 4.0 \text{ mA}$<br>$ I_{out}  \leq 5.2 \text{ mA}$ | 4.5<br>6.0        | 0.26<br>0.26       | 0.33<br>0.33            | 0.40<br>0.40             |               |
| $I_{in}$ | Maximum Input Leakage Current                  | $V_{in} = V_{CC} \text{ or GND}$                                                                           | 6.0               | $\pm 0.1$          | $\pm 1.0$               | $\pm 1.0$                | $\mu\text{A}$ |
| $I_{CC}$ | Maximum Quiescent Supply Current (per Package) | $V_{in} = V_{CC} \text{ or GND}$<br>$I_{out} = 0 \mu\text{A}$                                              | 6.0               | 8                  | 80                      | 160                      | $\mu\text{A}$ |

# MC74HC151A

## AC ELECTRICAL CHARACTERISTICS (C<sub>L</sub> = 50 pF, Input t<sub>r</sub> = t<sub>f</sub> = 6 ns)

| Symbol                                 | Parameter                                                                   | V <sub>CC</sub><br>V | Guaranteed Limit |                 |                 | Unit |
|----------------------------------------|-----------------------------------------------------------------------------|----------------------|------------------|-----------------|-----------------|------|
|                                        |                                                                             |                      | – 55 to 25°C     | ≤ 85°C          | ≤ 125°C         |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Input D to Output Y<br>(Figures 2 and 7)         | 2.0<br>4.5<br>6.0    | 170<br>34<br>29  | 215<br>43<br>37 | 255<br>51<br>43 | ns   |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Input D to Output $\bar{Y}$<br>(Figures 4 and 7) | 2.0<br>4.5<br>6.0    | 185<br>37<br>31  | 230<br>46<br>39 | 280<br>56<br>48 | ns   |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Input D to Output Y<br>(Figures 3 and 7)         | 2.0<br>4.5<br>6.0    | 185<br>37<br>31  | 230<br>46<br>39 | 280<br>56<br>48 | ns   |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Input A to Output $\bar{Y}$<br>(Figures 3 and 7) | 2.0<br>4.5<br>6.0    | 205<br>41<br>35  | 255<br>51<br>43 | 310<br>62<br>53 | ns   |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Input D to Output Y<br>(Figures 5 and 7)         | 2.0<br>4.5<br>6.0    | 125<br>25<br>21  | 155<br>31<br>26 | 190<br>38<br>32 | ns   |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Strobe to Output $\bar{Y}$<br>(Figures 6 and 7)  | 2.0<br>4.5<br>6.0    | 125<br>25<br>21  | 155<br>31<br>26 | 190<br>38<br>32 | ns   |
| t <sub>TLH</sub> ,<br>t <sub>THL</sub> | Maximum Output Transition Time, Any Output<br>(Figures 2, 4 and 7)          | 2.0<br>4.5<br>6.0    | 75<br>15<br>13   | 95<br>19<br>16  | 110<br>22<br>19 | ns   |
| C <sub>in</sub>                        | Maximum Input Capacitance                                                   | –                    | 10               | 10              | 10              | pF   |

|                 |                                             |                                         |    |
|-----------------|---------------------------------------------|-----------------------------------------|----|
| C <sub>PD</sub> | Power Dissipation Capacitance (Per Package) | Typical @ 25°C, V <sub>CC</sub> = 5.0 V | pF |
|                 |                                             | 36                                      |    |

## PIN DESCRIPTIONS

### INPUTS

#### D0, D1, ..., D7 (Pins 4, 3, 2, 1, 15, 14, 13, 12)

Data inputs. Data on any one of these eight binary inputs may be selected to appear on the output.

### CONTROL INPUTS

#### A0, A1, A2 (Pins 11, 10, 9)

Address inputs. The data on these pins are the binary address of the selected input (see the Function Table).

### Strobe (Pin 7)

Strobe. This input pin must be at a low level for the selected data to appear at the outputs. If the Strobe pin is high, the Y output is forced to a low level and the  $\bar{Y}$  output is forced to a high level.

### OUTPUTS

#### Y, $\bar{Y}$ (Pins 5, 6)

Data outputs. The selected data is presented at these pins in both true (Y output) and complemented ( $\bar{Y}$  output) forms.

# MC74HC151A

## SWITCHING WAVEFORMS




Figure 2.




Figure 3.




Figure 4.




Figure 5.





Figure 6.



\*Includes all probe and jig capacitance

Figure 7. Test Circuit

MC74HC151A




Figure 8. Expanded Logic Diagram

ORDERING INFORMATION

| Device          | Package              | Shipping†        |
|-----------------|----------------------|------------------|
| MC74HC151ADG    | SOIC-16<br>(Pb-Free) | 48 Units / Rail  |
| MC74HC151ADR2G  | SOIC-16<br>(Pb-Free) | 2500 Tape & Reel |
| MC74HC151ADTR2G | TSSOP-16*            | 2500 Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.  
\*This package is inherently Pb-Free.

## PACKAGE DIMENSIONS

Technical drawing of a 16-pin connector. The drawing includes a top view, a side view, and a detail view of the pin. The top view shows a rectangular body with 16 pins arranged in two rows of 8. Dimensions include overall width  $-A-$ , overall height  $-B-$ , pin pitch  $P$ , and pin diameter  $\varnothing$ . The side view shows the profile of the connector with dimensions  $K$ ,  $C$ , and  $D$ . The detail view shows the pin profile with dimensions  $R$ ,  $F$ ,  $M$ , and  $J$ . A table of values is provided below the drawing.

|               |              |     |   |     |
|---------------|--------------|-----|---|-----|
| $\varnothing$ | 0.25 (0.010) | (M) | B | (S) |
|---------------|--------------|-----|---|-----|

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |       | INCHES    |       |
|-----|-------------|-------|-----------|-------|
|     | MIN         | MAX   | MIN       | MAX   |
| A   | 9.80        | 10.00 | 0.386     | 0.393 |
| B   | 3.80        | 4.00  | 0.150     | 0.157 |
| C   | 1.35        | 1.75  | 0.054     | 0.068 |
| D   | 0.35        | 0.49  | 0.014     | 0.019 |
| F   | 0.40        | 1.25  | 0.016     | 0.049 |
| G   | 1.27 BSC    |       | 0.050 BSC |       |
| J   | 0.19        | 0.25  | 0.008     | 0.009 |
| K   | 0.10        | 0.25  | 0.004     | 0.009 |
| M   | 0 °         | 7 °   | 0 °       | 7 °   |
| P   | 5.80        | 6.20  | 0.229     | 0.244 |
| R   | 0.25        | 0.50  | 0.010     | 0.019 |


Diagram illustrating the 16X connector pinout. The connector is shown with 16 pins, numbered 1 through 8 on the left and 16 through 9 on the right. The total width of the connector is 6.40mm (8X). The pitch between pins is 1.27mm. The distance between the centerlines of the two rows of pins is 1.12mm (16X).

6

# MC74HC151A

## PACKAGE DIMENSIONS


TSSOP-16  
DT SUFFIX  
CASE 948F-01  
ISSUE B



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.18        | 0.28 | 0.007     | 0.011 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А