

1

2

3

4

5

6

7

8

PRODUCT NUMBER

10127396-00HI000LF

NOTES:

1.

"FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE P/N CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.

2.

MATERIALS:
HOUSING: GLASS FILLED WITH HIGH TEMP POLYAMIDE, UL94V-0.
POWER CONTACTS: COPPER ALLOY.
SIGNAL CONTACTS: COPPER ALLOY.
HOLD DOWN: COPPER ALLOY.

3.

PLATING SPECIFICATION: FCI 10135186.

4.

DENOTES CONNECTOR KEEP OUT ZONE.

5.

DATUM AND BASIC DIMENSION ARE ESTABLISHED BY CUSTOMER.

6.

ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.

7.

1.150±0.025mm DRILLED HOLE PLATED WITH 7.62µm MIN Sn OVER
25.4µm-76.2µm Cu PLATING TO ACHIEVE A 1.02±0.07mm FINISHED HOLE.

8.

PRODUCT SPECIFICATION: FCI GS-12-1176.
APPLICATION SPECIFICATION: FCI GS-20-0389.
PRODUCT PACKAGE SPECIFICATION: FCI GS-14-2354.

Amphenol
FCi

© 2016 AFci

1

2

3

4

5

PDS: Rev :A

STATUS:Released

Printed: Jun 16, 2016

spec ref

-

tolerance std

-

ASME Y14.5

✓

TOLERANCES UNLESS
OTHERWISE SPECIFIED

linear

0.X

±0.5

0.XX

±0.25

0.XXX

±0.130

angular

0°

±2°

dr

Daniel Xiao

2014/11/14

eng

Kaka Zhang

2016/06/16

chr

Fancy Zhang

2016/06/16

appr

Pei-Ming Zheng

2016/06/16

projection

mm

size

A2

scale

2:1

ecn no

-

product family

PwrBlade ULTRA

rel level

Released

Amphenol
FCi

title

2HP, PRESS-FIT
R/A PLUG, PwrBlade ULTRA

cat. no.

-

Product - Customer Drw

sheet 3 of 3

rev

A

rel level

Released

1

2

3

4

5

6

7

8

PRODUCT NUMBER

10127396-00HI000LF

NOTES:

1.

"FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE P/N CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.

2.

MATERIALS:
HOUSING: GLASS FILLED WITH HIGH TEMP POLYAMIDE, UL94V-0.
POWER CONTACTS: COPPER ALLOY.
SIGNAL CONTACTS: COPPER ALLOY.
HOLD DOWN: COPPER ALLOY.

3.

PLATING SPECIFICATION: FCI 10135186.

4.

DENOTES CONNECTOR KEEP OUT ZONE.

5.

DATUM AND BASIC DIMENSION ARE ESTABLISHED BY CUSTOMER.

6.

ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.

7.

1.150±0.025mm DRILLED HOLE PLATED WITH 7.62µm MIN Sn OVER
25.4µm-76.2µm Cu PLATING TO ACHIEVE A 1.02±0.07mm FINISHED HOLE.

8.

PRODUCT SPECIFICATION: FCI GS-12-1176.
APPLICATION SPECIFICATION: FCI GS-20-0389.
PRODUCT PACKAGE SPECIFICATION: FCI GS-14-2354.

Amphenol
FCi

© 2016 AFci

1

2

3

4

5

PDS: Rev :A

STATUS:Released

Printed: Jun 16, 2016

spec ref

-

tolerance std

-

ASME Y14.5

✓

TOLERANCES UNLESS
OTHERWISE SPECIFIED

linear

0.X

±0.5

0.XX

±0.25

0.XXX

±0.130

angular

0°

±2°

dr

Daniel Xiao

2014/11/14

eng

Kaka Zhang

2016/06/16

chr

Fancy Zhang

2016/06/16

appr

Pei-Ming Zheng

2016/06/16

projection

mm

size

A2

scale

2:1

ecn no

-

product family

PwrBlade ULTRA

rel level

Released

Amphenol
FCi

title

2HP, PRESS-FIT
R/A PLUG, PwrBlade ULTRA

cat. no.

-

Product - Customer Drw

sheet 3 of 3

rev

A

rel level

Released

1

2

3

4

5

6

7

8

PRODUCT NUMBER

10127396-00HI000LF

NOTES:

1.

"FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE P/N CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.

2.

MATERIALS:
HOUSING: GLASS FILLED WITH HIGH TEMP POLYAMIDE, UL94V-0.
POWER CONTACTS: COPPER ALLOY.
SIGNAL CONTACTS: COPPER ALLOY.
HOLD DOWN: COPPER ALLOY.

3.

PLATING SPECIFICATION: FCI 10135186.

4.

DENOTES CONNECTOR KEEP OUT ZONE.

5.

DATUM AND BASIC DIMENSION ARE ESTABLISHED BY CUSTOMER.

6.

ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.

7.

1.150±0.025mm DRILLED HOLE PLATED WITH 7.62µm MIN Sn OVER
25.4µm-76.2µm Cu PLATING TO ACHIEVE A 1.02±0.07mm FINISHED HOLE.

8.

PRODUCT SPECIFICATION: FCI GS-12-1176.
APPLICATION SPECIFICATION: FCI GS-20-0389.
PRODUCT PACKAGE SPECIFICATION: FCI GS-14-2354.

Amphenol
FCi

© 2016 AFci

1

2

3

4

5

PDS: Rev :A

STATUS:Released

Printed: Jun 16, 2016

spec ref

-

tolerance std

-

ASME Y14.5

✓

TOLERANCES UNLESS
OTHERWISE SPECIFIED

linear

0.X

±0.5

0.XX

±0.25

0.XXX

±0.130

angular

0°

±2°

dr

Daniel Xiao

2014/11/14

eng

Kaka Zhang

2016/06/16

chr

Fancy Zhang

2016/06/16

appr

Pei-Ming Zheng

2016/06/16

projection

mm

size

A2

scale

2:1

ecn no

-

product family

PwrBlade ULTRA

rel level

Released

Amphenol
FCi

title

2HP, PRESS-FIT
R/A PLUG, PwrBlade ULTRA

cat. no.

-

Product - Customer Drw

sheet 3 of 3

rev

A

rel level

Released

1

2

3

4

5

6

7

8

PRODUCT NUMBER

10127396-00HI000LF

NOTES:

1.

"FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE P/N CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.

2.

MATERIALS:
HOUSING: GLASS FILLED WITH HIGH TEMP POLYAMIDE, UL94V-0.
POWER CONTACTS: COPPER ALLOY.
SIGNAL CONTACTS: COPPER ALLOY.
HOLD DOWN: COPPER ALLOY.

3.

PLATING SPECIFICATION: FCI 10135186.

4.

DENOTES CONNECTOR KEEP OUT ZONE.

5.

DATUM AND BASIC DIMENSION ARE ESTABLISHED BY CUSTOMER.

6.

ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.

7.

1.150±0.025mm DRILLED HOLE PLATED WITH 7.62µm MIN Sn OVER
25.4µm-76.2µm Cu PLATING TO ACHIEVE A 1.02±0.07mm FINISHED HOLE.

8.

PRODUCT SPECIFICATION: FCI GS-12-1176.
APPLICATION SPECIFICATION: FCI GS-20-0389.
PRODUCT PACKAGE SPECIFICATION: FCI GS-14-2354.

Amphenol
FCi

© 2016 AFci

1

2

3

4

5

PDS: Rev :A

STATUS:Released

Printed: Jun 16, 2016

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А