

Features

- Qualified with 65kV/ μ s @ Vcommon mode =1KV
- UL/CSA and IEC/EN safety certified
- High isolation 6.4kVDC/1s
- Optional continuous short circuit protection
- /X2 version with >9mm input/output clearance
- Suitable for IGBT applications

Unregulated Converters



RxxPxx

**1 Watt
SIP7
Single and Dual
Output**



Description

The RxxPxxS_D Series of DC/DC Converters are certified to UL/CSA60950-1 as well as EN60950-1. This makes them ideal for safety applications where approved isolation is required.

Selection Guide


| Part Number | nom. Input Voltage [VDC] | Output Voltage [VDC] | Output Current [mA] | Efficiency typ. ⁽¹⁾ [%] | max. Capacitive Load ⁽²⁾ [μ F] |
|----------------------------|--------------------------|----------------------|---------------------|------------------------------------|--|
| RxxP3.3S ^(3,4) | 5, 12, 15, 24 | 3.3 | 303 | 70 | 2200 |
| RxxP05S ^(3,4) | 5, 12, 15, 24 | 5 | 200 | 70 - 75 | 1000 |
| RxxP09S ^(3,4) | 5, 12, 15, 24 | 9 | 111 | 70 - 75 | 1000 |
| RxxP12S ^(3,4) | 5, 12, 15, 24 | 12 | 84 | 70 - 75 | 470 |
| RxxP15S ^(3,4) | 5, 12, 15, 24 | 15 | 66 | 75 - 80 | 470 |
| RxxP3.3D ^(3,4) | 5, 12, 15, 24 | \pm 3.3 | \pm 151 | 70 | \pm 1000 |
| RxxP05D ^(3,4) | 5, 12, 15, 24 | \pm 5 | \pm 100 | 70 - 75 | \pm 470 |
| RxxP09D ^(3,4) | 5, 12, 15, 24 | \pm 9 | \pm 55 | 70 - 75 | \pm 470 |
| RxxP12D ^(3,4) | 5, 12, 15, 24 | \pm 12 | \pm 41 | 70 - 75 | \pm 220 |
| RxxP15D ^(3,4) | 5, 12, 15, 24 | \pm 15 | \pm 33 | 75 - 80 | \pm 220 |
| RxxP1509D ^(3,4) | 12, 24 | +15/-9 | +33/-56 | 70 - 80 | \pm 220 |
| R05P1509D ^(3,4) | 5 | +15/-9 | \pm 42 | 70 - 80 | +68/-220 |



Notes:

- Note1: Efficiency is tested at nominal input and full load at +25°C ambient
 Note2: Max. Capacitive Load is defined as the capacitive load that will allow start up in under 1 second without damage to the converter

Model Numbering



Notes:

- Note3: add suffix „/X2“ for single output with alternative pinout
 Note4: add suffix „P“ for continuous short circuit protection

Ordering Examples:

- R05P05S/P = 5V Input, 5V Output, Single Output, Continuous Short Circuit Protection
 R05P3.3D/P = 5V Input, 3.3V Output, Dual Output, Continuous Short Circuit Protection
 R05P05S/P/X2 = 5V Input, 5V Output, Single Output, Continuous Short Circuit Protection, Alternative Pinout



www.recom-power.com/eval-ref-boards

www.recom-power.com/bier


Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

BASIC CHARACTERISTICS


| Parameter | Condition | Min. | Typ. | Max. |
|------------------------------|------------------------|----------------|----------------|----------|
| Input Voltage Range | | | ±10% | |
| Minimum Load | | 0% | | |
| Internal Operating Frequency | all types PxxP1509D | 20kHz 20kHz | 50kHz 60kHz | 85kHz |
| Output Ripple and Noise | 20MHz BW | | | 200mVp-p |

Efficiency vs. Load


PxxP05S and PxxP09S




PxxP05D and PxxP09D



PxxP12S and PxxP15S



PxxP12D and PxxP15D



REGULATIONS

| Parameter | Condition | | Value |
|--------------------------------|----------------------------------|---------------------------|------------------------|
| Output Accuracy | | | ±5.0% max. |
| Line Regulation | low line to high line, full load | | ±1.2% of 1.0% Vin typ. |
| Load Regulation ⁽⁵⁾ | 10% to 100% load | 3.3, 5VDC 9, 12, 15VDC | 15% typ. 10% typ. |


Notes:

Note5: Operation below 10% load will not harm the converter, but specifications may not be met

continued on next page


Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Tolerance Envelope




Deviation vs. Load


PxxP05S and PxxP09S




PxxP05D and PxxP09D



PxxP12S and PxxP15S



PxxP12D and PxxP15D




Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

| PROTECTIONS | | | |
|---|------------------------------------|------------------------|--------------|
| Parameter | Type | Value | |
| Short Circuit Protection (SCP) | without suffix with suffix "/P" | 1 second continuous | |
| Isolation Voltage ⁽⁶⁾ | I/P to O/P | tested for 1 second | 6.4kVDC |
| | | rated for 1 minute | 3.2kVAC/60Hz |
| Isolation Resistance | | 15GΩ min. | |
| Isolation Capacitance | | 4.0pF min. / 10pF max. | |
| Insulation Grade | | basic | |
| Notes: Note6: For repeat Hi-Pot testing, reduce the time and/or the test voltage Note7: Refer to local safety regulations if input over-current protection is required. Recommended fuse: slow blow type | | | |

| ENVIRONMENTAL | | | |
|-----------------------------|---|----------------|------------------------------|
| Parameter | Condition | Value | |
| Operating Temperature Range | without derating @ free air convection(see graph) | -40°C to +90°C | |
| Operating Altitude | | 2000m | |
| Operating Humidity | non-condensing | 95% RH max. | |
| Pollution Degree | | PD2 | |
| MTBF | according to MIL-HDBK-217F, G.B. | +25°C | 2974 x 10 ³ hours |
| | | +85°C | 728 x 10 ³ hours |

Derating Graph

(@ Chamber and free air convection)




Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

SAFETY AND CERTIFICATIONS

| Certificate Type (Safety) | Report / File Number | Standard |
|--|----------------------|--|
| Information Technology Equipment, General Requirements for Safety | E224736-A56-UL | UL60950-1, 2nd Edition, 2014 CAN/CSA C22.2 No. 60950-1, 2nd Edition, 2014 |
| Information Technology Equipment, General Requirements for Safety | SPCLVD1602031 | EN60950-1:2006 +AM:2013 IEC60950-1:2005, 2nd Edition +AM:2013 |
| Audio/Video, information and communication technology equipment. Safety requirements | E224736-A56-UL | UL62368-1, 2nd Edition, 2014 CAN/CSA C22.2 No. 62368-1, 2nd Edition, 2014 |
| Audio/Video, information and communication technology equipment - Part1: Safety requirements (CB Scheme) | ATTCB106076 | IEC62368-1:2014, 2nd Edition |
| Audio/Video, information and communication technology equipment - Part1: Safety requirements | | EN62368-1: 2014 + A11:2017 |
| EAC | RU-AT.49.09571 | TP TC 004/2011 |
| RoHS 2+ | | RoHS-2011/65/EU + AM2015/863 |

| EMC Compliance | Condition | Standard / Criterion |
|---|---|--------------------------------------|
| Electromagnetic compatibility of multimedia equipment - Emission requirements | with external filter (see filter suggestion below) | EN55032, Class B EN55032, Class A |

EMC Filter Suggestion according to EN55032



Component List Class A

| MODEL | C1 | L1 | G2 | C3 (safety) |
|---------|-----------|-----|----------|-------------|
| R05P05S | 22µF | N/A | N/A | N/A |
| R05P12S | 50V MLCC | | N/A | |
| R12P05S | 10µF | | 4.7µF | |
| R24P05S | 100V MLCC | | 50V MLCC | |

Component List Class B

| MODEL | C1 | L1 | G2 | C3 (safety) |
|---------|-------------------|-----------------------|-----|-------------|
| R05P05S | 10µF 100V MLCC | 22µH choke RLS-226 | N/A | 1nF |
| R05P12S | | | | |
| R12P05S | | | | |
| R24P05S | | | | |

Notes:


Note8: Filter suggestions are valid for indicated part numbers only. For other part numbers, please contact RECOM tech support for advice

DIMENSION AND PHYSICAL CHARACTERISTICS

| Parameter | Type | Value |
|-------------------|------------------------|--|
| Material | case potting PCB | non-conductive black plastic, (UL94 V-0) silicon rubber compound, (UL94 V-0) FR4, (UL94 V-0) |
| Dimension (LxWxH) | | 19.5 x 9.8 x 12.5mm |
| Weight | | 4.3g typ. |


continued on next page

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)



INSTALLATION AND APPLICATION

IGBT Application Circuit



PACKAGING INFORMATION

| Parameter | Type | Value |
|-----------------------------|------|-----------------------|
| Packaging Dimension (LxWxH) | tube | 520.0 x 22.3 x 12.0mm |
| Packaging Quantity | tube | 25pcs |
| Storage Temperature Range | | -55°C to +125°C |
| Storage Humidity | | 95% RH max. |

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А