

## CG/CG2 Series



### Agency Approvals

| AGENCY                                                                            | AGENCY FILE NUMBER |
|-----------------------------------------------------------------------------------|--------------------|
|  | E128662            |
|  | E320116            |

### 2 Electrode GDT Graphical Symbol



### Description

Littelfuse highly reliable CG/CG2 Series GDTs provide a high degree of surge protection in a small size ideal for board level circuit protection.

GDTs function as switches which dissipate a minimum amount of energy and therefore handle currents that far surpass other types of transient voltage protection. Their gas-filled, rugged ceramic metal construction make them well suited to adverse environments.

The CG/CG2 series comes in a variety of forms including surface mount, core, straight and shaped leads, to serve a variety of mounting methods.

The CG Series (75-110V) is ideal for protection of test and communication equipment and other devices in which low voltage limits and extremely low arc voltages are required.

The CG2 Series (145V-1000V) is ideal for protecting equipment where higher voltage limits and holdover voltages are necessary.

### Features

- Rugged Ceramic-Metal construction
- Low Capacitance (<1.5pf)
- Meets REA PE-80
- Available in surface mount, and a variety of lead options options

### Applications

- Communication lines and equipment
- CATV equipment
- Test equipment
- Data lines
- Power supplies
- Instrumentation circuits
- Medical electronics
- ADSL equipment
- Telecom SLIC protection

### Electrical Characteristics

| Part Number          | Device Specifications (at 25°C)    |      |      |                                           |                                             |                                |                             | Life Ratings                                      |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
|----------------------|------------------------------------|------|------|-------------------------------------------|---------------------------------------------|--------------------------------|-----------------------------|---------------------------------------------------|------------------------------------|-----------------------------------------------|-------------------------------------------------------|--------------------------------------------|----------------------------------|----------------------------------------------------------------|--|
|                      | DC Breakdown in Volts<br>(@100V/s) |      |      | Impulse Break-down in Volts<br>(@100V/μs) | Impulse Break-down In Volts<br>(@1 Kv/μsec) | Insulation Resistance          | Capaci-<br>tance<br>(@1MHz) | Arc Voltage<br>(on state Voltage)<br>@1Amp<br>Min | Surge Life<br>(@500A<br>10/1000μs) | Nominal Impulse Discharge Current<br>(8/20μs) | Nominal AC Discharge Current<br>(10x1sec<br>@50-60Hz) | AC Discharge Current<br>(9 cycle<br>@50Hz) | DC Holdover Voltage <sup>2</sup> | Max Impulse Discharge Current<br>(1 Application<br>@ 10/350μs) |  |
|                      | MIN                                | TYP  | MAX  | MAX                                       |                                             | MIN                            | MAX                         | TYP                                               |                                    |                                               |                                                       |                                            | TYP                              |                                                                |  |
| CG75                 | 60                                 | 75   | 90   | 400                                       | 650                                         | 10 <sup>10</sup> Ω<br>(at 50V) | 1.5 pf                      | 15 V                                              | 400 shots                          | 10 shots<br>(@20kA) <sup>3</sup>              | 20 A                                                  | 100 A                                      | 52 V                             | 4kA                                                            |  |
| CG90                 | 72                                 | 90   | 108  | 400                                       | 600                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            | 80 V                             | 2.5kA                                                          |  |
| CG90 SN              | 72                                 | 90   | 108  | 400                                       | 600                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG110                | 88                                 | 110  | 132  | 450                                       | 600                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2145               | 116                                | 145  | 174  | 500                                       | 600                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2145 SN            | 120                                | 145  | 174  | 500                                       | 600                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2230               | 195                                | 230  | 265  | 600                                       | 700                                         | 135 V                          |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2230 SN            | 184                                | 230  | 276  | 600                                       | 700                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2250               | 213                                | 250  | 288  | 625                                       | 725                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2250 SN            | 200                                | 250  | 300  | 625                                       | 725                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2300               | 255                                | 300  | 345  | 700                                       | 800                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2300 SN            | 240                                | 300  | 360  | 700                                       | 800                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2350               | 297                                | 350  | 403  | 750                                       | 900                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2350 SN            | 280                                | 350  | 420  | 750                                       | 900                                         |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2420               | 357                                | 420  | 483  | 800                                       | 1000                                        |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2470               | 400                                | 470  | 540  | 850                                       | 1200                                        |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2470 SN            | 376                                | 470  | 564  | 850                                       | 1200                                        |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2600               | 510                                | 600  | 690  | 1000                                      | 1400                                        |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2600 SN            | 480                                | 600  | 720  | 1000                                      | 1400                                        |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |
| CG2800 <sup>1</sup>  | 680                                | 800  | 920  | 1200                                      | 1500                                        |                                |                             |                                                   |                                    | 10 shots<br>(@10kA)                           | 10 A                                                  | 65 A                                       |                                  |                                                                |  |
| CG21000 <sup>1</sup> | 850                                | 1000 | 1150 | 1500                                      | 1600                                        |                                |                             |                                                   |                                    |                                               |                                                       |                                            |                                  |                                                                |  |

#### NOTES:

1. Tested to UL1449 Third Edition

2. Reference REA PE-80, 0.2A. Tested to ITU-T Rec K.12 and REA PE 80 < 150 mSec.


### Product Characteristics

|                        |                                                                                                                                                                                                                                                                                                                            |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Materials</b>       | <b>LS, Axial:</b><br>Device: Tin Plated 2–5 Microns<br>Lead Wires: Tin Plated 17.5 ± 12.5 Microns<br>Construction: Ceramic Insulator<br><b>Core:</b><br>Device: Tin Plated 17.5 ± 12.5 Microns.<br>Construction: Ceramic Insulator<br><b>MS:</b><br>Device: Dull Tin Plated 7–9 Microns<br>Construction: Ceramic Insulator |
| <b>Product Marking</b> | LF Logo, Voltage and date code; Black in positive print                                                                                                                                                                                                                                                                    |


|                                              |                                                                                     |
|----------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Glow to arc transition current</b>        | < 0.5Amps                                                                           |
| <b>Glow Voltage</b>                          | 60-160 Volts                                                                        |
| <b>Storage and Operational Temperature</b>   | -40 to +90                                                                          |
| <b>Maximum Follow On Current<sup>1</sup></b> | 230 Volts r.m.s, 200 Amps.<br>(800V and 1000V devices tested to UL1449 3rd edition) |

### Device Dimensions


#### Leaded 'L' Type Straight Axial Devices




#### Core Devices



#### Leaded 'LS' Type Shaped Lead Devices




#### 'MS' Type Devices




### Soldering Parameters - Reflow Soldering (Surface Mount Devices)

|                                                       |                                    |                         |
|-------------------------------------------------------|------------------------------------|-------------------------|
| Reflow Condition                                      |                                    | Pb – Free assembly      |
| Pre Heat                                              | - Temperature Min ( $T_{s(min)}$ ) | 150°C                   |
|                                                       | - Temperature Max ( $T_{s(max)}$ ) | 200°C                   |
|                                                       | - Time (Min to Max) ( $t_s$ )      | 60 – 180 secs           |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak |                                    | 3°C/second max          |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                  |                                    | 5°C/second max          |
| Reflow                                                | - Temperature ( $T_L$ ) (Liquidus) | 217°C                   |
|                                                       | - Temperature ( $t_L$ )            | 60 – 150 seconds        |
| Peak Temperature ( $T_p$ )                            |                                    | 260 <sup>+0/-5</sup> °C |
| Time within 5°C of actual peak Temperature ( $t_p$ )  |                                    | 10 – 30 seconds         |
| Ramp-down Rate                                        |                                    | 6°C/second max          |
| Time 25°C to peak Temperature ( $T_p$ )               |                                    | 8 minutes Max.          |
| Do not exceed                                         |                                    | 260°C                   |



### Soldering Parameters - Wave Soldering (Thru-Hole Devices)



### Recommended Process Parameters:



| Wave Parameter                                                                                | Lead-Free Recommendation |
|-----------------------------------------------------------------------------------------------|--------------------------|
| <b>Preheat:</b><br>(Depends on Flux Activation Temperature) (Typical Industry Recommendation) |                          |
| Temperature Minimum:                                                                          | 100° C                   |
| Temperature Maximum:                                                                          | 150° C                   |
| Preheat Time:                                                                                 | 60-180 seconds           |
| <b>Solder Pot Temperature:</b>                                                                | 280° C Maximum           |
| <b>Solder Dwell Time:</b>                                                                     | 2-5 seconds              |

### Soldering Parameters - Hand Soldering



Solder Iron Temperature: 350° C +/- 5°C  
Heating Time: 5 seconds max.

### Packaging Dimensions



#### For 'L' Type Axial Lead Items



#### Core and 'MS' Type Items



#### For 'LS' Type Shaped Lead Items



### Part Numbering System and Ordering Information

| <b>CG2 XXX XX * XX</b>       |                                                                                                                                                                                                                                                                                                                                               |    |     |    |     |     |     |     |     |     |     |     |      |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|-----|----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| <b>Series</b>                | <p>CG – for 75, 90, or 110V</p> <p>CG2 – for 145V to 1000V</p>                                                                                                                                                                                                                                                                                |    |     |    |     |     |     |     |     |     |     |     |      |
| <b>Breakdown Voltage</b>     | <table> <tr><td>75</td><td>300</td></tr> <tr><td>90</td><td>350</td></tr> <tr><td>110</td><td>470</td></tr> <tr><td>145</td><td>600</td></tr> <tr><td>230</td><td>800</td></tr> <tr><td>250</td><td>1000</td></tr> </table>                                                                                                                   | 75 | 300 | 90 | 350 | 110 | 470 | 145 | 600 | 230 | 800 | 250 | 1000 |
| 75                           | 300                                                                                                                                                                                                                                                                                                                                           |    |     |    |     |     |     |     |     |     |     |     |      |
| 90                           | 350                                                                                                                                                                                                                                                                                                                                           |    |     |    |     |     |     |     |     |     |     |     |      |
| 110                          | 470                                                                                                                                                                                                                                                                                                                                           |    |     |    |     |     |     |     |     |     |     |     |      |
| 145                          | 600                                                                                                                                                                                                                                                                                                                                           |    |     |    |     |     |     |     |     |     |     |     |      |
| 230                          | 800                                                                                                                                                                                                                                                                                                                                           |    |     |    |     |     |     |     |     |     |     |     |      |
| 250                          | 1000                                                                                                                                                                                                                                                                                                                                          |    |     |    |     |     |     |     |     |     |     |     |      |
| <b>Lead Option Code</b>      | <p>(Blank) = No Leads / Core</p> <p>L = Straight Leads</p> <p>LS = Shaped Leads</p> <p>MS = Surface Mount</p>                                                                                                                                                                                                                                 |    |     |    |     |     |     |     |     |     |     |     |      |
| <b>Option Code*</b>          | <p>SN = may have different DC Breakover Voltage Limit. Please refer to Electrical Characteristics table for additional information.</p>                                                                                                                                                                                                       |    |     |    |     |     |     |     |     |     |     |     |      |
| <b>Packaging Option Code</b> | <p>(Blank) = No Leads / Core, Bulk Bag - 400 pcs</p> <p>L(Blank) = Straight Lead, Tray - 50 pcs</p> <p>LTR = Straight Lead, Tape &amp; Reel per EIA RS-296-E - 500 per reel</p> <p>LTE = Straight Lead, Tape &amp; Reel per IEC 60286-1 - 500 per reel</p> <p>LS(Blank) = Shaped Lead (see LS dimensions), Tape &amp; Reel - 500 per reel</p> |    |     |    |     |     |     |     |     |     |     |     |      |

#### Examples:

**CG75** – A non-leaded 75V device

**CG2230L** – A leaded 230V device

**CG2800LTR** – A leaded 800V device, tape-and-reel (per EIA standard RS-296-D)

#### Notes:

CG/CG2 devices with other breakdown voltages in the 75-1000 V range are available upon request.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А