

## ***SUPER-GRIP™ Cable Ties & Cable Tie Mounts***

Now More  
Sizes & Styles



### **Innovative Solution for Bundling Wire and Cable**

*SUPER-GRIP™* Cable Ties and Mounts are designed to withstand rough installation practices that occur in MRO and construction projects. *SUPER-GRIP™* Cable Ties provide superior bundle tightness, excellent tensile strength, and flexibility. *SUPER-GRIP™* Cable Ties resist lateral movement on the bundle because they are more flexible and can be installed tighter. *SUPER-GRIP™* Cable Tie Mounts are available in a wide variety of styles to maximize application flexibility. The *SUPER-GRIP™* product line expands the *PANDUIT* cable tie and accessory offering, the most comprehensive bundling solution available.

### ***Cable Ties Key Features***


### ***Benefits***

|                                        |                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b><i>High grip strength</i></b>       | Grips the bundle tightly, preventing ties from moving laterally along the length of the bundle                                    |
| <b><i>Thin, wide strap body</i></b>    | Improves tie flexibility while maintaining loop tensile strength, allowing cable tie to easily conform to irregular bundle shapes |
| <b><i>Distinctive flared neck</i></b>  | Offers improved strength and results in excellent small bundle performance                                                        |
| <b><i>Strong wedge and hinge</i></b>   | Improves tensile strength and enables the tie to withstand rough installation practices                                           |
| <b><i>Tapered tip</i></b>              | Threads easily into head for faster installation                                                                                  |
| <b><i>Aggressive tip grips</i></b>     | Allows temporary threading of tie, which permits positioning of tie prior to locking                                              |
| <b><i>Relief on bottom of head</i></b> | Reduces installed head height and minimizes gap between the head and bundle                                                       |

### ***Cable Tie Mounts Key Features***

### ***Benefits***

|                                      |                                                                                                                    |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b><i>Low profile design</i></b>     | Positions bundle closer to mounting surface to conserve space; reduces standoff height of cable bundle             |
| <b><i>Stronger bridge design</i></b> | Withstands rough installation practices beyond that of conventional designs; supports increased installation force |



Low Installed Head Height



Flared Neck



Tapered Tip with Aggressive Grips

## Ordering Information

### Cable Ties

| Cable Ties<br>Part Number |              | Material                          | Length<br>In.<br>(mm) | Width<br>In.<br>(mm) | Thickness<br>In.<br>(mm) | Max. Bundle<br>Diameter<br>In.<br>(mm) | Min. Loop<br>Tensile<br>Strength<br>Lbs. (N) | Recommended<br>Tools                                               | Packaging            |                      |                      |                      |
|---------------------------|--------------|-----------------------------------|-----------------------|----------------------|--------------------------|----------------------------------------|----------------------------------------------|--------------------------------------------------------------------|----------------------|----------------------|----------------------|----------------------|
| Standard                  | Bulk         |                                   |                       |                      |                          |                                        |                                              |                                                                    | Std.<br>Pkg.<br>Qty. | Std.<br>Ctn.<br>Qty. | Bulk<br>Pkg.<br>Qty. | Bulk<br>Ctn.<br>Qty. |
| SG100M-C                  | SG100M-M     | Nylon 6.6                         | 4.2<br>(106)          | .118<br>(3.0)        | .038<br>(1.0)            | 1.00<br>(25)                           | 18<br>(80)                                   | GTS, GTSL,<br>GS2B, PTS,<br>PPTS, STS2                             | 100                  | 1000                 | 1000                 | 50000                |
| SG100M-C0                 | SG100M-M0    | Weather<br>Resistant<br>Nylon 6.6 | 4.2<br>(106)          | .118<br>(3.0)        | .038<br>(1.0)            | 1.00<br>(25)                           | 18<br>(80)                                   |                                                                    | 100                  | 1000                 | 1000                 | 50000                |
| SG150I-C                  | SG150I-M     | Nylon 6.6                         | 6.2<br>(157)          | .168<br>(4.3)        | .040<br>(1.0)            | 1.50<br>(38)                           | 40<br>(178)                                  | GTS, GTSL,<br>GS2B, PTS,<br>PPTS, STS2                             | 100                  | 1000                 | 1000                 | 25000                |
| SG150I-C0                 | SG150I-M0    | Weather<br>Resistant<br>Nylon 6.6 | 6.2<br>(157)          | .168<br>(4.3)        | .040<br>(1.0)            | 1.50<br>(38)                           | 40<br>(178)                                  |                                                                    | 100                  | 1000                 | 1000                 | 25000                |
| SG200S-C                  | SG200S-M     | Nylon 6.6                         | 8.3<br>(211)          | .225<br>(5.7)        | .046<br>(1.2)            | 2.00<br>(51)                           | 50<br>(222)                                  | GTS, GTSL,<br>GS2B, GTH,<br>GS4H, PTS,<br>PTH, PPTS,<br>STS2, STH2 | 100                  | 1000                 | 1000                 | 10000                |
| SG200S-C0                 | SG200S-M0    | Weather<br>Resistant<br>Nylon 6.6 | 8.3<br>(211)          | .225<br>(5.7)        | .046<br>(1.2)            | 2.00<br>(51)                           | 50<br>(222)                                  |                                                                    | 100                  | 1000                 | 1000                 | 10000                |
| —                         | SG200S-M30   | Heat<br>Stabilized<br>Nylon 6.6   | 8.3<br>(211)          | .225<br>(5.7)        | .046<br>(1.2)            | 2.00<br>(51)                           | 50<br>(222)                                  |                                                                    | —                    | —                    | 1000                 | 10000                |
| SG250S-C                  | —            | Nylon 6.6                         | 10.4<br>(264)         | .225<br>(5.7)        | .050<br>(1.3)            | 2.60<br>(66)                           | 70<br>(311)                                  | GTS, GTSL,<br>GS2B, GTH,<br>GS4H, PTS,<br>PTH, PPTS,<br>STS2, STH2 | 100                  | 1000                 | —                    | —                    |
| SG250S-C0                 | —            | Weather<br>Resistant<br>Nylon 6.6 | 10.4<br>(264)         | .225<br>(5.7)        | .050<br>(1.3)            | 2.60<br>(66)                           | 70<br>(311)                                  |                                                                    | 100                  | 1000                 | —                    | —                    |
| SG300S-C                  | SG300S-M     | Nylon 6.6                         | 12.4<br>(315)         | .225<br>(5.7)        | .050<br>(1.3)            | 3.20<br>(81)                           | 70<br>(311)                                  |                                                                    | 100                  | 1000                 | 1000                 | 10000                |
| SG300S-C0                 | SG300S-M0    | Weather<br>Resistant<br>Nylon 6.6 | 12.4<br>(315)         | .225<br>(5.7)        | .050<br>(1.3)            | 3.20<br>(81)                           | 70<br>(311)                                  |                                                                    | 100                  | 1000                 | 1000                 | 10000                |
| —                         | SG300S-M30   | Heat<br>Stabilized<br>Nylon 6.6   | 12.4<br>(315)         | .225<br>(5.7)        | .050<br>(1.3)            | 3.20<br>(81)                           | 70<br>(311)                                  |                                                                    | —                    | —                    | 1000                 | 10000                |
| SG370S-C                  | SG370S-M     | Nylon 6.6                         | 15.3<br>(389)         | .225<br>(5.7)        | .052<br>(1.3)            | 4.20<br>(107)                          | 70<br>(311)                                  |                                                                    | 100                  | 1000                 | 1000                 | 5000                 |
| SG370S-C0                 | SG370S-M0    | Weather<br>Resistant<br>Nylon 6.6 | 15.3<br>(389)         | .225<br>(5.7)        | .052<br>(1.3)            | 4.20<br>(107)                          | 70<br>(311)                                  |                                                                    | 100                  | 1000                 | 1000                 | 5000                 |
| SG350LH-L                 | SG350LH-TL   | Nylon 6.6                         | 15.3<br>(389)         | .330<br>(8.4)        | .064<br>(1.6)            | 4.13<br>(105)                          | 120<br>(534)                                 | GTH, GS4H,<br>GS4EH, PTH,<br>STH2, ST3EH                           | 50                   | 500                  | 250                  | 2500                 |
| SG350LH-L0                | SG350LH-TL0  | Weather<br>Resistant<br>Nylon 6.6 | 15.3<br>(389)         | .330<br>(8.4)        | .064<br>(1.6)            | 4.13<br>(105)                          | 120<br>(534)                                 |                                                                    | 50                   | 500                  | 250                  | 2500                 |
| —                         | SG350LH-TL30 | Heat<br>Stabilized<br>Nylon 6.6   | 15.3<br>(389)         | .330<br>(8.4)        | .064<br>(1.6)            | 4.13<br>(105)                          | 120<br>(534)                                 |                                                                    | —                    | —                    | 250                  | 2500                 |
| SG450H-L                  | SG450H-C     | Nylon 6.6                         | 18.6<br>(471)         | .380<br>(9.7)        | .068<br>(1.7)            | 5.20<br>(132)                          | 175<br>(778)                                 | GTH, GS4H,<br>GS4EH, PTH,<br>STH2, ST3EH                           | 50                   | 500                  | 100                  | 2000                 |
| SG450H-L0                 | SG450H-C0    | Weather<br>Resistant<br>Nylon 6.6 | 18.6<br>(471)         | .380<br>(9.7)        | .068<br>(1.7)            | 5.20<br>(132)                          | 175<br>(778)                                 |                                                                    | 50                   | 500                  | 100                  | 2000                 |


## SUPER-GRIP™ Cable Tie Mounts



SGABM20-A-C



SGABM25-A-C



SGABM25-AT-C0



SGTA1S8-C

## Adhesive Backed Mounts


| Part Number   | Material                       | Used With Cable Ties                                                  | Length<br>In.<br>(mm) | Width<br>In.<br>(mm) | Mounting Method        | Std.<br>Pkg.<br>Qty. | Std.<br>Ctn.<br>Qty. |
|---------------|--------------------------------|-----------------------------------------------------------------------|-----------------------|----------------------|------------------------|----------------------|----------------------|
| SGABM20-A-C   | Nylon 6.6                      | SG100M, SG150I                                                        | .75<br>(19.0)         | .75<br>(19.0)        | Rubber Based Adhesive  | 100                  | 500                  |
| SGABM20-AT-C0 | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I                                                        | .75<br>(19.0)         | .75<br>(19.0)        | Acrylic Based Adhesive | 100                  | 500                  |
| SGABM25-A-C   | Nylon 6.6                      | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S                     | 1.00<br>(25.4)        | 1.00<br>(25.4)       | Rubber Based Adhesive  | 100                  | 1000                 |
| SGABM25-AT-C0 | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S                     | 1.00<br>(25.4)        | 1.00<br>(25.4)       | Acrylic Based Adhesive | 100                  | 1000                 |
| SGABM25-S6-C  | Nylon 6.6                      | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S                     | 1.00<br>(25.4)        | 1.00<br>(25.4)       | #6 (M3) Screw          | 100                  | 1000                 |
| SGABM25-S6-C0 | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S                     | 1.00<br>(25.4)        | 1.00<br>(25.4)       | #6 (M3) Screw          | 100                  | 1000                 |
| SGABM30-A-C   | Nylon 6.6                      | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S                     | 1.12<br>(28.5)        | 1.12<br>(28.5)       | Rubber Based Adhesive  | 100                  | 500                  |
| SGABM30-AT-C0 | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S                     | 1.12<br>(28.5)        | 1.12<br>(28.5)       | Acrylic Based Adhesive | 100                  | 500                  |
| SGABM40-A-L   | Nylon 6.6                      | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S,<br>SG350LH, SG450H | 1.50<br>(38.1)        | 1.50<br>(38.1)       | Rubber Based Adhesive  | 100                  | 500                  |
| SGABM40-AT-L0 | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S,<br>SG350LH, SG450H | 1.50<br>(38.1)        | 1.50<br>(38.1)       | Acrylic Based Adhesive | 100                  | 500                  |
| SGABM50-A-L   | Nylon 6.6                      | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S,<br>SG350LH, SG450H | 2.00<br>(50.8)        | 2.00<br>(50.8)       | Rubber Based Adhesive  | 100                  | 500                  |
| SGABM50-AT-L0 | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S,<br>SG350LH, SG450H | 2.00<br>(50.8)        | 2.00<br>(50.8)       | Acrylic Based Adhesive | 100                  | 500                  |

## Screw Applied Tie Anchor Mounts

| Part Number | Material                       | Used With Cable Ties                              | Length<br>In.<br>(mm) | Width<br>In.<br>(mm) | Mounting Method | Std.<br>Pkg.<br>Qty. | Std.<br>Ctn.<br>Qty. |
|-------------|--------------------------------|---------------------------------------------------|-----------------------|----------------------|-----------------|----------------------|----------------------|
| SGTA1S8-C   | Nylon 6.6                      | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S | .80<br>(20.3)         | .37<br>(9.4)         | #8 (M4) Screw   | 100                  | 500                  |
| SGTA1S8-C0  | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S | .80<br>(20.3)         | .37<br>(9.4)         | #8 (M4) Screw   | 100                  | 500                  |



**SGMPM**



**SGTMS8-C**

## Masonry Push Mounts

| Part Number         | Material                                          | Used With Cable Ties                                                  | Grip Length<br>In.<br>(mm) | Hole Diameter<br>In.<br>(mm) | Mounting Method | Std.<br>Pkg.<br>Qty. | Std.<br>Ctn.<br>Qty. |
|---------------------|---------------------------------------------------|-----------------------------------------------------------------------|----------------------------|------------------------------|-----------------|----------------------|----------------------|
| <b>SGMPMS19-C0</b>  | Impact Modified<br>Weather Resistant<br>Nylon 6.6 | SG100M, SG150I,<br>SG200S, SG250S,<br>SG300S, SG370S                  | .97<br>(24.6)              | .187<br>(4.7)                | Tree Barb       | 100                  | 500                  |
| <b>SGMPMS25-C0</b>  |                                                   | SG100M, SG150I,<br>SG200S, SG250S,<br>SG300S, SG370S                  | .97<br>(24.6)              | .250<br>(6.4)                |                 | 100                  | 500                  |
| <b>SGMPMH38-L0</b>  |                                                   | SG100M, SG150I,<br>SG200S, SG250S, SG300S,<br>SG370S, SG350LH, SG450H | 1.25<br>(31.8)             | .375<br>(9.5)                |                 | 50                   | 500                  |
| <b>SGMPMWH32-L0</b> |                                                   | SG100M, SG150I,<br>SG200S, SG250S, SG300S,<br>SG370S, SG350LH, SG450H | 1.41<br>(35.8)             | .315<br>(8.0)                |                 | 50                   | 500                  |

## Screw Applied Tie Mounts

| Part Number        | Material                       | Used With Cable Ties                                          | Length<br>In.<br>(mm) | Width<br>In.<br>(mm) | Mounting Method | Std.<br>Pkg.<br>Qty. | Std.<br>Ctn.<br>Qty. |
|--------------------|--------------------------------|---------------------------------------------------------------|-----------------------|----------------------|-----------------|----------------------|----------------------|
| <b>SGTM1S6-C</b>   | Nylon 6.6                      | SG100M                                                        | .51<br>(13.0)         | .37<br>(9.4)         | #6 (M3) Screw   | 100                  | 500                  |
| <b>SGTM1S6-C0</b>  | Weather Resistant<br>Nylon 6.6 | SG100M                                                        | .51<br>(13.0)         | .37<br>(9.4)         | #6 (M3) Screw   | 100                  | 500                  |
| <b>SGTM2S8-C</b>   | Nylon 6.6                      | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S             | .66<br>(16.7)         | .48<br>(12.2)        | #8 (M4) Screw   | 100                  | 500                  |
| <b>SGTM2S8-C0</b>  | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I, SG200S,<br>SG250S, SG300S, SG370S             | .66<br>(16.7)         | .48<br>(12.2)        | #8 (M4) Screw   | 100                  | 500                  |
| <b>SGTM3S10-C</b>  | Nylon 6.6                      | SG100M, SG150I, SG200S,<br>SG250S, SG300S,<br>SG370S, SG350LH | .91<br>(23.1)         | .61<br>(15.4)        | #10 (M5) Screw  | 100                  | 500                  |
| <b>SGTM3S10-C0</b> | Weather Resistant<br>Nylon 6.6 | SG100M, SG150I, SG200S,<br>SG250S, SG300S,<br>SG370S, SG350LH | .91<br>(23.1)         | .61<br>(15.4)        | #10 (M5) Screw  | 100                  | 500                  |

### WORLDWIDE SUBSIDIARIES AND SALES OFFICES

**PANDUIT CANADA**  
Markham, Ontario  
cs-cdn@panduit.com  
Phone: 800.777.3300

**PANDUIT EUROPE LTD.**  
London, UK  
cs-emea@panduit.com  
Phone: 44.20.8601.7200

**PANDUIT SINGAPORE PTE. LTD.**  
Republic of Singapore  
cs-ap@panduit.com  
Phone: 65.6379.6700

**PANDUIT JAPAN**  
Tokyo, Japan  
cs-japan@panduit.com  
Phone: 81.3.3767.7011

**PANDUIT LATIN AMERICA**  
Jalisco, Mexico  
cs-la@panduit.com  
Phone: 52.333.777.6000

**PANDUIT AUSTRALIA PTY. LTD.**  
Victoria, Australia  
cs-aus@panduit.com  
Phone: 61.3.9794.9020

For a copy of *PANDUIT* product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)



**For more information**  
**Visit us at [www.panduit.com](http://www.panduit.com)**

**Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)**  
**or by phone: 800-777-3300 and reference CTCB14**

©2006 *PANDUIT* Corp.  
ALL RIGHTS RESERVED.  
Printed in the U.S.A.  
Product Bulletin Number **SA-CTCB14**  
replaces SA-CTCB12  
6/2006

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А