


1

2

3

4

| FCI PART NO. | POWER TYPE | LENGTH "X" |
|--------------------|------------|------------|
| 10084088-Z0050YYLF | 12V | 500+25/-0 |
| 10084088-Z0100YYLF | 12V | 1000±15 |
| 10084088-Z0300YYLF | 12V | 3000±25 |
| 10084088-Z0500YYLF | 12V | 5000±25 |



| PIN ASSIGNMENT | | | | |
|----------------|-------------|------------|----------|-------|
| END A | SIGNAL NAME | WIRE COLOR | WIRE AWG | END B |
| 1 | VBUS (+5V) | RED | 20 | - |
| 2 | DATA - | WHITE | 28 | - |
| 3 | DATA + | GREEN | 28 | - |
| 4 | GND | BLACK | 20 | - |
| 5 | 12V GND | BLUE | 20 | - |
| 6 | +12V | BROWN | 20 | - |
| 7 | +12V | ORANGE | 20 | - |
| 8 | 12V GND | YELLOW | 20 | - |
| SHELL | FRAME GND | - | SHIELD | - |

Mark with
10075076001
REV. proi_revision
in area indicated
by X....

| rev | ecn no | dr | date |
|-----|----------|----|-----------|
| A | N08-0120 | ST | 6/18/2008 |

| TOLERANCES UNLESS OTHERWISE SPECIFIED | | | |
|---------------------------------------|----|-----|--|
| | | | |
| LINEAR | | | |
| ANGULAR | 0° | ±2° | |

| Material | | Spec ref | | spec_ref | |
|----------------|--------------|--------------------------|----------------|--------------|-------|
| Mat code | | surface | tolerance | projection | MM |
| Heattreat | | ISO 1302 | ISO 406 | | ←→ |
| Plating/Finish | | | ISO 1101 | size | Scale |
| Dr | Sunny Tsai | 10/11/2007 | | A3 | - |
| Eng | Sunny Tsai | 10/11/2007 | Product family | CABLE ASS'Y | |
| Chr | Jackson Wang | 10/11/2007 | Model Name | ECN | |
| Appr | Jackson Wang | 10/11/2007 | Model Revision | REL Level | |
| FCI | | title | | no | |
| | | SINGLE END POWER USB 12V | | 10084088 | |
| | | CABLE ASSEMBLY - BLACK | | Rev. | |
| Pro/E file | | catalog no | | A | |
| | | CUSTOMER DWG | | sheet 1 of 3 | |

REV F - 2006-04-17

2

3 PDM: Rev:A

STATUS Released

Printed: Jul 10, 2009

FCI CONFIDENTIAL



This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.


FCI PART NO. SEE SHEET 1

NOTES:

- 1. MATES WITH FCI PART NUMBER: 55917/57496.
- 2. UNLESS OTHERWISE SPECIFIED ASSEMBLED LENGTH TOLERANCE=
 - =< 1 METER= ±15.0mm
 - > 1 METER TO 10 METER= ±2% OF L1 OR L2
 - > 10 METER= +0%/-4% OF L1 OR L2

3. PART NUMBER SCHEME FOR CABLE ASSEMBLY:

10084088 - Z X X X X Y Y LF



- 4. UNLESS OTHERWISE SPECIFIED LABEL POSITION SHALL BE APPROXIMATELY 60mm FROM REAR OF CONNECTOR.
- 5. UNLESS OTHERWISE SPECIFIED STANDARD LABEL SHALL BE BRADY LABEL P/N THT-10-427-30.

LABEL DETAILS:

| | | |
|--------------------|-----|---------------------------|
| FCI | --- | MANUFACTURER CODE OR NAME |
| 10084088-ZXXXXYYLF | --- | FCI P/N |
| REV.A | --- | REVISION |
| WWYY | --- | DATE CODE WWYY FORMAT |
| MADE IN CHINA | --- | COUNTRY ORIGIN |

- 6. ALL CABLE ASSEMBLIES SHALL BE TESTED 100% FOR CONTINUITY AS DEFINED IN WIRING LIST.

- 7. UNLESS OTHERWISE SPECIFIED ALL CABLE ASSEMBLIES SHALL BE 100% HI-POT TESTED BY APPLYING 300V DC FOR MINIMUM OF 10ms, UNLESS ACTIVE COMPONENTS ARE USED IN THIS ASSEMBLY.
- 8. OTHER TESTING PERFORMED AS REQUIRED:
 - DIELECTRIC RESISTANCE: 50M Ohms MIN.
 - CONNECTION RESISTANCE: 0.8 Ohms MAX. (-Z0050YYLF, 0.5MR LENGTH)
 - 1.0 Ohms MAX. (-Z0100YYLF, 1.0MR LENGTH)
 - 1.2 Ohms MAX. (-Z0300YYLF, 3.0MR LENGTH)
 - 1.8 Ohms MAX. (-Z0500YYLF, 5.0MR LENGTH)
- 9. THIS DIMENSION IS A FINISHED PRODUCT LENGTH.
- 10. LEAD FREE PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- 11. CONNECTOR ASSEMBLIES SHOWN ARE FOR REFERENCE ONLY AND MAY NOT SHOWN ALL PART DETAIL, REFERENCE CONNECTOR ASSEMBLY DRAWINGS FOR COMPLETE DETAILS.
- 12. PACKAGE: EACH CABLE ASSEMBLY IN CLDEAR ZIP-LOCK BPLY BAG, THEN BULK PACKED IN A BOX.

| Mark with 10075076001 REV. prai_revision in area indicated by X.... | | | |
|---|-------------|----|------|
| rev | ecn no | dr | date |
| - | See sheet 1 | - | - |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |

| | | | | | | |
|----------------|--------------|------------|---|-----------|--------------|---------|
| Material | | | Spec ref | | spec_ref | |
| Mat code | | | surface | tolerance | projection | MM |
| Heat treat | | | ISO 1302 | ISO 406 | | ← → |
| Plating/Finish | | | | ISO 1101 | | |
| Dr | Sunny Tsai | 10/11/2007 | Product family | | CABLE ASS'Y | size A3 |
| Eng | Sunny Tsai | 10/11/2007 | Model Name | | ECN | Scale - |
| Chr | Jackson Wang | 10/11/2007 | Model Revision | | REL Level | |
| Appr | Jackson Wang | 10/11/2007 | | | | |
| FCI | | | title | | Rev. | |
| | | | SINGLE END POWER USB 12V CABLE ASSEMBLY - BLACK | | A | |
| Pro/E file | | | catalog no | | CUSTOMER DWG | |
| | | | | | sheet 2 of 3 | |

| TOLERANCES UNLESS OTHERWISE SPECIFIED | | | |
|---------------------------------------|----|-----|--|
| LINEAR | | | |
| | | | |
| ANGULAR | 0° | ±2° | |

FCI CONFIDENTIAL



This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

FCI PART NO. SEE SHEET 1

NOTES:

13. COMPONENT DETAIL

A) Pwr USB CONNECTOR KIT:

| MATERIALS | SPECIFICATIONS |
|---------------------------------|--|
| SHELLS | HIGH STRENGTH COPPER ALLOY |
| HOUSINGS | THERMOPLASTIC UL94V-0 RATED, COLOR: TEAL |
| TERMINALS | HIGH STRENGTH COPPER ALLOY |
| COVERS | THERMOPLASTIC UL94V-0 RATED PEBBLE GRAY |
| PLATING | |
| SHELL | UNDERPLATE; 40 MICROINCHES NI 100 MICROINCHES MIN BRIGHT TIN |
| TERMINALS | UNDERPLATE; 40 MICROINCHES NI CONTACT AREA; 30 MICROINCHES GXT TAIL AREA; 100 MICROINCHES MATTED TIN |
| ELECTRICAL | |
| VOLTAGE RATING | USB;5.25VDC,+POWER;12VDC |
| DIELECTRIC WITHSTANDING VOLTAGE | 750 VAC |
| INSUL. RESISTANCE | 1000 MEG OHMS AT 500 VDC |
| CURRENT RATING(NOTE 1) | 1.50A USB SECTION 3.00A POWER SECTION |

B) Pwr USB CABLE:

SPEC: 28AWG*1P+20AWG*6C+AL/MYLAR+DRAIN+BRAID

1) UL TYPE: CM
CSA TYPE: CMG

2) CONSTRUCTION:

| ITEM | SPECIFICATIONS | | |
|------------|----------------|--|---------------|
| CONDUCTOR | AWG | 28AWG | 20AWG |
| | MATERIAL | TINNED COPPER | TINNED COPPER |
| | COND.SIZE | 7/0.127mm | 19/0.20mm |
| INSULATION | MATERIAL | HD-PE | SR-PVC |
| | OD | 0.80±0.05mm | 1.5±0.05mm |
| | NO. | 1PAIR | 6C |
| AL/MYLAR | COVERAGE | 100% | |
| | OVERLAP | 25% Min. | |
| DRAIN | AWG | 28AWG | |
| | MATERIAL | TINNED COPPER | |
| | COND.SIZE | 7/0.127mm | |
| BRAID | MATERIAL | TINNED COPPER | |
| | SIZE | 16/7/0.10mm | |
| JACKET | MATERIAL | PVC | |
| | OD | 6.50±0.25mm | |
| | COLOR | BLACK (OTHER COLORS AVAILABLE ON REQUEST) | |

ELECTRICAL CHARACTERISTICS

| | |
|------------------------------------|--|
| RATING | RATING: TEMP 80°C VOLTAGE 30V |
| Conductor Resistance at 20°C (MAX) | 28AWG < 237.25 Ohm/KM 20AWG < 34.6 Ohm/KM |
| IMPEDANCE (Differential) | 90 Ohm±15%; at TDR |
| DELAY | < 26ns/Cable; at TDR |
| SKEW | 100ps MAX. |
| ATTENUATION | Refer to USB 2.0 Specification |

FCI CONFIDENTIAL



This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

Mark with 10075076001 REV. prai_revision in area indicated by X....

| rev | ecn no | dr | date |
|-----|-------------|----|------|
| - | See Sheet 1 | - | - |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |

| Material | Spec ref | spec_ref | projection | MM |
|-------------------|--|---------------------|--------------|-------|
| Mat code | surface | tolerance | | |
| Heat treat | ISO 1302 | ISO 406 ISO 1101 | | |
| Plating/Finish | | | size | Scale |
| Dr Sunny Tsai | 10/11/2007 | | A3 | - |
| Eng Sunny Tsai | 10/11/2007 | Product family | | |
| Chr Jackson Wang | 10/11/2007 | Model Name | | |
| Appr Jackson Wang | 10/11/2007 | Model Revision | | |
| | | | ECN | |
| | | | REL Level | |
| | title | cu dwg | | Rev. |
| | SINGLE END POWER USB 12V CABLE ASSEMBLY - BLACK | 10084088 | | A |
| Pro/E file | catalog no | CUSTOMER DWG | sheet 3 of 3 | |

| TOLERANCES UNLESS OTHERWISE SPECIFIED | | | |
|---------------------------------------|----|-----|--|
| LINEAR | | | |
| ANGULAR | 0° | ±2° | |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А