

# Dual 1-of-4 Decoder/Demultiplexer


## High-Speed Silicon-Gate CMOS

**IN74AC139**

The IN74AC139 is identical in pinout to the LS/ALS139, HC/HCT139. The device inputs are compatible with standard CMOS outputs; with pullup resistors, they are compatible with LS/ALS outputs.

This device consists of two independent 1-of-4 decoders, each of which decodes a two-bit Address to one-of-four active-low outputs. Active-low Selects are provided to facilitate the demultiplexing and cascading functions. The demultiplexing function is accomplished by using the Address inputs to select the desired device output, and utilizing the Select as a data input.

- Outputs Directly Interface to CMOS, NMOS, and TTL
- Operating Voltage Range: 2.0 to 6.0 V
- Low Input Current: 1.0  $\mu$ A; 0.1  $\mu$ A @ 25°C
- High Noise Immunity Characteristic of CMOS Devices
- Outputs Source/Sink 24 mA




### ORDERING INFORMATION

IN74AC139N Plastic

IN74AC139D SOIC

$T_A = -40^\circ$  to  $85^\circ$  C for all packages

### LOGIC DIAGRAM



PIN 16 =  $V_{CC}$   
PIN 8 = GND

### PIN ASSIGNMENT

|                     |   |    |                     |
|---------------------|---|----|---------------------|
| SELECT <sub>a</sub> | 1 | 16 | $V_{CC}$            |
| A0 <sub>a</sub>     | 2 | 15 | SELECT <sub>b</sub> |
| A1 <sub>a</sub>     | 3 | 14 | A0 <sub>b</sub>     |
| Y0 <sub>a</sub>     | 4 | 13 | A1 <sub>b</sub>     |
| Y1 <sub>a</sub>     | 5 | 12 | Y0 <sub>b</sub>     |
| Y2 <sub>a</sub>     | 6 | 11 | Y1 <sub>b</sub>     |
| Y3 <sub>a</sub>     | 7 | 10 | Y2 <sub>b</sub>     |
| GND                 | 8 | 9  | Y3 <sub>b</sub>     |

### FUNCTION TABLE

| Inputs |    |    | Outputs |    |    |    |
|--------|----|----|---------|----|----|----|
| Select | A1 | A0 | Y0      | Y1 | Y2 | Y3 |
| H      | X  | X  | H       | H  | H  | H  |
| L      | L  | L  | L       | H  | H  | H  |
| L      | L  | H  | H       | L  | H  | H  |
| L      | H  | L  | H       | H  | L  | H  |
| L      | H  | H  | H       | H  | H  | L  |

X = don't care

**MAXIMUM RATINGS\***

| Symbol    | Parameter                                                                        | Value                  | Unit |
|-----------|----------------------------------------------------------------------------------|------------------------|------|
| $V_{CC}$  | DC Supply Voltage (Referenced to GND)                                            | -0.5 to +7.0           | V    |
| $V_{IN}$  | DC Input Voltage (Referenced to GND)                                             | -0.5 to $V_{CC} + 0.5$ | V    |
| $V_{OUT}$ | DC Output Voltage (Referenced to GND)                                            | -0.5 to $V_{CC} + 0.5$ | V    |
| $I_{IN}$  | DC Input Current, per Pin                                                        | $\pm 20$               | mA   |
| $I_{OUT}$ | DC Output Sink/Source Current, per Pin                                           | $\pm 50$               | mA   |
| $I_{CC}$  | DC Supply Current, $V_{CC}$ and GND Pins                                         | $\pm 50$               | mA   |
| $P_D$     | Power Dissipation in Still Air, Plastic DIP+<br>SOIC Package+                    | 750<br>500             | mW   |
| Tstg      | Storage Temperature                                                              | -65 to +150            | °C   |
| $T_L$     | Lead Temperature, 1 mm from Case for 10 Seconds<br>(Plastic DIP or SOIC Package) | 260                    | °C   |

\*Maximum Ratings are those values beyond which damage to the device may occur.  
Functional operation should be restricted to the Recommended Operating Conditions.

+Derating - Plastic DIP: - 10 mW/°C from 65° to 125°C

SOIC Package: - 7 mW/°C from 65° to 125°C

**RECOMMENDED OPERATING CONDITIONS**

| Symbol                             | Parameter                                            | Min | Max             | Unit |
|------------------------------------|------------------------------------------------------|-----|-----------------|------|
| V <sub>CC</sub>                    | DC Supply Voltage (Referenced to GND)                | 2.0 | 6.0             | V    |
| V <sub>IN</sub> , V <sub>OUT</sub> | DC Input Voltage, Output Voltage (Referenced to GND) | 0   | V <sub>CC</sub> | V    |
| T <sub>J</sub>                     | Junction Temperature (PDIP)                          |     | 140             | °C   |
| T <sub>A</sub>                     | Operating Temperature, All Package Types             | -40 | +85             | °C   |
| I <sub>OH</sub>                    | Output Current - High                                |     | -24             | mA   |
| I <sub>OL</sub>                    | Output Current - Low                                 |     | 24              | mA   |
| t <sub>r</sub> , t <sub>f</sub>    | Input Rise and Fall Time *                           |     |                 |      |
|                                    | V <sub>CC</sub> =3.0 V                               | 0   | 150             | ns/V |
|                                    | V <sub>CC</sub> =4.5 V                               | 0   | 40              |      |
| V <sub>CC</sub> =5.5 V             | 0                                                    | 25  |                 |      |

\*  $V_{IN}$  from 30% to 70%  $V_{CC}$

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{IN}$  and  $V_{OUT}$  should be constrained to the range  $GND \leq (V_{IN} \text{ or } V_{OUT}) \leq V_{CC}$ .

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

**DC ELECTRICAL CHARACTERISTICS** (Voltages Referenced to GND)

| Symbol           | Parameter                                      | Test Conditions                                                                 | V <sub>CC</sub><br>V | Guaranteed Limits   |                     | Unit |
|------------------|------------------------------------------------|---------------------------------------------------------------------------------|----------------------|---------------------|---------------------|------|
|                  |                                                |                                                                                 |                      | 25 °C               | -40°C to 85°C       |      |
| V <sub>IH</sub>  | Minimum High-Level Input Voltage               | V <sub>OUT</sub> =0.1 V or V <sub>CC</sub> -0.1 V                               | 3.0<br>4.5<br>5.5    | 2.1<br>3.15<br>3.85 | 2.1<br>3.15<br>3.85 | V    |
| V <sub>IL</sub>  | Maximum Low - Level Input Voltage              | V <sub>OUT</sub> =0.1 V or V <sub>CC</sub> -0.1 V                               | 3.0<br>4.5<br>5.5    | 0.9<br>1.35<br>1.65 | 0.9<br>1.35<br>1.65 | V    |
| V <sub>OH</sub>  | Minimum High-Level Output Voltage              | I <sub>OUT</sub> ≤ -50 µA                                                       | 3.0<br>4.5<br>5.5    | 2.9<br>4.4<br>5.4   | 2.9<br>4.4<br>5.4   | V    |
|                  |                                                | *V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> =-12 mA | 3.0                  | 2.56                | 2.46                |      |
|                  |                                                | I <sub>OH</sub> =-24 mA                                                         | 4.5                  | 3.86                | 3.76                |      |
|                  |                                                | I <sub>OH</sub> =-24 mA                                                         | 5.5                  | 4.86                | 4.76                |      |
| V <sub>OL</sub>  | Maximum Low-Level Output Voltage               | I <sub>OUT</sub> ≤ 50 µA                                                        | 3.0<br>4.5<br>5.5    | 0.1<br>0.1<br>0.1   | 0.1<br>0.1<br>0.1   | V    |
|                  |                                                | *V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OL</sub> =12 mA  | 3.0                  | 0.36                | 0.44                |      |
|                  |                                                | I <sub>OL</sub> =24 mA                                                          | 4.5                  | 0.36                | 0.44                |      |
|                  |                                                | I <sub>OL</sub> =24 mA                                                          | 5.5                  | 0.36                | 0.44                |      |
| I <sub>IN</sub>  | Maximum Input Leakage Current                  | V <sub>IN</sub> =V <sub>CC</sub> or GND                                         | 5.5                  | ±0.1                | ±1.0                | µA   |
| I <sub>OLD</sub> | +Minimum Dynamic Output Current                | V <sub>OLD</sub> =1.65 V Max                                                    | 5.5                  |                     | 75                  | mA   |
| I <sub>OHD</sub> | +Minimum Dynamic Output Current                | V <sub>OHD</sub> =3.85 V Min                                                    | 5.5                  |                     | -75                 | mA   |
| I <sub>CC</sub>  | Maximum Quiescent Supply Current (per Package) | V <sub>IN</sub> =V <sub>CC</sub> or GND                                         | 5.5                  | 8.0                 | 80                  | µA   |

\* All outputs loaded; thresholds on input associated with output under test.

+Maximum test duration 2.0 ms, one output loaded at a time.

Note: I<sub>IN</sub> and I<sub>CC</sub> @ 3.0 V are guaranteed to be less than or equal to the respective limit @ 5.5 V V<sub>CC</sub>


**AC ELECTRICAL CHARACTERISTICS** ( $C_L=50\text{pF}$ , Input  $t_r=t_f=3.0\text{ ns}$ )

| Symbol           | Parameter                                          | V <sub>CC</sub> <sup>*</sup><br>V | Guaranteed Limits |             |               |           | Unit |
|------------------|----------------------------------------------------|-----------------------------------|-------------------|-------------|---------------|-----------|------|
|                  |                                                    |                                   | 25 °C             |             | -40°C to 85°C |           |      |
|                  |                                                    |                                   | Min               | Max         | Min           | Max       |      |
| t <sub>PLH</sub> | Propagation Delay , Input A to Output Y (Figure 2) | 3.3<br>5.0                        | 4.0<br>3.0        | 11.5<br>8.5 | 3.5<br>2.5    | 13<br>9.5 | ns   |
| t <sub>PHL</sub> | Propagation Delay , Input A to Output Y (Figure 2) | 3.3<br>5.0                        | 3.0<br>2.5        | 10<br>7.5   | 2.5<br>2.0    | 11<br>8.5 | ns   |
| t <sub>PLH</sub> | Propagation Delay, Select to Output Y (Figure 1)   | 3.3<br>5.0                        | 4.5<br>3.5        | 12<br>8.5   | 3.5<br>3.0    | 13<br>10  | ns   |
| t <sub>PHL</sub> | Propagation Delay, Select to Output Y (Figure 1)   | 3.3<br>5.0                        | 4.0<br>2.5        | 10<br>7.5   | 3.0<br>2.5    | 11<br>8.5 | ns   |
| C <sub>IN</sub>  | Maximum Input Capacitance                          | 5.0                               | 4.5               |             | 4.5           |           | pF   |


| C <sub>PD</sub> | Power Dissipation Capacitance | Typical @25°C,V <sub>CC</sub> =5.0 V |  | pF |
|-----------------|-------------------------------|--------------------------------------|--|----|
|                 |                               | 40                                   |  |    |

\*Voltage Range 3.3 V is 3.3 V  $\pm$ 0.3 V

Voltage Range 5.0 V is 5.0 V  $\pm$ 0.5 V




**Figure 1. Switching Waveform**






**Figure 2. Switching Waveform**

## EXPANDED LOGIC DIAGRAM



**N SUFFIX PLASTIC DIP**  
**(MS - 001BB)**






$$\oplus 0.25 (0.010) \text{ (M) } T$$

**NOTES:**

- Dimensions "A", "B" do not include mold flash or protrusions.  
Maximum mold flash or protrusions 0.25 mm (0.010) per side.

|        | Dimension, mm |       |
|--------|---------------|-------|
| Symbol | MIN           | MAX   |
| A      | 18.67         | 19.69 |
| B      | 6.1           | 7.11  |
| C      |               | 5.33  |
| D      | 0.36          | 0.56  |
| F      | 1.14          | 1.78  |
| G      | 2.54          |       |
| H      | 7.62          |       |
| J      | 0°            | 10°   |
| K      | 2.92          | 3.81  |
| L      | 7.62          | 8.26  |
| M      | 0.2           | 0.36  |
| N      | 0.38          |       |

**D SUFFIX SOIC**  
**(MS - 012AC)**



$$\oplus 0.25 (0.010) \text{ (M) } T \text{ C (M) }$$

**NOTES:**

- Dimensions A and B do not include mold flash or protrusion.
- Maximum mold flash or protrusion 0.15 mm (0.006) per side  
for A; for B - 0.25 mm (0.010) per side.

|        | Dimension, mm |      |
|--------|---------------|------|
| Symbol | MIN           | MAX  |
| A      | 9.8           | 10   |
| B      | 3.8           | 4    |
| C      | 1.35          | 1.75 |
| D      | 0.33          | 0.51 |
| F      | 0.4           | 1.27 |
| G      | 1.27          |      |
| H      | 5.72          |      |
| J      | 0°            | 8°   |
| K      | 0.1           | 0.25 |
| M      | 0.19          | 0.25 |
| P      | 5.8           | 6.2  |
| R      | 0.25          | 0.5  |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А