


 ELECTRONICS

Millipacs® and *CompactPCI* Core Product Selector


5 Row Signal - Standard




Type A




Type B



Type AB



Type C



Type CR

| Millipacs® 5 row signal-standard | | | Header Straight | | Shroud | Receptacle Right Angle | |
|----------------------------------|---|--------------|------------------|------------------|------------|------------------------|------------------|
| | | | shielded | non-shielded | | top shielded | non-shielded |
| Type A | module length 50 mm 110 pos service center | press-fit | HM2P07PD5111N9LF | HM2P07PD5110N9LF | HM2H07P1LF | HM2R01PA5108N9LF | HM2R01PA5100N9LF |
| | | rear-plug-up | HM2P07PK5111GFLF | HM2P07PK5110GFLF | | | |
| Type B | module length 50 mm 125 pos no service center | press-fit | HM2P08PD5111N9LF | HM2P08PD5110N9LF | HM2H08P1LF | HM2R02PA5108N9LF | HM2R02PA5100N9LF |
| | | rear-plug-up | HM2P08PK5111GFLF | HM2P08PK5110GFLF | | | |
| Type AB | module length 50 mm 110 pos guiding pegs | press-fit | HM2P65PD5111N9LF | HM2P65PD5110N9LF | HM2H65P1LF | HM2R65PA5108N9LF | HM2R65PA5100N9LF |
| | | rear-plug-up | HM2P65PK5111GFLF | HM2P65PK5110GFLF | | | |
| Type C | module length 25 mm 55 pos service center-left | press-fit | HM2P09PD5111N9LF | HM2P09PD5110N9LF | HM2H09P1LF | HM2R03PA5108N9LF | HM2R03PA5100N9LF |
| | | rear-plug-up | HM2P09PK5111GFLF | HM2P09PK5110GFLF | | | |
| Type CR | module length 25 mm 55 pos service center-right | press-fit | HM2P80PD5111N9LF | HM2P80PD5110N9LF | HM2H80P1LF | HM2R20PA5108N9LF | HM2R20PA5100N9LF |
| | | rear-plug-up | HM2P80PK5111GFLF | HM2P80PK5110GFLF | | | |

TECHNICAL DATA

PHYSICAL

Header Housing Thermoplastic (UL94 V-0)
 Receptacle Housing high temp. Thermoplastic (UL94 V-0)
 Pin/contact Phosher Bronze
 Performance Telecordia CO and IEC Performance Level 2
 Temperature -55 C to +125 C

MECHANICAL

Insertion force 0.75 N min. per contact pair
 Withdrawal force 0.15 N min. per contact pair
 Mating force 0.75 N min. per contact pair
 Mating cycles 250

ELECTRICAL

Current rating 1.5 A / 1 A
 Resistance (contact) 20 milli ohms max.
 Resistance (Insulation) 10,000 M ohm min.
 Voltage 750 V rms

MOUNTING STYLE

Press-fit

PACKAGING

Trays

REFERENCE DATA

Product specification GS-12-203
 Application specification GS-20-022

5 Row - Pin-in-Paste



Type C

| Millipacs® 5 row Pin-in Paste | | Header Straight non-shielded |
|-------------------------------|---|------------------------------|
| Type C | module length 25 mm 55 positions guiding pegs | HM2P09SZ5111N9LF |

TECHNICAL DATA

PHYSICAL

Header Housing high temp. Thermoplastic (UL94 V-0)
 Pin/contact Phosher Bronze
 Performance Telecordia CO and IEC Performance Level 2
 Temperature -55 C to +125 C

MECHANICAL

Insertion force 0.75 N min. per contact pair
 Withdrawal force 0.15 N min. per contact pair
 Mating force 0.75 N min. per contact pair
 Mating cycles 250

ELECTRICAL

Current rating 1.5 A / 1 A
 Resistance (contact) 20 milli ohms max.
 Resistance (Insulation) 10,000 M ohm min.
 Voltage 750 V rms

MOUNTING STYLE

Pin-in-Paste, Short tail 1mm, PIP version


PACKAGING

Tape&reel

REFERENCE DATA

Product specification GS-12-203
 Application specification GS-20-022


5 Row Signal - Reversed



Type A



Type B



Type C

| Millipacs® 5 row signal-reversed | | Header Right Angle | | Receptacle Straight | |
|----------------------------------|--|--------------------|------------------|---------------------|------------------|
| | | top shielded | non-shielded | shielded | non-shielded |
| Type A | module length 50 mm 110 pos service center | HM2J07PE5118N9LF | HM2J07PE5110N9LF | HM2S10PE5101N9LF | HM2S10PE5100N9LF |
| Type B | module length 50 mm 125 pos no service center | HM2J08PE5118N9LF | HM2J08PE5110N9LF | HM2S02PE5101N9LF | HM2S02PE5100N9LF |
| Type C | module length 25 mm 55 pos service center-left | HM2J09PE5118N9LF | HM2J09PE5110N9LF | HM2S30PE5101N9LF | HM2S30PE5100N9LF |

TECHNICAL DATA

PHYSICAL

Header Housing high temp. Thermoplastic (UL94 V-0)
 Receptacle Housing high temp. Thermoplastic (UL94 V-0)
 Pin/contact Phosher Bronze
 Performance Telecordia CO and IEC Performance Level 2
 Temperature -55 C to +125 C

MECHANICAL

Insertion force 0.75 N min. per contact pair
 Withdrawal force 0.15 N min. per contact pair
 Mating force 0.75 N min. per contact pair
 Mating cycles 250

ELECTRICAL

Current rating 1.5 A / 1 A
 Resistance (contact) 20 milli ohms max.
 Resistance (Insulation) 10,000 M ohm min.
 Voltage 750 V rms

MOUNTING STYLE

Press-fit

PACKAGING

Trays

REFERENCE DATA

Product specification GS-12-203
 Application specification GS-20-022

8 Row Signal - Standard



Type D



Type DE



Type E



Type F

| Millipacs® 8 row signal-standard | | | Header Straight | | Shroud | Receptacle Right Angle | |
|----------------------------------|--|--------------|------------------|------------------|------------|------------------------|------------------|
| | | | shielded | non-shielded | | top shielded | non-shielded |
| Type D | module length 50 mm 176 pos service center | press-fit | HM2P87PD8111N9LF | HM2P87PD8110N9LF | HM2H87P1LF | HM2R87PA8108N9LF | HM2R87PA8100N9LF |
| | | rear-plug-up | HM2P87PK8111GFLF | HM2P87PK8110GFLF | | | |
| Type DE | module length 50 mm 200 pos guiding pegs | press-fit | HM2P95PD8111N9LF | HM2P95PD8110N9LF | HM2H95P1LF | HM2R95PA8108N9LF | HM2R95PA8100N9LF |
| | | rear-plug-up | HM2P95PK8111GFLF | HM2P95PK8110GFLF | | | |
| Type E | module length 50 mm 200 pos no service center | press-fit | HM2P88PD8111N9LF | HM2P88PD8110N9LF | HM2H88P1LF | HM2R88PA8101N9LF | HM2R88PA8100N9LF |
| | | rear-plug-up | HM2P88PK8111GFLF | HM2P88PK8110GFLF | | | |
| Type F | module length 25 mm 88 pos service center-left | press-fit | HM2P89PD8111N9LF | HM2P89PD8110N9LF | HM2H89P1LF | HM2R89PA8108N9LF | HM2R89PA8100N9LF |
| | | rear-plug-up | HM2P89PK8111GFLF | HM2P89PK8110GFLF | | | |

TECHNICAL DATA

PHYSICAL

Header Housing Thermoplastic (UL94 V-0)
 Receptacle Housing high temp. Thermoplastic (UL94 V-0)
 Pin/contact Phosher Bronze
 Performance Telecordia CO and IEC Performance Level 2
 Temperature -55 C to +125 C

MECHANICAL

Insertion force 0.75 N min. per contact pair
 Withdrawal force 0.15 N min. per contact pair
 Mating force 0.75 N min. per contact pair
 Mating cycles 250

ELECTRICAL

Current rating 1.5 A / 1 A
 Resistance (contact) 20 milli ohms max.
 Resistance (Insulation) 10,000 M ohm min.
 Voltage 750 V rms

MOUNTING STYLE

Press-fit

PACKAGING

Trays


REFERENCE DATA

Product specification GS-12-203
 Application specification GS-20-022


Cable Connectors



cable connector non-shielded



cable connector shielded



shroud and locking key

| LF - Low Frequency | | AWG 26 | AWG 28 - 30 | |
|--------------------|--------------|-----------------|------------------|------------------|
| Cable Connector | non-shielded | 2 x 5 positions | HM2C06D2C010N9LF | HM2C06D0C010N9LF |
| | | 4 x 5 positions | HM2C01D2C010N9LF | HM2C01D0C010N9LF |
| | shielded | 2 x 5 positions | HM2C09D2C011N9LF | HM2C09D0C011N9LF |
| | | 6 x 5 positions | HM2C11D2C011N9LF | HM2C11D0C011N9LF |
| | | 8 x 5 positions | HM2C12D2C011N9LF | HM2C12D0C011N9LF |

Rear-plug-up accessories

| | | |
|-----------------------|------------------|------------|
| Cable-to-board Shroud | 5 x 5 positions | HM2H04P1LF |
| | 5 x 25 positions | HM2H05P1LF |
| Locking Key | | HM2LK1LF |

TECHNICAL DATA

PHYSICAL

| | |
|-------------|---|
| Receptacle | Housing high temp. Thermoplastic (UL94 V-0) |
| Pin/contact | Phosher Bronze |
| Performance | Telecordia CO and IEC Performance Level 2 |
| Temperature | -55 C to +125 C |

MECHANICAL

| | |
|------------------|------------------------------|
| Withdrawal force | 0.15 N min. per contact pair |
| Mating force | 0.75 N min. per contact pair |
| Mating cycles | 250 |

ELECTRICAL

| | |
|-------------------------|--------------------|
| Current rating | 1.5 A / 1 A |
| Resistance (contact) | 20 milli ohms max. |
| Resistance (Insulation) | 10,000 M ohm min. |
| Voltage | 750 V rms |

MOUNTING STYLE

IDC for AWG 24-26

PACKAGING

Trays


REFERENCE DATA

Product specification GS-12-203

Signal & Power



Type L



Type N



Type M

| | Signal & Power | Header Straight | Receptacle Right Angle |
|--------|--|------------------|------------------------|
| Type L | module length 50 mm 6 power positions service center | HM2A30PG5000LF | HM2E30PH5000LF |
| Type N | module length 25 mm 3 power positions service center | HM2A32PG5000LF | HM2E32PH5000LF |
| Type M | module length 50 mm 3 power + 55 signal positions service center + location pegs | HM2P11PD5111N9LF | HM2R05PA5108N9LF |

TECHNICAL DATA

PHYSICAL

| | |
|-------------|---|
| Header | housing high temp. Thermoplastic (UL94 V-0) |
| Receptacle | housing high temp. Thermoplastic (UL94 V-0) |
| Pin/contact | Phosher Bronze |
| Performance | Telecordia CO and IEC Performance Level 2 |
| Temperature | -55 C to +125 C |

MECHANICAL

| | |
|------------------|------------------------------|
| Insertion force | 0.75 N min. per contact pair |
| Withdrawal force | 0.15 N min. per contact pair |
| Mating force | 0.75 N min. per contact pair |
| Mating cycles | 250 |

ELECTRICAL

| | |
|-------------------------|--------------------|
| Current rating | 1.5 A / 1 A |
| Resistance (contact) | 20 milli ohms max. |
| Resistance (Insulation) | 10,000 M ohm min. |
| Voltage | 750 V rms |

MOUNTING STYLE

Signal contacts press-fit,
Power contacts press-fit DIN41626

PACKAGING

Trays

REFERENCE DATA

Product specification GS-12-203

5 Row - CompactPCI



Type AB19



Type AB22



Type B22

| CompactPCI 5 row | | | Header Straight | | Shroud | Receptacle Right Angle | |
|------------------|---------------------|--------------|------------------|------------------|------------|------------------------|------------------|
| | | | shielded | non-shielded | | top shielded | non-shielded |
| Type AB19 | module length 38 mm | press-fit | HM2P67PD5111N9LF | HM2P67PD5110N9LF | HM2H67P1LF | HM2R67PA5108N9LF | HM2R67PA5100N9LF |
| | 95 pos | rear-plug-up | HM2P67PK5111GFLF | HM2P67PK5110GFLF | | | |
| Type AB22 | module length 44 mm | press-fit | HM2P66PD5111N9LF | HM2P66PD5110N9LF | HM2H66P1LF | HM2R66PA5108N9LF | HM2R66PA5100N9LF |
| | 110 pos | rear-plug-up | HM2P66PK5111GFLF | HM2P66PK5110GFLF | | | |
| Type B22 | module length 44 mm | press-fit | HM2P70PD5111N9LF | HM2P70PD5110N9LF | HM2H70P1LF | HM2R70PA5108N9LF | HM2R70PA5100N9LF |
| | 110 pos | rear-plug-up | HM2P70PK5111GFLF | HM2P70PK5110GFLF | | | |

TECHNICAL DATA

PHYSICAL

Header Housing Thermoplastic (UL94 V-0)
 Receptacle Housing high temp. Thermoplastic (UL94 V-0)
 Pin/contact Phosher Bronze
 Performance Telecordia CO and IEC Performance Level 2
 Temperature -55 C to +125 C

ELECTRICAL

Current rating 1.5 A / 1 A
 Resistance (contact) 20 milli ohms max.
 Resistance (Insulation) 10,000 M ohm min.
 Voltage 750 V rms

MOUNTING STYLE

Press-fit

PACKAGING

Trays

REFERENCE DATA

Product specification GS-12-203
 Application specification GS-20-022

MECHANICAL

Insertion force 0.75 N min. per contact pair
 Withdrawal force 0.15 N min. per contact pair
 Mating force 0.75 N min. per contact pair
 Mating cycles 250

Bottom Shield



Coding Devices



Power Contacts



Accessories

| Accessories | Connector Type | | Part number |
|---------------|----------------|------------|-------------|
| Bottom shield | Type A | Millipacs | HM2LS22ALF |
| | Type AB | Millipacs | HM2LS22ALF |
| | Type AB19 | CompactPCI | HM2LS66ALF |
| | Type AB22 | CompactPCI | HM2LS67ALF |
| | Type B22 | CompactPCI | HM2LS70ALF |
| | Type C | Millipacs | HM2LS11ALF |
| | Type CR | Millipacs | HM2LS11ALF |
| | Type D | Millipacs | HM2LS22A8LF |
| | Type DE | Millipacs | HM2LS25A8LF |
| | Type E | Millipacs | HM2LS25A8LF |
| | Type F | Millipacs | HM2LS11A8LF |
| | Type M | Millipacs | HM2LS11ALF |

| Accessories | Colour | Plug | Receptacle |
|----------------|----------------|--------------|--------------|
| Coding Devices | cadmium-yellow | HM2DK3456PLF | HM2DK1278RLF |
| | brilliant-blue | HM2DK1567PLF | HM2DK2348RLF |
| | reseda-green | HM2DK2578PLF | HM2DK1346RLF |
| | strawberry-red | HM2DK1248PLF | HM2DK3567RLF |

| Accessories | Pin contact | Socket contact |
|---|----------------|----------------|
| Dipsolder Power contacts (10 A max current) | RM12PIE52ERPLF | RC12PIE52ERPLF |

REFERENCE DATA

Product specification GS-12-203

For more information about e-catalog or FCI
sales offices, headquarters, agents and local distributors,
visit www.fci.com



Americas - Phone: 1 (800) 237 2374 ■ Europe- - Phone: 33 1 39 49 21 83 ■ Asia/Pacific - Phone: 65 6549 6666

ELXMILLIPAC0608EA4

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А