


# ***Preferred Connector Products***

Technology to Inspire Innovation

# **JAE**



***JAE Electronics, Inc.***

***For Additional Information Visit [www.jae-connector.com](http://www.jae-connector.com)***

**J**apan Aviation Electronics Industry, Ltd. (JAE) is an international manufacturer and supplier of electronic components and systems. For over four decades, JAE has provided the electronics industry with solutions to complex design requirements. Since its founding, the Company has strived to contribute to society through market-driven, technology-based global business operations under the philosophy: "Technology to Inspire Innovation."

With worldwide and world-class manufacturing certified to ISO 9001 and QS 9000, JAE has made the commitment to meet the global requirements of our customer. In addition to a network of state of the art manufacturing facilities, JAE has technical service offices located around the world, staffed with experts in connector design and application.

This catalog contains a select overview of JAE Connector Products. For in-depth information on our complete product line, and information on new developments, visit JAE's online catalog at [www.jae-connector.com](http://www.jae-connector.com).

Innovative design, quality oriented manufacturing, commitment to our customers and sensitivity to the environment assures JAE's leadership position in the 21<sup>st</sup> century.

## Table of Contents

| Product Series                 | Contact Spacing                      | Pages   |
|--------------------------------|--------------------------------------|---------|
| <b>SOCKETS/MEMORY PRODUCTS</b> |                                      |         |
| PCMCIA                         |                                      |         |
| JC22.....                      | 1.27mm (.050") .....                 | 5       |
| COMPACT FLASH                  |                                      |         |
| JC26C2.....                    | 1.27mm (.050") .....                 | 6 - 7   |
| JC26E.....                     | 1.27mm (.050") .....                 | 8       |
| JC26F.....                     | 1.27mm (.050") .....                 | 9       |
| PCI EXPRESS MINI CARD          |                                      |         |
| MM60.....                      | 0.8mm (.031") .....                  | 10      |
| EXPRESSCARD                    |                                      |         |
| PX10/11 .....                  | 1.0mm (.039") .....                  | 11 - 12 |
| PX20/22 .....                  | 1.0mm (.039") / 0.635mm (.025")..... | 13 - 14 |
| SMART/SIM CARD                 |                                      |         |
| SF2.....                       | 2.54mm (.100") .....                 | 15      |
| SF3.....                       | 2.54mm (.100") .....                 | 16      |
| SF6.....                       | 2.54mm (.100") .....                 | 17      |
| SF7.....                       | 2.54mm (.100") .....                 | 18      |
| SF7 (Slim).....                | 2.54mm (.100") .....                 | 19      |
| SF9.....                       | 2.54mm (.100") .....                 | 20      |
| SECURE DIGITAL CARD            |                                      |         |
| SG5.....                       | 2.50mm (.098") .....                 | 21      |
| MINI SECURE DIGITAL CARD (SD)  |                                      |         |
| ST4.....                       | 1.1mm (.043") .....                  | 22      |
| SC1.....                       | 2.50mm (.098") .....                 | 23      |
| MICRO SD/TRANSFLASH™           |                                      |         |
| ST1.....                       | 1.1mm (.043") .....                  | 24      |
| ST2.....                       | 1.1mm (.043") .....                  | 25      |

## BOARD-TO-BOARD CONNECTOR PRODUCTS

|                |                      |         |
|----------------|----------------------|---------|
| BOARD-TO-BOARD |                      |         |
| AA03.....      | 0.40mm (.020") ..... | 26      |
| WA6.....       | 0.40mm (.020") ..... | 27      |
| WH1.....       | 0.40mm (.020") ..... | 28      |
| AA01A .....    | 0.50mm (.020") ..... | 29      |
| IL-312.....    | 0.50mm (.020") ..... | 30      |
| WR.....        | 0.50mm (.020") ..... | 31 - 32 |
| WB3.....       | 0.50mm (.020") ..... | 33      |
| IL-WX .....    | 0.80mm (.031") ..... | 34      |
| KX14/15 .....  | 0.80mm (.031") ..... | 35 - 36 |
| PM1 .....      | 0.80mm (.031") ..... | 37      |
| WM1.....       | 1.00mm (.039") ..... | 38      |
| WM2.....       | 1.00mm (.039") ..... | 39      |
| TX24/TX25..... | 1.27mm (.050") ..... | 40      |

## Table of Contents

| Product Series                           | Contact Spacing      | Pages   |
|------------------------------------------|----------------------|---------|
| <b>BOARD-TO-BOARD CONNECTOR PRODUCTS</b> |                      |         |
| WIRE-TO-BOARD                            |                      |         |
| PCB-TO-FPC/FFC                           |                      |         |
| FB3.....                                 | 0.30mm (.012").....  | 41      |
| FB5.....                                 | 0.30mm (.012").....  | 42      |
| FB6.....                                 | 0.30mm (.012").....  | 43      |
| FF02.....                                | 0.30mm (.012").....  | 44      |
| FF02S.....                               | 0.30mm (.012").....  | 45      |
| FB8.....                                 | 0.30mm (.012").....  | 46      |
| FA5.....                                 | 0.50mm (.020").....  | 47      |
| FF03.....                                | 0.50mm (.020").....  | 48      |
| IL-FPR.....                              | 0.50mm (.020").....  | 49      |
| PCB-TO-CABLE/FPC                         |                      |         |
| FI-J.....                                | 0.40mm (.016").....  | 50 - 51 |
| FI-R.....                                | 0.50mm (.020").....  | 52 - 53 |
| FI-X.....                                | 1.00mm (.039").....  | 54 - 55 |
| FI.....                                  | 1.25mm (.049").....  | 56 - 58 |
| PCB-TO-CABLE                             |                      |         |
| DX2/3.....                               | 0.80mm (.031").....  | 59      |
| FI-E.....                                | 1.00mm (.039").....  | 60 - 61 |
| CN10.....                                |                      | 62 - 63 |
| CV10.....                                |                      | 64      |
| IL-Z.....                                | 1.25mm (.049").....  | 65 - 66 |
| IL-S.....                                | 2.00mm (.079").....  | 67 - 68 |
| LY.....                                  | 2.00mm (.079").....  | 69      |
| KD10/20.....                             | 2.00mm (.079").....  | 70      |
| IL-G.....                                | 2.50mm (.098").....  | 71      |
| <b>INPUT/OUTPUT CONNECTOR PRODUCTS</b>   |                      |         |
| PCB-TO-CABLE                             |                      |         |
| DD1.....                                 | 0.50mm (.020").....  | 72 - 73 |
| DD2.....                                 | 0.50mm (.020").....  | 74 - 75 |
| DG1.....                                 | 0.50mm (.020").....  | 76      |
| RA1.....                                 | 0.50mm (.020").....  | 77      |
| RC1.....                                 | 0.50mm (.020").....  | 78      |
| DA1.....                                 | 0.60mm (.024").....  | 79      |
| DE1.....                                 | 1.27mm (.050").....  | 80      |
| TX20A.....                               | 1.27mm (.050").....  | 81      |
| DV2.....                                 | 1.905mm (.075")..... | 82 - 84 |
| CIRCULAR                                 |                      |         |
| JN1.....                                 |                      | 85 - 86 |
| JN2.....                                 |                      | 87 - 88 |
| JB5.....                                 |                      | 89      |

## Table of Contents

*Product Series*

*Contact Spacing*

*Pages*

### INPUT/OUTPUT CONNECTOR PRODUCTS

#### CIRCULAR

|             |         |
|-------------|---------|
| JL04V ..... | 90 - 91 |
| JL05 .....  | 92 - 93 |
| JB1 .....   | 94 - 95 |
| SRCN .....  | 96 - 97 |
| N/MS .....  | 98 - 99 |

### FIBER OPTIC PRODUCTS

|             |     |
|-------------|-----|
| FO-FC ..... | 100 |
| FO-EX ..... | 101 |

### AUTOMOTIVE CONNECTOR PRODUCTS

#### PCB-TO-CABLE

|              |                      |           |
|--------------|----------------------|-----------|
| MX34 .....   | 1.1mm (.043") .....  | 102       |
| MX7 .....    | 2.30mm (.091") ..... | 103       |
| IL-AG7 ..... | 2.50mm (.098") ..... | 104       |
| MX17 .....   | 2.50mm (.098") ..... | 105 - 106 |
| MX23A .....  | 2.50mm (.098") ..... | 107 - 108 |
| MX10 .....   | 2.50mm (.098") ..... | 109       |
| MX5 .....    | 3.00mm (.118") ..... | 110       |

#### PCB-TO-CABLE/CABLE-TO-CABLE

|              |                      |     |
|--------------|----------------------|-----|
| IL-AG5 ..... | 2.50mm (.098") ..... | 111 |
| IL-AG6 ..... | 2.50mm (.098") ..... | 112 |
| MX9 .....    | 3.50mm (.138") ..... | 113 |
| MX25 .....   | 6.7mm (2.64") .....  | 114 |
| MX36 .....   | 2.50mm (.098") ..... | 115 |

#### CABLE-TO-CABLE

|              |                      |           |
|--------------|----------------------|-----------|
| IL-AG9 ..... | 2.50mm (.098") ..... | 116 - 118 |
| MX19 .....   | 2.50mm (.098") ..... | 119       |

- All JAE connector products shown in this catalog are lead free.
- We reserve the right to modify designs in order to improve quality, keep pace with technological advancements or meet particular requirements in production.
- Products shown in this catalog are made for the applications specified. However, if the above-mentioned products are to be used in aerospace devices, marine cable-connection devices, atomic power control systems, medical equipment for life-support systems, or any other specific application requiring extremely high reliability, please contact JAE for further information. Recommended Applications: Computers, Office Machines, Measuring Devices, Telecommunications Devices (Terminals, Mobile Devices) AV Devices, Household Applications, FA Devices, etc.
- Refer to end of catalog for alphabetical index of products.

# SRCN SERIES CONNECTORS


## Low Cost, General Purpose Miniature Circular Connectors



### FEATURES

- Miniature, lightweight, solid construction
- General purpose
- Low cost connector
- Product approved by UL standard:  
File No. E-67741 (s)
- Highly reliable contact finish
- Stable connections
- Positive polarization with five keys and keyways

Connector Profile (Ref.)



.....

SRCN Series connectors are low cost, light weight, general purpose, circular connectors with soldering termination, recognized under the Component Program of Underwriter Laboratories, File No. E-67741 (S). Three styles are available for making connection between cables, and between cable and panel: Straight Plug, Cable Connecting Plug and Box Mounting Receptacle. Both pin and socket inserts are available in each style.

Applications include broadcast and communication systems, medical equipment, telecommunications, measurement equipment, business machines, computers and peripherals, automation equipment, tooling, controlling devices, vending machines, electronic entertainment equipment and other electronic equipment.

### GENERAL SPECIFICATIONS

|                                 |                                                           |
|---------------------------------|-----------------------------------------------------------|
| Number of Contacts              | #16: 3, 7, 10, 16<br>#20: 5, 10, 16, 24                   |
| Current Rating<br>(Per contact) | 5 Amp max. for #20 contact<br>10 Amp max. for #16 contact |
| Operating Voltage               | 250 VAC r.m.s., max.<br>350 VDC max.                      |
| Operating Temperature           | -25°C to +85°C                                            |
| Dielectric Withstanding Voltage | 250 VAC r.m.s. (for one minute)                           |
| Insulation Resistance           | 1000 megohms min.                                         |
| Contact Resistance              | 5 milliohms max.                                          |
| Durability                      | 500 cycles                                                |

### MATERIALS AND FINISHES


| Description                                 | Materials/Finishes                    |
|---------------------------------------------|---------------------------------------|
| Shell, Barrel, Endbell, Coupling Nut, Clamp | Aluminum alloy, Nickel Plated (satin) |
| Insulator                                   | Synthetic resin, UL94V-0 (Green)      |
| Contact                                     | Copper alloy, Silver Plated           |
| Retaining Ring                              | Copper alloy, Nickel Plated           |
| Set Screw, Clamp Screw                      | Steel, Nickel Plated                  |

Dimensions and specifications subject to change without notice.


# SRCN SERIES CONNECTORS

*Low Cost, General Purpose Miniature Circular Connectors*


## ORDERING INFORMATION



## RECEPTACLE: SRCN2A



## PLUG: SRCN6A



Dimensions in mm (inches).

Technology to Inspire Innovation



***"Building Technologies  
to Connect Your World"***



**Japan Aviation Electronics Industry, Limited**

1-19, Aobadai 3-chome, Meguro-ku  
Tokyo 153-8539, Japan  
Telephone: 03-3780-2736  
Fax: 03-3780-2883

**JAE Electronics, Inc.**

142 Technology Drive, Suite 100  
Irvine, California 92618-2430, U.S.A.  
Telephone: 949-753-2600  
Fax: 949-753-2699  
800-523-7278 Toll free in the U.S.A.

**JAE Europe**

Coliseum Business Centre  
Riverside Way, Camberley  
Surrey, GU15 3YL, England  
Telephone: 44-1276-404000  
Fax: 44-1276-404010

**JAE Taiwan, Ltd.**

4F-1, No. 88, Chung Hsiao E. Rd.  
Sec. 2, Taipei, Taiwan, R.O.C.  
Telephone: 886-2-2396-7676  
Fax: 886-2-2392-5929

**JAE Hong Kong, Ltd.**

Suites 1407-11, 14/F, Tower 2, The Gateway,  
25 Canton Road, Tsimshatsui, Kowloon, Hong Kong  
Telephone: 852-2723-7782  
Fax: 852-2723-9028

**JAE Korea, Inc.**

1602, Korea City Air Tower  
159-9 Samsung-Dong, Kangnam-ku  
Seoul, 135-973, Korea  
Telephone: 82-2-551-8959  
Fax: 82-2-551-8958

**JAE Philippines, Inc.**

PEZA Zone, Gateway Business Park, Javalera  
General Trias, 4107 Cavite, Philippines  
Telephone: 63-46-433-0285  
Fax: 63-46-433-0287

**JAE Singapore Pte., Ltd.**

33 Tannery Lane, #02-01 Hoesteel  
Industrial Building  
Singapore 347789  
Telephone: 65-6748-1332  
Fax: 65-6748-2920

**JAE Shanghai Co., Ltd.**

RM 1407, Shanghai Mart 2299 Yanan Rd.  
West Shanghai 200336 P.R.C.  
Telephone: 86-21-6236-0322  
Fax: 86-21-6236-1292

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## JAE Electronics:

[SRCN1A13-5S](#) [SRCN2A13-3P](#) [SRCN2A13-5S](#) [SRCN1A13-3P](#) [SRCN6A13-3S](#) [SRCN2A13-3S](#) [SRCN6A13-5S](#)  
[SRCN2A13-5P](#) [SRCN6A13-5P](#) [SRCN1A13-5P](#) [SRCN6A16-10P](#) [SRCN2A16-10P](#) [SRCN2A16-10S](#) [SRCN1A25-16P](#)  
[SRCN2A25-16S](#) [SRCN1A16-7P](#) [SRCN2A16-7P](#) [SRCN6A16-7P](#) [SRCN6A25-16P](#) [SRCN2A21-10P](#) [SRCN1A21-10S](#)  
[SRCN6A21-10P](#) [SRCN2A21-16P](#) [SRCN6A21-16S](#) [SRCN2A21-10S](#) [SRCN6A21-16P](#) [SRCN1A21-16S](#) [SRCN1A16-](#)  
[10S](#) [SRCN1A21-10P](#) [SRCN2A25-24P](#) [SRCN6A21-18P](#) [SRCN6A21-18S](#) [SRCN2A25-16P](#) [SRCN6A13-5SX](#)  
[SRCN2A21-18P](#) [SRCN2A16-10P-TH-N](#) [SRCN6A13-3SX](#) [SRCN2A21-18S](#) [SRCN2A13-5PX](#)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А