






# Coupled Inductors – LPD3015

For SEPIC and other Applications



- Only 1.4 mm high and 3 mm square
- Ideal for use in flyback, multi-output buck, SEPIC and Zeta applications.
- High inductance, high efficiency and excellent current handling
- Can also be used as two single inductors connected in series or parallel or as a common mode choke.



Dimensions are in  $\frac{\text{inches}}{\text{mm}}$



**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 661-1 Revised 11/09/15  
 © Coilcraft Inc. 2015  
 This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.



# Coupled Inductors for SEPIC - LPD3015 Series

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>±20% (µH) | DCR max <sup>3</sup><br>(Ohms) | SRF typ <sup>4</sup><br>(MHz) | Coupling<br>coefficient<br>typ | Leakage<br>L typ <sup>5</sup><br>(µH) | Isat (A) <sup>6</sup> |             |             | Irms (A)                      |                             |
|--------------------------|--------------------------------------|--------------------------------|-------------------------------|--------------------------------|---------------------------------------|-----------------------|-------------|-------------|-------------------------------|-----------------------------|
|                          |                                      |                                |                               |                                |                                       | 10%<br>drop           | 20%<br>drop | 30%<br>drop | both<br>windings <sup>7</sup> | one<br>winding <sup>8</sup> |
| LPD3015-391MR_           | 0.39                                 | 0.071                          | 289                           | 0.89                           | 0.08                                  | 3.2                   | 3.3         | 3.4         | 1.45                          | 2.05                        |
| LPD3015-561MR_           | 0.56                                 | 0.079                          | 235                           | 0.93                           | 0.08                                  | 2.7                   | 2.8         | 2.8         | 1.37                          | 1.94                        |
| LPD3015-102MR_           | 1.0                                  | 0.129                          | 160                           | 0.95                           | 0.09                                  | 2.0                   | 2.1         | 2.2         | 1.08                          | 1.52                        |
| LPD3015-152MR_           | 1.5                                  | 0.204                          | 140                           | 0.96                           | 0.11                                  | 1.6                   | 1.7         | 1.8         | 0.86                          | 1.20                        |
| LPD3015-182MR_           | 1.8                                  | 0.273                          | 135                           | 0.96                           | 0.13                                  | 1.5                   | 1.6         | 1.6         | 0.78                          | 1.10                        |
| LPD3015-222MR_           | 2.2                                  | 0.300                          | 110                           | 0.97                           | 0.14                                  | 1.5                   | 1.6         | 1.6         | 0.75                          | 1.05                        |
| LPD3015-332MR_           | 3.3                                  | 0.337                          | 90                            | 0.98                           | 0.16                                  | 1.0                   | 1.1         | 1.2         | 0.67                          | 0.94                        |
| LPD3015-472MR_           | 4.7                                  | 0.503                          | 79                            | 0.98                           | 0.18                                  | 0.86                  | 0.87        | 0.88        | 0.54                          | 0.76                        |
| LPD3015-682MR_           | 6.8                                  | 0.622                          | 58                            | 0.98                           | 0.22                                  | 0.77                  | 0.78        | 0.79        | 0.49                          | 0.69                        |
| LPD3015-103MR_           | 10                                   | 1.040                          | 48                            | 0.99                           | 0.28                                  | 0.58                  | 0.59        | 0.60        | 0.38                          | 0.53                        |
| LPD3015-153MR_           | 15                                   | 1.420                          | 35                            | 0.99                           | 0.37                                  | 0.49                  | 0.50        | 0.51        | 0.32                          | 0.46                        |
| LPD3015-183MR_           | 18                                   | 1.550                          | 33                            | 0.99                           | 0.42                                  | 0.46                  | 0.47        | 0.48        | 0.31                          | 0.44                        |
| LPD3015-223MR_           | 22                                   | 1.89                           | 30                            | 0.99                           | 0.48                                  | 0.42                  | 0.43        | 0.44        | 0.28                          | 0.40                        |
| LPD3015-333MR_           | 33                                   | 2.84                           | 23                            | 0.99                           | 0.63                                  | 0.34                  | 0.35        | 0.36        | 0.23                          | 0.32                        |
| LPD3015-473MR_           | 47                                   | 4.03                           | 17                            | 0.99                           | 0.81                                  | 0.28                  | 0.29        | 0.30        | 0.19                          | 0.27                        |
| LPD3015-683MR_           | 68                                   | 6.11                           | 14                            | 0.99                           | 1.13                                  | 0.24                  | 0.25        | 0.26        | 0.16                          | 0.22                        |
| LPD3015-104MR_           | 100                                  | 8.54                           | 11                            | 0.99                           | 1.50                                  | 0.20                  | 0.21        | 0.22        | 0.13                          | 0.19                        |
| LPD3015-124MR_           | 120                                  | 9.23                           | 9.0                           | 0.99                           | 1.76                                  | 0.19                  | 0.20        | 0.20        | 0.13                          | 0.18                        |
| LPD3015-154MR_           | 150                                  | 12.40                          | 8.0                           | 0.99                           | 2.22                                  | 0.16                  | 0.17        | 0.18        | 0.11                          | 0.16                        |
| LPD3015-184MR_           | 180                                  | 15.32                          | 7.5                           | 0.99                           | 2.79                                  | 0.15                  | 0.16        | 0.17        | 0.10                          | 0.14                        |
| LPD3015-224MR_           | 220                                  | 18.56                          | 6.0                           | 0.99                           | 3.56                                  | 0.13                  | 0.14        | 0.15        | 0.09                          | 0.13                        |
| LPD3015-334MR_           | 330                                  | 27.70                          | 5.0                           | 0.99                           | 5.18                                  | 0.11                  | 0.12        | 0.12        | 0.07                          | 0.10                        |

1. When ordering, please specify **termination** and **packaging** codes:

#### LPD3015-334MRC

**Termination:** **R** = Matte tin over nickel over silver  
Special order, added cost: **Q** = RoHS tin-silver-copper (95.5/4/0.5) or **P** = non-RoHS tin-lead (63/37)

**Packaging:** **C** = 7" machine-ready reel. EIA-481 embossed plastic tape (1000 parts per full reel).

**B** = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter D instead.

**D** = 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (3500 parts per full reel).

- Inductance shown for each winding, measured at 100 kHz, 0.1 Vrms, 0 Adc on an Agilent/HP 4284A LCR meter or equivalent. When leads are connected in parallel, inductance is the same value. When leads are connected in series, inductance is four times the value.
- DCR is for each winding. When leads are connected in parallel, DCR is half the value. When leads are connected in series, DCR is twice the value.
- SRF measured using an Agilent/HP 4191A or equivalent. When leads are connected in parallel, SRF is the same value.
- Leakage Inductance is for L1 and is measured with L2 shorted
- DC current at 25°C that causes the specified inductance drop from its value without current. It is the sum of the current flowing in both windings.
- Equal current when applied to each winding simultaneously that causes a 40°C temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
- Maximum current when applied to one winding that causes a 40°C temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
- Electrical specifications at 25°C.

Refer to Doc 639 "Selecting Coupled Inductors for SEPIC Applications."

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

#### Coupled Inductor Core and Winding Loss Calculator

This web-based utility allows you to enter frequency, peak-to-peak (ripple) current, and Irms current to predict temperature rise and overall losses, including core loss. [Go to online calculator.](#)

**Core material** Ferrite

**Core and winding loss** [Go to online calculator](#)

**Weight** 45 – 52 mg

**Terminations** RoHS compliant matte tin over nickel over silver. Other terminations available at additional cost.

**Ambient temperature** -40°C to +85°C with (40°C rise) Irms current.

**Maximum part temperature** +125°C (ambient + temp rise).

**Storage temperature** Component: -40°C to +125°C.

Tape and reel packaging: -40°C to +80°C

**Winding to winding isolation** 100 Vrms

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

**Packaging** 1000/7" reel; 3500/13" reel Plastic tape: 12 mm wide,

0.26 mm thick, 8 mm pocket spacing, 1.65 mm pocket depth

**Recommended pick and place nozzle** OD: 3 mm; ID: ≤ 1.5 mm

**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787\\_PCB\\_Washing.pdf](#).



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com

**UK** +44-1236-730595 sales@coilcraft-europe.com

**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw

**China** +86-21-6218 8074 sales@coilcraft.com.cn

**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 661-2 Revised 11/09/15


© Coilcraft Inc. 2015

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.




# Coupled Inductors for SEPIC - LPD3015 Series

## Typical L vs Current



## Typical L vs Frequency



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 661-3 Revised 11/09/15

© Coilcraft Inc. 2015

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А