


●Application

- Motor drive
- Converter
- Photovoltaics, wind power generation.

●Features

- 1) Low surge, low switching loss.
- 2) High-speed switching possible.
- 3) Reduced temperature dependence.


●Circuit diagram



●Construction

This product is a chopper module consisting of SiC-UMOSFET and SiC-SBD from ROHM.

●Dimensions & Pin layout (Unit : mm)




●Absolute maximum ratings ($T_j = 25^\circ\text{C}$)

| Parameter | Symbol | Conditions | Ratings | Unit |
|---|----------------|---|------------|------------------|
| Drain - Source Voltage | V_{DSS} | G-S short | 1200 | V |
| Repetitive Reverse Voltage | V_{RRM} | Clamp diode | 1200 | |
| Gate - Source Voltage (+) | V_{GSS} | D-S short | 22 | |
| Gate - Source Voltage (-) | V_{GSS} | D-S short | -4 | |
| G - S Voltage ($t_{surge} < 300\text{nsec}$) | $V_{GSSsurge}$ | D-S short | -4 to 26 | |
| Drain Current <small>Note 1)</small> | I_D | DC($T_c=60^\circ\text{C}$) $V_{GS}=18\text{V}$ | 576 | A |
| | I_D | DC($T_c=50^\circ\text{C}$) $V_{GS}=18\text{V}$ | 600 | |
| | I_{DRM} | Pulse ($T_c = 60^\circ\text{C}$) 1ms $V_{GS}=18\text{V}$ <small>Note 2)</small> | 1200 | |
| Source Current <small>Note 1)</small> | I_S | DC($T_c=60^\circ\text{C}$) $V_{GS}=18\text{V}$ | 576 | |
| | I_S | DC($T_c=50^\circ\text{C}$) $V_{GS}=18\text{V}$ | 600 | |
| | I_{SRM} | Pulse ($T_c = 60^\circ\text{C}$) 1ms $V_{GS}=18\text{V}$ <small>Note 2)</small> | 1200 | |
| | I_{SRM} | Pulse ($T_c = 60^\circ\text{C}$) 1ms $V_{GS}=0\text{V}$ <small>Note 2)</small> | 1200 | |
| Forward Current (clamp diode) <small>Note 1)</small> | I_F | DC($T_c = 60^\circ\text{C}$) | 600 | |
| | I_{FRM} | Pulse ($T_c = 60^\circ\text{C}$) 1ms <small>Note 2)</small> | 1200 | |
| Total Power Dissipation <small>Note 3)</small> | P_{tot} | $T_c = 25^\circ\text{C}$ | 2460 | |
| Max Junction Temperature | T_{jmax} | | 175 | $^\circ\text{C}$ |
| Junction Temperature | T_{jop} | | -40 to 150 | |
| Storage Temperature | T_{stg} | | -40 to 125 | |
| Isolation Voltage | Visol | Terminals to baseplate $f = 60\text{Hz AC}$ 1 min. | 2500 | Vrms |
| Mounting Torque | - | Main Terminals : M6 screw | 4.5 | N · m |
| | | Mounting to heat sink M5 screw | 3.5 | |

Note 1) Case temperature (T_c) is defined on the surface of base plate just under the chips.

Note 2) Repetition rate should be kept within the range where temperature rise if die should not exceed T_{jmax} .

Note 3) T_j is less than 175°C .

Example of acceptable VGS waveform


●Electrical characteristics (T_j=25°C)

| Parameter | Symbol | Conditions | Ratings | | | Unit | |
|---------------------------------------|----------------------|--|-----------------------|------|------|-------|---|
| | | | Min. | Typ. | Max. | | |
| On-state static Drain-Source Voltage | V _{DS(on)} | I _D =600A, V _{GS} =18V | T _j =25°C | — | 1.8 | 2.4 | V |
| | | | T _j =125°C | — | 2.6 | — | |
| | | | T _j =150°C | — | 2.9 | 4.1 | |
| Drain Cutoff Current | I _{DSS} | V _{DS} =1200V, V _{GS} =0V | — | — | 10 | μA | |
| Forward Voltage | V _F | I _F =600A | T _j =25°C | — | 1.8 | 2.2 | V |
| | | | T _j =125°C | — | 2.4 | — | |
| | | | T _j =150°C | — | 2.6 | 3.2 | |
| Reverse current | I _{RRM} | Clamp diode | — | — | 4 | mA | |
| Gate-Source Threshold Voltage | V _{GS(th)} | V _{DS} =10V, I _D =182mA | 2.7 | — | 5.6 | V | |
| Gate-Source Leak Current | I _{GSS} | V _{GS} =22V, V _{DS} =0V | — | — | 0.5 | μA | |
| | | V _{GS} =-4V, V _{DS} =0V | -0.5 | — | — | | |
| Switching Characteristics | td(on) | V _{GS(on)} =18V, V _{GS(off)} =0V V _{DS} =600V I _D =600A R _{G(on)} =0.2 ohm, R _{G(off)} =0.2 ohm Inductive load | — | 70 | — | ns | |
| | tr | | — | 50 | — | | |
| | trr | | — | 20 | — | | |
| | td(off) | | — | 240 | — | | |
| | tf | | — | 65 | — | | |
| Input Capacitance | C _{iss} | V _{DS} =10V, V _{GS} =0V, 200kHz | — | 28 | — | nF | |
| Gate Resistance | R _{Gint} | T _j =25°C | — | 1.4 | — | Ω | |
| NTC Rated Resistance | R ₂₅ | | — | 5.0 | — | kΩ | |
| NTC B Value | B _{50/25} | | — | 3370 | — | K | |
| Stray Inductance | L _s | | — | 10.0 | — | nH | |
| Creepage Distance | - | Terminal to heat sink | — | 16.7 | — | mm | |
| | | Terminal to terminal | — | 16.7 | — | mm | |
| Clearance Distance | - | Terminal to heat sink | — | 12.0 | — | mm | |
| | | Terminal to terminal | — | 11.0 | — | mm | |
| Junction-to -Case Thermal Resistance | R _{th(j-c)} | UMOSFET (1/2 module) <small>Note 4)</small> | — | — | 61 | °C/kW | |
| | | SBD (1/2 module) <small>Note 4)</small> | — | — | 61 | | |
| Case-to -heat sink Thermal Resistance | R _{th(c-f)} | Case to heat sink, per 1 module. Thermal grease applied. <small>Note 5)</small> | — | 15 | — | | |


Note 4) Measurement of T_c is to be done at the point just under the chip.

Note 5) Typical value is measured by using thermally conductive grease of λ=0.9W/(m·K).

Note 6) SiC devices have lower short circuit withstand capability due to high current density. Please be advised to pay careful attention to short circuit accident and try to adjust protection time to shutdown them as short as possible.

Note 7) If the Product is used beyond absolute maximum ratings defined in the Specifications, as its internal structure may be damaged, please replace such Product with a new one.

<Wavelength for Switching Test>



●Electrical characteristic curves (Typical)

Fig.1 Output characteristic 25°C (TYP)




Fig.2 Drain source voltage characteristic (TYP)




Fig.3 Drain source voltage characteristic 25°C (TYP)





Fig.4 Ron vs Tj characteristic (TYP)



●Electrical characteristic curves (Typical)

Fig.5 Forward characteristic of Diode (TYP)




Fig.6 Forward characteristic of Diode (TYP)




Fig.7 Drain Current vs Gate Voltage (TYP)





Fig.8 Drain Current vs Gate Voltage (TYP)



●Electrical characteristic curves (Typical)

Fig.9 Switching time vs drain current at 25°C (TYP)




Fig.10 Switching time vs drain current at 125°C (TYP)




Fig.11 Switching time vs drain current at 150°C (TYP)





Fig.12 Switching loss vs drain current at 25°C (TYP)



●Electrical characteristic curves (Typical)

Fig.13 Switching loss vs drain current at 125°C (TYP)




Fig.14 Switching loss vs drain current at 150°C (TYP)




Fig.15 Recovery characteristic vs drain current at 25°C (TYP)





Fig.16 Recovery characteristic vs drain current at 125°C (TYP)



●Electrical characteristic curves (Typical)

Fig.17 Recovery characteristic vs drain current at 150°C (TYP)




Fig.18 Switching time vs gate resistance at 25°C (TYP)




Fig.19 Switching time vs gate resistance at 125°C (TYP)





Fig.20 Switching time vs gate resistance at 150°C (TYP)



●Electrical characteristic curves (Typical)

Fig.21 Switching loss vs gate resistance at 25°C (TYP)




Fig.22 Switching loss vs gate resistance at 125°C (TYP)





Fig.23 Switching loss vs gate resistance at 150°C (TYP)



●Electrical characteristic curves (Typical)

Fig.24 Capacitance vs Drain source voltage (TYP)




Fig.25 Gate charge characteristic (TYP)





Fig.26 Transient thermal impedance (TYP)



Notes

- 1) The information contained herein is subject to change without notice.
- 2) Before you use our Products, please contact our sales representative and verify the latest specifications.
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Products beyond the rating specified by ROHM.
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products specified in this document are not designed to be radiation tolerant.
- 7) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, and power transmission systems.
- 8) Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 9) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 10) ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrants that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 11) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting non-compliance with any applicable laws or regulations.
- 12) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 13) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations.
More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

<http://www.rohm.com/contact/>

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».



JONHON

«**JONHON**» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А