



ON Semiconductor®

<http://onsemi.com>

EFC6602R

N-Channel Power MOSFET 12V, 18A, 5.9mΩ, Dual EFCP

Features

- 2.5V drive
- Common-drain type
- 2KV ESD HBM
- Protection diode in
- Halogen free compliance

Specifications

Absolute Maximum Ratings at Ta=25°C


Parameter	Symbol	Conditions	Ratings	Unit
Source-to-Source Voltage	V _{SSS}		12	V
Gate-to-Source Voltage	V _{GSS}		±12	V
Source Current (DC)	I _S		18	A
Source Current (Pulse)	I _{SP}	PW≤10μs, duty cycle≤1%	60	A
Total Dissipation	P _T	When mounted on ceramic substrate (5000mm²×0.8mm)	2.0	W
Channel Temperature	T _{ch}		150	°C
Storage Temperature	T _{stg}		-55 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions

unit : mm (typ)


7073-001



Product & Package Information

- Package : EFCP
- JEITA, JEDEC : -
- Minimum Packing Quantity : 5,000 pcs./reel


Taping Type : TR



Marking



Electrical Connection



EFC6602R

Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Source-to-Source Breakdown Voltage	$V_{(BR)SSS}$	$I_S=1mA$, $V_{GS}=0V$ Test Circuit 1	12			V
Zero-Gate Voltage Source Current	I_{SSS}	$V_{SS}=10V$, $V_{GS}=0V$ Test Circuit 1			1	μA
Gate-to-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 8V$, $V_{SS}=0V$ Test Circuit 2			± 1	μA
Cutoff Voltage	$V_{GS(off)}$	$V_{SS}=6V$, $I_S=1mA$ Test Circuit 3	0.5		1.3	V
Forward Transfer Admittance	$ y_{fs} $	$V_{SS}=6V$, $I_S=3A$ Test Circuit 4		13		S
Static Source-to-Source On-State Resistance	$R_{SS(on)1}$	$I_S=3A$, $V_{GS}=4.5V$ Test Circuit 5	3.1	4.5	5.9	$m\Omega$
	$R_{SS(on)2}$	$I_S=3A$, $V_{GS}=4.0V$ Test Circuit 5	3.3	4.8	6.3	$m\Omega$
	$R_{SS(on)3}$	$I_S=3A$, $V_{GS}=3.8V$ Test Circuit 5	3.5	5	6.5	$m\Omega$
	$R_{SS(on)4}$	$I_S=3A$, $V_{GS}=3.1V$ Test Circuit 5	4.0	5.8	8.2	$m\Omega$
	$R_{SS(on)5}$	$I_S=3A$, $V_{GS}=2.5V$ Test Circuit 5	5.2	7.5	11	$m\Omega$
Turn-ON Delay Time	$t_{d(on)}$	$V_{DD}=6V$, $V_{GS}=4.5V$, $I_S=3A$ Test Circuit 7		530		ns
Rise Time	t_r			2100		ns
Turn-OFF Delay Time	$t_{d(off)}$			6200		ns
Fall Time	t_f			5500		ns
Total Gate Charge	Q_g	$V_{DD}=6V$, $V_{GS}=4.5V$, $I_S=18A$ Test Circuit 8		55		nC
Forward Source-to-Source Voltage	$V_{F(S-S)}$	$I_S=3A$, $V_{GS}=0V$ Test Circuit 6		0.76	1.2	V


Ordering Information

Device	Package	Shipping	memo
EFC6602R-TR	EFCP	5,000pcs./reel	Pb Free and Halogen Free

Test circuits are example of measuring FET1 side


Test Circuit 1

I_{SSS}



Test Circuit 2


I_{GSS}



When FET1 is measured, Gate and Source of FET2 are short-circuited.

Test Circuit 3


$V_{GS(off)}$



When FET1 is measured, Gate and Source of FET2 are short-circuited.

Test Circuit 4


$|y_{fs}|$



When FET1 is measured, Gate and Source of FET2 are short-circuited.


Test Circuit 5

$R_{SS(on)}$




Test Circuit 6

$V_F(S-S)$



When FET1 is measured, +4.5V is added to V_{GS} of FET2.


Test Circuit 7
 $t_d(on), t_r, t_d(off), t_f$











When FET1 is measured, Gate and Source of FET2 are short-circuited.



Test Circuit 8

Q_g



When FET1 is measured, Gate and Source of FET2 are short-circuited.






Taping Specification


EFC6602R-TR

1. Taping Configuration


1-1 .Carrier Tape Size (unit:mm)




1-2 .Device Placement Direction




1-3 .Leader portion and Trailer portion (unit:mm)



Outline Drawing
EFC6602R-TR



Land Pattern Example



Note on usage : Since the EFC6602R is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[EFC6602R-A-TR](#)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А