

LCD- GRAPHIC MODULE 180x32

04.2011

INCL. CONTROLLER PT6520 FOR 8-BIT BUS

new !



EA DIP180B-5NLW
Dimension 102 x 27 mm

FEATURES

- * HIGH CONTRAST LCD SUPERTWIST DISPLAY
- * BLUE-WHITE WITH BRIGHT BACKLIGHT: EA DIP180B-5NLW
- * CONTROLLER PT6520 OR COMPATIBLE IS BUILT-IN
- * DIRECT INTERFACE TO 8-BIT DATA BUS
- * POWER SUPPLY +5V / -3.3V max. 800µA
- * LED BACKLIGHTH WHITE max. 45mA@+25°C
- * MORE MODULES MADE IN SAME TECHNOLOGY:
 - DOTMATRIX 1x8, 2x16, 4x20
 - GRAPHIC 122x32, 128x64 AND 240x128
- * NO MOUNTING REQUIRED: JUST SOLDER INTO PCB
- * DETACHABLE VIA SOCKET EA B200-9 (2 PCS. ARE REQUIRED)
- * OPERATING TEMPERATURE RANGE -20..+70°C WITH
- * BUILT-IN TEMPERATURE COMPENSATION

ORDERING CODE

LCD GRAPHIC MODULE 180x32 WITH LED BACKLIGHT
9-PIN SOCKET 4.3mm, pitch 2.0mm (1 PC.)

EA DIP180B-5NLW
EA B200-9

**ELECTRONIC
ASSEMBLY**

making things easy

PINOUT

Pin	Symbol	Level	Funktion	Pin	Symbol	Level	Funktion
1	VSS	L	Stromversorgung 0V (GND)	10	D3	H / L	Display Data
2	VDD	H	Stromversorgung +5V	11	D4	H / L	Display Data
3	VEE	-	Kontrastspg. (ca. -3,3V)	12	D5	H / L	Display Data
4	A0	H / L	Umschaltung Befehl / Daten	13	D6	H / L	Display Data
5	R/W	H / L	H=Read, L=Write	14	D7	H / L	Display Data, MSB
6	E1	H	Enable Spalte 1..60	15	E2	H	Enable Spalte 61..120
7	D0	H / L	Display Data, LSB	16	RES	L	Reset
8	D1	H / L	Display Data	17	E3	H	Enable Spalte 121..180
9	D2	H / L	Display Data	18	C	-	LED (ext. Vorwiderstand!)

CONTROLLER PT6520

The display EA DIP180-5 is featuring 3 controller PT65520 or compatible (for the left, middle and right third of display).

The PT6520 is a full graphic controller without text function. Various character set are supplied on the disc EA DISKFONT1520 which is available as an accessory.

A detailed description for the commands and the interface timing you can find in the user manual for PT6520 / SED1520*).



Column address

0 -----79

D0 } D7	Page 0
D0 } D7	Page 1
D0 } D7	Page 2
D0 } D7	Page 3

Instructions	Code											Function
	A0	RD	WR	D7	D6	D5	D4	D3	D2	D1	D0	
Display ON/OFF	0	1	0	1	0	1	0	1	1	1	0/1	Turns Display on or off. 0=OFF; 1=ON;
Display start line	0	1	0	1	1	0	Display start address (0 - 31)					Specifies RAM line corresponding to top of display.
Set page address	0	1	0	1	0	1	1	1	0	Page (0-3)		Sets display RAM page.
Set Column address	0	1	0	0	Column address (0 - 79)							Sets display RAM column address.
Read Status	0	0	1	B U S Y	A D C	O N / O F F	R E S E T	0	0	0	0	Read the following status: BUSY: 1=Busy; 0=Ready; ADC: 1=CW output; 0=CCW output; ON/OFF: 1=Display off; 0=Display on; RESET: 1=Being reset; 0=Normal;
Write display data	1	1	0	Write data						Writes data into display RAM.		
Read display data	1	0	1	Read data						Reads data from display RAM.		
Select ADC	0	1	0	1	0	1	0	0	0	0	0/1	0=CW output; 1=CCW output;
Static drive ON/OFF	0	1	0	1	0	1	0	0	1	0	0/1	Selects static driving operation. 0=Normal driving; 1=Static drive;
Select duty	0	1	0	1	0	1	0	1	0	0	0/1	Select duty cycle. 0=1/16; 1=1/32;
Read-Modify-Write	0	1	0	1	1	1	0	0	0	0	0	Read-modify-write ON
End	0	1	0	1	1	1	0	1	1	1	0	Read-modify-write OFF
Reset	0	1	0	1	1	1	0	0	0	1	0	Software reset.

*) On internet at <http://www.lcd-module.de/eng/pdf/zubehoer/pt6520.pdf>

CONTRAST ADJUSTMENT

Contrast voltage for EA DIP180-5 is ca. -3.3V. That means that with 5V operation the display do need an additional negative voltage.

An automatic temperature compensation is built-in. A manually realign of contrast while operation over various temperatures is no longer required. Furthermore the display is equipped with a Superfast-Liquid, which fast enough even at the very low temperature of -20°C. Response time is typ. 2.5 seconds only.


BACKLIGHT

The built-in backlight requires a current source or an external limiting resistor. Forward voltage for backlight is between 3.0V and 3.6V. Please consider that a current derating is necessary for operating und temperatures above +25°C.

Note that display cannot be read without backlight. But even with some single mA reading is possible. When ambient brightness grows, then backlight brightness need to grow also.

Attention: do never connect the backlight direct to 5V. This will damage the display immediately !

DIMENSION



ELECTRONIC ASSEMBLY

making things easy

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А