


# TWA Series – DSCC 93026



## TWA Wet Electrolytic Tantalum Capacitor




The TWA series is an axial leaded wet electrolytic tantalum capacitor and represents a new level of high CV (capacitance/voltage) previously unavailable in this technology. TWA incorporates a novel, very high capacitance cathode system that allows for higher CV designs, well beyond values specified in the Mil-PRF-39006 drawing.

TWA products are listed in DSCC 93026, which includes new high capacitance/voltage ratings. This design includes a welded tantalum can and header assembly that provides a hermetic seal to withstand harsh shock and vibration requirements of 39006. Wet tantalums do not require the same derating as solid tantalums. AVX recommends derating components by only 20% in order to enhance reliability.

Customized capacitance and voltage packages are possible and welcomed. Contact the factory about design possibilities beyond those contained in this datasheet.

### OUTLINE DIMENSIONS



### CASE DIMENSIONS: millimeters (inches)

| DSCC Case Size | AVX Case Size | L<br>+0.79 (0.031)<br>-0.41 (0.016) | D<br>Without Insulating Sleeve<br>±0.41 (0.016) | D<br>With Insulating Sleeve<br>Max | E<br>±6.35 (0.250) |
|----------------|---------------|-------------------------------------|-------------------------------------------------|------------------------------------|--------------------|
| T1             | A             | 11.51 (0.453)                       | 4.78 (0.188)                                    | 5.56 (0.219)                       | 38.10 (1.500)      |
| T2             | B             | 16.28 (0.641)                       | 7.14 (0.281)                                    | 7.92 (0.312)                       | 57.15 (2.250)      |
| T3             | D             | 19.46 (0.766)                       | 9.52 (0.375)                                    | 10.31 (0.406)                      | 57.15 (2.250)      |
| T4             | E             | 26.97 (1.062)                       | 9.52 (0.375)                                    | 10.31 (0.406)                      | 57.15 (2.250)      |

### VOLTAGE RATINGS (Operating Temperature -55°C to 125°C)

| Voltage (DC)          |       |      |      |      |    |      |     |     |
|-----------------------|-------|------|------|------|----|------|-----|-----|
| Rated Voltage: (Ur)   | 85°C  | 25   | 30   | 50   | 60 | 75   | 100 | 125 |
| Derated Voltage: (Uc) | 125°C | 15   | 20   | 30   | 40 | 50   | 65  | 85  |
| Surge Voltage: (Us)   | 85°C  | 28.8 | 34.5 | 57.5 | 69 | 86.3 | 115 | 144 |



# TWA Series – DSCC 93026



## TWA Wet Electrolytic Tantalum Capacitor

### HOW TO ORDER

#### AVX PART NUMBER:

| TWA  | D         | 227                                                                                                                                      | *                                             | 035          | □                                                          | B                          | S                                                                   | Z                         | 0                                                   | 0                                     | 00                                   |
|------|-----------|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|--------------|------------------------------------------------------------|----------------------------|---------------------------------------------------------------------|---------------------------|-----------------------------------------------------|---------------------------------------|--------------------------------------|
| Type | Case Size | Capacitance Code<br>pF code:<br>1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow) | Capacitance Tolerance<br>K = ±10%<br>M = ±20% | Voltage Code | Insulation Sleeve<br>C = Without Sleeve<br>S = With Sleeve | Packaging<br>B = Tray Pack | Inspection Level<br>S = Std. Conformance<br>D = DSCC<br>L = Group A | Reliability<br>Z = Non-ER | Qualification Level<br>0 = COTS-Plus<br>9 = SRC9000 | Termination Finish<br>0 = Sn/Pb 60/40 | Custom Test Options<br>00 = Standard |

#### DSCC PART IDENTIFICATION NUMBER (PIN):

| 93026          | -XX                              | *                                             | □                                                          |
|----------------|----------------------------------|-----------------------------------------------|------------------------------------------------------------|
| Drawing Number | Dash Number<br>See Rating Tables | Capacitance Tolerance<br>K = ±10%<br>M = ±20% | Insulation Sleeve<br>U = Without Sleeve<br>S = With Sleeve |

#### SPACE LEVEL OPTIONS TO SRC9000\*:

| TWA  | D         | 227                                                                                                                                      | *                                             | 035          | □                                                          | B                          | L                               | Z                         | 9                                  | 0                                     | 00                                   |
|------|-----------|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|--------------|------------------------------------------------------------|----------------------------|---------------------------------|---------------------------|------------------------------------|---------------------------------------|--------------------------------------|
| Type | Case Size | Capacitance Code<br>pF code:<br>1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow) | Capacitance Tolerance<br>M = ±20%<br>K = ±10% | Voltage Code | Insulation Sleeve<br>C = Without Sleeve<br>S = With Sleeve | Packaging<br>B = Tray Pack | Inspection Level<br>L = Group A | Reliability<br>Z = Non-ER | Qualification Level<br>9 - SRW9000 | Termination Finish<br>0 = Sn/Pb 60/40 | Custom Test Options<br>00 = Standard |

\* Check with factory for availability and testing details

### RIPPLE CURRENT MULTIPLIERS vs. Frequency, temperature and applied voltage<sup>1/2/</sup>

| Frequency of Applied Ripple Current |         | 120Hz |      |      |      | 800Hz |      |      |      | 1kHz |      |      |      |
|-------------------------------------|---------|-------|------|------|------|-------|------|------|------|------|------|------|------|
|                                     |         | ≤55   | 85   | 105  | 125  | ≤55   | 85   | 105  | 125  | ≤55  | 85   | 105  | 125  |
| Ambient Still Air Temperature (°C)  | % of    | 100%  | 0.60 | 0.39 | –    | 0.71  | 0.43 | –    | –    | 0.72 | 0.45 | –    | –    |
|                                     | 85°C    | 90%   | 0.60 | 0.46 | –    | 0.71  | 0.55 | –    | –    | 0.72 | 0.55 | –    | –    |
| Rated Peak                          | 80%     | 0.60  | 0.52 | 0.35 | –    | 0.71  | 0.62 | 0.42 | –    | 0.72 | 0.62 | 0.42 | –    |
|                                     | 70%     | 0.60  | 0.58 | 0.44 | –    | 0.71  | 0.69 | 0.52 | –    | 0.72 | 0.70 | 0.52 | –    |
| Voltage                             | 66-2/3% | 0.60  | 0.60 | 0.46 | 0.27 | 0.71  | 0.71 | 0.55 | 0.32 | 0.72 | 0.72 | 0.55 | 0.32 |

| Frequency of Applied Ripple Current |         | 10kHz |      |      |      | 40kHz |      |      |      | 100kHz |      |      |      |
|-------------------------------------|---------|-------|------|------|------|-------|------|------|------|--------|------|------|------|
|                                     |         | ≤55   | 85   | 105  | 125  | ≤55   | 85   | 105  | 125  | ≤55    | 85   | 105  | 125  |
| Ambient Still Air Temperature (°C)  | % of    | 100%  | 0.88 | 0.55 | –    | 1.00  | 0.63 | –    | –    | 1.10   | 0.69 | –    | –    |
|                                     | 85°C    | 90%   | 0.88 | 0.67 | –    | 1.00  | 0.77 | –    | –    | 1.10   | 0.85 | –    | –    |
| Rated Peak                          | 80%     | 0.88  | 0.76 | 0.52 | –    | 1.00  | 0.87 | 0.59 | –    | 1.10   | 0.96 | 0.65 | –    |
|                                     | 70%     | 0.88  | 0.85 | 0.64 | –    | 1.00  | 0.97 | 0.73 | –    | 1.10   | 1.07 | 0.80 | –    |
| Voltage                             | 66-2/3% | 0.88  | 0.88 | 0.68 | 0.40 | 1.00  | 1.00 | 0.77 | 0.45 | 1.10   | 1.10 | 0.85 | 0.50 |

1/ At 125°C the rated voltage of the capacitors decreases to 66 2/3 of the 85°C rated voltage.

2/ The peak of the applied ac ripple voltage plus the applied dc voltage must not exceed the dc voltage rating of the capacitors.



# TWA Series – DSCC 93026



## TWA Wet Electrolytic Tantalum Capacitor

### RATINGS & PART NUMBER REFERENCE

| AVX Part Number                 | DSCC Part Number | Cap (µF)<br>25°C<br>at 120Hz | DC Rated Voltage (V)<br>at 85°C | ESR max (ohms)<br>at 120Hz | DC Leakage max (µA) |               | Impedance max (Ohms)<br>-55°C at 120Hz | Maximum Capacitance Change (%) |       |        | AC Ripple (mA rms)<br>85°C at 40kHz | Case Size |      |
|---------------------------------|------------------|------------------------------|---------------------------------|----------------------------|---------------------|---------------|----------------------------------------|--------------------------------|-------|--------|-------------------------------------|-----------|------|
|                                 |                  |                              |                                 |                            | +25°C               | +85°C & 125°C |                                        | -55°C                          | +85°C | +125°C |                                     | AVX       | DSCC |
| 25 VDC at 85°C 15 VDC at 125°C  |                  |                              |                                 |                            |                     |               |                                        |                                |       |        |                                     |           |      |
| TWAA127*025□BSZ0000             | 93026- 29*□      | 120                          | 25                              | 1.3                        | 1                   | 5             | 25                                     | -42                            | 8     | 12     | 1250                                | A         | T1   |
| TWAB567*025□BSZ0000             | 93026- 30*□      | 560                          | 25                              | 0.83                       | 2                   | 10            | 12                                     | -65                            | 10    | 15     | 2100                                | B         | T2   |
| TWAD128*025□BSZ0000             | 93026- 31*□      | 1200                         | 25                              | 0.65                       | 5                   | 20            | 7                                      | -70                            | 12    | 18     | 2600                                | D         | T3   |
| TWAE188*025□BSZ0000             | 93026- 32*□      | 1800                         | 25                              | 0.5                        | 6                   | 25            | 7                                      | -75                            | 12    | 20     | 3100                                | E         | T4   |
| TWAE228*025□BSZ0000             | 93026- 64*□      | 2200                         | 25                              | 0.5                        | 10                  | 80            | 10                                     | -90                            | 30    | 50     | 3200                                | E         | T4   |
| 30 VDC at 85°C 20 VDC at 125°C  |                  |                              |                                 |                            |                     |               |                                        |                                |       |        |                                     |           |      |
| TWAA107*030□BSZ0000             | 93026- 33*□      | 100                          | 30                              | 1.3                        | 1                   | 5             | 25                                     | -38                            | 8     | 12     | 1200                                | A         | T1   |
| TWAB477*030□BSZ0000             | 93026- 34*□      | 470                          | 30                              | 0.85                       | 2                   | 10            | 15                                     | -65                            | 10    | 18     | 1800                                | B         | T2   |
| TWAD108*030□BSZ0000             | 93026- 35*□      | 1000                         | 30                              | 0.7                        | 7                   | 25            | 7                                      | -70                            | 10    | 18     | 2500                                | D         | T3   |
| TWAE158*030□BSZ0000             | 93026- 36*□      | 1500                         | 30                              | 0.6                        | 12                  | 35            | 6                                      | -72                            | 10    | 20     | 3000                                | E         | T4   |
| 50 VDC at 85°C 30 VDC at 125°C  |                  |                              |                                 |                            |                     |               |                                        |                                |       |        |                                     |           |      |
| TWAA686*050□BSZ0000             | 93026- 37*□      | 68                           | 50                              | 1.5                        | 1                   | 5             | 35                                     | -25                            | 8     | 15     | 1050                                | A         | T1   |
| TWAB227*050□BSZ0000             | 93026- 38*□      | 220                          | 50                              | 0.9                        | 2                   | 10            | 17.5                                   | -50                            | 8     | 15     | 1800                                | B         | T2   |
| TWAD477*050□BSZ0000             | 93026- 39*□      | 470                          | 50                              | 0.75                       | 3                   | 25            | 10                                     | -50                            | 8     | 15     | 2100                                | D         | T3   |
| TWAE687*050□BSZ0000             | 93026- 40*□      | 680                          | 50                              | 0.7                        | 5                   | 40            | 8                                      | -58                            | 10    | 20     | 2750                                | E         | T4   |
| 60 VDC at 85°C 40 VDC at 125°C  |                  |                              |                                 |                            |                     |               |                                        |                                |       |        |                                     |           |      |
| TWAA476*060□BSZ0000             | 93026- 41*□      | 47                           | 60                              | 2                          | 1                   | 5             | 44                                     | -25                            | 8     | 12     | 1050                                | A         | T1   |
| TWAB157*060□BSZ0000             | 93026- 42*□      | 150                          | 60                              | 1.1                        | 2                   | 10            | 20                                     | -40                            | 8     | 15     | 1650                                | B         | T2   |
| TWAD397*060□BSZ0000             | 93026- 43*□      | 390                          | 60                              | 0.9                        | 3                   | 25            | 15                                     | -60                            | 8     | 15     | 2100                                | D         | T3   |
| TWAE567*060□BSZ0000             | 93026- 44*□      | 560                          | 60                              | 0.8                        | 5                   | 40            | 10                                     | -58                            | 8     | 15     | 2750                                | E         | T4   |
| TWAE108*060□BSZ0000             | 93026- 65*□      | 1000                         | 60                              | 1                          | 12                  | 90            | 20                                     | -90                            | 30    | 50     | 3200                                | E         | T4   |
| 75 VDC at 85°C 50 VDC at 125°C  |                  |                              |                                 |                            |                     |               |                                        |                                |       |        |                                     |           |      |
| TWAA336*075□BSZ0000             | 93026- 45*□      | 33                           | 75                              | 2.5                        | 1                   | 5             | 66                                     | -25                            | 5     | 9      | 1050                                | A         | T1   |
| TWAB117*075□BSZ0000             | 93026- 46*□      | 110                          | 75                              | 1.3                        | 2                   | 10            | 24                                     | -35                            | 6     | 10     | 1650                                | B         | T2   |
| TWAD337*075□BSZ0000             | 93026- 47*□      | 330                          | 75                              | 1                          | 3                   | 30            | 12                                     | -45                            | 6     | 10     | 2100                                | D         | T3   |
| TWAE477*075□BSZ0000             | 93026- 48*□      | 470                          | 75                              | 0.9                        | 5                   | 50            | 12                                     | -55                            | 6     | 10     | 2750                                | E         | T4   |
| 100 VDC at 85°C 65 VDC at 125°C |                  |                              |                                 |                            |                     |               |                                        |                                |       |        |                                     |           |      |
| TWAA156*100□BSZ0000             | 93026- 49*□      | 15                           | 100                             | 3.5                        | 1                   | 5             | 125                                    | -18                            | 3     | 10     | 1050                                | A         | T1   |
| TWAB686*100□BSZ0000             | 93026- 50*□      | 68                           | 100                             | 2.1                        | 2                   | 10            | 37                                     | -30                            | 4     | 12     | 1650                                | B         | T2   |
| TWAD157*100□BSZ0000             | 93026- 51*□      | 150                          | 100                             | 1.6                        | 3                   | 25            | 22                                     | -35                            | 6     | 12     | 2100                                | D         | T3   |
| TWAE227*100□BSZ0000             | 93026- 52*□      | 220                          | 100                             | 1.2                        | 5                   | 50            | 15                                     | -40                            | 6     | 12     | 2750                                | E         | T4   |
| 125 VDC at 85°C 85 VDC at 125°C |                  |                              |                                 |                            |                     |               |                                        |                                |       |        |                                     |           |      |
| TWAA106*125□BSZ0000             | 93026- 53*□      | 10                           | 125                             | 5.5                        | 1                   | 5             | 175                                    | -15                            | 3     | 10     | 1050                                | A         | T1   |
| TWAB476*125□BSZ0000             | 93026- 54*□      | 47                           | 125                             | 2.3                        | 2                   | 10            | 47                                     | -25                            | 5     | 12     | 1650                                | B         | T2   |
| TWAD107*125□BSZ0000             | 93026- 55*□      | 100                          | 125                             | 1.8                        | 3                   | 25            | 35                                     | -35                            | 5     | 12     | 2100                                | D         | T3   |
| TWAE157*125□BSZ0000             | 93026- 56*□      | 150                          | 125                             | 1.6                        | 5                   | 50            | 20                                     | -35                            | 6     | 12     | 2750                                | E         | T4   |

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5RMS with DC bias of 2.2V. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the rights to supply higher voltage rating in the same case size, to the same reliability standards.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А