

### Features

- High static and dynamic commutation
- Three quadrants
- Logic level (direct microcontroller driven)
- Package is RoHS (2002/95/EC) compliant
- Tab insulated, voltage = 2500 V rms
- UL certified (ref. file E81734)

### Applications


- General purpose AC line load switching
- Home appliances:
  - Fan
  - Pump
  - Solenoid
- Lighting
- Heaters
- Inrush current limiting circuits
- Overvoltage crowbar protection circuits

### Description

Available in TO220AB-Insulated (ceramic insulated), the T1610T-8I series of Triac can be used in an on/off or phase angle control function in general purpose AC switching.

T1610T-8I can be directly driven through a microcontroller allowing usage of small capacitive or resistive power supplies.

Provides insulation rated at 2500 V rms (TO-220AB insulated package).



**Table 1. Device summary**

| Order code | Quadrants    | Value $I_{GT}$ (mA) |
|------------|--------------|---------------------|
| T1610T-8I  | I - II - III | 10                  |

# 1 Characteristics

**Table 2. Absolute maximum rating ( $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified)**

| Symbol                | Parameter  |                      | Value                             | Unit        |                        |
|-----------------------|--|----------------------|-----------------------------------|-------------|------------------------|
| $I_{T(RMS)}$          | On-state rms current (full sine wave)  |                      | $T_c = 108\text{ }^\circ\text{C}$ | 16          | A                      |
|                       |  |                      | $T_c = 119\text{ }^\circ\text{C}$ | 12          |                        |
| $I_{TSM}$             | Non repetitive surge peak on-state current (full cycle, $T_j$ initial = $25\text{ }^\circ\text{C}$ ) | $F = 50\text{ Hz}$   | $t = 20\text{ ms}$                | 120         | A                      |
|                       |  | $F = 60\text{ Hz}$   | $t = 16.7\text{ ms}$              | 126         |                        |
| $I^2t$                | $I^2t$ Value for fusing  |                      | $t_p = 10\text{ ms}$              | 95          | $\text{A}^2\text{s}$   |
| $V_{DRM}, V_{RRM}$    | Repetitive peak off-state voltage, gate open   |                      | $T_j = 150\text{ }^\circ\text{C}$ | 600         | V                      |
|                       |  |                      | $T_j = 125\text{ }^\circ\text{C}$ | 800         |                        |
| $V_{DSM}, V_{RSM}$    | Non repetitive surge peak off-state voltage  | $t_p = 10\text{ ms}$ | $T_j = 25\text{ }^\circ\text{C}$  | 900         | V                      |
| $di/dt$               | Critical rate of rise of on-state current $I_G = 2 \times I_{GT}$                                    |                      | $F = 100\text{ Hz}$               | 100         | $\text{A}/\mu\text{s}$ |
| $I_{GM}$              | Peak gate current  |                      | $t_p = 20\text{ }\mu\text{s}$     | 4           | A                      |
| $P_{G(AV)}$           | Average gate power dissipation   |                      |                                   | 1           | W                      |
| $T_{stg}, T_j$        | Storage junction temperature range   |                      |                                   | -40 to +150 | $^\circ\text{C}$       |
|                       | Operating junction temperature range   |                      |                                   | -40 to +150 |                        |
| $T_L$                 | Lead temperature for soldering during 10 s (at 4 mm from case for TO220AB-ins.)                      |                      |                                   | 260         | $^\circ\text{C}$       |
| $V_{ins}(\text{rms})$ | Insulation rms voltage, 1 minute, TO220AB ceramic insulated  |                      |                                   | 2500        | V                      |

**Table 3. Electrical characteristics ( $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified)**

| Symbol            | Test conditions  | Quadrant                          |      | Value | Unit             |
|-------------------|--|-----------------------------------|------|-------|------------------|
| $I_{GT}^{(1)}$    | $V_D = 12\text{ V}$ , $R_L = 30\ \Omega$   | I - II - III                      | MIN. | 0.5   | mA               |
|                   |  | I - II - III                      | MAX. | 10    | mA               |
| $V_{GT}$          | $V_D = 12\text{ V}$ , $R_L = 30\ \Omega$   | All                               | MAX. | 1.3   | V                |
| $V_{GD}$          | $V_D = 800\text{ V}$ , $R_L = 3.3\text{ k}\Omega$ , $T_j = 125\text{ }^\circ\text{C}$  | All                               | MIN. | 0.2   | V                |
| $I_H^{(1)}$       | $I_T = 500\text{ mA}$  |                                   | MAX. | 25    | mA               |
| $I_L$             | $I_G = 1.2 I_{GT}$   | I - III                           | MAX. | 20    | mA               |
|                   |  | II                                |      | 30    |                  |
| $dV/dt^{(1)}$     | $V_D = 67\% \times 800\text{ V}$ gate open   | $T_j = 125\text{ }^\circ\text{C}$ | MIN. | 100   | V/ $\mu\text{s}$ |
|                   | $V_D = 67\% \times 600\text{ V}$ gate open   | $T_j = 150\text{ }^\circ\text{C}$ |      | 50    |                  |
| $(dI/dt)_c^{(1)}$ | $(dV/dt)_c = 0.1\text{ V}/\mu\text{s}$   | $T_j = 125\text{ }^\circ\text{C}$ | MIN. | 9     | A/ms             |
|                   | $(dV/dt)_c = 10\text{ V}/\mu\text{s}$  | $T_j = 125\text{ }^\circ\text{C}$ |      | 3     |                  |
|                   | $(dV/dt)_c = 0.1\text{ V}/\mu\text{s}$   | $T_j = 150\text{ }^\circ\text{C}$ |      | 5.4   |                  |
|                   | $(dV/dt)_c = 10\text{ V}/\mu\text{s}$  | $T_j = 150\text{ }^\circ\text{C}$ |      | 1.8   |                  |
| $t_{GT}$          | gate controlled turn on time $I_{TM} = 13\text{ A}$ , $V_D = 400\text{ V}$ ,<br>$I_G = 100\text{ mA}$ , $dI_G/dt = 100\text{ mA}/\mu\text{s}$ , $R_L = 30\ \Omega$ | I - II - III                      | TYP. | 2     | $\mu\text{s}$    |

1. For both polarities of A2 referenced to A1

**Table 4. Static characteristics**

| Symbol                 | Test conditions                                     |                                   |      | Value | Unit             |
|------------------------|---|-----------------------------------|------|-------|------------------|
| $V_{TM}^{(1)}$         | $I_{TM} = 22.6\text{ A}$ , $t_p = 380\ \mu\text{s}$ | $T_j = 25\text{ }^\circ\text{C}$  | MAX. | 1.55  | V                |
| $V_{to}^{(1)}$         | Threshold voltage                                   | $T_j = 150\text{ }^\circ\text{C}$ | MAX. | 0.85  | V                |
| $R_d^{(1)}$            | Dynamic resistance                                  | $T_j = 150\text{ }^\circ\text{C}$ | MAX. | 30    | $\text{m}\Omega$ |
| $I_{DRM}$<br>$I_{RRM}$ | $V_{DRM} = V_{RRM} = 800\text{ V}$                  | $T_j = 25\text{ }^\circ\text{C}$  | MAX. | 5     | $\mu\text{A}$    |
|                        |   | $T_j = 125\text{ }^\circ\text{C}$ |      | 1     | mA               |
|                        | $V_{DRM} = V_{RRM} = 600\text{ V}$                  | $T_j = 150\text{ }^\circ\text{C}$ |      | 3.6   |                  |

1. for both polarities of A2 referenced to A1

**Table 5. Thermal resistance**

| Symbol        | Parameter             | Value | Unit                      |
|---------------|-----------------------|-------|---------------------------|
| $R_{th(j-c)}$ | Junction to case (AC) | 2.1   | $^\circ\text{C}/\text{W}$ |
| $R_{th(j-a)}$ | Junction to ambient   | 60    | $^\circ\text{C}/\text{W}$ |

Figure 1. Maximum power dissipation versus on-state rms current (full cycle)




Figure 2. On-state rms current versus case temperature (full cycle)




Figure 3. On-state rms current versus ambient temperature (free air convection)




Figure 4. Relative variation of thermal impedance versus pulse duration




Figure 5. On-state characteristics (maximum values)




Figure 6. Surge peak on-state current versus number of cycles




Figure 7. Non repetitive surge peak on-state current and corresponding values of  $I^2t$




Figure 8. Relative variation of gate trigger current versus junction temperature (typical values)




Figure 9. Relative variation of gate trigger voltage versus junction temperature (typical values)




Figure 10. Relative variation of holding current and latching current versus junction temperature




Figure 11. Relative variation of critical rate of decrease of current (di/dt)<sub>c</sub> versus reapplied (dV/dt)<sub>c</sub>




Figure 12. Relative variation of critical rate of decrease of current (di/dt)<sub>c</sub> versus junction temperature




Figure 13. Relative variation of static dV/dt immunity versus junction temperature




Figure 14. Relative variation of static dV/dt immunity versus junction temperature





Figure 15. Relative variation of leakage current versus junction temperature for different values of blocking voltage




## 2 Package information

- Epoxy meets UL94, V0
- Recommended torque value: 0.4 to 0.6 N-m

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.


**Table 6. TO-220AB insulated dimensions**

| Ref. | Dimensions  |       |       |        |       |       |
|------|-------------|-------|-------|--------|-------|-------|
|      | Millimeters |       |       | Inches |       |       |
|      | Min.        | Typ.  | Max.  | Min.   | Typ.  | Max.  |
| A    | 15.20       |       | 15.90 | 0.598  |       | 0.625 |
| a1   |             | 3.75  |       |        | 0.147 |       |
| a2   | 13.00       |       | 14.00 | 0.511  |       | 0.551 |
| B    | 10.00       |       | 10.40 | 0.393  |       | 0.409 |
| b1   | 0.61        |       | 0.88  | 0.024  |       | 0.034 |
| b2   | 1.23        |       | 1.32  | 0.048  |       | 0.051 |
| C    | 4.40        |       | 4.60  | 0.173  |       | 0.181 |
| c1   | 0.49        |       | 0.70  | 0.019  |       | 0.027 |
| c2   | 2.40        |       | 2.72  | 0.094  |       | 0.107 |
| e    | 2.40        |       | 2.70  | 0.094  |       | 0.106 |
| F    | 6.20        |       | 6.60  | 0.244  |       | 0.259 |
| ØI   | 3.75        |       | 3.85  | 0.147  |       | 0.151 |
| I4   | 15.80       | 16.40 | 16.80 | 0.622  | 0.646 | 0.661 |
| L    | 2.65        |       | 2.95  | 0.104  |       | 0.116 |
| I2   | 1.14        |       | 1.70  | 0.044  |       | 0.066 |
| I3   | 1.14        |       | 1.70  | 0.044  |       | 0.066 |
| M    |             | 2.60  |       |        | 0.102 |       |



### 3 Ordering information scheme

Figure 16. Ordering information scheme





## 4 Ordering information

Table 7. Ordering information

| Order code | Marking   | Package               | Weight | Base qty | Delivery mode |
|------------|-----------|-----------------------|--------|----------|---------------|
| T1610T-8I  | T1610T-8I | TO-220AB<br>insulated | 2.3    | 50       | Tube          |

## 5 Revision history

Table 8. Document revision history

| Date        | Revision | Changes   |
|-------------|----------|---|
| 08-Aug-2011 | 1        | First issue.  |
| 20-Jan-2012 | 2        | Corrected subscripting error in <a href="#">Table 3</a> . |
| 25-Apr-2012 | 3        | Updated UL certification.                                 |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А