
EVERLIGHT ELECTRONICS CO.,LTD.

Technical Data Sheet

4.7mm 1Pcs Circuit Board Indicator

A2753/SDR/S530-A3-I1



■ Features :

- Low power consumption
- High efficiency and low cost
- Good control and free combinations on the colors of LED lamps
- Good lock and easy to assembly
- Stackable and easy to assembly
  Stackable vertically and easy to assembly
- Versatile mounting on P.C board or panel
- Stackable horizontally and easy to assembly
- Pb free
- The product itself will remain within RoHS compliant version

■ Descriptions :

- ARRAY=Plastic Holder+Combinations of Lamps
- The array will easily mount the applicable lamps on any panel up to

■ Applications :


- 1.Used as indicators of indicating the Degree, Functions, Positions etc, in electronic instruments.

PART NO.	Chip		Lens Color
	Material	Emitted Color	
7363-2SDRD/S530-A3	AlGaInP	Super Deep-Red	Red Diffused

Technical Data Sheet
4.7mm 1Pcs Circuit Board Indicator

A2753/SDR/S530-A3-I1

Package Dimensions



Notes: 1.All dimensions are in millimeters, tolerance is 0.25mm except being specified
2.Lead spacing is measured where the lead emerge from the package

■ Absolute Maximum Ratings at Ta = 25℃

Parameter	Symbol	Rating	Unit
Forward Current	IF	25	mA
Operating Temperature	Topr	-40 to +85	℃
Storage Temperature	Tstg	-40 to +100	℃
Soldering Temperature	Tsol	260 ± 5	℃
Electrostatic Discharge	ESD	2000	V
Power Dissipation	Pd	60	mW
Reverse Voltage	VR	5	V

Note: *1:Soldering time ≦ 5 seconds.

Technical Data Sheet
4.7mm 1Pcs Circuit Board Indicator


A2753/SDR/S530-A3-I1


Electro-Optical Characteristics(Ta=25℃)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	I_F= 20 mA	／	2.0	2.4	V
Reverse Current	I_R	V_R= 5 V	／	／	10	μA
Luminous Intensity	Iv	I_F= 20 mA	25	50	／	mcd
Viewing Angle	2θ1/2	I_F= 20 mA	／	40	／	deg
Peak Wavelength	λp	I_F= 20 mA	／	650	／	nm
Dominant Wavelength	λd	I_F= 20 mA	／	639	／	nm
Spectrum Radiation Bandwidth	△λ	I_F= 20 mA	／	20	／	nm


■ Typical Electro-Optical Characteristic Curves:


(SDR)














Technical Data Sheet
4.7mm 1Pcs Circuit Board Indicator

A2753/SDR/S530-A3-I1

■ Reliability test items and conditions:

The reliability of products shall be satisfied with items listed below.

Confidence level：97%

LTPD：3%

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Failure Judgment Criteria	Ac/Re
1	Solder Heat	TEMP : 260℃ ± 5 ℃	10 SEC	76 PCS	Iv≦Ivt*0.5 or Vf≧U or Vf≦L	0/1
2	Temperature Cycle	H : +100℃ 15min ∫ 5 min L : -40℃ 15min	300 CYCLES	76 PCS		0/1
3	Thermal Shock	H : +100℃ 5min ∫ 10 sec L : -10℃ 5min	300 CYCLES	76 PCS		0/1
4	High Temperature Storage	TEMP : 100℃	1000 HRS	76 PCS		0/1
5	Low Temperature Storage	TEMP : -40℃	1000 HRS	76 PCS		0/1
6	DC Operating Life	TEMP : 25℃ I_F = 20mA	1000 HRS	76 PCS		0/1
7	High Temperature / High Humidity	85℃ / 85% RH	1000 HRS	76 PCS		0/1

Note： Ivt：To test Iv value of the chip before the reliablility test

Iv：The test value of the chip that has completed the reliablility test

U：Upper Specification Limit

L： Lower Specification Limit

Technical Data Sheet
4.7mm 1Pcs Circuit Board Indicator

A2753/SDR/S530-A3-I1

Packing Quantity Specification

1. 236PCS/1Plate，4Plates/1Box
2. 10Boxes/1Carton

Label Form Specification



CPN: Customer’ s Production Number
P/N : Production Number
QTY: Packing Quantity
CAT: Ranks
HUE:Dominant Wavelength
REF: Reference
LOT No: Lot Number
MADE IN TAIWAN: Production Place

Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.

The product itself will remain within RoHS compliant version for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.

3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don’ t reproduce or cause anyone to reproduce them without EVERLIGHT’ sconsent.

EVERLIGHT ELECTRONICS CO., LTD. *Tel: (886-2-2267-2000, 2267-9936*
Office: No 25, Lane 76, Sec 3, Chung Yang Rd, *Fax: 886-2267-6244, 2267-6189, 2267-6306*
Tucheng, Taipei 236, Taiwan, R.O.C *http:\\www.everlight.com*

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А