

## 1585A Multi-Conductor - Category 5e Nonbonded-Pair Cable



For more Information  
please call

1-800-Belden1



### Description:

24 AWG Solid Bare Copper Conductors, Dual FRPO/FEP Insulation, Twisted pairs, Rip Cord, Flamarrest® Jacket.

### Usage (Overall)

**Suitable Applications:** Horizontal Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Video, RS-422

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Pairs	AWG	Stranding	Conductor Material
4	24	Solid	BC - Bare Copper

#### Insulation

##### Insulation Material:

Insulation Material
FRPO/FEP - Flame Retardant Polyolefin/Fluorinated Ethylene Propylene

#### Outer Shield

##### Outer Shield Material:

Outer Shield Material
Unshielded

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

##### Outer Jacket Diameter:

Nom. Dia. (mm)
4.826

**Outer Jacket Ripcord:** Yes

### Overall Cabling

#### Pair

##### Pair Color Code Chart:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Mechanical Characteristics (Overall)

**Storage Temperature Range:** -20°C To +75°C

**Installation Temperature Range:** 0°C To +60°C

**Operating Temperature Range:** -20°C To +60°C

**Bulk Cable Weight:** 29.764 Kg/Km

## 1585A Multi-Conductor - Category 5e Nonbonded-Pair Cable

Max. Recommended Pulling Tension:	155.687 N
Min. Bend Radius (Install)/Minor Axis:	25.400 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
NEC Articles:	800
CEC/C(UL) Specification:	CMP
Other Standards:	ISO/IEC 11801 ed 2.1 (2008) Class D
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 5e - TIA 568.C.2
Other Specification:	NEMA WC-63.1 Category 5e, UL Verified to Category 5e

#### Applicable Patents:

Country	Patent
US	5563377
CANADA	2144694

#### Flame Test

UL Flame Test:	NFPA 262 Plenum Flame Test (UL910)(FT6)
C(UL) Flame Test:	FT6
CSA Flame Test:	FT6

#### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Aerial:	No
Suitability - Burial:	No
Sunlight Resistance:	No
Oil Resistance:	No
Non-halogenated:	No

#### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	1583A

### Electrical Characteristics (Overall)

#### Nom. Mutual Capacitance:

Capacitance (pF/m)
49.215

Maximum Capacitance Unbalance (pF/100 m):	330
-------------------------------------------	-----

#### Nominal Velocity of Propagation:

VP (%)
--------

## 1585A Multi-Conductor - Category 5e Nonbonded-Pair Cable

72

**Maximum Delay:**

Delay (ns/100 m)  
538 @ 100MHz

**Max. Delay Skew:**

Delay Skew (ns/100 m)  
45

**Maximum Conductor DC Resistance:**

DCR @ 20°C (Ohm/100 m)  
9.38

**Max. Operating Voltage - UL:**

Voltage  
300 V RMS

**Maximum DCR Unbalanced:**

DCR Unbalance @ 20°C (%)  
3

### Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)	Min. SRL (dB)
1	2.0	65.3	62.3	63.0	60.3	20.0	23.0
4	4.1	56.3	53.3	51.0	49.2	23.0	23.0
8	5.8	51.8	48.8	46.0	43.0	24.5	24.5
10	6.5	50.3	47.3	43.0	40.8	25.0	25.0
16	8.2	47.3	44.3	39.0	36.0	25.0	25.0
20	9.3	45.8	42.8	36.5	33.5	25.0	25.0
25	10.4	44.3	41.3	33.9	30.9	24.3	24.3
31.25	11.7	42.9	39.9	31.0	28.2	23.6	23.6
62.5	17.0	38.4	35.4	22.0	19.0	21.5	21.5
100	22.0	35.3	32.3	14.0	10.3	20.1	20.1
155	28.1	32.5	29.5	4.4	1.4	15.8	
200	32.0	30.8	27.8	4.0	1.0	15.0	

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.8	60.8
4	100 ± 15	100 ± 15	51.7	48.7
8	100 ± 15	100 ± 15	45.7	42.7
10	100 ± 15	100 ± 15	43.8	40.8
16	100 ± 15	100 ± 15	39.7	36.7
20	100 ± 15	100 ± 15	37.7	34.7
25	100 ± 15	100 ± 15	35.8	32.8
31.25	100 ± 15	100 ± 15	33.9	30.9
62.5	100 ± 15	100 ± 15	27.8	24.9
100	100 ± 15	100 ± 15	23.8	20.8
155	100 ± 25	100 ± 15	19.9	16.9
200	100 ± 25	100 ± 15	17.7	14.7

### Notes (Overall)

**Notes:** Jacket sequentially marked at 2 ft. intervals. Third party verified to ANSI/TIA-568-C.2, Category 5e.

### Related Documents:

No related documents are available for this product

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

## 1585A Multi-Conductor - Category 5e Nonbonded-Pair Cable

1585A D15U1000	305 MT	10.433 KG	BLUE		CAT5E 4PR U/UTP CMP BOX
1585A D151000	305 MT	10.886 KG	BLUE	C	CAT5E 4PR U/UTP CMP REEL
1585A D153000	914 MT	31.298 KG	BLUE	C	CAT5E 4PR U/UTP CMP REEL
1585A 002U1000	305 MT	10.433 KG	RED		CAT5E 4PR U/UTP CMP BOX
1585A 0021000	305 MT	10.886 KG	RED	C	CAT5E 4PR U/UTP CMP REEL
1585A 003U1000	305 MT	10.433 KG	ORANGE		CAT5E 4PR U/UTP CMP BOX
1585A 0031000	305 MT	10.886 KG	ORANGE	C	CAT5E 4PR U/UTP CMP REEL
1585A 004U1000	305 MT	10.433 KG	YELLOW		CAT5E 4PR U/UTP CMP BOX
1585A 0041000	305 MT	10.886 KG	YELLOW	C	CAT5E 4PR U/UTP CMP REEL
1585A 005U1000	305 MT	10.433 KG	GREEN, DARK		CAT5E 4PR U/UTP CMP BOX
1585A 0051000	305 MT	10.886 KG	GREEN, DARK	C	CAT5E 4PR U/UTP CMP REEL
1585A 008U1000	305 MT	10.433 KG	GRAY		CAT5E 4PR U/UTP CMP BOX
1585A 0081000	305 MT	10.886 KG	GRAY	C	CAT5E 4PR U/UTP CMP REEL
1585A 009U1000	305 MT	9.979 KG	WHITE		CAT5E 4PR U/UTP CMP BOX
1585A 0091000	305 MT	10.886 KG	WHITE	C	CAT5E 4PR U/UTP CMP REEL
1585A 010U1000	305 MT	10.433 KG	BLACK		CAT5E 4PR U/UTP CMP BOX
1585A 0101000	305 MT	10.886 KG	BLACK	C	CAT5E 4PR U/UTP CMP REEL
1585A 012U1000	305 MT	10.433 KG	PINK		CAT5E 4PR U/UTP CMP BOX
1585A 0121000	305 MT	10.886 KG	PINK	C	CAT5E 4PR U/UTP CMP REEL
1585A 877U1000	305 MT	10.433 KG	NATURAL		CAT5E 4PR U/UTP CMP BOX
1585A 8771000	305 MT	10.886 KG	NATURAL	C	CAT5E 4PR U/UTP CMP REEL

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 4    Revision Date: 05-04-2011

© 2011 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А