

● PROFESSIONAL LED INDICATORS Ø13mm Mounting

FEATURES



528 SERIES

PACK QUANTITY = 10 PIECES

- Robust stainless steel housing
- Low profile styling, sunlight readable LEDs
- Sealed to IP67
- Flying lead terminations available
- Suitable for high vibration applications
- Internal reverse protection diode fitted as standard in all voltage models.

SPECIFICATION

Ordering Information & Typical Technical Characteristics (Ta = 25°C)

Mean Time Between Failure = 100,000 Hours. Luminous intensity figures refer to the unmodified discrete LED.

PART NUMBER	COLOUR	LENS	VOLTAGE DC (Vdc) Vopr	CURRENT DC (mA) Iopr	LUMINOUS INTENSITY Iv@20mA (mcd)	WAVE LENGTH λ.p (nm)	OPERATING TEMP Topr	STORAGE TEMP Tstg	
HIGH INTENSITY									
528-501-21	Red		12	19	11000	643	-40 ~ +95 [^]	-40 ~ +100	Yes
528-521-21	Yellow		12	19	16000	591	-40 ~ +95 [^]	-40 ~ +100	Yes
528-532-21	Green		12	20	23000	527	-40 ~ +95 [^]	-40 ~ +100	Yes
528-930-21	Blue		12	20	7000	470	-40 ~ +95 [^]	-40 ~ +100	Yes
528-997-21	Cool White		12	20	14000	*see below	-40 ~ +95 [^]	-40 ~ +100	Yes
528-501-23	Red		24-28	20	11000	643	-40 ~ +95 [^]	-40 ~ +100	Yes
528-521-23	Yellow		24-28	20	16000	591	-40 ~ +95 [^]	-40 ~ +100	Yes
528-532-23	Green		24-28	20	23000	527	-40 ~ +95 [^]	-40 ~ +100	Yes
528-930-23	Blue		24-28	20	7000	470	-40 ~ +95 [^]	-40 ~ +100	Yes
528-997-23	Cool White		24-28	20	14000	*see below	-40 ~ +95 [^]	-40 ~ +100	Yes
UNITS			Vdc	mA	mcd	nm	°C	°C	



Other voltages AC/DC available. Please contact our Technical Sales.

[^] = Products must be derated according to the derating information. Each derating graph refers to specific LEDs.

997F-C	*Typical emission colour cool white			
x	0.245	0.361	0.356	0.264
y	0.229	0.385	0.351	0.220

Intensities (Iv) and colour shades of white (x,y co-ordinates) may vary between LEDs within a batch.

How to Order:

website: www.marl.co.uk • email: sales@marl.co.uk •


• Telephone +44 (0)1229 582430 • Fax: +44 (0)1229 585155

The information contained in this datasheet does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. Marl International reserve the right to alter without notice the specification or any conditions of supply for products or service.



BS EN ISO 9001:2000
Approved Manufacturer

528 Series




Dimensions in mm (Typical)
Not to scale

Mounting hole to be clean and burr free

MATERIALS

Body	Stainless steel grade 303
Nut	Stainless steel grade 303
Panel Seal	Viton
Termination	Brass to BS 2874 CZ108 Copper flash undercoat with silver flash finish
Lock Washer	Stainless steel
Fresnel lens	Polycarbonate
Encapsulation	PC5430 resin
Header	Nylon 6 A82

PUSH-ON CONNECTORS



925-000-00 is brass tin plated.
For use with 528 series lamps.

Dimensions in mm (Typical)
Not to scale

TECHNICAL CHARACTERISTICS

SERIES	MAXIMUM POWER DISSIPATION	MAXIMUM REVERSE VOLTAGE	PANEL CUTOUT	NUT MOUNTING TORQUE	MINIMUM MOUNTING CENTRES	MIN/MAX. PANEL THICKNESS
528	825	1000	13.0	1.0	x,y=26.0	2.0-10.0
	mw	Vdc	mm	Nm	mm	mm

* = current version

• = voltage version

OPTIONAL FLYING LEAD TERMINATIONS

ORDER CODE SUFFIX	SUPPLY VOLTAGE	WIRE COLOUR	WIRE LENGTH	NO/DIAMETER OF CONDUCTORS	DIAMETER OVER INSULATION	COMMENTS
15	DC Products	Red-anode / Black-cathode	150mm	19/0.15mm	1.2mm	Customised lengths available
15	AC Products	Brown-live / Blue-neutral	150mm			
19	DC Products	Red-anode / Black-cathode	1000mm			
19	AC Products	Brown-live / Blue-neutral	1000mm			



website: www.marl.co.uk • email: sales@marl.co.uk •
• Telephone +44 (0)1229 582430 • Fax: +44 (0)1229 585155

The information contained in this datasheet does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. Marl International reserve the right to alter without notice the specification or any conditions of supply for products or service.



BS EN ISO 9001:2000
Approved Manufacturer

DERATING INFORMATION



ALSO AVAILABLE

Part numbers also available in the 528 Series:

PART NO.	COLOUR	VOLTAGE DC (Vdc) Vopr
528-000-00-50		125 VDC
528-501-04	Red	20mA
528-501-21-15	Red	12 VDC
528-501-21-19	Red	12 VDC
528-501-22	Red	24 VDC
528-501-22-15	Red	24 VDC
528-501-22-19	Red	24 VDC
528-501-22-50	Red	24 VDC
528-501-23-15	Red	28 VDC
528-501-24-19	Red	48 VDC
528-501-25	Red	110 VDC
528-501-72	Red	24 VAC
528-501-75	Red	110 VAC
528-501-76	Red	230 VAC
528-501-76-15	Red	230 VAC
528-501-76-50	Red	230 VAC
528-501-86	Red	115 VAC
528-506-23	Orange	28 VDC
528-512-21-15	Green	12 VDC
528-512-22-15	Green	24 VDC
528-512-76	Green	230 VAC
528-521-04	Yellow	20mA
528-521-21-19	Yellow	12 VDC
528-521-22	Yellow	24 VDC
528-521-22-15	Yellow	24 VDC
528-521-22-19	Yellow	24 VDC
528-521-22-50	Yellow	24 VDC
UNITS		

PART NO.	COLOUR	VOLTAGE DC (Vdc) Vopr
528-521-23-15	Yellow	28 VDC
528-521-23-50	Yellow	28 VDC
528-521-53	Yellow	50 VDC
528-521-72	Yellow	24 VAC
528-521-75	Yellow	110 VAC
528-521-76	Yellow	230 VAC
528-521-76-50	Yellow	230 VAC
528-521-86	Yellow	115 VAC
528-532-04	Green	20mA
528-532-20	Green	5/6 VDC
528-532-21-19	Green	12 VDC
528-532-22	Green	24 VDC
528-532-22-19	Green	24 VDC
528-532-22-50	Green	24 VDC
528-532-24	Green	48 VDC
528-532-25	Green	110 VDC
528-532-42	Green	15 VDC
528-532-72	Green	24 VAC
528-532-74	Green	48 VAC
528-532-75	Green	110 VAC
528-532-76	Green	230 VAC
528-532-76-19	Green	230 VAC
528-532-76-21	Green	230 VAC
528-532-76-50	Green	230 VAC
528-532-86	Green	115 VAC
528-930-04	Blue	20mA
528-930-04-15	Blue	20mA
UNITS		

PART NO.	COLOUR	VOLTAGE DC (Vdc) Vopr
528-930-04-50	Blue	20mA
528-930-04-51	Blue	20mA
528-930-21-19	Blue	12 VDC
528-930-22	Blue	24 VDC
528-930-25	Blue	110 VDC
528-930-75	Blue	110 VAC
528-930-76	Blue	230 VAC
528-997-04	White	20mA
528-997-21-19	White	12 VDC
528-997-22	White	24 VDC
528-997-22-19	White	24 VDC
528-997-22-50	White	24 VDC
528-997-24	White	48 VDC
528-997-72	White	24 VAC
528-997-75	White	110 VAC
528-997-76	White	230 VAC
528-997-76-19	White	230 VAC
528-997-76-50	White	230 VAC
528-997-86	White	115 VAC
UNITS		

The products listed above illustrate all of the options available to order. These products may have custom modifications that alter their operation beyond the generic information contained within this datasheet. Please contact sales for further information.

website: www.marl.co.uk • email: sales@marl.co.uk •
 Telephone +44 (0)1229 582430 • Fax: +44 (0)1229 585155

The information contained in this datasheet does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. Marl International reserve the right to alter without notice the specification or any conditions of supply for products or service.



BS EN ISO 9001:2000
Approved Manufacturer

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».



JONHON

«**JONHON**» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А