

Film Capacitors

Metallized Polypropylene Film Capacitors (MKP)

Series/Type: B32651 ... B32658

Date: November 2019

High pulse (wound)**Typical applications**

- Electronic ballasts
- Switch-mode power supplies
- IGBT
- Snubbing

Climatic

- Max. operating temperature: 110 °C
- Climatic category (IEC 60068-1:2013): 55/100/56

Construction

- Dielectric: polypropylene (PP)(MKP)
- Wound capacitor technology with internal series connection
- Plastic case (UL 94 V-0)
- Epoxy resin sealing (UL 94 V-0)

Features

- High pulse strength
- High contact reliability
- RoHS-compatible
- Very low inductance
- Halogen-free capacitors available on request
- AEC-Q200D compliant

Terminals

- Parallel wire leads, lead-free tinned
- Special lead lengths available on request

Marking

Manufacturer's logo,
lot number ($\square \leq 27.5$ mm), series number (e.g. 651),
rated capacitance (coded), cap. tolerance (code letter),
rated DC voltage (AC voltage for 1600 V DC/700 V AC
and 2000 V DC/1000 V AC),
date of manufacture (coded)

Delivery mode

Bulk (untaped)

Taped (Ammo pack or reel)

For notes on taping, refer to chapter "Taping and packing".


Dimensional drawings

| Number of wires | Lead spacing e ± 0.4 | Lead diameter d_1 ± 0.05 | Type | Drawing |
|-----------------|-------------------------------|-----------------------------------|-----------|---------|
| 2-pin | 10 | 0.6 | B32651 | A1 |
| 2-pin | 15 | 0.8 | B32652 | A1 |
| 2-pin | 22.5 | 0.8 | B32653 | A1 |
| 2-pin | 27.5 | 0.8 | B32654 | A1 |
| 2-pin | 37.5 | 1.0 | B32656A/J | A1 |
| 2-pin | 37.5 | 1.0 | B32656T | A2 |
| 4-pin | 37.5 | 1.2 | B32656G | B1 |
| 4-pin | 52.5 | 1.2 | B32658G | B1 |

(Dimensions in mm)

Dimensional drawings 2-pin versions

Drawing A1



| | B32651 | B32652 | B32653 | B32654 | B32656A/J |
|------------------------------|--------|--------|--------|--------|-----------|
| Lead spacing e ± 0.4 : | 10 | 15 | 22.5 | 27.5 | 37.5 |
| Lead diameter d_1 : | 0.6 | 0.8 | 0.8 | 0.8 | 1.0 |


(Dimensions in mm)



B32651 ... B32658

High pulse (wound)

Drawing A2 (low profile)





| | |
|----------------------------|------|
| Lead spacing $e \pm 0.4$: | 37.5 |
| Lead diameter d_1 : | 1.0 |

(Dimensions in mm)

Dimensional drawings 4-pin versions

Drawing B1



| | B32656G | B32658G |
|----------------------------|---------|---------|
| Lead spacing $e \pm 0.4$: | 37.5 | 52.5 |
| Lead diameter d_1 : | 1.2 | 1.2 |

(Dimensions in mm)

B32651 ... B32658

High pulse (wound)



Overview of available types

| | |
|------------------|--------|
| Lead spacing | 10 mm |
| Type | B32651 |
| Page | 12 |
| V_R (V DC) | 1250 |
| V_{RMS} (V AC) | 450 |
| C_R (nF) | |
| 2.2 | |
| 3.3 | |
| 4.7 | |
| 6.8 | |




B32651 ... B32658

High pulse (wound)


Overview of available types

| | | | | | | | | |
|------------------|--------|-----|-----|------|------|------|------|------|
| Lead spacing | 15 mm | | | | | | | |
| Type | B32652 | | | | | | | |
| Page | 13 | | | | | | | |
| V_R (V DC) | 250 | 400 | 630 | 1000 | 1250 | 1600 | 1600 | 2000 |
| V_{RMS} (V AC) | 160 | 200 | 250 | 250 | 500 | 500 | 700 | 700 |
| C_R (nF) | | | | | | | | |
| 1.0 | | | | | | | | |
| 1.5 | | | | | | | | |
| 2.2 | | | | | | | | |
| 3.3 | | | | | | | | |
| 4.7 | | | | | | | | |
| 5.6 | | | | | | | | |
| 6.8 | | | | | | | | |
| 10 | | | | | | | | |
| 12 | | | | | | | | |
| 15 | | | | | | | | |
| 22 | | | | | | | | |
| 33 | | | | | | | | |
| 47 | | | | | | | | |
| 56 | | | | | | | | |
| 68 | | | | | | | | |
| 100 | | | | | | | | |
| 120 | | | | | | | | |
| 150 | | | | | | | | |
| 220 | | | | | | | | |
| 330 | | | | | | | | |
| 390 | | | | | | | | |
| 470 | | | | | | | | |
| 560 | | | | | | | | |
| 680 | | | | | | | | |
| 820 | | | | | | | | |
| 1000 | | | | | | | | |



Overview of available types

| | | | | | | | | |
|------------------|---------|-----|-----|------|------|------|------|------|
| Lead spacing | 22.5 mm | | | | | | | |
| Type | B32653 | | | | | | | |
| Page | 16 | | | | | | | |
| V_R (V DC) | 250 | 400 | 630 | 1000 | 1250 | 1600 | 2000 | 2000 |
| V_{RMS} (V AC) | 160 | 200 | 250 | 250 | 500 | 500 | 700 | 1000 |
| C_R (nF) | | | | | | | | |
| 2.2 | | | | | | | | |
| 3.3 | | | | | | | | |
| 4.7 | | | | | | | | |
| 6.8 | | | | | | | | |
| 10 | | | | | | | | |
| 12 | | | | | | | | |
| 15 | | | | | | | | |
| 22 | | | | | | | | |
| 33 | | | | | | | | |
| 47 | | | | | | | | |
| 56 | | | | | | | | |
| 68 | | | | | | | | |
| 82 | | | | | | | | |
| 100 | | | | | | | | |
| 120 | | | | | | | | |
| 150 | | | | | | | | |
| 220 | | | | | | | | |
| 330 | | | | | | | | |
| 470 | | | | | | | | |
| 560 | | | | | | | | |
| 680 | | | | | | | | |
| 1000 | | | | | | | | |
| 1200 | | | | | | | | |
| 1500 | | | | | | | | |
| 2200 | | | | | | | | |
| 3300 | | | | | | | | |



B32651 ... B32658

High pulse (wound)

Overview of available types

| | | | | | | | |
|------------------|---------|-----|-----|------|------|------|------|
| Lead spacing | 27.5 mm | | | | | | |
| Type | B32654 | | | | | | |
| Page | 19 | | | | | | |
| V_R (V DC) | 250 | 400 | 630 | 1000 | 1250 | 1600 | 2000 |
| V_{RMS} (V AC) | 160 | 200 | 250 | 250 | 500 | 500 | 700 |
| C_R (nF) | | | | | | | |
| 22 | | | | | | | |
| 33 | | | | | | | |
| 47 | | | | | | | |
| 68 | | | | | | | |
| 82 | | | | | | | |
| 100 | | | | | | | |
| 150 | | | | | | | |
| 220 | | | | | | | |
| 330 | | | | | | | |
| 470 | | | | | | | |
| 560 | | | | | | | |
| 680 | | | | | | | |
| 820 | | | | | | | |
| 1000 | | | | | | | |
| 1200 | | | | | | | |
| 1500 | | | | | | | |
| 2200 | | | | | | | |
| 2700 | | | | | | | |
| 3300 | | | | | | | |
| 4700 | | | | | | | |
| 5600 | | | | | | | |
| 6800 | | | | | | | |
| 8200 | | | | | | | |



Overview of available types

| | | | | |
|------------------|---------|-----|-----|-----|
| Lead spacing | 37.5 mm | | | |
| Type | B32656 | | | |
| Page | 21 | | | |
| V_R (V DC) | 250 | 400 | 630 | 750 |
| V_{RMS} (V AC) | 160 | 200 | 250 | 350 |
| C_R (nF) | | | | |
| 470 | | | | |
| 560 | | | | |
| 680 | | | | |
| 820 | | | | |
| 1000 | | | | |
| 1200 | | | | |
| 1500 | | | | |
| 1800 | | | | |
| 2000 | | | | |
| 2200 | | | | |
| 2500 | | | | |
| 2700 | | | | |
| 3000 | | | | |
| 3300 | | | | |
| 3500 | | | | |
| 4000 | | | | |
| 4700 | | | | |
| 5600 | | | | |
| 6800 | | | | |
| 7000 | | | | |
| 7500 | | | | |
| 8000 | | | | |
| 10000 | | | | |
| 12000 | | | | |
| 14000 | | | | |
| 15000 | | | | |
| 17000 | | | | |
| 20000 | | | | |
| 24000 | | | | |



B32651 ... B32658

High pulse (wound)

Overview of available types

| | | | | | |
|------------------|---------|------|------|------|------|
| Lead spacing | 37.5 mm | | | | |
| Type | B32656 | | | | |
| Page | 24 | | | | |
| V_R (V DC) | 850 | 1000 | 1250 | 1600 | 2000 |
| V_{RMS} (V AC) | 450 | 500 | 500 | 600 | 700 |
| C_R (nF) | | | | | |
| 68 | | | | | |
| 100 | | | | | |
| 120 | | | | | |
| 150 | | | | | |
| 220 | | | | | |
| 270 | | | | | |
| 330 | | | | | |
| 390 | | | | | |
| 470 | | | | | |
| 560 | | | | | |
| 680 | | | | | |
| 820 | | | | | |
| 900 | | | | | |
| 1000 | | | | | |
| 1200 | | | | | |
| 1500 | | | | | |
| 1800 | | | | | |
| 2200 | | | | | |
| 2500 | | | | | |
| 2700 | | | | | |
| 3000 | | | | | |
| 3300 | | | | | |
| 3800 | | | | | |



Overview of available types

| | | | | | | | | | |
|------------------|---------|-----|-----|-----|-----|------|------|------|------|
| Lead spacing | 52.5 mm | | | | | | | | |
| Type | B32658 | | | | | | | | |
| Page | 28 | | | | | | | | |
| V_R (V DC) | 250 | 400 | 630 | 750 | 850 | 1000 | 1250 | 1600 | 2000 |
| V_{RMS} (V AC) | 160 | 200 | 250 | 350 | 450 | 500 | 500 | 600 | 700 |
| C_R (nF) | | | | | | | | | |
| 680 | | | | | | | | | |
| 820 | | | | | | | | | |
| 1000 | | | | | | | | | |
| 1200 | | | | | | | | | |
| 1500 | | | | | | | | | |
| 2000 | | | | | | | | | |
| 2200 | | | | | | | | | |
| 2700 | | | | | | | | | |
| 3300 | | | | | | | | | |
| 4500 | | | | | | | | | |
| 4700 | | | | | | | | | |
| 5600 | | | | | | | | | |
| 6000 | | | | | | | | | |
| 6800 | | | | | | | | | |
| 9000 | | | | | | | | | |
| 12000 | | | | | | | | | |
| 15000 | | | | | | | | | |
| 20000 | | | | | | | | | |
| 26000 | | | | | | | | | |
| 30000 | | | | | | | | | |
| 40000 | | | | | | | | | |



B32651

High pulse (wound)

Ordering codes and packing units (lead spacing 10 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./MOQ | Untaped pcs./MOQ |
|--------------------|-----------------------------|-------|--|---|--------------------------|------------------|---------------------|
| V DC ¹⁾ | V AC | nF | | | | | |
| 1250 | 450 | 2.2 | 4.0 × 9.0 × 13.0 | B32651A7222+*** | 4000 | 6800 | 4000 |
| | | 3.3 | 5.0 × 11.0 × 13.0 | B32651A7332+*** | 3320 | 5200 | 4000 |
| | | 4.7 | 5.0 × 11.0 × 13.0 | B32651A7472+*** | 3320 | 5200 | 4000 |
| | | 6.8 | 6.0 × 12.0 × 13.0 | B32651A7682+*** | 2720 | 4400 | 4000 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%


*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 – 1 mm)

1) For pulse loads (pulse width ≤ 1000 μs), a peak voltage of 1400 V_p can be permitted.


Ordering codes and packing units (lead spacing 15 mm)

| V_R | V_{RMS} $f \leq 1 \text{ kHz}$ | C_R | Max. dimensions $w \times h \times l$ mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./MOQ | Untaped pcs./MOQ |
|-------|-------------------------------------|-------|--|---|--------------------------|------------------|---------------------|
| V DC | V AC | nF | | | | | |
| 250 | 160 | 150 | 5.0 × 10.5 × 18.0 | B32652A3154+*** | 4680 | 5200 | 4000 |
| | | 220 | 6.0 × 11.0 × 18.0 | B32652A3224+*** | 3840 | 4400 | 4000 |
| | | 330 | 7.0 × 12.5 × 18.0 | B32652A3334+*** | 3320 | 3600 | 4000 |
| | | 470 | 8.5 × 14.5 × 18.0 | B32652A3474+*** | 2720 | 2800 | 2000 |
| | | 680 | 9.0 × 17.5 × 18.0 | B32652A3684+*** | 2560 | 2800 | 2000 |
| | | 820 | 11.0 × 18.5 × 18.0 | B32652A3824+*** | — | 2200 | 1200 |
| | | 1000 | 11.0 × 18.5 × 18.0 | B32652A3105+*** | — | 2200 | 1200 |
| 400 | 200 | 68 | 5.0 × 10.5 × 18.0 | B32652A4683+*** | 4680 | 5200 | 4000 |
| | | 100 | 5.0 × 10.5 × 18.0 | B32652A4104+*** | 4680 | 5200 | 4000 |
| | | 150 | 6.0 × 11.0 × 18.0 | B32652A4154+*** | 3840 | 4400 | 4000 |
| | | 220 | 7.0 × 12.5 × 18.0 | B32652A4224+*** | 3320 | 3600 | 4000 |
| | | 330 | 8.5 × 14.5 × 18.0 | B32652A4334+*** | 2720 | 2800 | 2000 |
| | | 470 | 9.0 × 17.5 × 18.0 | B32652A4474+*** | 2560 | 2800 | 2000 |
| | | 560 | 11.0 × 18.5 × 18.0 | B32652A4564+*** | — | 2200 | 1200 |
| | | 680 | 11.0 × 18.5 × 18.0 | B32652A4684+*** | — | 2200 | 1200 |
| 630 | 250 | 33 | 5.0 × 10.5 × 18.0 | B32652A6333+*** | 4680 | 5200 | 4000 |
| | | 47 | 5.0 × 10.5 × 18.0 | B32652A6473+*** | 4680 | 2800 | 4000 |
| | | 68 | 6.0 × 11.0 × 18.0 | B32652A6683+*** | 3840 | 4400 | 4000 |
| | | 100 | 7.0 × 12.5 × 18.0 | B32652A6104+*** | 3320 | 3600 | 4000 |
| | | 150 | 8.5 × 14.5 × 18.0 | B32652A6154+*** | 2720 | 2800 | 2000 |
| | | 220 | 9.0 × 17.5 × 18.0 | B32652A6224+*** | 2560 | 2800 | 2000 |
| | | 330 | 11.0 × 18.5 × 18.0 | B32652A6334+*** | — | 2200 | 1200 |
| | | 390 | 11.0 × 18.5 × 18.0 | B32652A6394+*** | — | 2200 | 1200 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%


J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 – 1 mm)


B32652
High pulse (wound)
Ordering codes and packing units (lead spacing 15 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./MOQ | Untaped pcs./MOQ |
|-------|-----------------------------|-------|--|---|--------------------------|------------------|---------------------|
| V DC | V AC | nF | | | | | |
| 1000 | 250 | 10 | 5.0 × 10.5 × 18.0 | B32652A0103+*** | 4680 | 5200 | 4000 |
| | | 15 | 5.0 × 10.5 × 18.0 | B32652A0153+*** | 4680 | 5200 | 4000 |
| | | 22 | 5.0 × 10.5 × 18.0 | B32652A0223+*** | 4680 | 5200 | 4000 |
| | | 33 | 6.0 × 11.0 × 18.0 | B32652A0333+*** | 3840 | 4400 | 4000 |
| | | 47 | 7.0 × 12.5 × 18.0 | B32652A0473+*** | 3320 | 3600 | 4000 |
| | | 68 | 8.5 × 14.5 × 18.0 | B32652A0683+*** | 2720 | 2800 | 2000 |
| | | 100 | 9.0 × 17.5 × 18.0 | B32652A0104+*** | 2560 | 2800 | 2000 |
| | | 120 | 11.0 × 18.5 × 18.0 | B32652A0124+*** | — | 2200 | 1200 |
| | | 150 | 11.0 × 18.5 × 18.0 | B32652A0154+*** | — | 2200 | 1200 |
| 1250 | 500 | 6.8 | 5.0 × 10.5 × 18.0 | B32652A7682+*** | 4680 | 5200 | 4000 |
| | | 10 | 6.0 × 11.0 × 18.0 | B32652A7103+*** | 3840 | 4400 | 4000 |
| | | 15 | 7.0 × 12.5 × 18.0 | B32652A7153+*** | 3320 | 3600 | 4000 |
| | | 22 | 8.5 × 14.5 × 18.0 | B32652A7223+*** | 2720 | 2800 | 2000 |
| | | 33 | 9.0 × 17.5 × 18.0 | B32652A7333+*** | 2560 | 2800 | 2000 |
| | | 47 | 11.0 × 18.5 × 18.0 | B32652A7473+*** | — | 2200 | 1200 |
| | | 56 | 11.0 × 18.5 × 18.0 | B32652A7563+*** | — | 2200 | 1200 |
| | | 1600 | 500 | 3.3 | 5.0 × 10.5 × 18.0 | B32652A1332+*** | 4680 |
| 4.7 | 6.0 × 11.0 × 18.0 | | | B32652A1472+*** | 3840 | 4400 | 4000 |
| 6.8 | 7.0 × 12.5 × 18.0 | | | B32652A1682+*** | 3320 | 3600 | 4000 |
| 10 | 8.5 × 14.5 × 18.0 | | | B32652A1103+*** | 2720 | 2800 | 2000 |
| 15 | 9.0 × 17.5 × 18.0 | | | B32652A1153+*** | 2560 | 2800 | 2000 |
| 22 | 11.0 × 18.5 × 18.0 | | | B32652A1223+*** | — | 2200 | 1200 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%


J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 – 1 mm)


Ordering codes and packing units (lead spacing 15 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ mm | Ordering code (composition see below) | Ammo pack pcs./MOQ | Reel pcs./MOQ | Untaped pcs./MOQ |
|-------|-----------------------------|-------|--|---|--------------------------|------------------|---------------------|
| V DC | V AC | nF | | | | | |
| 1600 | 700 | 2.2 | 5.0 × 10.5 × 18.0 | B32652J1222+*** | 4680 | 5200 | 4000 |
| | | 3.3 | 6.0 × 11.0 × 18.0 | B32652J1332+*** | 3840 | 4400 | 4000 |
| | | 4.7 | 7.0 × 12.5 × 18.0 | B32652J1472+*** | 3320 | 3600 | 4000 |
| | | 6.8 | 8.5 × 14.5 × 18.0 | B32652J1682+*** | 2720 | 2800 | 2000 |
| | | 10 | 9.0 × 17.5 × 18.0 | B32652J1103+*** | 2560 | 2800 | 2000 |
| | | 12 | 9.0 × 17.5 × 18.0 | B32652J1123+*** | 2560 | 2800 | 2000 |
| | | 15 | 11.0 × 18.5 × 18.0 | B32652J1153+*** | — | 2200 | 1200 |
| 2000 | 700 | 1.0 | 5.0 × 10.5 × 18.0 | B32652A2102+*** | 4680 | 5200 | 4000 |
| | | 1.5 | 6.0 × 11.0 × 18.0 | B32652A2152+*** | 3840 | 4400 | 4000 |
| | | 2.2 | 7.0 × 12.5 × 18.0 | B32652A2222+*** | 3320 | 3600 | 4000 |
| | | 3.3 | 8.5 × 14.5 × 18.0 | B32652A2332+*** | 2720 | 2800 | 2000 |
| | | 4.7 | 9.0 × 17.5 × 18.0 | B32652A2472+*** | 2560 | 2800 | 2000 |
| | | 5.6 | 9.0 × 17.5 × 18.0 | B32652A2562+*** | — | 2200 | 1000 |
| | | 6.8 | 11.0 × 18.5 × 18.0 | B32652A2682+*** | — | 2200 | 1200 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 –1 mm)


B32653
High pulse (wound)
Ordering codes and packing units (lead spacing 22.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Ammo pack pcs./ MOQ | Reel pcs./ MOQ | Untaped pcs./ MOQ |
|-------|-----------------------------|-------|--|---|---------------------------|----------------------|-------------------------|
| V DC | V AC | nF | mm | | | | |
| 250 | 160 | 220 | 6.0 × 15.0 × 26.5 | B32653A3224+*** | 2720 | 2800 | 2880 |
| | | 330 | 6.0 × 15.0 × 26.5 | B32653A3334+*** | 2720 | 2800 | 2880 |
| | | 470 | 7.0 × 16.0 × 26.5 | B32653A3474+*** | 2320 | 2400 | 2520 |
| | | 680 | 8.5 × 16.5 × 26.5 | B32653A3684+*** | 1920 | 2000 | 2040 |
| | | 1000 | 10.5 × 16.5 × 26.5 | B32653A3105+*** | 1560 | 1600 | 2160 |
| | | 1200 | 10.5 × 18.5 × 26.5 | B32653A3125+*** | 1560 | 1600 | 2160 |
| | | 1500 | 11.0 × 20.5 × 26.5 | B32653A3155+*** | 1480 | 1400 | 2040 |
| | | 2200 | 14.5 × 29.5 × 26.5 | B32653A3225+000 | — | — | 1040 |
| 400 | 200 | 3300 | 14.5 × 29.5 × 26.5 | B32653A3335+000 | — | — | 1040 |
| | | 150 | 6.0 × 15.0 × 26.5 | B32653A4154+*** | 2720 | 2800 | 2880 |
| | | 220 | 6.0 × 15.0 × 26.5 | B32653A4224+*** | 2720 | 2800 | 2880 |
| | | 330 | 7.0 × 16.0 × 26.5 | B32653A4334+*** | 2320 | 2400 | 2520 |
| | | 470 | 8.5 × 16.5 × 26.5 | B32653A4474+*** | 1920 | 2000 | 2040 |
| | | 680 | 10.5 × 16.5 × 26.5 | B32653A4684+*** | 1560 | 1600 | 2160 |
| | | 1000 | 11.0 × 20.5 × 26.5 | B32653A4105+*** | 1480 | 1400 | 2040 |
| | | 1200 | 12.0 × 22.0 × 26.5 | B32653A4125+000 | — | — | 1800 |
| 630 | 250 | 1500 | 14.5 × 29.5 × 26.5 | B32653A4155+000 | — | — | 1040 |
| | | 2200 | 14.5 × 29.5 × 26.5 | B32653A4225+000 | — | — | 1040 |
| | | 100 | 6.0 × 15.0 × 26.5 | B32653A6104+*** | 2720 | 2800 | 2880 |
| | | 150 | 6.0 × 15.0 × 26.5 | B32653A6154+*** | 2720 | 2800 | 2880 |
| | | 220 | 8.5 × 16.5 × 26.5 | B32653A6224+*** | 1920 | 2000 | 2040 |
| | | 330 | 10.5 × 16.5 × 26.5 | B32653A6334+*** | 1560 | 1600 | 2160 |
| | | 470 | 11.0 × 20.5 × 26.5 | B32653A6474+*** | 1480 | 1400 | 2040 |
| | | 560 | 11.0 × 20.5 × 26.5 | B32653A6564+*** | 1480 | 1400 | 2040 |
| | | 680 | 14.5 × 29.5 × 26.5 | B32653A6684+000 | — | — | 1040 |
| | | 1000 | 14.5 × 29.5 × 26.5 | B32653A6105+000 | — | — | 1040 |
| | | 1200 | 14.5 × 29.5 × 26.5 | B32653A6125+000 | — | — | 1040 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%


J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 – 1 mm)


Ordering codes and packing units (lead spacing 22.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Ammo pack pcs./ MOQ | Reel pcs./ MOQ | Untaped pcs./ MOQ | | |
|-------|-----------------------------|-------|--|---|---------------------------|----------------------|-------------------------|---|------|
| V DC | V AC | nF | mm | | | | | | |
| 1000 | 250 | 33 | 6.0 × 15.0 × 26.5 | B32653A0333+*** | 2720 | 2800 | 2880 | | |
| | | 47 | 6.0 × 15.0 × 26.5 | B32653A0473+*** | 2720 | 2800 | 2880 | | |
| | | 68 | 6.0 × 15.0 × 26.5 | B32653A0683+*** | 2720 | 2800 | 2880 | | |
| | | 100 | 8.5 × 16.5 × 26.5 | B32653A0104+*** | 1920 | 2000 | 2040 | | |
| | | 150 | 10.5 × 16.5 × 26.5 | B32653A0154+*** | 1560 | 1600 | 2160 | | |
| | | 220 | 11.0 × 20.5 × 26.5 | B32653A0224+*** | 1480 | 1400 | 2040 | | |
| | | 330 | 14.5 × 29.5 × 26.5 | B32653A0334+000 | — | — | 1040 | | |
| | | 470 | 14.5 × 29.5 × 26.5 | B32653A0474+000 | — | — | 1040 | | |
| | | 560 | 14.5 × 29.5 × 26.5 | B32653A0564+000 | — | — | 1040 | | |
| 1250 | 500 | 22 | 6.0 × 15.0 × 26.5 | B32653A7223+*** | 2720 | 2800 | 2880 | | |
| | | 33 | 6.0 × 15.0 × 26.5 | B32653A7333+*** | 2720 | 2800 | 2880 | | |
| | | 47 | 8.5 × 16.5 × 26.5 | B32653A7473+*** | 1920 | 2000 | 2040 | | |
| | | 68 | 10.5 × 16.5 × 26.5 | B32653A7683+*** | 1560 | 1600 | 2160 | | |
| | | 100 | 11.0 × 20.5 × 26.5 | B32653A7104+*** | 1480 | 1400 | 2040 | | |
| | | 120 | 12.0 × 22.0 × 26.5 | B32653A7124+000 | — | — | 1800 | | |
| | | 150 | 14.5 × 29.5 × 26.5 | B32653A7154+000 | — | — | 1040 | | |
| | | 220 | 14.5 × 29.5 × 26.5 | B32653A7224+000 | — | — | 1040 | | |
| 1600 | 500 | 6.8 | 6.0 × 15.0 × 26.5 | B32653A1682+*** | 2720 | 2800 | 2880 | | |
| | | 10 | 6.0 × 15.0 × 26.5 | B32653A1103+*** | 2720 | 2800 | 2880 | | |
| | | 15 | 7.0 × 16.0 × 26.5 | B32653A1153+*** | 2320 | 2400 | 2520 | | |
| | | 22 | 8.5 × 16.5 × 26.5 | B32653A1223+*** | 1920 | 2000 | 2040 | | |
| | | 33 | 10.5 × 16.5 × 26.5 | B32653A1333+*** | 1560 | 1600 | 2160 | | |
| | | 47 | 11.0 × 20.5 × 26.5 | B32653A1473+*** | 1480 | 1400 | 2040 | | |
| | | 56 | 12.0 × 22.0 × 26.5 | B32653A1563+000 | — | — | 1800 | | |
| | | 68 | 14.5 × 29.5 × 26.5 | B32653A1683+000 | — | — | 1040 | | |
| | | 82 | 14.5 × 29.5 × 26.5 | B32653A1823+000 | — | — | 1040 | | |
| | | | | 100 | 14.5 × 29.5 × 26.5 | B32653A1104+000 | — | — | 1040 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 – 1 mm)



B32653

High pulse (wound)

Ordering codes and packing units (lead spacing 22.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | Ordering code (composition see below) | Ammo pack pcs./ MOQ | Reel pcs./ MOQ | Untaped pcs./ MOQ |
|-------|-----------------------------|-------|--|---|---------------------------|----------------------|-------------------------|
| V DC | V AC | nF | mm | | | | |
| 2000 | 700 | 3.3 | 6.0 × 15.0 × 26.5 | B32653A2332+*** | 2720 | 2800 | 2880 |
| | | 4.7 | 6.0 × 15.0 × 26.5 | B32653A2472+*** | 2720 | 2800 | 2880 |
| | | 6.8 | 8.5 × 16.5 × 26.5 | B32653A2682+*** | 1920 | 2000 | 2040 |
| | | 10 | 10.5 × 16.5 × 26.5 | B32653A2103+*** | 1560 | 1600 | 2160 |
| | | 15 | 11.0 × 20.5 × 26.5 | B32653A2153+*** | 1480 | 1400 | 2040 |
| | | 22 | 14.5 × 29.5 × 26.5 | B32653A2223+000 | — | — | 1040 |
| | | 33 | 14.5 × 29.5 × 26.5 | B32653A2333+000 | — | — | 1040 |
| 2000 | 1000 | 2.2 | 6.0 × 15.0 × 26.5 | B32653A8222+*** | 2720 | 2800 | 2880 |
| | | 3.3 | 6.0 × 15.0 × 26.5 | B32653A8332+*** | 2720 | 2800 | 2880 |
| | | 4.7 | 8.5 × 16.5 × 26.5 | B32653A8472+*** | 1920 | 2000 | 2040 |
| | | 6.8 | 10.5 × 16.5 × 26.5 | B32653A8682+*** | 1560 | 1600 | 2160 |
| | | 10 | 10.5 × 20.5 × 26.5 | B32653A8103+*** | 1560 | 1600 | 2160 |
| | | 12 | 12.0 × 22.0 × 26.5 | B32653A8123+000 | — | — | 1800 |
| | | 15 | 14.5 × 29.5 × 26.5 | B32653A8153+000 | — | — | 1040 |
| | | 22 | 14.5 × 29.5 × 26.5 | B32653A8223+000 | — | — | 1040 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%


J = ±5%

*** = Packaging code:

289 = Straight terminals, Ammo pack

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 – 1 mm)


Ordering codes and packing units (lead spacing 27.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ mm | Ordering code (composition see below) | Ammo pack pcs./ MOQ | Reel pcs./ MOQ | Untaped pcs./ MOQ |
|-------|-----------------------------|-------|--|---|---------------------------|----------------------|-------------------------|
| V DC | V AC | nF | | | | | |
| 250 | 160 | 1500 | 11.0 × 21.0 × 31.5 | B32654A3155+*** | — | 1400 | 1280 |
| | | 2200 | 12.5 × 21.5 × 31.5 | B32654A3225+*** | — | 1200 | 1120 |
| | | 3300 | 15.0 × 24.5 × 31.5 | B32654A3335+000 | — | — | 960 |
| | | 4700 | 18.0 × 27.5 × 31.5 | B32654A3475+000 | — | — | 800 |
| | | 5600 | 19.0 × 30.0 × 31.5 | B32654A3565+000 | — | — | 720 |
| | | 6800 | 22.0 × 36.5 × 31.5 | B32654A3685+000 | — | — | 640 |
| | | 8200 | 22.0 × 36.5 × 31.5 | B32654A3825+000 | — | — | 640 |
| 400 | 200 | 1000 | 11.0 × 21.0 × 31.5 | B32654A4105+*** | — | 1400 | 1280 |
| | | 1500 | 12.5 × 21.5 × 31.5 | B32654A4155+*** | — | 1200 | 1120 |
| | | 2200 | 14.0 × 24.5 × 31.5 | B32654A4225+*** | — | 1000 | 1040 |
| | | 3300 | 19.0 × 30.0 × 31.5 | B32654A4335+000 | — | — | 720 |
| | | 4700 | 22.0 × 36.5 × 31.5 | B32654A4475+000 | — | — | 640 |
| | | 5600 | 22.0 × 36.5 × 31.5 | B32654A4565+000 | — | — | 640 |
| 630 | 250 | 680 | 11.0 × 21.0 × 31.5 | B32654A6684+*** | — | 1400 | 1280 |
| | | 1000 | 13.5 × 23.0 × 31.5 | B32654A6105+*** | — | 1000 | 1040 |
| | | 1500 | 18.0 × 27.5 × 31.5 | B32654A6155+000 | — | — | 800 |
| | | 2200 | 18.0 × 33.0 × 31.5 | B32654A6225+000 | — | — | 800 |
| | | 2700 | 22.0 × 36.5 × 31.5 | B32654A6275+000 | — | — | 640 |
| | | 3300 | 22.0 × 36.5 × 31.5 | B32654A6335K000 | — | — | 640 |
| 1000 | 250 | 220 | 11.0 × 21.0 × 31.5 | B32654A0224+*** | — | 1400 | 1280 |
| | | 330 | 11.0 × 21.0 × 31.5 | B32654A0334+*** | — | 1400 | 1280 |
| | | 470 | 14.0 × 24.5 × 31.5 | B32654A0474+*** | — | 1000 | 1040 |
| | | 680 | 18.0 × 27.5 × 31.5 | B32654A0684+000 | — | — | 800 |
| | | 820 | 19.0 × 30.0 × 31.5 | B32654A0824+000 | — | — | 720 |
| | | 1000 | 21.0 × 31.0 × 31.5 | B32654A0105+000 | — | — | 720 |
| | | 1200 | 22.0 × 36.5 × 31.5 | B32654A0125+000 | — | — | 640 |
| | | 1500 | 22.0 × 36.5 × 31.5 | B32654A0155K000 | — | — | 640 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

*** = Packaging code:

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 – 1 mm)


B32654
High pulse (wound)
Ordering codes and packing units (lead spacing 27.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ mm | Ordering code (composition see below) | Ammo pack pcs./ MOQ | Reel pcs./ MOQ | Untaped pcs./ MOQ |
|-------|-----------------------------|-------|--|---|---------------------------|----------------------|-------------------------|
| V DC | V AC | nF | | | | | |
| 1250 | 500 | 100 | 11.0 × 21.0 × 31.5 | B32654A7104+*** | — | 1400 | 1280 |
| | | 150 | 11.0 × 21.0 × 31.5 | B32654A7154+*** | — | 1400 | 1280 |
| | | 220 | 14.0 × 24.5 × 31.5 | B32654A7224+*** | — | 1000 | 1040 |
| | | 330 | 18.0 × 27.5 × 31.5 | B32654A7334+000 | — | — | 800 |
| | | 470 | 21.0 × 31.0 × 31.5 | B32654A7474+000 | — | — | 720 |
| | | 560 | 22.0 × 36.5 × 31.5 | B32654A7564+000 | — | — | 640 |
| | | 680 | 22.0 × 36.5 × 31.5 | B32654A7684+000 | — | — | 640 |
| 1600 | 500 | 47 | 11.0 × 21.0 × 31.5 | B32654A1473+*** | — | 1400 | 1280 |
| | | 68 | 11.0 × 21.0 × 31.5 | B32654A1683+*** | — | 1400 | 1280 |
| | | 100 | 14.0 × 24.5 × 31.5 | B32654A1104+*** | — | 1000 | 1040 |
| | | 150 | 18.0 × 27.5 × 31.5 | B32654A1154+000 | — | — | 800 |
| | | 220 | 21.0 × 31.0 × 31.5 | B32654A1224+000 | — | — | 720 |
| 2000 | 700 | 22 | 11.0 × 21.0 × 31.5 | B32654A2223+*** | — | 1400 | 1280 |
| | | 33 | 13.5 × 23.0 × 31.5 | B32654A2333+*** | — | 1000 | 1040 |
| | | 47 | 18.0 × 27.5 × 31.5 | B32654A2473+000 | — | — | 800 |
| | | 68 | 19.0 × 30.0 × 31.5 | B32654A2683+000 | — | — | 720 |
| | | 82 | 22.0 × 36.5 × 31.5 | B32654A2823+000 | — | — | 640 |
| | | 100 | 22.0 × 36.5 × 31.5 | B32654A2104+000 | — | — | 640 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:


K = ±10%

J = ±5%

*** = Packaging code:

189 = Straight terminals, Reel

000 = Straight terminals, Untaped (standard lead length 6 – 1 mm)


Ordering codes and packing units (lead spacing 37.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | P_1 | Ordering code (composition see below) | Untaped |
|-------|-----------------------------|-------|--|-------|---|----------|
| V DC | V AC | nF | mm | mm | | pcs./MOQ |
| 250 | 160 | 2700 | 12.0 × 22.0 × 42.0 | – | B32656A3275+000 | 1620 |
| | | 3000 | 12.0 × 22.0 × 42.0 | – | B32656A3305+000 | 1620 |
| | | 3300 | 14.0 × 25.0 × 42.0 | – | B32656A3335+000 | 1380 |
| | | 4000 | 14.0 × 25.0 × 42.0 | – | B32656A3405+000 | 1380 |
| | | 4000 | 24.0 × 15.0 × 42.0 | – | B32656T3405+000 | 1040 |
| | | 4700 | 16.0 × 28.5 × 42.0 | – | B32656A3475+000 | 800 |
| | | 5600 | 16.0 × 28.5 × 42.0 | – | B32656A3565+000 | 800 |
| | | 5600 | 24.0 × 19.0 × 42.0 | – | B32656T3565+000 | 780 |
| | | 6800 | 18.0 × 32.5 × 42.0 | – | B32656A3685+000 | 720 |
| | | 8000 | 18.0 × 32.5 × 42.0 | – | B32656A3805+000 | 720 |
| | | 10000 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G3106+000 | 640 |
| | | 10000 | 20.0 × 39.5 × 42.0 | – | B32656A3106+000 | 640 |
| | | 12000 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G3126K000 | 640 |
| | | 12000 | 20.0 × 39.5 × 42.0 | – | B32656A3126K000 | 640 |
| | | 15000 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G3156K000 | 440 |
| | | 15000 | 28.0 × 37.0 × 42.0 | – | B32656A3156K000 | 440 |
| | | 17000 | 28.0 × 42.5 × 42.0 | 10.2 | B32656G3176+000 | 440 |
| | | 17000 | 28.0 × 42.5 × 42.0 | – | B32656A3176+000 | 440 |
| | | 20000 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G3206+000 | 400 |
| | | 20000 | 30.0 × 45.0 × 42.0 | – | B32656A3206+000 | 400 |
| 24000 | 33.0 × 48.0 × 42.0 | 20.3 | B32656G3246+000 | 180 | | |
| 24000 | 33.0 × 48.0 × 42.0 | – | B32656A3246+000 | 180 | | |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%


B32656
High pulse (wound)
Ordering codes and packing units (lead spacing 37.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | P_1 | Ordering code (composition see below) | Untaped |
|-------|-----------------------------|-------|--|-------|---|----------|
| V DC | V AC | nF | mm | mm | | pcs./MOQ |
| 400 | 200 | 2000 | 12.0 × 22.0 × 42.0 | – | B32656A4205+000 | 1620 |
| | | 2700 | 14.0 × 25.0 × 42.0 | – | B32656A4275+000 | 1380 |
| | | 2700 | 24.0 × 15.0 × 42.0 | – | B32656T4275+000 | 1040 |
| | | 3500 | 24.0 × 19.0 × 42.0 | – | B32656T4355+000 | 780 |
| | | 4000 | 16.0 × 28.5 × 42.0 | – | B32656A4405+000 | 800 |
| | | 5600 | 18.0 × 32.5 × 42.0 | – | B32656A4565+000 | 720 |
| | | 7500 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G4755+000 | 640 |
| | | 7500 | 20.0 × 39.5 × 42.0 | – | B32656A4755+000 | 640 |
| | | 10000 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G4106+000 | 440 |
| | | 10000 | 28.0 × 37.0 × 42.0 | – | B32656A4106+000 | 440 |
| | | 12000 | 28.0 × 42.5 × 42.0 | 10.2 | B32656G4126+000 | 440 |
| | | 12000 | 28.0 × 42.5 × 42.0 | – | B32656A4126+000 | 440 |
| | | 14000 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G4146+000 | 400 |
| | | 14000 | 30.0 × 45.0 × 42.0 | – | B32656A4146+000 | 400 |
| | | 17000 | 33.0 × 48.0 × 42.0 | 20.3 | B32656G4176+000 | 180 |
| | | 17000 | 33.0 × 48.0 × 42.0 | – | B32656A4176+000 | 180 |
| | | 630 | 250 | 1000 | 12.0 × 22.0 × 42.0 | – |
| 1500 | 14.0 × 25.0 × 42.0 | | | – | B32656A6155+000 | 1380 |
| 1500 | 24.0 × 15.0 × 42.0 | | | – | B32656T6155+000 | 1040 |
| 2200 | 16.0 × 28.5 × 42.0 | | | – | B32656A6225+000 | 800 |
| 2200 | 24.0 × 19.0 × 42.0 | | | – | B32656T6225+000 | 780 |
| 3000 | 18.0 × 32.5 × 42.0 | | | – | B32656A6305+000 | 720 |
| 4000 | 20.0 × 39.5 × 42.0 | | | 10.2 | B32656G6405+000 | 640 |
| 4000 | 20.0 × 39.5 × 42.0 | | | – | B32656A6405+000 | 640 |
| 5600 | 28.0 × 37.0 × 42.0 | | | 10.2 | B32656G6565+000 | 440 |
| 5600 | 28.0 × 37.0 × 42.0 | | | – | B32656A6565+000 | 440 |
| 7000 | 28.0 × 42.5 × 42.0 | | | 10.2 | B32656G6705K000 | 440 |
| 7000 | 28.0 × 42.5 × 42.0 | | | – | B32656A6705K000 | 440 |
| 8000 | 30.0 × 45.0 × 42.0 | | | 20.3 | B32656G6805+000 | 400 |
| 8000 | 30.0 × 45.0 × 42.0 | | | – | B32656A6805+000 | 400 |
| 10000 | 33.0 × 48.0 × 42.0 | | | 20.3 | B32656G6106K000 | 180 |
| 10000 | 33.0 × 48.0 × 42.0 | | | – | B32656A6106K000 | 180 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%


Ordering codes and packing units (lead spacing 37.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | P_1 | Ordering code (composition see below) | Untaped pcs./MOQ |
|-------|-----------------------------|-------|--|-------|---|---------------------|
| V DC | V AC | nF | mm | mm | | |
| 750 | 350 | 470 | 12.0 × 22.0 × 42.0 | – | B32656A5474+000 | 1620 |
| | | 560 | 12.0 × 22.0 × 42.0 | – | B32656A5564+000 | 1620 |
| | | 680 | 12.0 × 22.0 × 42.0 | – | B32656A5684+000 | 1620 |
| | | 820 | 14.0 × 25.0 × 42.0 | – | B32656A5824+000 | 1380 |
| | | 1000 | 16.0 × 28.5 × 42.0 | – | B32656A5105+000 | 800 |
| | | 1000 | 24.0 × 15.0 × 42.0 | – | B32656T5105K000 | 1040 |
| | | 1200 | 16.0 × 28.5 × 42.0 | – | B32656A5125+000 | 800 |
| | | 1200 | 24.0 × 19.0 × 42.0 | – | B32656T5125+000 | 780 |
| | | 1500 | 18.0 × 32.5 × 42.0 | – | B32656A5155+000 | 720 |
| | | 1800 | 18.0 × 32.5 × 42.0 | – | B32656A5185+000 | 720 |
| | | 2200 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G5225+000 | 640 |
| | | 2200 | 20.0 × 39.5 × 42.0 | – | B32656A5225+000 | 640 |
| | | 2500 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G5255+000 | 640 |
| | | 2500 | 20.0 × 39.5 × 42.0 | – | B32656A5255+000 | 640 |
| | | 2700 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G5275+000 | 440 |
| | | 2700 | 28.0 × 37.0 × 42.0 | – | B32656A5275+000 | 440 |
| | | 3300 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G5335+000 | 440 |
| | | 3300 | 28.0 × 37.0 × 42.0 | – | B32656A5335+000 | 440 |
| | | 4000 | 28.0 × 42.5 × 42.0 | 10.2 | B32656G5405+000 | 440 |
| | | 4000 | 28.0 × 42.5 × 42.0 | – | B32656A5405+000 | 440 |
| | | 4700 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G5475+000 | 400 |
| | | 4700 | 30.0 × 45.0 × 42.0 | – | B32656A5475+000 | 400 |
| | | 5600 | 33.0 × 48.0 × 42.0 | 20.3 | B32656G5565+000 | 180 |
| 5600 | 33.0 × 48.0 × 42.0 | – | B32656A5565+000 | 180 | | |


MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%


B32656
High pulse (wound)
Ordering codes and packing units (lead spacing 37.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | P_1 | Ordering code (composition see below) | Untaped |
|-------|-----------------------------|-------|--|-------|---|----------|
| V DC | V AC | nF | mm | mm | | pcs./MOQ |
| 850 | 450 | 220 | 12.0 × 22.0 × 42.0 | – | B32656A8224+000 | 1620 |
| | | 330 | 12.0 × 22.0 × 42.0 | – | B32656A8334+000 | 1620 |
| | | 470 | 12.0 × 22.0 × 42.0 | – | B32656A8474+000 | 1620 |
| | | 680 | 16.0 × 28.5 × 42.0 | – | B32656A8684+000 | 800 |
| | | 680 | 24.0 × 15.0 × 42.0 | – | B32656T8684+000 | 1040 |
| | | 820 | 24.0 × 19.0 × 42.0 | – | B32656T8824+000 | 780 |
| | | 1000 | 18.0 × 32.5 × 42.0 | – | B32656A8105+000 | 720 |
| | | 1200 | 18.0 × 32.5 × 42.0 | – | B32656A8125+000 | 720 |
| | | 1500 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G8155+000 | 640 |
| | | 1500 | 20.0 × 39.5 × 42.0 | – | B32656A8155+000 | 640 |
| | | 1800 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G8185+000 | 640 |
| | | 1800 | 20.0 × 39.5 × 42.0 | – | B32656A8185+000 | 640 |
| | | 2200 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G8225+000 | 440 |
| | | 2200 | 28.0 × 37.0 × 42.0 | – | B32656A8225+000 | 440 |
| | | 2500 | 28.0 × 42.5 × 42.0 | 10.2 | B32656G8255+000 | 440 |
| | | 2500 | 28.0 × 42.5 × 42.0 | – | B32656A8255+000 | 440 |
| | | 2700 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G8275+000 | 400 |
| | | 2700 | 30.0 × 45.0 × 42.0 | – | B32656A8275+000 | 400 |
| | | 3000 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G8305+000 | 400 |
| | | 3000 | 30.0 × 45.0 × 42.0 | – | B32656A8305+000 | 400 |
| | | 3300 | 33.0 × 48.0 × 42.0 | 20.3 | B32656G8335+000 | 180 |
| | | 3300 | 33.0 × 48.0 × 42.0 | – | B32656A8335+000 | 180 |
| | | 3800 | 33.0 × 48.0 × 42.0 | 20.3 | B32656G8385+000 | 180 |
| 3800 | 33.0 × 48.0 × 42.0 | – | B32656A8385+000 | 180 | | |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%


Ordering codes and packing units (lead spacing 37.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | P_1 | Ordering code (composition see below) | Untaped pcs./MOQ |
|-------|-----------------------------|-------|--|-------|---|---------------------|
| V DC | V AC | nF | mm | mm | | |
| 1000 | 500 | 330 | 12.0 × 22.0 × 42.0 | – | B32656A0334+000 | 1620 |
| | | 470 | 14.0 × 25.0 × 42.0 | – | B32656A0474+000 | 1380 |
| | | 470 | 24.0 × 15.0 × 42.0 | – | B32656T0474+000 | 1040 |
| | | 680 | 16.0 × 28.5 × 42.0 | – | B32656A0684+000 | 800 |
| | | 680 | 24.0 × 19.0 × 42.0 | – | B32656T0684+000 | 780 |
| | | 1000 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G0105+000 | 640 |
| | | 1000 | 20.0 × 39.5 × 42.0 | – | B32656A0105+000 | 640 |
| | | 1200 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G0125+000 | 440 |
| | | 1200 | 28.0 × 37.0 × 42.0 | – | B32656A0125+000 | 440 |
| | | 1500 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G0155+000 | 440 |
| | | 1500 | 28.0 × 37.0 × 42.0 | – | B32656A0155+000 | 440 |
| | | 2200 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G0225+000 | 400 |
| | | 2200 | 30.0 × 45.0 × 42.0 | – | B32656A0225+000 | 400 |
| | | 2700 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G0275M000 | 400 |
| | | 2700 | 30.0 × 45.0 × 42.0 | – | B32656A0275M000 | 400 |
| | | 2700 | 33.0 × 48.0 × 42.0 | 20.3 | B32656G0275+000 | 180 |
| 2700 | 33.0 × 48.0 × 42.0 | – | B32656A0275+000 | 180 | | |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:
K = ±10%
J = ±5%


B32656
High pulse (wound)
Ordering codes and packing units (lead spacing 37.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | P_1 | Ordering code (composition see below) | Untaped pcs./MOQ |
|-------|-----------------------------|-------|--|-------|---|---------------------|
| V DC | V AC | nF | mm | mm | | |
| 1250 | 500 | 150 | 12.0 × 22.0 × 42.0 | – | B32656A7154+000 | 1620 |
| | | 220 | 14.0 × 25.0 × 42.0 | – | B32656A7224+000 | 1380 |
| | | 270 | 24.0 × 15.0 × 42.0 | – | B32656T7274+000 | 1040 |
| | | 330 | 16.0 × 28.5 × 42.0 | – | B32656A7334+000 | 800 |
| | | 390 | 24.0 × 19.0 × 42.0 | – | B32656T7394+000 | 780 |
| | | 470 | 18.0 × 32.5 × 42.0 | – | B32656A7474+000 | 720 |
| | | 680 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G7684+000 | 640 |
| | | 680 | 20.0 × 39.5 × 42.0 | – | B32656A7684+000 | 640 |
| | | 820 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G7824+000 | 440 |
| | | 820 | 28.0 × 37.0 × 42.0 | – | B32656A7824+000 | 440 |
| | | 1000 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G7105+000 | 440 |
| | | 1000 | 28.0 × 37.0 × 42.0 | – | B32656A7105+000 | 440 |
| | | 1200 | 28.0 × 42.5 × 42.0 | 10.2 | B32656G7125+000 | 440 |
| | | 1200 | 28.0 × 42.5 × 42.0 | – | B32656A7125+000 | 440 |
| | | 1500 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G7155+000 | 400 |
| | | 1500 | 30.0 × 45.0 × 42.0 | – | B32656A7155+000 | 400 |
| 1800 | 33.0 × 48.0 × 42.0 | 20.3 | B32656G7185K000 | 180 | | |
| 1800 | 33.0 × 48.0 × 42.0 | – | B32656A7185K000 | 180 | | |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%


Ordering codes and packing units (lead spacing 37.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | P_1 | Ordering code (composition see below) | Untaped pcs./MOQ |
|-------|-----------------------------|-------|--|-------|---|---------------------|
| V DC | V AC | nF | mm | mm | | |
| 1600 | 600 | 100 | 12.0 × 22.0 × 42.0 | – | B32656J1104+000 | 1620 |
| | | 150 | 14.0 × 25.0 × 42.0 | – | B32656J1154+000 | 1380 |
| | | 150 | 24.0 × 15.0 × 42.0 | – | B32656T1154+000 | 1040 |
| | | 220 | 16.0 × 28.5 × 42.0 | – | B32656J1224+000 | 800 |
| | | 220 | 24.0 × 19.0 × 42.0 | – | B32656T1224+000 | 780 |
| | | 330 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G1334+000 | 640 |
| | | 330 | 20.0 × 39.5 × 42.0 | – | B32656J1334+000 | 640 |
| | | 470 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G1474+000 | 440 |
| | | 470 | 28.0 × 37.0 × 42.0 | – | B32656J1474+000 | 440 |
| | | 560 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G1564+000 | 440 |
| | | 560 | 28.0 × 37.0 × 42.0 | – | B32656J1564+000 | 440 |
| | | 680 | 28.0 × 42.5 × 42.0 | 10.2 | B32656G1684+000 | 440 |
| | | 680 | 28.0 × 42.5 × 42.0 | – | B32656J1684+000 | 440 |
| | | 820 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G1824+000 | 400 |
| | | 820 | 30.0 × 45.0 × 42.0 | – | B32656J1824+000 | 400 |
| | | 2000 | 700 | 900 | 33.0 × 48.0 × 42.0 | 20.3 |
| 900 | 33.0 × 48.0 × 42.0 | | | – | B32656J1905+000 | 180 |
| 68 | 12.0 × 22.0 × 42.0 | | | – | B32656J2683+000 | 1620 |
| 100 | 14.0 × 25.0 × 42.0 | | | – | B32656J2104+000 | 1380 |
| 100 | 24.0 × 15.0 × 42.0 | | | – | B32656T2104+000 | 1040 |
| 120 | 24.0 × 19.0 × 42.0 | | | – | B32656T2124+000 | 780 |
| | | 150 | 18.0 × 32.5 × 42.0 | – | B32656J2154+000 | 720 |
| | | 220 | 20.0 × 39.5 × 42.0 | 10.2 | B32656G2224+000 | 640 |
| | | 220 | 20.0 × 39.5 × 42.0 | – | B32656J2224+000 | 640 |
| | | 330 | 28.0 × 37.0 × 42.0 | 10.2 | B32656G2334+000 | 440 |
| | | 330 | 28.0 × 37.0 × 42.0 | – | B32656J2334+000 | 440 |
| | | 470 | 30.0 × 45.0 × 42.0 | 20.3 | B32656G2474+000 | 400 |
| | | 470 | 30.0 × 45.0 × 42.0 | – | B32656J2474+000 | 400 |
| | | 560 | 33.0 × 48.0 × 42.0 | 20.3 | B32656G2564+000 | 180 |
| | | 560 | 33.0 × 48.0 × 42.0 | – | B32656J2564+000 | 180 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.
Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%


B32658
High pulse (wound)
Ordering codes and packing units (lead spacing 52.5 mm)

| V_R | V_{RMS} $f \leq 1$ kHz | C_R | Max. dimensions $w \times h \times l$ | P_1 | Ordering code (composition see below) | Untaped pcs./MOQ |
|-------|-----------------------------|-------|--|-------|---|---------------------|
| V DC | V AC | nF | mm | mm | | |
| 250 | 160 | 30000 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G3306+000 | 280 |
| | | 40000 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G3406K000 | 108 |
| 400 | 200 | 20000 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G4206+000 | 280 |
| | | 26000 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G4266+000 | 108 |
| 630 | 250 | 12000 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G6126K000 | 280 |
| | | 15000 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G6156+000 | 108 |
| 750 | 350 | 6800 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G5685+000 | 280 |
| | | 9000 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G5905+000 | 108 |
| 850 | 450 | 4700 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G8475+000 | 280 |
| | | 5600 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G8565+000 | 108 |
| | | 6000 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G8605+000 | 108 |
| 1000 | 500 | 3300 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G0335+000 | 280 |
| | | 4500 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G0455+000 | 108 |
| 1250 | 500 | 2000 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G7205+000 | 280 |
| | | 2200 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G7225+000 | 108 |
| | | 2700 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G7275+000 | 108 |
| 1600 | 600 | 1000 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G1105+000 | 280 |
| | | 1200 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G1125K000 | 280 |
| | | 1500 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G1155+000 | 108 |
| 2000 | 700 | 680 | 30.0 × 45.0 × 57.5 | 20.3 | B32658G2684+000 | 280 |
| | | 820 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G2824+000 | 108 |
| | | 1000 | 35.0 × 50.0 × 57.5 | 20.3 | B32658G2105K000 | 108 |

MOQ = Minimum Order Quantity, consisting of 4 packing units.

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

Technical data

Reference standard: IEC 60384-16:2005 and AEC-Q200D. All data given at $T = 20\text{ °C}$, unless otherwise specified.

| | | | | | |
|--|---|-------------------------------------|--|--|------------------------------|
| Operating temperature range | Max. operating temperature $T_{op,max}$ | | +110 °C | | |
| | Upper category temperature T_{max} | | +100 °C | | |
| | Lower category temperature T_{min} | | -55 °C | | |
| | Rated temperature T_R | | +85 °C | | |
| Dissipation factor $\tan \delta$ (in 10^{-3}) at 20 °C (upper limit values) | at | $\leq 27\text{ nF}$ | $27\text{ nF} < C_R \leq 0.1\text{ }\mu\text{F}$ | $0.1\text{ }\mu\text{F} < C_R \leq 1\text{ }\mu\text{F}$ | $C_R > 1\text{ }\mu\text{F}$ |
| | 1 kHz | 0.8 | 0.8 | 0.8 | 0.8 |
| | 10 kHz | 1.0 | 1.0 | 1.0 | — |
| | 100 kHz | 2.0 | 3.0 | — | — |
| Insulation resistance R_{ins} or time constant $\tau = C_R \cdot R_{ins}$ at 20 °C, rel. humidity $\leq 65\%$ (minimum as-delivered values) | $C_R \leq 0.33\text{ }\mu\text{F}$ | | $C_R > 0.33\text{ }\mu\text{F}$ | | |
| | 100 G Ω | | 30000 s | | |
| DC test voltage | $1.6 \cdot V_R, 2\text{ s}$ | | | | |
| Capacitance tolerance codes | J = $\pm 5\%$ K = $\pm 10\%$ M = $\pm 20\%$ | | | | |
| Category voltage V_C (continuous operation with V_{DC} or V_{AC} at $f \leq 1\text{ kHz}$) | T_{op} (°C) | DC voltage derating | | AC voltage derating | |
| | $T_{op} \leq 85$ | $V_C = V_R$ | | $V_{C,RMS} = V_{RMS}$ | |
| | $85 < T_{op} \leq 100$ | $V_C = V_R \cdot (165 - T_{op})/80$ | | $V_{C,RMS} = V_{RMS} \cdot (165 - T_{op})/80$ | |
| Operating voltage V_{op} for short operating periods (V_{DC} or V_{AC} at $f \leq 1\text{ kHz}$) | T_{op} (°C) | DC voltage (max. hours) | | AC voltage (max. hours) | |
| | $T_{op} \leq 85$ | $V_{op} = 1.25 \cdot V_C$ (2000 h) | | $V_{op} = 1.0 \cdot V_{C,RMS}$ (2000 h) | |
| | $85 < T_{op} \leq 100$ | $V_{op} = 1.25 \cdot V_C$ (1000 h) | | $V_{op} = 1.0 \cdot V_{C,RMS}$ (1000 h) | |
| Biased humidity Limit values after biased humidity test | 1000 h / 40 °C / 93% relative humidity with $V_{R,DC}$ | | | | |
| | Capacitance change $ \Delta C/C $ | | $\leq 5\%$ | | |
| | Dissipation factor change $\Delta \tan \delta$ | | $\leq 2.0 \cdot 10^{-3}$ (at 1 kHz) | | |
| | Insulation resistance R_{ins} or time constant $\tau = C_R \cdot R_{ins}$ | | $\geq 50\%$ of minimum as-delivered values | | |
| Reliability: Failure rate λ Service life t_{SL} | 1 fit ($\leq 1 \cdot 10^{-9}/h$) at $0.5 \cdot V_R, 40\text{ °C}$ 200 000 h at $1.0 \cdot V_R, 85\text{ °C}$ | | | | |
| Failure criteria: Total failure | For conversion to other operating conditions and temperatures, refer to chapter "Quality, 2 Reliability". | | | | |
| Failure due to variation of parameters | Short circuit or open circuit | | | | |
| | Capacitance change $ \Delta C/C $ | | $> 10\%$ | | |
| | Dissipation factor $\tan \delta$ | | $> 4 \cdot$ upper limit value | | |
| | Insulation resistance R_{ins} or time constant $\tau = C_R \cdot R_{ins}$ | | $< 1500\text{ M}\Omega$ ($C_R \leq 0.33\text{ }\mu\text{F}$) $< 500\text{ s}$ ($C_R > 0.33\text{ }\mu\text{F}$) | | |



B32651 ... B32658

High pulse (wound)

Pulse handling capability

"dV/dt" represents the maximum permissible voltage change per unit of time for non-sinusoidal voltages, expressed in V/μs.

"k₀" represents the maximum permissible pulse characteristic of the waveform applied to the capacitor, expressed in V²/μs.

Note:

The values of dV/dt and k₀ provided below must not be exceeded in order to avoid damaging the capacitor.

dV/dt values


| Lead spacing | | 10 mm | 15 mm | 22.5 mm | 27.5 mm | 37.5 mm | 52.5 mm |
|------------------------|--------------------------|---------------|-------|---------|---------|---------|---------|
| V _R V DC | V _{RMS} V AC | dV/dt in V/μs | | | | | |
| 250 | 160 | — | 200 | 120 | 50 | 36 | 24 |
| 400 | 200 | — | 300 | 180 | 100 | 55 | 36 |
| 630 | 250 | — | 400 | 300 | 150 | 80 | 50 |
| 750 | 350 | — | — | — | — | 250 | 160 |
| 850 | 450 | — | — | — | — | 340 | 220 |
| 1000 | 250 | — | 975 | 600 | 300 | — | — |
| | 500 | — | — | — | — | 400 | 265 |
| 1250 | 450 | 4000 | — | — | — | — | — |
| | 500 | — | 1850 | 1150 | 600 | 500 | 350 |
| 1600 | 500 | — | 4500 | 2400 | 1000 | — | — |
| | 600 | — | — | — | — | 600 | 400 |
| | 700 | — | 5200 | — | — | — | — |
| 2000 | 700 | — | 8000 | 7000 | 2300 | 700 | 475 |
| | 1000 | — | — | 7500 | — | — | — |


 k_0 values

| Lead spacing | 10 mm | 15 mm | 22.5 mm | 27.5 mm | 37.5 mm | 52.5 mm | |
|--------------|-----------|----------------------|------------|------------|------------|-----------|-----------|
| V_R | V_{RMS} | k_0 in $V^2/\mu s$ | | | | | |
| V DC | V AC | | | | | | |
| 250 | 160 | — | 100 000 | 60 000 | 25 000 | 18 000 | 12 000 |
| 400 | 200 | — | 250 000 | 200 000 | 110 000 | 44 000 | 28 800 |
| 630 | 250 | — | 500 000 | 350 000 | 250 000 | 100 800 | 63 000 |
| 750 | 350 | — | — | — | — | 375 000 | 240 000 |
| 850 | 450 | — | — | — | — | 578 000 | 374 000 |
| 1000 | 250 | — | 3 000 000 | 1 500 000 | 1 000 000 | — | — |
| | 500 | — | — | — | — | 800 000 | 530 000 |
| 1250 | 450 | 25 000 000 | — | — | — | — | — |
| | 500 | — | 9 000 000 | 3 750 000 | 2 000 000 | 1 250 000 | 875 000 |
| 1600 | 500 | — | 20 000 000 | 10 000 000 | 4 000 000 | — | — |
| | 600 | — | — | — | — | 1 920 000 | 1 280 000 |
| | 700 | — | 28 000 000 | — | — | — | — |
| 2000 | 700 | — | 60 000 000 | 40 000 000 | 15 000 000 | 2 800 000 | 1 900 000 |
| | 1000 | — | — | 50 000 000 | — | — | — |

Impedance Z versus frequency f

(typical values)





B32651


High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90\text{ }^\circ\text{C}$)

For $T_A > 90\text{ }^\circ\text{C}$, please refer to "General technical information", section 3.2.3.

Lead spacing 10 mm

1250 V DC/450 V AC





Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)

For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 15 mm

250 V DC/160 V AC



400 V DC/200 V AC




630 V DC/250 V AC



1000 V DC/250 V AC





B32652

High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 15 mm


1250 V DC/500 V AC




1600 V DC/500 V AC



1600 V DC/700 V AC



2000 V DC/700 V AC



B32653

High pulse (wound)



Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 22.5 mm

250 V DC/160 V AC




400 V DC/200 V AC




630 V DC/250 V AC



1000 V DC/250 V AC





B32653


High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 22.5 mm


1250 V DC/500 V AC




1600 V DC/500 V AC



2000 V DC/700 V AC




2000 V DC/1000 V AC



B32654

High pulse (wound)




Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)

For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 27.5 mm


250 V DC/160 V AC



400 V DC/200 V AC



630 V DC/250 V AC



1000 V DC/250 V AC





B32654


High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ\text{C}$)

For $T_A > 90^\circ\text{C}$, please refer to "General technical information", section 3.2.3.

Lead spacing 27.5 mm


1250 V DC/500 V AC



1600 V DC/500 V AC



2000 V DC/700 V AC



B32656

High pulse (wound)




Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm


250 V DC/160 V AC




250 V DC/160 V AC



250 V DC/160 V AC





B32656


High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm


400 V DC/200 V AC



400 V DC/200 V AC




400 V DC/200 V AC



B32656

High pulse (wound)




Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm


630 V DC/250 V AC



630 V DC/250 V AC



630 V DC/250 V AC





B32656


High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm


750 V DC/350 V AC



750 V DC/350 V AC



750 V DC/350 V AC



B32656

High pulse (wound)



Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)

For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm

850 V DC/450 V AC



850 V DC/450 V AC



850 V DC/450 V AC





B32656


High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ\text{C}$)


For $T_A > 90^\circ\text{C}$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm


1000 V DC/500 V AC



1000 V DC/500 V AC



1000 V DC/500 V AC



B32656

High pulse (wound)




Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm


1250 V DC/500 V AC




1250 V DC/500 V AC



1250 V DC/500 V AC





B32656


High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm


1600 V DC/600 V AC



1600 V DC/600 V AC




1600 V DC/600 V AC



B32656

High pulse (wound)




Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 37.5 mm


2000 V DC/700 V AC




2000 V DC/700 V AC



2000 V DC/700 V AC





B32658

High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)

For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 52.5 mm

250 V DC/160 V AC



400 V DC/200 V AC



630 V DC/250 V AC




750 V DC/350 V AC



B32658

High pulse (wound)




Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ C$)


For $T_A > 90^\circ C$, please refer to "General technical information", section 3.2.3.

Lead spacing 52.5 mm


850 V DC/450 V AC




1000 V DC/500 V AC



1250 V DC/500 V AC



1600 V DC/600 V AC





B32658

High pulse (wound)

Permissible AC voltage V_{RMS} versus frequency f (for sinusoidal waveforms, $T_A \leq 90^\circ\text{C}$)

For $T_A > 90^\circ\text{C}$, please refer to "General technical information", section 3.2.3.

Lead spacing 52.5 mm

2000 V DC/700 V AC





Mounting guidelines

1 Soldering

1.1 Solderability of leads

The solderability of terminal leads is tested to IEC 60068-2-20:2008, test Ta, method 1.

Before a solderability test is carried out, terminals are subjected to accelerated ageing (to IEC 60068-2-2:2007, test Ba: 4 h exposure to dry heat at 155 °C). Since the ageing temperature is far higher than the upper category temperature of the capacitors, the terminal wires should be cut off from the capacitor before the ageing procedure to prevent the solderability being impaired by the products of any capacitor decomposition that might occur.

| | |
|-------------------------|---|
| Solder bath temperature | 235 ±5 °C |
| Soldering time | 2.0 ±0.5 s |
| Immersion depth | 2.0 +0/−0.5 mm from capacitor body or seating plane |
| Evaluation criteria: | |
| Visual inspection | Wetting of wire surface by new solder ≥90%, free-flowing solder |

1.2 Resistance to soldering heat

Resistance to soldering heat is tested to IEC 60068-2-20:2008, test Tb, method 1.


Conditions:

| Series | Solder bath temperature | Soldering time |
|---|-------------------------|--|
| MKT boxed (except 2.5 × 6.5 × 7.2 mm) coated uncoated (lead spacing >10 mm) | 260 ±5 °C | 10 ±1 s |
| MFP MKP (lead spacing >7.5 mm) | | |
| MKT boxed (case 2.5 × 6.5 × 7.2 mm) | 260 ±5 °C | 5 ±1 s |
| MKP (lead spacing ≤7.5 mm) | | <4 s |
| MKT uncoated (lead spacing ≤10 mm) insulated (B32559) | | recommended soldering profile for MKT uncoated (lead spacing ≤ 10 mm) and insulated (B32559) |



B32651 ... B32658

High pulse (wound)



| | |
|----------------------|---|
| Immersion depth | 2.0 +0/−0.5 mm from capacitor body or seating plane |
| Shield | Heat-absorbing board, (1.5 ±0.5) mm thick, between capacitor body and liquid solder |
| Evaluation criteria: | |
| Visual inspection | No visible damage |
| $\Delta C/C_0$ | 2% for MKT/MKP/MFP 5% for EMI suppression capacitors |
| $\tan \delta$ | As specified in sectional specification |

1.3 General notes on soldering

Permissible heat exposure loads on film capacitors are primarily characterized by the upper category temperature T_{max} . Long exposure to temperatures above this type-related temperature limit can lead to changes in the plastic dielectric and thus change irreversibly a capacitor's electrical characteristics. For short exposures (as in practical soldering processes) the heat load (and thus the possible effects on a capacitor) will also depend on other factors like:


- Pre-heating temperature and time
- Forced cooling immediately after soldering
- Terminal characteristics:
diameter, length, thermal resistance, special configurations (e.g. crimping)
- Height of capacitor above solder bath
- Shadowing by neighboring components
- Additional heating due to heat dissipation by neighboring components
- Use of solder-resist coatings



The overheating associated with some of these factors can usually be reduced by suitable countermeasures. For example, if a pre-heating step cannot be avoided, an additional or reinforced cooling process may possibly have to be included.

Recommendations


As a reference, the recommended wave soldering profile for our film capacitors is as follows:



T_s : Capacitor body maximum temperature at wave soldering

T_p : Capacitor body maximum temperature at pre-heating

KMK1745-A-E



KMK1744-9-E



B32651 ... B32658

High pulse (wound)

Body temperature should follow the description below:

- MKP capacitor
 - During pre-heating: $T_p \leq 110 \text{ }^\circ\text{C}$
 - During soldering: $T_s \leq 120 \text{ }^\circ\text{C}$, $t_s \leq 45 \text{ s}$
- MKT capacitor
 - During pre-heating: $T_p \leq 125 \text{ }^\circ\text{C}$
 - During soldering: $T_s \leq 160 \text{ }^\circ\text{C}$, $t_s \leq 45 \text{ s}$

When SMD components are used together with leaded ones, the film capacitors should not pass into the SMD adhesive curing oven. The leaded components should be assembled after the SMD curing step.

Leaded film capacitors are not suitable for reflow soldering.


In order to ensure proper conditions for manual or selective soldering, the body temperature of the capacitor (T_s) must be $\leq 120 \text{ }^\circ\text{C}$.

One recommended condition for manual soldering is that the tip of the soldering iron should be $< 360 \text{ }^\circ\text{C}$ and the soldering contact time should be no longer than 3 seconds.

For uncoated MKT capacitors with lead spacings $\leq 10 \text{ mm}$ (B32560/B32561) the following measures are recommended:

- pre-heating to not more than $110 \text{ }^\circ\text{C}$ in the preheater phase
- rapid cooling after soldering

Please refer to our Film Capacitors Data Book in case more details are needed.



Cautions and warnings

- Do not exceed the upper category temperature (UCT).
- Do not apply any mechanical stress to the capacitor terminals.
- Avoid any compressive, tensile or flexural stress.
- Do not move the capacitor after it has been soldered to the PC board.
- Do not pick up the PC board by the soldered capacitor.
- Do not place the capacitor on a PC board whose PTH hole spacing differs from the specified lead spacing.
- Do not exceed the specified time or temperature limits during soldering.
- Avoid external energy inputs, such as fire or electricity.
- Avoid overload of the capacitors.
- Consult us if application is with severe temperature and humidity condition.
- There are no serviceable or repairable parts inside the capacitor. Opening the capacitor or any attempts to open or repair the capacitor will void the warranty and liability of TDK Electronics.
- Please note that the standards referred to in this publication may have been revised in the meantime.

The table below summarizes the safety instructions that must always be observed. A detailed description can be found in the relevant sections of the chapters "General technical information" and "Mounting guidelines".

| Topic | Safety information | Reference chapter "General technical information" |
|-------------------------|---|--|
| Storage conditions | Make sure that capacitors are stored within the specified range of time, temperature and humidity conditions. | 4.5 "Storage conditions" |
| Flammability | Avoid external energy, such as fire or electricity (passive flammability), avoid overload of the capacitors (active flammability) and consider the flammability of materials. | 5.3 "Flammability" |
| Resistance to vibration | Do not exceed the tested ability to withstand vibration. The capacitors are tested to IEC 60068-2-6:2007. TDK Electronics offers film capacitors specially designed for operation under more severe vibration regimes such as those found in automotive applications. Consult our catalog "Film Capacitors for Automotive Electronics". | 5.2 "Resistance to vibration" |



B32651 ... B32658


High pulse (wound)

| Topic | Safety information | Reference chapter "Mounting guidelines" |
|--|---|--|
| Soldering | Do not exceed the specified time or temperature limits during soldering. | 1 "Soldering" |
| Cleaning | Use only suitable solvents for cleaning capacitors. | 2 "Cleaning" |
| Embedding of capacitors in finished assemblies | When embedding finished circuit assemblies in plastic resins, chemical and thermal influences must be taken into account. Caution: Consult us first, if you also wish to embed other uncoated component types! | 3 "Embedding of capacitors in finished assemblies" |

Display of ordering codes for TDK Electronics products


The ordering code for one and the same product can be represented differently in data sheets, data books, other publications, on the company website, or in order-related documents such as shipping notes, order confirmations and product labels. The varying representations of the ordering codes are due to different processes employed and do not affect the specifications of the respective products.

Detailed information can be found on the Internet under www.tdk-electronics.tdk.com/orderingcodes.



Symbols and terms

| Symbol | English | German |
|----------------------|---|---|
| α | Heat transfer coefficient | Wärmeübergangszahl |
| α_C | Temperature coefficient of capacitance | Temperaturkoeffizient der Kapazität |
| A | Capacitor surface area | Kondensatoroberfläche |
| β_C | Humidity coefficient of capacitance | Feuchtekoeffizient der Kapazität |
| C | Capacitance | Kapazität |
| C_R | Rated capacitance | Nennkapazität |
| ΔC | Absolute capacitance change | Absolute Kapazitätsänderung |
| $\Delta C/C$ | Relative capacitance change (relative deviation of actual value) | Relative Kapazitätsänderung (relative Abweichung vom Ist-Wert) |
| $\Delta C/C_R$ | Capacitance tolerance (relative deviation from rated capacitance) | Kapazitätstoleranz (relative Abweichung vom Nennwert) |
| dt | Time differential | Differentielle Zeit |
| Δt | Time interval | Zeitintervall |
| ΔT | Absolute temperature change (self-heating) | Absolute Temperaturänderung (Selbsterwärmung) |
| $\Delta \tan \delta$ | Absolute change of dissipation factor | Absolute Änderung des Verlustfaktors |
| ΔV | Absolute voltage change | Absolute Spannungsänderung |
| dV/dt | Time differential of voltage function (rate of voltage rise) | Differentielle Spannungsänderung (Spannungsflankensteilheit) |
| $\Delta V/\Delta t$ | Voltage change per time interval | Spannungsänderung pro Zeitintervall |
| E | Activation energy for diffusion | Aktivierungsenergie zur Diffusion |
| ESL | Self-inductance | Eigeninduktivität |
| ESR | Equivalent series resistance | Ersatz-Serienwiderstand |
| f | Frequency | Frequenz |
| f_1 | Frequency limit for reducing permissible AC voltage due to thermal limits | Grenzfrequenz für thermisch bedingte Reduzierung der zulässigen Wechselspannung |
| f_2 | Frequency limit for reducing permissible AC voltage due to current limit | Grenzfrequenz für strombedingte Reduzierung der zulässigen Wechselspannung |
| f_r | Resonant frequency | Resonanzfrequenz |
| F_D | Thermal acceleration factor for diffusion | Therm. Beschleunigungsfaktor zur Diffusion |
| F_T | Derating factor | Deratingfaktor |
| i | Current (peak) | Stromspitze |
| I_C | Category current (max. continuous current) | Kategoriestrom (max. Dauerstrom) |



B32651 ... B32658

High pulse (wound)

| Symbol | English | German |
|------------------|--|---|
| I_{RMS} | (Sinusoidal) alternating current, root-mean-square value | (Sinusförmiger) Wechselstrom |
| i_z | Capacitance drift | Inkonstanz der Kapazität |
| k_0 | Pulse characteristic | Impuls Kennwert |
| L_S | Series inductance | Serieninduktivität |
| λ | Failure rate | Ausfallrate |
| λ_0 | Constant failure rate during useful service life | Konstante Ausfallrate in der Nutzungsphase |
| λ_{test} | Failure rate, determined by tests | Experimentell ermittelte Ausfallrate |
| P_{diss} | Dissipated power | Abgegebene Verlustleistung |
| P_{gen} | Generated power | Erzeugte Verlustleistung |
| Q | Heat energy | Wärmeenergie |
| ρ | Density of water vapor in air | Dichte von Wasserdampf in Luft |
| R | Universal molar constant for gases | Allg. Molarkonstante für Gas |
| R | Ohmic resistance of discharge circuit | Ohmscher Widerstand des Entladekreises |
| R_i | Internal resistance | Innenwiderstand |
| R_{ins} | Insulation resistance | Isolationswiderstand |
| R_P | Parallel resistance | Parallelwiderstand |
| R_S | Series resistance | Serienwiderstand |
| S | severity (humidity test) | Schärfegrad (Feuchtetest) |
| t | Time | Zeit |
| T | Temperature | Temperatur |
| τ | Time constant | Zeitkonstante |
| $\tan \delta$ | Dissipation factor | Verlustfaktor |
| $\tan \delta_D$ | Dielectric component of dissipation factor | Dielektrischer Anteil des Verlustfaktors |
| $\tan \delta_P$ | Parallel component of dissipation factor | Parallelanteil des Verlustfaktors |
| $\tan \delta_S$ | Series component of dissipation factor | Serienanteil des Verlustfaktors |
| T_A | Temperature of the air surrounding the component | Temperatur der Luft, die das Bauteil umgibt |
| T_{max} | Upper category temperature | Obere Kategorietemperatur |
| T_{min} | Lower category temperature | Untere Kategorietemperatur |
| t_{OL} | Operating life at operating temperature and voltage | Betriebszeit bei Betriebstemperatur und -spannung |
| T_{op} | Operating temperature, $T_A + \Delta T$ | Betriebstemperatur, $T_A + \Delta T$ |
| T_R | Rated temperature | Nenntemperatur |
| T_{ref} | Reference temperature | Referenztemperatur |
| t_{SL} | Reference service life | Referenz-Lebensdauer |



| Symbol | English | German |
|-------------|---|---|
| V_{AC} | AC voltage | Wechselspannung |
| V_C | Category voltage | Kategorie spannung |
| $V_{C,RMS}$ | Category AC voltage | (Sinusförmige) Kategorie-Wechselspannung |
| V_{CD} | Corona-discharge onset voltage | Teilentlade-Einsatzspannung |
| V_{ch} | Charging voltage | Ladespannung |
| V_{DC} | DC voltage | Gleichspannung |
| V_{FB} | Fly-back capacitor voltage | Spannung (Flyback) |
| V_i | Input voltage | Eingangsspannung |
| V_o | Output voltage | Ausgangsspannung |
| V_{op} | Operating voltage | Betriebsspannung |
| V_p | Peak pulse voltage | Impuls-Spitzen spannung |
| V_{pp} | Peak-to-peak voltage Impedance | Spannungshub |
| V_R | Rated voltage | Nennspannung |
| \hat{V}_R | Amplitude of rated AC voltage | Amplitude der Nenn-Wechselspannung |
| V_{RMS} | (Sinusoidal) alternating voltage, root-mean-square value | (Sinusförmige) Wechselspannung |
| V_{SC} | S-correction voltage | Spannung bei Anwendung "S-correction" |
| V_{sn} | Snubber capacitor voltage | Spannung bei Anwendung "Beschaltung" |
| Z | Impedance | Scheinwiderstand |
| e | Lead spacing | Rastermaß |

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, we are either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether a product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.tdk-electronics.tdk.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to our General Terms and Conditions of Supply**.

Important notes

7. **Our manufacturing sites serving the automotive business apply the IATF 16949 standard.** The IATF certifications confirm our compliance with requirements regarding the quality management system in the automotive industry. Referring to customer requirements and customer specific requirements (“CSR”) TDK always has and will continue to have the policy of respecting individual agreements. Even if IATF 16949 may appear to support the acceptance of unilateral requirements, we hereby like to emphasize that **only requirements mutually agreed upon can and will be implemented in our Quality Management System.** For clarification purposes we like to point out that obligations from IATF 16949 shall only become legally binding if individually agreed upon.
8. The trade names EPCOS, CeraCharge, CeraDiode, CeraLink, CeraPad, CeraPlas, CSMP, CTVS, DeltaCap, DigiSiMic, ExoCore, FilterCap, FormFit, LeaXield, MiniBlue, MiniCell, MKD, MKK, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, PowerHap, PQSine, PQvar, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.tdk-electronics.tdk.com/trademarks.

Release 2018-10

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EPCOS / TDK:

[B32652A103J189](#) [B32652A103J289](#) [B32652A103K289](#) [B32652A1182J](#) [B32652A1182J189](#) [B32652A1182K289](#)
[B32652A1272J](#) [B32652A1272J189](#) [B32652A1272K189](#) [B32652A1392J](#) [B32652A1392J189](#) [B32652A1392J289](#)
[B32652A1552J](#) [B32652A1612J](#) [B32652A1702J](#) [B32652A1772J](#) [B32652A1822J](#) [B32652A1822J189](#) [B32652A183J](#)
[B32652A183J189](#) [B32652A183K](#) [B32652A2182J](#) [B32652A2182J289](#) [B32652A2221J189](#) [B32652A223K189](#)
[B32652A2252J](#) [B32652A2392J](#) [B32652A2512K](#) [B32652A2562K](#) [B32652A2622K](#) [B32652A2681J289](#) [B32652A273J](#)
[B32652A3124J](#) [B32652A3184J](#) [B32652A3274J](#) [B32652A3274K](#) [B32652A3324K189](#) [B32652A333J289](#)
[B32652A3364J](#) [B32652A3394J](#) [B32652A3394J289](#) [B32652A3824J](#) [B32652A393J](#) [B32652A4184J](#) [B32652A4184K](#)
[B32652A4273J](#) [B32652A4274J](#) [B32652A4394J](#) [B32652A4684J](#) [B32652A473J289](#) [B32652A4863K](#) [B32652A6273J](#)
[B32652A6273J189](#) [B32652A6273K](#) [B32652A6273K289](#) [B32652A6334J](#) [B32652A6393J189](#) [B32652A683J189](#)
[B32652A7273J](#) [B32652A7273J289](#) [B32652J1182J289](#) [B32652J1272J](#) [B32652J1272J189](#) [B32652J1272J289](#)
[B32652J1392J289](#) [B32653A1183J](#) [B32653A174J](#) [B32653A1822J](#) [B32653A1822J189](#) [B32653A1822J289](#)
[B32653A1912K](#) [B32653A2272J](#) [B32653A2392J](#) [B32653A2722J](#) [B32653A2732J](#) [B32653A2742J](#) [B32653A2752J](#)
[B32653A2772J](#) [B32653A2822K](#) [B32653A3274J](#) [B32653A3394J](#) [B32653A3394J189](#) [B32653A3394K](#) [B32653A3904J](#)
[B32653A3904J189](#) [B32653A393J](#) [B32653A4274J](#) [B32653A4394J](#) [B32653A6564K](#) [B32654A3275K](#) [B32656A8105J](#)
[B32656A8105K](#) [B32656A8224J](#) [B32656A8224K](#) [B32656A8334J](#) [B32656A8334K](#) [B32656A8474J](#) [B32656A8474K](#)
[B32656A8684J](#) [B32656A8684K](#)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А