# Type TE Series

## Key Features

**Up to 2500W Power rating in free air**

**Flameproof construction – UL94V coating**

**RoHS compliant**

**Custom terminations / leads available**



## Applications

**Large electrical and production machinery**

**Load test simulation**

**Motor start / stop cycles**

**Dynamic braking**

**Equipment discharge**

TE Connectivity is a leading supplier of standard and custom-designed power resistors for industrial, control and general- purpose applications.

The TE range of flameproof coated tubular ceramic core resistors use both standard and edge wound (corrugated) winding methods to improve power handling capability. Designed for heavy duty machinery, electrical equipment, motor control etc. requiring stability and reliability.

## Characteristics – Electrical

| | |
|---|---|
| Power rating @70°C in free air | 50W – 2500W (see table) |
| Resistance range | See table |
| Selection series | E12 |
| Tolerance | ±5%  ±10% |
| Temperature Coefficient of resistance | <20Ω ±400PPM/°C<br>≥20Ω ±300PPM/°C |
| Operating temperature range | -55 ~ +155°C |
| Short term overload | 3 x rated power / 5 seconds |
| Dielectric strength | 2500VAC Min. |
| Insulation resistance | DC500V 20MΩ min. |

## Specifications – Electrical

| Power Rating | Resistance Value | Tolerance | Dielectric Strength | Appearance |
|---|---|---|---|---|
| 50W | R10 ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 60W | R10 ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 80W | R10 ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 100W | 1R0 ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 120W | 1R0 ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 150W | 1R0 ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 200W | 1R0 ~ 9R1 | ±5% ±10% | 300VAC | Ribbed |
| | 10R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 300W | 1R0 ~ 9R1 | ±5% ±10% | 300VAC | Ribbed |
| | 10R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 400W | 1R0 ~ 15R | ±5% ±10% | 300VAC | Ribbed |
| | 16R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 500W | 1R0 ~ 20R | ±5% ±10% | 300VAC | Ribbed |
| | 21R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 600W | 1R0 ~ 20R | ±5% ±10% | 300VAC | Ribbed |
| | 21R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 750W | 1R0 ~ 75R | ±5% ±10% | 300VAC | Ribbed |
| | 76R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 1000W | 1R0 ~ 100R | ±5% ±10% | 300VAC | Ribbed |
| | 101R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 1200W | 1R0 ~ 100R | ±5% ±10% | 300VAC | Ribbed |
| | 101R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 1500W | 1R0 ~ 120R | ±5% ±10% | 300VAC | Ribbed |
| | 121R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 2000W | 1R0 ~ 120R | ±5% ±10% | 300VAC | Ribbed |
| | 121R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |
| 2500W | 1R0 ~ 120R | ±5% ±10% | 300VAC | Ribbed |
| | 121R ~ 2K7 | ±5% ±10% | 500VAC | Smooth |

## Voltage rating:

Resistors shall have a rated direct-current (DC) continuous working voltage or an approximate sine-wave root-mean-square (RMS) alternating-current (AC) continuous working voltage at commercial line frequency and waveform corresponding to the power rating, as determined from the following formula:

$RCWV = \sqrt{P} \times R$

Where : RCWV = Rated DC or RMS AC continuous working voltage at commercial-line frequency and waveform (volt)

P = Power Rating (watt)

R = Nominal Resistance (ohm)

Derating Curve




Temperature Rise Chart




Construction:

Smooth:




Ribbed:




| No. | Name | Material | Material Generic Name |
|---|---|---|---|
| 1 | Basic Body | Rod Type Ceramics | $Al_2O_3$, $SiO_2$ |
| 2 | Terminal | Tin plated terminal cap | Fe : 73%, Mn : 21%, C : 5% |
| 3 | Resistance Wire | Ni-Cr or Cu-Ni Alloy | Ni-Cr or Cu-Ni Alloy |
| 4 | Coating | Insulated and non-flame paint (Color: Green) | Non-Flame paint UL94V |
| 5 | Marking | Marking Ink | --- |

## Environmental Characteristics:

| Characteristics | Limits | Test Methods (JIS C 5201-1) |
|---|---|---|
| Temperature Coefficient | <20Ω : ± 400 PPM/℃ Max.<br>≥20Ω : ± 300 PPM/℃ Max. | Natural Resistance change per temperature degree centigrade.<br>$\frac{R_2-R_1}{R_1(t_2-t_1)} \times 10^6$ (PPM/°C)<br><br>$R_1$ : Resistance value at room temperature ($t_1$)<br>$R_2$ : Resistance value at room temperature +100°C ($t_2$)<br>(Sub-clause 4.8) |
| Short term overload | ±(2% + 0.05Ω) Max. with no evidence of mechanical damage | Permanent resistance change after the application of a potential of 3 x RCWV for 5 seconds<br>(Sub-clause 4.13 |
| Terminal Strength | No evidence of mechanical damage | **Direct load** :<br>Resistance to a 2.5 kgs direct load for 10 secs. in the direction of the longitudinal axis of the terminal leads<br><br>**Twist Test** :<br>Terminal leads shall be bent through 90 ° at a point of about 6mm from the body of the resistor and shall be rotated through 360° about the original axis of the bent terminal in alternating direction for a total of 3 rotations<br>(Sub-clause 4.16) |
| Solderability | 95 % coverage Min. | The area covered with a new smooth, clean, shiny and continuous surface free from concentrated pinholes.<br>Test temp. of solder : 245℃ ± 3℃<br>Dwell time in solder : 2 ~ 3 seconds<br>(Sub-clause 4.17) |
| Soldering Temp. Reference | Electrical Characteristics shall be satisfied without distinct deformation in appearance. (95% coverage Min.) | Terminals immersed into solder bath to 3.2 ~ 4.8mm from the body. Permanent resistance change shall be checked.<br><br><u>Wave soldering condition (2 cycles max.)</u><br>Pre-heat : 100 ~ 120 ℃, 30 ± 5sec.<br>Suggested solder temp.: 235 ~ 255 ℃, 10 sec. (max.)<br>Peak temp.: 260 ℃<br><br><u>Hand soldering condition:</u><br>Hand Soldering bit temp. : 380 ± 10 ℃<br>Dwell time in solder : 3 +1/-0 sec. |
| Resistance to soldering heat | Resistance change rate ±(1%+0.05Ω) with no evidence of mechanical damage | Permanent resistance change when terminals immersed to 3.2 ~ 4.8mm from body in 350°C ±10°C solder for 3±0.5 seconds<br>Sub-clause 4.18 |
| Load life in humidity | Resistance change rate ±(5%+ 0.05Ω) Max. with no evidence of mechanical damage | Resistance change after 1,000 hours (1.5 hours "on", 0.5 hour "off") at RCWV in a humidity test chamber controlled at 40 ℃± 2 ℃ and 90 to 95 % relative humidity<br>(Sub-clause 4.24.2.1) |
| Load Life | Resistance change rate ±(5%+ 0.05Ω) Max. with no evidence of mechanical damage | Permanent resistance change after 1,000 hours operating at RCWV with duty cycle of (1.5 hours "on", 0.5 hour "off") at 70℃ ± 2℃ ambient<br>(Sub-clause 4.25.1) |

Dimensions:




| Power rating | Dimension | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | B±2 | E±5 | F±3 | D±2 | H±1 | H1±3 | M±0.5 | K±1 | T±0.5 | t±0.5 | Ød ±0.5 |
| 50W | 102 | 124 | 146 | 28 | 28 | 61 | 6.5 | 28 | 8 | 1.8 | 4.3 |
| 60W | 102 | 124 | 146 | 28 | 28 | 61 | 6.5 | 28 | 8 | 1.8 | 4.3 |
| 80W | 152 | 174 | 196 | 28 | 28 | 61 | 6.5 | 28 | 8 | 1.8 | 4.3 |
| 100W | 182 | 204 | 226 | 28 | 28 | 61 | 6.5 | 28 | 8 | 1.8 | 4.3 |
| 120W | 182 | 204 | 226 | 28 | 28 | 61 | 6.5 | 28 | 8 | 1.8 | 4.3 |
| 150W | 195 | 217 | 239 | 40 | 41 | 81 | 8 | 40 | 10 | 1.8 | 5.5 |
| 200W | 195 | 217 | 239 | 40 | 41 | 81 | 8 | 40 | 10 | 1.8 | 5.5 |
| 300W | 282 | 304 | 326 | 40 | 41 | 81 | 8 | 40 | 10 | 1.8 | 5.5 |
| 400W | 282 | 304 | 326 | 40 | 41 | 81 | 8 | 40 | 10 | 1.8 | 5.5 |
| 500W | 316 | 338 | 360 | 50 | 45 | 101 | 8 | 50 | 16 | 1.8 | 6.5 |
| 600W | 345 | 367 | 389 | 40 | 41 | 81 | 8 | 40 | 10 | 1.8 | 5.5 |
| 750W | 316 | 338 | 360 | 50 | 45 | 101 | 8 | 50 | 16 | 1.8 | 6.5 |
| 1000W | 300 | 325 | 350 | 60 | 60 | 119 | 8.5 | 60 | 15 | 2 | 6.5 |
| 1200W | 415 | 440 | 465 | 60 | 60 | 119 | 8.5 | 60 | 15 | 2 | 6.5 |
| 1500W | 415 | 440 | 465 | 60 | 60 | 119 | 8.5 | 60 | 15 | 2 | 6.5 |
| 2000W | 510 | 535 | 560 | 60 | 60 | 119 | 8.5 | 60 | 15 | 2 | 6.5 |
| 2500W | 600 | 625 | 650 | 60 | 60 | 119 | 8.5 | 60 | 15 | 2 | 6.5 |

How To Order

| TE | 50 | B | 1K0 | J |
|---|---|---|---|---|
| Common Part | Power Rating | Mounting | Resistance Value | Tolerance |
| TE – High Power Wirewound Resistor | 50 50W<br>60 60W<br>80 80W<br>100 100W<br>etc. | A – No Bracket<br>B – With Bracket (standard) | 100R - 100Ω<br>1K0 - 1000Ω<br>10K – 10,000Ω | J - ±5%<br>K - ±10% |



Dimensions in millimetres unless otherwise specified

Dimensions Shown for reference purposes only. Specifications subject to change

For Email, phone or live chat, go to: www.te.com/help

# OCEAN CHIPS
## Океан Электроники
## Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

**«JONHON»** (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

**«FORSTAR»** (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А