Notice for TAIYO YUDEN Products

Please read this notice before using the TAIYO YUDEN products.

!\ REMINDERS

Product information in this catalog is as of October 2017. All of the contents specified herein are subject to change without notice due to technical improvements, etc. Therefore, please check for the latest information carefully before practical application or use of our products.

Please note that TAIYO YUDEN shall not be in any way responsible for any damages and defects in products or equipment incorporating our products, which are caused under the conditions other than those specified in this catalog or individual product specification sheets.

- Please contact TAIYO YUDEN for further details of product specifications as the individual product specification sheets are available.
- Please conduct validation and verification of our products in actual condition of mounting and operating environment before using our products.
- The products listed in this catalog are intended for use in general electronic equipment (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC) and medical equipment classified as Class I or II by IMDRF. Please be sure to contact TAIYO YUDEN for further information before using the products for any equipment which may directly cause loss of human life or bodily injury (e.g., transportation equipment including, without limitation, automotive powertrain control system, train control system, and ship control system, traffic signal equipment, disaster prevention equipment, medical equipment classified as Class III by IMDRF, highly public information network equipment including, without limitation, telephone exchange, and base station).

Please do not incorporate our products into any equipment requiring high levels of safety and/or reliability (e.g., aerospace equipment, aviation equipment*, medical equipment classified as Class IV by IMDRF, nuclear control equipment, undersea equipment, military equipment).

*Note: There is a possibility that our products can be used only for aviation equipment that does not directly affect the safe operation of aircraft (e.g., in-flight entertainment, cabin light, electric seat, cooking equipment) if such use meets requirements specified separately by TAIYO YUDEN. Please be sure to contact TAIYO YUDEN for further information before using our products for such aviation equipment.

When our products are used even for high safety and/or reliability-required devices or circuits of general electronic equipment, it is strongly recommended to perform a thorough safety evaluation prior to use of our products and to install a protection circuit as necessary.

Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of the products listed in this catalog for any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.

- Information contained in this catalog is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.
- Please note that the scope of warranty for our products is limited to the delivered our products themselves and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a fault or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement.
- The contents of this catalog are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter "TAIYO YUDEN's official sales channel"). Please note that the contents of this catalog are not applicable to our products purchased from any seller other than TAIYO YUDEN's official sales channel.
- Caution for Export

Some of our products listed in this catalog may require specific procedures for export according to "U.S. Export Administration Regulations", "Foreign Exchange and Foreign Trade Control Law" of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.

Wireless Module

Our recommended Line Up of Bluetooth®, W-LAN & GPS Module

■ For Smartphone Peripheral & IoT Solution







Bluetooth® low energy Module

For Industrial Market







WLAN (+BT)
Original or ON-board Antenna & FPC Connector

For IoT Solution & Industrial







WLAN Module







*As some of the Wireless Modules listed above are still under development, the specification is subject to change without prior notice. We also have Evaluation Kits for our modules.

For the latest information, please visit our web site at http://www.ty-top.com/ or feel free to contact our sales department.

**The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by TAIYO YUDEN CO., LTD. is under license. Other trademarks and trade names are those of their respective owners.

[▶] This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (http://www.ty-top.com/).

■ Bluetooth® low energy Module I/F Function Module type Type approval 802.11a 802.11b 802.11n GLONASS 802.11g Part number UART USB BLE NFC GPS PCM SMD 500 ANT SPI 12C 128 В 2 CE 0 0 EYSHSNZWZ 0 0* 0 0 0 0 0 O O O O* Ultra Small,64k RAM 0 0 0 ō 0* 0 0 0 0 0 0 0 O* 64k RAM FYSHJN7W7 O O O O* 16k RAM 0 0 0 FYSGJN7XX EYSGJNZWY C 0 0 0 0 0 O O O O* 32k RAM EYSGJNAWY-1X 0 0 0 0 O O O O* TY's APP(Lite) O O O O* TY's APP EYSGJNAWY-WX 0 0 0 0 EYSHCNZWZ 0 0* 0 0 0 0 0 0 0 0 0 0 Ŏ* 32k X'tal,64k RAM EYSGCNZXX 0 0 0 0 0 0 0 0 0 0* 32k X'tal,16k RAM EYSGCNZWY 0 0 0 0 0 0 0 0 0 0* 32k X'tal,32k RAM 0 0 0 O O O O* 32k X'tal,TY's APP(Lite) EYSGCNAWY-1X 0 EYSGCNAWY-WX 0 0 0 O O O O * 32k X'tal,TY's APP

*Softdevice S332

*CE Conducted test report available

Rluetooth®	1014	onormi	9	ANT	Madula

					F	unctio	n								I/F				Мо	dule t	уре	T	уре а	pprov	al	
Part number	BLE	ВТ	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	12C	128	SDIO	SMD	Connector	Antenna	Japan	FCC	IC	CE	Remark
EYAGJNZXX	0		0									0			0	0			0		0	0	0	0	0*	32k RAM

*CE Conducted test report available

Bluetooth®	Dual	Mode	Modula

Ī						F	unctic	n								I/F				Мо	dule t	ype	T	ype a	pprov	al	
	Part number	BLE	ВТ	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	12C	12.8	SDIO	SMD	Connector	Antenna	Japan	FCC	IC	CE	Remark
ſ	EYSGCCAXX	0	0										0							0		0	0	0	0	0*	
	EYSGCCSXX	0	0											0						0		0	0	0	0	0*	

*CE Conducted test report available

CPU Embedded WLAN Module

ſ						F	unctic	n								I/F				Мо	dule t	ype	Т	уре а	pprov	al	
	Part number	BLE	ВТ	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	12C	128	SDIO	SMD	Connector	Antenna	Japan	FCC	IC	CE	Remark
I	WYSACVLXY-XZ						0	0	0				0							0		0	0	0	0	0*	
	WYSACVLXY-XX						0	0	0				0							0		0	0	0	0	0*	TY's APP

*CE Conducted test report available

WLAN or WLAN+BT Module

WLAN OF WLAN-BT	WIOUU	110																								
					F	unctio	n								I/F				Mo	dule t	уре	Т	ype a	pprov	al	
Part number	BLE	ВТ	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	12 C	128	SDIO	SMD	Connector	Antenna	Japan	FCC	IC	CE	Remark
WYSBHVGXG	0	0			0	0	0	0	0					0				0	0							
WYSAGVDX7						0	0	0										0		0	0	0	0	0		
WYSAAVDXB		0			0	0	0	0						0				0		0	0	0				
WYSAAVDX7						0	0	0										0	0		0	0	0	0		
WYSBMVGXB		0			0	0	0	0						0				0	0							
WYSAGVDXG	0	0			0	0	0	0	0									0	0		0	0	0	0	0*	

*CE Conducted test report available

■GNSS Module

					F	unctio	n								I/F				Мо	dule t	уре	Т	уре а	pprov	al	
Part number	BLE	ВТ	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	12C	128	SDIO	SMD	Connector	Antenna	Japan	FCC	IC	CE	Remark
GYSFFMAXB										0		0							0							
GYSFFMAXC										0	0	0							0							
GYSFDMAXB										0		0								0	0					

[▶] This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (http://www.ty-top.com/).

Part number	Function	Module type	I/F	Feature	Outline [mm] (Height : Maximum)
EYSHSNZWZ	Bluetooth® low energy v5.0	BLE Slave and Master	UART	w/CPU (Cortex M4F)	8.55 x 3.25 x 0.9
(nRF52832)	& NFC-A Type-2	NFC-A Type-2	I2C	Antenna	
		SMD type	SPI	512KB Flash	
			I2S PDM	64KB RAM	
			15 GPIO	FCC/IC/Japan certified CE Conducted test report available	
				,	
EYSHJNZWZ	Bluetooth® low energy v5.0	BLE Slave and Master	UART I2C	w/CPU (Cortex M4F)	11.3 x 5.1 x 1.3
(nRF52832)	& NFC-A Type-2	NFC-A Type-2 SMD type	SPI	Antenna 512KB Flash	
		OND type	I2S	64KB RAM	
			PDM	FCC/IC/Japan certified	
			15 GPIO	CE Conducted test report available	
EYSGJNZXX	Bluetooth® low energy v4.2 (*)	BLE Slave and Master	UART	w/CPU (Cortex M0)	11.3 x 5.1 x 1.3
(nRF51822)	Diactocaro low chargy VI.2 (1)	SMD type	I2C	Antenna	
			SPI	256KB Flash	
			14 GPIO	16KB RAM	
				FCC/IC/Japan certified CE Conducted test report available	
				OL Conducted test report available	
EYSGJNZWY	Bluetooth® low energy v4.2 (*)	BLE Slave and Master	UART	w/CPU (Cortex M0)	11.3 x 5.1 x 1.3
(nRF51822)		SMD type	I2C	Antenna	
			SPI	256KB Flash	
			14 GPIO	32KB RAM FCC/IC/Japan certified	
				CE Conducted test report available	
				,	
EYSGJNAWY-1X	Bluetooth® low energy v4.1	BLE Slave and Master	UART	w/CPU (Cortex M0)	11.3 x 5.1 x 1.3
(nRF51822)		SMD type TAIYO YUDEN Software Embedded		Antenna FCC/IC/Japan certified	T
		(Lite Version)		CE Conducted test report available	
		(
EYSGJNAWY-WX	Bluetooth® low energy v4.1	BLE Slave and Master	UART	w/CPU (Cortex M0)	11.3 x 5.1 x 1.3
(nRF51822)	Diagram of the original of the original	SMD type	5,	Antenna	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
		TAIYO YUDEN Software Embedded		FCC/IC/Japan certified	
		(Full Version)		CE Conducted test report available	
EYSHCNZWZ	Bluetooth® low energy v5.0	BLE Slave and Master	UART	w/CPU (Cortex M4F)	12.9 x 9.6 x 2.0
(nRF52832)	& NFC-A Type-2	NFC-A Type-2	I2C SPI	Antenna 512KB Flash	
		SMD type	I2S	64KB RAM	
			PDM	32kHz Crystal	
			PDM 30 GPIO	32kHz Crystal FCC/IC/Japan certified	
			I	32kHz Crystal	
			I	32kHz Crystal FCC/IC/Japan certified	
EYSGCNZXX	Bluetooth® low energy v4.2 (*)	BLE Slave and Master	30 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0)	
EYSGCNZXX (nRF51822)	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type	30 GPIO UART I2C	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna	12.9 x 9.6 x 2.0
	Bluetooth® low energy v4.2 (*)		30 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash	12.9 x 9.6 x 2.0
	Bluetooth® low energy v4.2 (*)		30 GPIO UART I2C	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna	12.9 x 9.6 x 2.0
	Bluetooth® low energy v4.2 (*)		30 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified	12.9 x 9.6 x 2.0
	Bluetooth® low energy v4.2 (*)		30 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal	12.9 x 9.6 x 2.0
	Bluetooth® low energy v4.2 (*)		30 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified	12.9 x 9.6 x 2.0
(nRF51822) EYSGCNZWY	Bluetooth® low energy v4.2 (*) Bluetooth® low energy v4.2 (*)	SMD type BLE Slave and Master	30 GPIO UART I2C SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0)	12.9 x 9.6 x 2.0
(nRF51822)		SMD type	JUART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna	12.9 x 9.6 x 2.0
(nRF51822) EYSGCNZWY		SMD type BLE Slave and Master	JO GPIO UART I2C SPI 29 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0)	12.9 x 9.6 x 2.0
(nRF51822) EYSGCNZWY		SMD type BLE Slave and Master	JUART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash	12.9 x 9.6 x 2.0
(nRF51822) EYSGCNZWY		SMD type BLE Slave and Master	JO GPIO UART I2C SPI 29 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32KB RAM 32KHz Crystal FCC/IC/Japan certified	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
(nRF51822) EYSGCNZWY		SMD type BLE Slave and Master	JO GPIO UART I2C SPI 29 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32KB RAM 32KHz Crystal	12.9 x 9.6 x 2.0
(nRF51822) EYSGCNZWY		SMD type BLE Slave and Master	JO GPIO UART I2C SPI 29 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32KB RAM 32KHz Crystal FCC/IC/Japan certified	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNZWY		BLE Slave and Master SMD type BLE Slave and Master	JO GPIO UART I2C SPI 29 GPIO UART I2C SPI	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32kB RAM 32kB zAM 32kBz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32KB zAM	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822)	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type BLE Slave and Master SMD type	JO GPIO UART IZC SPI 29 GPIO UART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32KHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB report available w/CPU (Cortex M0) Antenna	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNZWY	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	JO GPIO UART IZC SPI 29 GPIO UART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB Flash 16kB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB Flash 32kB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB rash 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNZWY	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type BLE Slave and Master SMD type	JO GPIO UART IZC SPI 29 GPIO UART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32KHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNZWY	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	JO GPIO UART IZC SPI 29 GPIO UART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB Flash 16kB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB Flash 32kB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB rash 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNZWY	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	JO GPIO UART IZC SPI 29 GPIO UART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32KHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNAWY-1X	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	JO GPIO UART IZC SPI 29 GPIO UART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32KHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNAWY-1X (nRF51822)	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	JO GPIO UART IZC SPI 29 GPIO UART IZC SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32KHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNAWY-1X (nRF51822)	Bluetooth® low energy v4.2 (*) Bluetooth® low energy v4.1	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Lite Version) BLE Slave and Master SMD type	UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB Flash 16kB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256kB Flash 32kB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna w/CPU (Cortex M0) Antenna	12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNAWY-1X (nRF51822)	Bluetooth® low energy v4.2 (*) Bluetooth® low energy v4.1	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Lite Version) BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0
EYSGCNAWY-1X (nRF51822) EYSGCNAWY-1X (nRF51822)	Bluetooth® low energy v4.2 (*) Bluetooth® low energy v4.1	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Lite Version) BLE Slave and Master SMD type	UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNAWY-1X (nRF51822)	Bluetooth® low energy v4.2 (*) Bluetooth® low energy v4.1	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Lite Version) BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNAWY-1X (nRF51822)	Bluetooth® low energy v4.2 (*) Bluetooth® low energy v4.1	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Lite Version) BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0
EYSGCNZWY (nRF51822) EYSGCNZWY (nRF51822) EYSGCNAWY-1X (nRF51822)	Bluetooth® low energy v4.2 (*) Bluetooth® low energy v4.1	BLE Slave and Master SMD type BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Lite Version) BLE Slave and Master SMD type TAIYO YUDEN Software Embedded	UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO UART I2C SPI 29 GPIO	32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 12.9 x 9.6 x 2.0

[▶] This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (http://www.ty-top.com/).

(*)Supported by S130

Part number	Function	Module type	I/F	Feature	Outline [mm] (Height : Maximum)
EYAGJNZXX (nRF51422)	Biuetooth® low energy v4.2 & ANT	BLE Slave ANT SMD type	UART I2C SPI 14 GPIO	w/CPU (Cortex M0) Antenna 256KB Flash	11.3 x 5.1 x 1.3
■ <i>Bluetooth</i> ® Dual		<u> </u>			
Part number EYSGCCAXX	Function Bluetooth® Legacy and BLE	Module type SMD type	I/F UART	Feature Integrated System Clock	Outline [mm] (Height : Maximum) 15.4 x 10.0 x 2.0
				Antenna FCC/IC/Japan certified CE Conducted test report available	
EYSGCCSXX	Bluetooth® Legacy and BLE	SMD type	USB	Integrated System Clock Antenna FCC/IC/Japan certified CE Conducted test report available	15.4 x 10.0 x 2.0
■CPU Embedded V	/LAN Module				
Part number	Function	Module type	I/F	Feature	Outline [mm] (Height : Maximum)
WYSACVLXY-XZ	IEEE802.11b/g/n	SMD type	UART SPI	Integrated System Clock Antenna Supprt Micro AP Supprt WiFi Direct FCC/IC/Japan certified CE Conducted test report available	21.4 x 14.0 x 2.4
WYSACVLXY-XX	IEEE802.11b/g/n	SMD type Original Software Embedded	UART SPI	Integrated System Clock Antenna Supprt Micro AP FCC/IC/Japan certified CE Conducted test report available	21.4 × 14.0 × 2.4

[▶] This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (http://www.ty-top.com/).

Part number	Function	Module type	I/F	Feature	Outline [mm] (Height : Maximum)
WYSBHVGXG	IEEE802.11ac/a/b/g/n+Bluetooth® 4.2	SMD type	SDIO	Integrated System Clock	12.6 x 8.9 x 1.9
			PCM	2.4GHz & 5GHz	
				11ac(HT80)	
WYSAGVDX7	IEEE802.11b/g/n	Connector type	SDIO	Integrated System Clock	20.0 x 11.0 x 2.15
WISAGVDXI	ILLEGOZ.11D/ g/ II	Connector type	3510	Antenna	20.0 x 11.0 x 2.13
				FCC/IC/Japan certified	
					9-11
MANCA AND VD	IEEE000 11 - /b / -/ Blooks - 4b @ 2.0	0	CDIO	Total model of Contains Objects	20.0 15.0 0.45
WYSAAVDXB	IEEE802.11 a/b/g/n+Bluetooth® 3.0	Connector type	SDIO PCM	Integrated System Clock Dual Band Antenna	30.0 x 15.0 x 2.45
				HT40	
				Japan certified	
					lual Ba
					Shielding Case
W (0 1 / · · · ·					
WYSAAVDX7	IEEE802.11b/g/n	Connector type	SDIO	Integrated System Clock Antenna	35.0 x 15.0 x 2.9
				HT40	
				FCC/IC/Japan certified	
					Power Shielding Block Case
WYSBMVGXB	IEEE802.11 a/b/g/n+Bluetooth® 3.0	SMD type	SDIO PCM	2.4GHz & 5GHz HT40	13.1 x 6.1 x 1.35
			POM	H140	
WYSAGVDXG	IEEE802.11ac/a/b/g/n+Bluetooth® 4.2	SMD type	SDIO PCM	Integrated System Clock 2.4GHz & 5GHz	24.0 x 11.5 x 2.0
			POM	11ac(HT80)	
				Antenna	
				FCC/IC/Japan certified	
				CE Conducted test report available	
GNSS Module					
Part number	Function	Module type	I/F	Feature	Outline [mm] (Height : Maximum)
GYSFFMAXB	GPS Full Module	SMD type	UART	TCXO	10.8 x 10.0 x 2.05
	NMEA Output			RTC LNA	Г П
				SAW	
				On-chip Logger	1 I d H
					1 1 1 1
					0 0
GYSFFMAXC	GPS&GLONASS	SMD type	UART	тсхо	10.8 x 10.0 x 2.05
	Full Module			RTC	
	NMEA Output			LNA SAW	
				On-chip Logger	
				=	
					ш Ц
GYSFDMAXB	GPS Full Module	Connector type	UART	Patch Antenna	23.2 x 15.3 x 6.9
	NMEA Output			TCXO	C-
				RTC LNA	
				SAW	
				On-chip Logger	
		•		•	Ol

[▶] This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (http://www.ty-top.com/).



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: http://oceanchips.ru/

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А