

1353A Multi-Conductor - AES/EBU Digital Audio Cable

For more Information
please call

1-800-Belden1



General Description:

24 AWG Bonded-Pairs stranded (7x32) bare copper conductors, polyolefin insulation, PVC jacket.

Usage (Overall)

Suitable Applications: Field Deployable Cat 5e Patch, CobraNet, eSnake, Ethersound, Digital Audio over Ethernet

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material | Dia. (in.) |
|---------|-----|-----------|--------------------|------------|
| 1 | 24 | 7x32 | BC - Bare Copper | .022 |

Total Number of Conductors: 2

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (in.) | Dia. (in.) |
|---------------------|----------------------|------------|
| PO - Polyolefin | .0085 | .041 |

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material | Nom. Wall Thickness (in.) |
|--------------------------|---------------------------|
| PVC - Polyvinyl Chloride | .022 |

Overall Cable

Overall Nominal Diameter: 0.126 in.

Pair

Pair Color Code Chart:

| Number | Color |
|--------|----------------------------|
| 1 | White/Brown Stripe & Brown |

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +60°C

Bulk Cable Weight: 8 lbs/1000 ft.

Max. Recommended Pulling Tension: 18 lbs.

Min. Bend Radius/Minor Axis: 1.500 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 03/15/2007

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

1353A Multi-Conductor - AES/EBU Digital Audio Cable

Other Specification: NEMA WC-63.1 Category 5, ICEA 661, Category 5e Patch, TIA/EI-568-B.2, Category 5e

Applicable Patents:

Country

www.belden.com/p

Flame Test

UL Flame Test: UL1666 Riser

CSA Flame Test: FT4

Suitability

Suitability - Indoor: Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

14.500

Nominal Velocity of Propagation:

VP (%)

70

Maximum Delay:

Delay (ns/100 m)

510

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

9

Max. Operating Voltage - UL:

Voltage

300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)

3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|-------------|---------------|
| 1 | 2.400 | 20.000 | 23.0 |
| 4 | 4.900 | 23.000 | 23.0 |
| 6 | 6.000 | | |
| 8 | 6.900 | 24.500 | 23.0 |
| 10 | 7.800 | 25.000 | 23.0 |
| 12 | 8.400 | | |
| 16 | 9.900 | 25.000 | 23.0 |
| 20 | 11.100 | 25.000 | 23.0 |
| 25 | 12.500 | 24.300 | 22.0 |
| 31.25 | 14.100 | 23.600 | 21.0 |
| 62.5 | 20.400 | 21.500 | 18.0 |
| 100 | 26.400 | 20.100 | 16.0 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Fitted Impedance |
|-------------|------------------|
| 1 | 105 ± 15 |
| 4 | 100 ± 15 |
| 8 | 100 ± 15 |
| 10 | 100 ± 15 |
| 16 | 100 ± 15 |
| 20 | 100 ± 15 |
| 25 | 100 ± 15 |
| 31.25 | 100 ± 15 |
| 62.5 | 100 ± 15 |
| 100 | 100 ± 15 |

Notes (Overall)

Notes: EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc. Operating temperatures are subject to length de-rating.

1353A Multi-Conductor - AES/EBU Digital Audio Cable

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|----------|-------------|-------------|-------|-------------------|
| 1353A N3UU1000 | 1,000 FT | 9.000 LB | GREEN, MIL | | 1 PR #24 PP FRPVC |
| 1353A 001U1000 | 1,000 FT | 9.000 LB | BROWN | | 1 PR #24 PP FRPVC |
| 1353A 002U1000 | 1,000 FT | 9.000 LB | RED | | 1 PR #24 PP FRPVC |
| 1353A 003U1000 | 1,000 FT | 9.000 LB | ORANGE | | 1 PR #24 PP FRPVC |
| 1353A 004U1000 | 1,000 FT | 9.000 LB | YELLOW | | 1 PR #24 PP FRPVC |
| 1353A 006U1000 | 1,000 FT | 9.000 LB | BLUE, LIGHT | | 1 PR #24 PP FRPVC |
| 1353A 007U1000 | 1,000 FT | 9.000 LB | VIOLET | | 1 PR #24 PP FRPVC |
| 1353A 008U1000 | 1,000 FT | 9.000 LB | GRAY | | 1 PR #24 PP FRPVC |
| 1353A 009U1000 | 1,000 FT | 9.000 LB | WHITE | | 1 PR #24 PP FRPVC |
| 1353A 010U1000 | 1,000 FT | 9.000 LB | BLACK | | 1 PR #24 PP FRPVC |
| 1353A 0101000 | 1,000 FT | 9.000 LB | BLACK | | 1 PR #24 PP FRPVC |
| 1353A 010500 | 500 FT | 5.500 LB | BLACK | | 1 PR #24 PP FRPVC |

Revision Number: 1 Revision Date: 02-28-2014

© 2014 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А