

## Type HS Series

### Key Features

- Established product with proven reliability
  - Leading the way with over 50 years of design and manufacturing experience
- 5 Watts to 300 Watts (500 Watt and 1000 Watt versions available)
  - Largest range on the market
- Versatile product
  - Bench mark in every industry
- Custom designs
  - Windings, terminations, mountings - We have a solution for your application
- Low resistance, low inductance and higher voltage versions available
  - Specialising the standard

### Applications

- Braking Resistor
- Balancing Resistor
- Capacitor Charging & Discharging
- Crowbar
- Filter
- Electrical Machinery general use
- Available through Distribution



TE Connectivity are the leading European supplier of standard and custom designed aluminium housed resistors for general-purpose use, power supplies, power generation and the traction industry. The HS is a range of extremely stable, high quality wire wound resistors capable of dissipating high power in a limited space with relatively low surface temperature. The power is rapidly dissipated as heat through the aluminium housing to a specified heatsink.

The resistors are made from quality materials for optimum reliability and stability. TE can test resistors to conform to relevant international, MIL or customer specifications.

TE are happy to advise on the use of resistors for pulse applications and to supply information for high voltage use and low-ohmic value, alternative mountings and termination type.

### Characteristics - Electrical HSA & HSC - 5 Watts to 75 Watts

|                                                  | HSA5   | HSA10  | HSA25  | HSA50  | HSC75  |
|--------------------------------------------------|--------|--------|--------|--------|--------|
| Dissipation @ 25°C with Heatsink (Watts):        | 10     | 16     | 25     | 50     | 75     |
| Without Heatsink:                                | 5.5    | 8      | 12.5   | 20     | 45     |
| Ohmic Value Min (Ohms):                          | R01    | R01    | R01    | R01    | R05    |
| Max:                                             | 10K    | 15K    | 36K    | 100K   | 50K    |
| Max. Working Voltage (DC or ACrms) Volts:        | 160    | 265    | 550    | 1250   | 1400   |
| Dielectric Strength (AC Peak) Volts:             | 1400   | 1400   | 2500   | 2500   | 5000   |
| Stability (% resistance change, 1000 hours) (%): | 1      | 1      | 1      | 1      | 2      |
| Standard Heatsink - Area (mm²):                  | 41500  | 41500  | 53500  | 53500  | 99500  |
| Thickness (mm):                                  | 1      | 1      | 1      | 1      | 3      |
| Number of Mounting Holes:                        | 2 hole | 2 hole | 2 hole | 2 hole | 4 hole |

### Characteristics - Electrical HSC - 100 Watts to 300 Watts


|                                                  | HSC100 | HSC150 | HSC200 | HSC250 | HSC300 |
|--------------------------------------------------|--------|--------|--------|--------|--------|
| Dissipation @ 25°C with Heatsink (Watts):        | 100    | 150    | 200    | 250    | 300    |
| Without Heatsink:                                | 50     | 55     | 50     | 60     | 75     |
| Ohmic Value Min (Ohms):                          | R05    | R10    | R10    | R10    | R10    |
| Max:                                             | 100K   | 100K   | 50K    | 68K    | 82K    |
| Max. Working Voltage (DC or ACrms) Volts:        | 1900   | 2500   | 1900   | 2200   | 2500   |
| Dielectric Strength (AC Peak) Volts:             | 5000   | 5000   | 5600   | 5600   | 5600   |
| Stability (% resistance change, 1000 hours) (%): | 2      | 2      | 3      | 3      | 3      |
| Standard Heatsink - Area (mm²):                  | 99500  | 99500  | 375000 | 476500 | 578000 |
| Thickness (mm):                                  | 3      | 3      | 3      | 3      | 3      |
| Number of Mounting Holes:                        | 4 hole | 4 hole | 6 hole | 6 hole | 6 hole |

## Type HS Series


### Characteristics - Electrical

|                               |                                                                                                                                                                                                                                                                                                  |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Long Term Stability:</b>   | For improvements in long-term stability, resistors must be derated as follows; for 50% of stated $\Delta R$ maximum dissipation must not exceed 70% of rating; for 25% of stated $\Delta R$ maximum, dissipation must not exceed 50% of rating                                                   |
| <b>Insulation Resistance:</b> | Dry: 10,000M $\Omega$ minimum. After moisture test: 1000M $\Omega$ minimum.                                                                                                                                                                                                                      |
| <b>Heat Dissipation:</b>      | Although the use of proprietary heat sinks with lower thermal resistance is acceptable, up rating is not recommended.<br>The use of proprietary heat sink compound to improve thermal conductivity is recommended for optimum performance of all sizes but essential for HSC200, HSC250 & HSC300 |
| <b>Specification:</b>         | Temperature coefficient below 100R, 50ppm/ $^{\circ}$ C<br>Temperature coefficient above 100R, 30ppm/ $^{\circ}$ C<br>Tolerance, 5% standard: 10%, 3%, 2%, 0.5% & 0.25% available<br>Tolerance for values below R10, 10% standard                                                                |


### Derating Curve HSA5 to HSA50



### Derating Curve HSC75 to HSC300




### Pulse Energy HSA5 to HSC75




## Type HS Series

### Pulse Energy HSC100 to HSC300




### Power Overload




This graph indicates the amount that the rated power (at 20°C) of the standard HS Series resistor may be increased for overloads of 100mS to 60S

### Surface Temperature Rise




For resistor mounted on standard heatsink, related to power dissipation

### Product Specifications - HSA5 - HSC150




| Type            | L  |
|-----------------|----|
| HSA5, 10        | 7  |
| HSA25, 50       | 10 |
| HSC75, 100, 150 | 8  |

### HSC200 - HSC300




## Type HS Series


### Dimensions - HSA5 - HSA50



### HSC75 - HSC150



### HSC200+



| Type   | H±0.3 | J±0.3 | K±0.2 | L Max | M Max | N Max | P Max | R Min | T±0.5 | U Max |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| HSA5   | 11.3  | 12.4  | 2.4   | 17.0  | 30.0  | 17.0  | 9.0   | 1.9   | 4.3   | 2.5   |
| HSA10  | 14.3  | 15.9  | 2.4   | 21.0  | 36.5  | 21.0  | 11.0  | 1.9   | 5.2   | 3.2   |
| HSA25  | 18.3  | 19.8  | 3.3   | 29.0  | 51.0  | 28.0  | 15.0  | 2.8   | 7.2   | 3.2   |
| HSA50  | 39.7  | 21.4  | 3.3   | 51.0  | 72.5  | 30.0  | 17.0  | 2.8   | 8.2   | 3.2   |
| HSC75  | 29.0  | 37.0  | 4.4   | 49.0  | 71.0  | 47.5  | 26.0  | 5.0   | 11.5  | 3.5   |
| HSC100 | 35.0  | 37.0  | 4.4   | 65.5  | 87.5  | 47.5  | 26.0  | 5.0   | 11.5  | 3.5   |
| HSC150 | 58.0  | 37.0  | 4.4   | 98.0  | 122.0 | 47.5  | 26.0  | 5.0   | 11.5  | 3.5   |
| HSC200 | 35.0  | 57.2  | 5.3   | 90.0  | 143.0 | 73.0  | 42.0  | 5.6   | 20.25 | 5.3   |
| HSC250 | 44.5  | 57.2  | 5.3   | 109.0 | 163.0 | 73.0  | 42.0  | 5.6   | 20.25 | 5.3   |
| HSC300 | 52.0  | 59.0  | 6.5   | 128.0 | 180.0 | 73.0  | 42.0  | 5.6   | 20.25 | 5.3   |

### How to Order

| HS                                    | A                                                                                | 50                                                                                                | 680R                                                                                     | J                                               |
|---------------------------------------|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-------------------------------------------------|
| Common Part                           | Mounting Style                                                                   | Power Rating                                                                                      | Resistance Value                                                                         | Tolerance                                       |
| HS - Standard<br>NHS - Low Inductance | A - Single Opposing mounting Feet<br>B - Flange One Side<br>C - Flange Two Sides | 10 Watt = HSA5<br>16 Watt = HSA10<br>25 Watt = HSA25<br>50 Watt = HSA50<br>75 Watt = HSA75<br>etc | 0.1ohm (100 mille ohms)<br>R10<br>1ohm (1000 mille ohms)<br>1R0<br>1K (1000 ohms)<br>1KO | F - 1%<br>G - 2%<br>E - 3%<br>J - 5%<br>K - 10% |

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.

Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this datasheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А