

| | |
|---|----------------|
|  | E480232 |
|---|----------------|

Features

- For Surface Mount Application in Order to Optimize Board Space
- Built-in Strain Relief
- Glass Passivated Junction
- Plastic Package Has Underwrites Laboratory Flammability
- Temperature Coefficient, Typical Value is 0.1%
- Fast Response Time: Typical Less than 1ps from 0V to BV Min
- Typical I_D Less than 1μA Above 10V
- High Temperature Soldering: 260°C/10 Seconds at Terminals
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant (Note1) ("P" Suffix Designates Compliant. See Ordering Information)

Mechanical Data

- Polarity: Color Band Denotes Positive End(Cathode) Except Bi-directional Types(Note4)
- Weight: 0.007 ounce, 0.21 gram
- IEC-61000-4-2 ESD 15kV(Air), 8kV(Contact)
- Standard Packaging: 16mm Tape Per (EIA 481)
- Terminals: Solderable Per MIL-STD-750, Method 2026

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +175°C
- Storage Temperature Range: -55°C to +175°C
- Typical Thermal Resistance: 15°C/W Junction to Lead
- Typical Thermal Resistance: 75°C/W Junction to Ambient


Electrical Characteristics @ 25°C Unless Otherwise Specified

| | | | |
|--|------------------|--------------------------------|------------------------|
| Peak Pulse Power Surge Current on 10/1000μs Waveform | I _{PPM} | See the Table | Note 2 |
| Peak Pulse Power Dissipation on 10/1000μs Waveform | P _{PPM} | 1500W | Note 2,3,Fig1 |
| Power Dissipation on infinite heat sink | P _D | 6.5W | T _L = 75°C. |
| Peak forward surge current, 8.3 ms single half sine-wave unidirectional only | I _{FSM} | 200A | |
| Maximum instantaneous forward voltage at 100A for unidirectional only | V _F | 3.5V MAX 1.7 TYP /5V MAX 4 TYP | Note 5 |

1. High Temperature Solder Exemption Applied, see EU Directive Annex 7a.
2. Non-repetitive current pulse, per Fig.3 and derated above T_A=25°C per Fig.4.
3. Mounted on 8.0mm²copper pads to each terminal.
4. Unidirectional and bidirectional available, for bidirectional devices add "C" suffix to the pn#SMCJ5.0CA
5. V_F<3.5V for devices of V_{BR}<200V and V_F<5.0V for devices of V_{BR}>201V


**1500 Watt TVS
5.0 to 440 Volts**

**SMC (DO-214AB)
(LEAD FRAME)**



| DIM | INCHES | | MM | | NOTE |
|-----|--------|-------|-------|-------|------|
| | MIN | MAX | MIN | MAX | |
| A | 0.079 | 0.103 | 2.00 | 2.62 | |
| B | 0.108 | 0.128 | 2.75 | 3.25 | |
| C | 0.002 | 0.008 | 0.051 | 0.203 | |
| D | 0.006 | 0.012 | 0.152 | 0.305 | |
| E | 0.030 | 0.060 | 0.76 | 1.52 | |
| F | 0.305 | 0.320 | 7.75 | 8.13 | |
| G | 0.260 | 0.280 | 6.60 | 7.11 | |
| H | 0.220 | 0.245 | 5.59 | 6.22 | |

Suggested Solder Pad Layout



Electrical Characteristics @ 25°C Unless Otherwise Specified

| MCC Part Number | | Reverse Stand-Off Voltage | Breakdown Voltage $V_{BR}(V)$ | | Test Current | Max. Clamping Voltage @ I_{PP} | Peak Pulse Current | Reverse Leakage Current@ V_{WM} | Marking Code | |
|-----------------|-----------|---------------------------|-------------------------------|-------|--------------|----------------------------------|--------------------|-----------------------------------|--------------|-----|
| Uni-Polar | Bi-Polar | $V_{WM}(V)$ | Min | Max | $I_T(mA)$ | $V_C(V)$ | $I_{PP}(A)$ | $I_D(\mu A)$ | UNI | BI |
| SMCJ5.0A | SMCJ5.0CA | 5 | 6.4 | 7.0 | 10 | 9.2 | 163.0 | 800 | GDE | BDE |
| SMCJ6.0A | SMCJ6.0CA | 6 | 6.7 | 7.4 | 10 | 10.3 | 145.7 | 800 | GDG | BDG |
| SMCJ6.5A | SMCJ6.5CA | 6.5 | 7.2 | 8.0 | 10 | 11.2 | 134.0 | 500 | GDK | BDK |
| SMCJ7.0A | SMCJ7.0CA | 7 | 7.8 | 8.6 | 10 | 12.0 | 125.0 | 200 | GDM | BDM |
| SMCJ7.5A | SMCJ7.5CA | 7.5 | 8.3 | 9.2 | 1 | 12.9 | 116.3 | 100 | GDP | BDP |
| SMCJ8.0A | SMCJ8.0CA | 8 | 8.9 | 9.8 | 1 | 13.6 | 110.3 | 50 | GDR | BDR |
| SMCJ8.5A | SMCJ8.5CA | 8.5 | 9.4 | 10.4 | 1 | 14.4 | 104.2 | 20 | GDT | BDT |
| SMCJ9.0A | SMCJ9.0CA | 9 | 10.0 | 11.1 | 1 | 15.4 | 97.4 | 10 | GDV | BDV |
| SMCJ10A | SMCJ10CA | 10 | 11.1 | 12.3 | 1 | 17.0 | 88.3 | 5 | GDY | BDY |
| SMCJ11A | SMCJ11CA | 11 | 12.2 | 13.5 | 1 | 18.2 | 82.5 | 1 | GDZ | BDZ |
| SMCJ12A | SMCJ12CA | 12 | 13.3 | 14.7 | 1 | 19.9 | 75.4 | 1 | GEE | BEE |
| SMCJ13A | SMCJ13CA | 13 | 14.4 | 15.9 | 1 | 21.5 | 69.8 | 1 | GEG | BEG |
| SMCJ14A | SMCJ14CA | 14 | 15.6 | 17.2 | 1 | 23.2 | 64.7 | 1 | GEK | BEK |
| SMCJ15A | SMCJ15CA | 15 | 16.7 | 18.5 | 1 | 24.4 | 61.5 | 1 | GEM | BEM |
| SMCJ16A | SMCJ16CA | 16 | 17.8 | 19.7 | 1 | 26.0 | 57.7 | 1 | GEP | BEP |
| SMCJ17A | SMCJ17CA | 17 | 18.9 | 20.9 | 1 | 27.6 | 54.4 | 1 | GER | BER |
| SMCJ18A | SMCJ18CA | 18 | 20.0 | 22.1 | 1 | 29.2 | 51.4 | 1 | GET | BET |
| SMCJ20A | SMCJ20CA | 20 | 22.2 | 24.5 | 1 | 32.4 | 46.3 | 1 | GEV | BEV |
| SMCJ22A | SMCJ22CA | 22 | 24.4 | 26.9 | 1 | 35.5 | 42.3 | 1 | GEX | BEX |
| SMCJ24A | SMCJ24CA | 24 | 26.7 | 29.5 | 1 | 38.9 | 38.6 | 1 | GEZ | BEZ |
| SMCJ26A | SMCJ26CA | 26 | 28.9 | 31.9 | 1 | 42.1 | 35.7 | 1 | GFE | BFE |
| SMCJ28A | SMCJ28CA | 28 | 31.1 | 34.4 | 1 | 45.4 | 33.1 | 1 | GFG | BFG |
| SMCJ30A | SMCJ30CA | 30 | 33.3 | 36.8 | 1 | 48.4 | 31.0 | 1 | GFK | BFK |
| SMCJ33A | SMCJ33CA | 33 | 36.7 | 40.6 | 1 | 53.3 | 28.2 | 1 | GFM | BFM |
| SMCJ36A | SMCJ36CA | 36 | 40.0 | 44.2 | 1 | 58.1 | 25.9 | 1 | GFP | BFP |
| SMCJ40A | SMCJ40CA | 40 | 44.4 | 49.1 | 1 | 64.5 | 23.3 | 1 | GFR | BFR |
| SMCJ43A | SMCJ43CA | 43 | 47.8 | 52.8 | 1 | 69.4 | 21.7 | 1 | GFT | BFT |
| SMCJ45A | SMCJ45CA | 45 | 50.0 | 55.3 | 1 | 72.7 | 20.6 | 1 | GFV | BFV |
| SMCJ48A | SMCJ48CA | 48 | 53.3 | 58.9 | 1 | 77.4 | 19.4 | 1 | GFX | BFX |
| SMCJ51A | SMCJ51CA | 51 | 56.7 | 62.7 | 1 | 82.4 | 18.2 | 1 | GFZ | BFZ |
| SMCJ54A | SMCJ54CA | 54 | 60.0 | 66.3 | 1 | 87.1 | 17.3 | 1 | GGE | BGE |
| SMCJ58A | SMCJ58CA | 58 | 64.4 | 71.2 | 1 | 93.6 | 16.1 | 1 | GGG | BGG |
| SMCJ60A | SMCJ60CA | 60 | 66.7 | 73.7 | 1 | 96.8 | 15.5 | 1 | GGK | BGK |
| SMCJ64A | SMCJ64CA | 64 | 71.1 | 78.6 | 1 | 103.0 | 14.6 | 1 | GGM | BGM |
| SMCJ70A | SMCJ70CA | 70 | 77.8 | 86.0 | 1 | 113.0 | 13.3 | 1 | GGP | BGP |
| SMCJ75A | SMCJ75CA | 75 | 83.3 | 92.1 | 1 | 121.0 | 12.4 | 1 | GGR | BGR |
| SMCJ78A | SMCJ78CA | 78 | 86.7 | 95.8 | 1 | 126.0 | 11.9 | 1 | GGT | BGT |
| SMCJ85A | SMCJ85CA | 85 | 94.4 | 104.0 | 1 | 137.0 | 11.0 | 1 | GGV | BGV |
| SMCJ90A | SMCJ90CA | 90 | 100.0 | 111.0 | 1 | 146.0 | 10.3 | 1 | GGX | BGX |
| SMCJ100A | SMCJ100CA | 100 | 111.0 | 123.0 | 1 | 162.0 | 9.3 | 1 | GGZ | BGZ |
| SMCJ110A | SMCJ110CA | 110 | 122.0 | 135.0 | 1 | 177 | 8.5 | 1 | GHE | BHE |
| SMCJ120A | SMCJ120CA | 120 | 133.0 | 147.0 | 1 | 193 | 7.8 | 1 | GHG | BHG |
| SMCJ130A | SMCJ130CA | 130 | 144.0 | 159.0 | 1 | 209 | 7.2 | 1 | GHK | BHK |
| SMCJ150A | SMCJ150CA | 150 | 167.0 | 185.0 | 1 | 243 | 6.2 | 1 | GHM | BHM |
| SMCJ160A | SMCJ160CA | 160 | 178.0 | 197.0 | 1 | 259 | 5.8 | 1 | GHP | BHP |
| SMCJ170A | SMCJ170CA | 170 | 189.0 | 209.0 | 1 | 275 | 5.5 | 1 | GHR | BHR |
| SMCJ180A | SMCJ180CA | 180 | 201.0 | 222.0 | 1 | 292 | 5.1 | 1 | GHT | BHT |
| SMCJ200A | SMCJ200CA | 200 | 224.0 | 247.0 | 1 | 324 | 4.6 | 1 | GHV | BHV |

For bi-directional type having V_{WM} of 10volts and less, the I_R limit is double. For parts without A, the V_{BR} is $\pm 10\%$

Electrical Characteristics @ 25°C Unless Otherwise Specified

| MCC Part Number | | Reverse Stand-Off Voltage | Breakdown Voltage $V_{BR}(V)$ | | Test Current | Max. Clamping Voltage @ I_{PP} | Peak Pulse Current | Reverse Leakage Current @ V_{WM} | Marking Code | |
|-----------------|-----------|---------------------------|-------------------------------|-------|--------------|----------------------------------|--------------------|------------------------------------|--------------|-----|
| SMCJ220A | SMCJ220CA | 220 | 246.0 | 272.0 | 1 | 356 | 4.2 | 1 | GHX | BHX |
| SMCJ250A | SMCJ250CA | 250 | 279.0 | 309.0 | 1 | 405 | 3.7 | 1 | GHZ | BHZ |
| SMCJ300A | SMCJ300CA | 300 | 335.0 | 371.0 | 1 | 486 | 3.1 | 1 | GJE | BJE |
| SMCJ350A | SMCJ350CA | 350 | 391.0 | 432.0 | 1 | 567 | 2.6 | 1 | GJG | BJG |
| SMCJ400A | SMCJ400CA | 400 | 447.0 | 494.0 | 1 | 648 | 2.3 | 1 | GJK | BJK |
| SMCJ440A | SMCJ440CA | 440 | 492.0 | 543.0 | 1 | 713 | 2.1 | 1 | GJM | BJM |

For bi-directional type having V_{WM} of 10volts and less, the I_R limit is double. For parts without A, the V_{BR} is $\pm 10\%$

Curve Characteristics

Fig. 1 - Peak Pulse Power Rating Curve



Fig. 2 - Typical Junction Capacitance



Fig. 3 - Pulse Waveform




Fig. 4 - Pulse Derating Curve



Ordering Information

| Device | Packing |
|----------------|----------------------|
| Part Number-TP | Tape&Reel:3Kpcs/Reel |

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».



JONHON

«**JONHON**» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А