

## 1533R Multi-Conductor - Category 5e Nonbonded-Pair Cable



For more Information  
please call

1-800-Belden1



### Description:

24 AWG solid bare copper conductors, non-plenum, Polyolefin insulation, overall Beldfoil® shield drain wire, RJ-45 compatible, see color code chart (below), PVC jacket (red, orange, yellow, green, blue or gray).

### Usage (Overall)

**Suitable Applications:** Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Noisy Environments, 100MHz Category 5e

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Pairs	AWG	Stranding	Conductor Material
4	24	Solid	BC - Bare Copper

**Total Number of Conductors:** 8

#### Insulation

##### Insulation Material:

Insulation Material
PO - Polyolefin

#### Outer Shield

##### Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

##### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

#### Outer Jacket

##### Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

##### Outer Jacket Diameter:

Nom. Dia. (in.)
0.260

#### Pair

##### Pair Color Code Chart:

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** -20°C To +75°C

**Bulk Cable Weight:** 30 lbs/1000 ft.

## 1533R Multi-Conductor - Category 5e Nonbonded-Pair Cable

Max. Recommended Pulling Tension:	25 lbs.
Min. Bend Radius/Minor Axis:	1 in.
Min. Bend/Installation:	2.600 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR, UL444
CEC/C(UL) Specification:	CMR
Other Standards:	11801 Category 5
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	568-B.2 Category 5e
Other Specification:	NEMA WC-63.1 Category 5e, UL Verified to Category 5e

#### Flame Test

UL Flame Test:	UL1666 Riser
CSA Flame Test:	FT4

#### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	1533P

### Electrical Characteristics (Overall)

#### Nom. Mutual Capacitance:

Capacitance (pF/ft)  
15

Maximum Capacitance Unbalance (pF/100 m): 330

#### Nominal Velocity of Propagation:

VP (%)  
70

#### Maximum Delay:

Delay (ns/100 m)  
538 @ 100MHz

#### Max. Delay Skew:

Delay Skew (ns/100 m)  
45

#### Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)  
9.38

#### Max. Operating Voltage - UL:

Voltage  
300 V RMS

#### Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)

## 1533R Multi-Conductor - Category 5e Nonbonded-Pair Cable

3

### Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)	Min. SRL (dB)
1	2.0	65.3	62.3	60.3	60.3	20.0	23.0
4	4.1	56.3	53.3	49.2	49.2	23.0	23.0
8	5.8	51.8	48.8	43.0	43.0	24.5	24.5
10	6.5	50.3	47.3	40.8	40.8	25.0	25.0
16	8.2	47.3	44.3	36.0	36.0	25.0	25.0
20	9.3	45.8	42.8	33.5	33.5	25.0	25.0
25	10.4	44.3	41.3	30.9	30.9	24.3	24.3
31.25	11.7	42.9	39.9	28.2	28.2	23.6	23.6
62.5	17.0	38.4	35.4	18.4	18.4	21.5	21.5
100	22.0	35.3	32.3	10.3	10.3	20.1	20.1

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.8	60.8
4	100 ± 15	100 ± 15	51.7	48.7
8	100 ± 15	100 ± 15	45.7	42.7
10	100 ± 15	100 ± 15	43.8	40.8
16	100 ± 15	100 ± 15	39.7	36.7
20	100 ± 15	100 ± 15	37.7	34.7
25	100 ± 15	100 ± 15	35.8	32.8
31.25	100 ± 15	100 ± 15	33.9	30.9
62.5	100 ± 15	100 ± 15	27.8	24.8
100	100 ± 15	100 ± 15	23.8	20.8

### Notes (Overall)

**Notes:** Shield is bonded to jacket inner wall for electrical stability. RJ-45 Compatible. Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1533R F2VA1000	1,000 FT	35.000 LB	GRAY, DEC		CAT5E 4PR F/UTP CMR RIB
1533R F2V1000	1,000 FT	34.000 LB	GRAY, DEC	C	CAT5E 4PR F/UTP CMR REEL
1533R F2V1640	1,640 FT	57.400 LB	GRAY, DEC	C	CAT5E 4PR F/UTP CMR REEL
1533R 002A1000	1,000 FT	35.000 LB	RED	C	CAT5E 4PR F/UTP CMR RIB
1533R 002I1000	1,000 FT	34.000 LB	RED	C	CAT5E 4PR F/UTP CMR REEL
1533R 003A1000	1,000 FT	35.000 LB	ORANGE	C	CAT5E 4PR F/UTP CMR RIB
1533R 003I1000	1,000 FT	34.000 LB	ORANGE	C	CAT5E 4PR F/UTP CMR REEL
1533R 004A1000	1,000 FT	35.000 LB	YELLOW	C	CAT5E 4PR F/UTP CMR RIB
1533R 004I1000	1,000 FT	34.000 LB	YELLOW	C	CAT5E 4PR F/UTP CMR REEL
1533R 005A1000	1,000 FT	35.000 LB	GREEN, DARK	C	CAT5E 4PR F/UTP CMR RIB
1533R 005I1000	1,000 FT	34.000 LB	GREEN, DARK	C	CAT5E 4PR F/UTP CMR REEL
1533R 006A1000	1,000 FT	35.000 LB	BLUE, LIGHT		CAT5E 4PR F/UTP CMR RIB
1533R 006I1000	1,000 FT	34.000 LB	BLUE, LIGHT	C	CAT5E 4PR F/UTP CMR REEL
1533R 010A1000	1,000 FT	35.000 LB	BLACK		CAT5E 4PR F/UTP CMR RIB
1533R 010I1000	1,000 FT	34.000 LB	BLACK	C	CAT5E 4PR F/UTP CMR REEL

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 07-10-2012

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

## 1533R Multi-Conductor - Category 5e Nonbonded-Pair Cable

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А