

# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs

### General Description

The MAX2667/MAX2669 high-gain, low-noise amplifiers (LNAs) are designed for GPS L1, Galileo, and GLONASS applications. Designed in Maxim's advanced SiGe process, the devices achieve a high gain and our lowest noise figure, while maximizing the input-referred 1dB compression point and the 3rd-order intercept point.

The devices operate from a +1.6V to +3.3V single supply. The MAX2667 is optimized for low current. The MAX2669 is optimized for high linearity. The shutdown feature in the device reduces the supply current to be less than 10 $\mu$ A. The devices are available in a very small, lead-free, RoHS-compliant, 0.86mm x 1.26mm x 0.65mm wafer-level package (WLP).

### Applications

Automotive Navigation  
 Location-Enabled Mobile Devices  
 Telematics (Asset Tracking and Management)  
 Personal Navigation Devices (PNDs)  
 Cellular Phones with GPS  
 Notebook PCs/Ultra-Mobile PCs  
 Recreational, Marine Navigation  
 Avionics  
 Watches

### Features


- ◆ **19dB High-Power Gain (MAX2667)**
- ◆ **Ultra-Low Noise Figure: 0.65dB**
- ◆ **Integrated 50 $\Omega$  Output Matching Circuit**
- ◆ **Low 4.1mA Supply Current (MAX2667)**
- ◆ **Wide 1.6V to 3.3V Supply Voltage Range**
- ◆ **Low Bill of Materials: Two Inductors, Three Capacitors, and One Resistor**
- ◆ **Small Footprint: 0.86mm x 1.26mm**
- ◆ **Thin Profile: 0.65mm**
- ◆ **0.4mm-Pitch Wafer-Level Package (WLP)**

### Ordering Information

| PART         | TEMP RANGE     | PIN-PACKAGE |
|--------------|----------------|-------------|
| MAX2667EWT+T | -40°C to +85°C | 6 WLP       |
| MAX2669EWT+T | -40°C to +85°C | 6 WLP       |

+ Denotes a lead(Pb)-free/RoHS-compliant package.  
 T = Tape and reel.

### Typical Application Circuit



For pricing, delivery, and ordering information, please contact Maxim Direct at 1-888-629-4642, or visit Maxim's website at [www.maximintegrated.com](http://www.maximintegrated.com).


# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs

### ABSOLUTE MAXIMUM RATINGS

|  |  |
|--|--|
| VCC to GND_.....-0.3V to +3.6V                               | Maximum Current into RF Input ..... 10mA             |
| RFOUT and BIAS to GND_ ..... -0.3V to (Operating VCC + 0.3V) | Operating Temperature Range ..... -40°C to +85°C     |
| Maximum RF Input Power ..... +5dBm                           | Junction Temperature ..... +150°C                    |
| Continuous Power Dissipation (TA = +70°C)                    | Storage Temperature Range.....-65°C to +160°C        |
| WLP (derates 10.5mW/°C above +70°C) ..... 840mW              | Soldering Temperature (reflow) (Note 1) ..... +260°C |

**Note 1:** Refer to Application Note 1891: *Wafer-level packaging (WLP) and its applications*.



Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

### PACKAGE THERMAL CHARACTERISTICS (Note 2)

Junction-to-Ambient Thermal Resistance ( $\theta_{JA}$ ) ..... 95°C/W

**Note 2:** Package thermal resistances were obtained using the method described in JEDEC specification JESD51-7, using a four-layer board. For detailed information on package thermal considerations, refer to [www.maximintegrated.com/thermal-tutorial](http://www.maximintegrated.com/thermal-tutorial).

### DC ELECTRICAL CHARACTERISTICS

(MAX2667/MAX2669 EV kit. VCC = 1.6V to 3.3V, no RF signals are applied, TA = -40°C to +85°C. Typical values are at VCC = 2.85V and TA = +25°C, unless otherwise noted.) (Note 2)

| PARAMETER                | CONDITIONS                                    |         | MIN | TYP  | MAX  | UNITS   |
|--------------------------|---|---------|-----|------|------|---------|
| Supply Voltage           |   |         | 1.6 | 2.85 | 3.3  | V       |
| Supply Current           | $\overline{\text{SHDN}}$ = high               | MAX2667 | 4.1 |      |      | mA      |
|                          |   | MAX2669 | 7.7 |      |      |         |
|                          | Shutdown mode, $\overline{\text{SHDN}}$ = low |         |     |      | 10   | $\mu$ A |
| Digital Input Logic-High | TA = +25°C                                    |         | 1.2 |      |      | V       |
| Digital Input Logic-Low  | TA = +25°C                                    |         |     |      | 0.45 | V       |

### AC ELECTRICAL CHARACTERISTICS

(MAX2667/MAX2669 EV kit. VCC = 1.6V to 3.3V, fRFIN = 1575.42MHz, TA = -40°C to +85°C. Typical values are at VCC = 2.85V and TA = +25°C, unless otherwise noted.) (Note 2)

| PARAMETER    | CONDITIONS  |         | MIN        | TYP  | MAX  | UNITS |
|--------------|-------------|---------|------------|------|------|-------|
| RF Frequency | L1 band     |         | 1575.42    |      |      | MHz   |
| Power Gain   | VCC = 2.85V | MAX2667 | 15.0       | 19.5 |      | dB    |
|              |             | MAX2669 | 14.6       | 17.7 |      |       |
|              | VCC = 1.6V  | MAX2667 | 14.8       | 19.4 |      | dB    |
|              |             | MAX2669 | 14.3       | 17.6 |      |       |
| Noise Figure |             |         | VCC = 1.8V |      | 0.65 |       |
|              |             |         | VCC = 3.3V |      | 0.65 |       |

# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs

### AC ELECTRICAL CHARACTERISTICS (continued)

(MAX2667/MAX2669 EV kit.  $V_{CC} = 1.6V$  to  $3.3V$ ,  $f_{RFIN} = 1575.42MHz$ ,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ . Typical values are at  $V_{CC} = 2.85V$  and  $T_A = +25^{\circ}C$ , unless otherwise noted.) (Note 2)

| PARAMETER                                   | CONDITIONS |         | MIN | TYP   | MAX | UNITS |
|---|------------|---------|-----|-------|-----|-------|
| In-Band 3rd-Order Input Intercept Point     | (Note 3)   | MAX2667 |     | -3.5  |     | dBm   |
|   |            | MAX2669 |     | +4.5  |     |       |
| Out-of-Band 3rd-Order Input Intercept Point | (Note 4)   | MAX2667 |     | +2.5  |     | dBm   |
|   |            | MAX2669 |     | +8    |     |       |
| Input 1dB Compression Point                 | (Note 5)   | MAX2667 |     | -12.5 |     | dBm   |
|   |            | MAX2669 |     | -10   |     |       |
| Input Return Loss                           |            |         |     | 10    |     | dB    |
| Output Return Loss                          |            |         |     | 15    |     | dB    |
| Reverse Isolation                           |            |         |     | 30    |     | dB    |

**Note 2:** Min and max limits guaranteed by test at  $T_A = +25^{\circ}C$  and guaranteed by design and characterization at  $T_A = -40^{\circ}C$  and  $T_A = +85^{\circ}C$ .

**Note 3:** Measured with the two tones located at 1MHz and 2MHz offset from the center of the GPS band with -30dBm/tone for MAX2667 and -27dBm/tone for MAX2669.

**Note 4:** Measured with input tones at 1713MHz (-25dBm) and 1851MHz (-49dBm).







**Note 5:** Measured with a tone located at 5MHz offset from the center of the GPS band.

# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs

### Typical Operating Characteristics

(MAX2667/MAX2669 EV kit. Typical values are at  $V_{CC} = 2.85V$ ,  $f_{RFIN} = 1575.42MHz$ ,  $T_A = +25^{\circ}C$ , unless otherwise noted.)




# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs


### Typical Operating Characteristics (continued)

(MAX2667/MAX2669 EV kit. Typical values are at  $V_{CC} = 2.85V$ ,  $f_{RFIN} = 1575.42MHz$ ,  $T_A = +25^{\circ}C$ , unless otherwise noted.)


**MAX2667 OUT-OF-BAND IIP3 vs. SUPPLY VOLTAGE AND TEMPERATURE**  
(TONE 1 AT 1713MHz, -25dBm;  
TONE 2 AT 1851MHz, -49dBm)




**MAX2669 OUT-OF-BAND IIP3 vs. SUPPLY VOLTAGE AND TEMPERATURE**  
(TONE 1 AT 1713MHz, -25dBm;  
TONE 2 AT 1851MHz, -49dBm)



**MAX2667 INPUT P1dB COMPRESSION vs. SUPPLY VOLTAGE AND TEMPERATURE**




**MAX2669 INPUT P1dB COMPRESSION vs. SUPPLY VOLTAGE AND TEMPERATURE**



# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs

### Bump Configuration



### Bump Description

| BUMP | NAME       | FUNCTION  |
|------|------------|---|
| A1   | BIAS       | Provides Bias for LNA Input. Connect to B1 (RFIN) through a high-value inductor (100nH), and bypass to ground close to the pin.   |
| A2   | RFOUT/SHDN | RF Output and SHDN Logic Input. RFOUT is internally matched to 50Ω and has an internal DC-blocking capacitor. The SHDN logic requires an external 25kΩ resistor to the logic control. |
| B1   | RFIN       | RF Input. Connect to A1 through bias choke, and connect matching network and DC-blocking capacitor.   |
| B2   | VCC        | Supply Voltage. Bypass to ground with a capacitor close to the IC.  |
| C1   | GNDAC      | Ground of the RF Path. Connect to the 2nd-layer PCB ground plane with a via next to the pin pad.  |
| C2   | GNDDC      | Ground of Bias Circuit. Connect to the 2nd-layer PCB ground plane with a <b>separate</b> via from pin C1. Sharing a ground via with pin C1 might cause stability problems.            |

### Detailed Description

The MAX2667/MAX2669 are LNAs designed for GPS L1, Galileo, and GLONASS applications. The devices feature a power-shutdown control mode to eliminate the need for an external supply switch. The devices achieve a high gain and an ultra-low noise figure.

#### Input and Output Matching

The devices require an off-chip input matching. Only an inductor in series with a DC-blocking capacitor is

needed to form the input matching circuit. The *Typical Application Circuit* shows the recommended input-matching network. These values are optimized for the best simultaneous gain, noise figure, and return loss performance. Tables 1 and 2 list typical device S parameters and K<sub>f</sub> values. The devices integrate an on-chip output matching to 50Ω at the output, eliminating the need for external matching components. The value of the input coupling capacitor affects IIP3. A smaller coupling capacitor results in lower IIP3.

# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs

### Shutdown

The devices include a shutdown feature to turn off the entire chip. A logic-high must be applied to the RFOUT/ (SHDN) pin using a 25k $\Omega$  external resistor to place the part in active mode, and a logic-low to place the part in shutdown mode.

### Applications Information

A properly designed PCB is essential to any RF microwave circuit. Use controlled-impedance lines on all

high-frequency inputs and outputs. Bypass VCC with decoupling capacitors located close to the device. For long VCC lines, it may be necessary to add decoupling capacitors. Locate these additional capacitors further away from the device package. Proper grounding of the GND\_ pins is essential. If the PCB uses a top-side RF ground, connect it directly to the GND\_ pins. For a board where the ground is not on the component layer, connect the GND\_ pins to the board with multiple vias close to the package.

**Table 1. MAX2667 Typical Device S-Parameter Values and K-Factor**

| FREQ. (MHz) | S11 MAG (dB) | S11 PHASE (Degrees) | S21 MAG (dB) | S21 PHASE (Degrees) | S12 MAG (dB) | S12 PHASE (Degrees) | S22 MAG (dB) | S22 PHASE (Degrees) | K <sub>f</sub> |
|-------------|--------------|---------------------|--------------|---------------------|--------------|---------------------|--------------|---------------------|----------------|
| 1000        | -2.0         | -47.7               | 6.0          | -100.0              | -47.5        | -148.0              | -1.0         | -55.0               | 5.1            |
| 1100        | -2.1         | -48.6               | 7.4          | -100.6              | -45.7        | -150.0              | -1.0         | -58.1               | 3.8            |
| 1200        | -2.2         | -51.6               | 9.6          | -107.3              | -42.9        | -153.5              | -1.4         | -65.4               | 3.1            |
| 1300        | -2.4         | -55.0               | 12.0         | -117.2              | -39.6        | -160.2              | -2.1         | -74.1               | 2.5            |
| 1400        | -2.7         | -58.6               | 14.0         | -129.5              | -37.0        | -168.5              | -3.6         | -85.5               | 2.3            |
| 1500        | -6.5         | -61.9               | 16.2         | -146.5              | -34.1        | 178.5               | -7.4         | -100.0              | 2.8            |
| 1575        | -4.3         | -62.3               | 17.1         | -164.2              | -32.9        | 162.8               | -15.3        | -100.8              | 2.1            |
| 1600        | -4.6         | -61.6               | 17.3         | -170.6              | -32.8        | 156.6               | -20.6        | -78.9               | 2.0            |
| 1700        | -5.4         | -55.3               | 17.1         | 165.5               | -32.5        | 136.5               | -9.5         | 10.0                | 1.8            |
| 1800        | -5.2         | -49.8               | 15.7         | 145.8               | -33.8        | 121.6               | -4.5         | -2.4                | 1.6            |
| 1900        | -4.8         | -47.3               | 13.9         | 135.2               | -35.2        | 113.8               | -2.7         | -13.2               | 1.6            |
| 2000        | -4.5         | -46.7               | 12.7         | 127.3               | -36.7        | 109.6               | -1.8         | -21.2               | 1.5            |

**Table 2. MAX2669 Typical Device S-Parameter Values and K-Factor**

| FREQ. (MHz) | S11 MAG (dB) | S11 PHASE (Degrees) | S21 MAG (dB) | S21 PHASE (Degrees) | S12 MAG (dB) | S12 PHASE (Degrees) | S22 MAG (dB) | S22 PHASE (Degrees) | K <sub>f</sub> |
|-------------|--------------|---------------------|--------------|---------------------|--------------|---------------------|--------------|---------------------|----------------|
| 1000        | -3.0         | -57.0               | 10.8         | -120.0              | -43.0        | -154.0              | -1.3         | -65.0               | 3.2            |
| 1100        | -3.3         | -58.2               | 11.6         | -124.5              | -42.1        | -155.0              | -1.6         | -70.2               | 3.3            |
| 1200        | -3.5         | -60.0               | 13.4         | -134.6              | -39.3        | -160.5              | -2.4         | -79.6               | 2.8            |
| 1300        | -3.8         | -62.3               | 14.9         | -148.0              | -37.2        | -168.3              | -4.0         | -90.0               | 2.7            |
| 1400        | -4.3         | -63.3               | 15.9         | -162.3              | -35.4        | -178.2              | -7.3         | -101.0              | 2.7            |
| 1500        | -4.9         | -62.0               | 16.6         | -178.9              | -33.9        | 171.0               | -14.5        | -100.6              | 2.6            |
| 1575        | -5.3         | -59.7               | 16.6         | 168.0               | -33.5        | 161.7               | -19.6        | -26.0               | 2.5            |
| 1600        | -5.4         | -58.5               | 16.5         | 163.9               | -33.6        | 157.5               | -16.7        | -6.0                | 2.5            |
| 1700        | -5.5         | -53.7               | 15.8         | 149.3               | -33.6        | 148.3               | -9.0         | 3.6                 | 2.3            |
| 1800        | -5.3         | -50.3               | 14.7         | 136.8               | -34.2        | 142.5               | -5.7         | -2.8                | 2.2            |
| 1900        | -5.1         | -48.0               | 13.4         | 130.0               | -35.1        | 139.6               | -4.0         | -9.6                | 2.3            |
| 2000        | -4.9         | -46.3               | 12.7         | 123.9               | -35.8        | 138.6               | -3.0         | -15.0               | 2.1            |

# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs

**Table 3. MAX2667 Typical Noise Parameters (VCC = 2.85V, TA = +25°C)**

| FREQUENCY (MHz) | FMIN (dB) | $\Gamma_{OPT}$ | $\Gamma_{OPT}$   ANGLE | RN ( $\Omega$ ) |
|-----------------|-----------|----------------|------------------------|-----------------|
| 1550            | 0.54      | 0.48           | 39.9                   | 8.43            |
| 1560            | 0.55      | 0.48           | 40.2                   | 8.42            |
| 1570            | 0.55      | 0.48           | 40.5                   | 8.41            |
| 1575            | 0.55      | 0.48           | 40.7                   | 8.41            |
| 1580            | 0.55      | 0.48           | 40.9                   | 8.40            |
| 1590            | 0.55      | 0.48           | 41.2                   | 8.39            |
| 1600            | 0.55      | 0.48           | 41.5                   | 8.38            |

**Table 4. MAX2669 Typical Noise Parameters (VCC = 2.85V, TA = +25°C)**

| FREQUENCY (MHz) | FMIN (dB) | $\Gamma_{OPT}$ | $\Gamma_{OPT}$   ANGLE | RN ( $\Omega$ ) |
|-----------------|-----------|----------------|------------------------|-----------------|
| 1550            | 0.57      | 0.29           | 76.1                   | 4.53            |
| 1560            | 0.57      | 0.29           | 76.6                   | 4.53            |
| 1570            | 0.57      | 0.29           | 77.0                   | 4.53            |
| 1575            | 0.57      | 0.29           | 77.3                   | 4.52            |
| 1580            | 0.57      | 0.29           | 77.5                   | 4.52            |
| 1590            | 0.57      | 0.29           | 78.0                   | 4.52            |
| 1600            | 0.57      | 0.29           | 78.5                   | 4.52            |

### Chip Information

PROCESS: SiGe BiCMOS

### Package Information

For the latest package outline information and land patterns (footprints), go to [www.maximintegrated.com/packages](http://www.maximintegrated.com/packages). Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

| PACKAGE TYPE | PACKAGE CODE | OUTLINE NO.             | LAND PATTERN NO.                          |
|--------------|--------------|-------------------------|---|
| 6 WLP        | W61B1+1      | <a href="#">21-0217</a> | Refer to <a href="#">Application 1891</a> |



# MAX2667/MAX2669

## GPS/GNSS Ultra-Low-Noise-Figure LNAs

### Revision History

| REVISION NUMBER | REVISION DATE | DESCRIPTION   | PAGES CHANGED |
|-----------------|---------------|---|---------------|
| 0               | 9/10          | Initial release   | —             |
| 1               | 9/12          | Updated <i>Bump Description</i> , updated <i>Shutdown</i> section | 5, 6          |



Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the Electrical Characteristics table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

**Maxim Integrated 160 Rio Robles, San Jose, CA 95134 USA 1-408-601-1000**

9

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А