

### FEATURES

- ◆ Efficiency up to 83%
- ◆ SMD Package with Industry Standard Pinout
- ◆ Isolation Voltage 1500VDC
- ◆ 2:1 Wide Input Range
- ◆ Low ripple and noise
- ◆ Short Circuit Protection
- ◆ Temperature Performance -40°C to +71°C
- ◆ CSA60950-1 Safety Approval
- ◆ > 1MHours MTBF
- ◆ Lead free, RoHS Compliant
- ◆ 3 Years Product Warranty



The SE03S/D series are miniature, SMD Package, isolated 3W DC/DC converters with 1,500VDC isolation. The SE03S/D series features fully regulated output and ultra wide 2:1 input voltage ranges. It offers short circuit protection and allows a wide operating temperature range of -40°C to +71°C. These isolated DC/DC converters are the latest offering from a world leader in power systems technology and manufacturing — Delta Electronics, Inc.

### Model List

| Model Number | Input Voltage (Range)<br>VDC | Output Voltage<br>VDC | Output Current |            | Input Current          |                      | Reflected Ripple Current<br>mA(typ.) | Max. capacitive Load<br>uF | Efficiency (typ.)<br>@Max. Load<br>% |
|--------------|------------------------------|-----------------------|----------------|------------|------------------------|----------------------|--------------------------------------|----------------------------|--------------------------------------|
|              |                              |                       | Max.<br>mA     | Min.<br>mA | @Max. Load<br>mA(typ.) | @No Load<br>mA(typ.) |                                      |                            |                                      |
|              |                              |                       |                |            |                        |                      |                                      |                            |                                      |
| SE03S1203A   | 12<br>(9 ~ 18)               | 3.3                   | 700            | 70         | 257                    | 20                   | 25                                   | 4700                       | 75                                   |
| SE03S1205A   |                              | 5                     | 600            | 60         | 316                    |                      |                                      |                            | 79                                   |
| SE03S1212A   |                              | 12                    | 250            | 25         | 305                    |                      |                                      |                            | 82                                   |
| SE03S1215A   |                              | 15                    | 200            | 20         | 305                    |                      |                                      |                            | 82                                   |
| SE03D1205A   |                              | ±5                    | ±300           | ±30        | 321                    |                      |                                      | 180*                       | 78                                   |
| SE03D1212A   |                              | ±12                   | ±125           | ±12.5      | 309                    |                      |                                      |                            | 81                                   |
| SE03D1215A   |                              | ±15                   | ±100           | ±10        | 309                    |                      |                                      |                            | 81                                   |
| SE03S2403A   | 24<br>(18 ~ 36)              | 3.3                   | 700            | 70         | 127                    | 5                    | 15                                   | 4700                       | 76                                   |
| SE03S2405A   |                              | 5                     | 600            | 60         | 156                    |                      |                                      |                            | 80                                   |
| SE03S2412A   |                              | 12                    | 250            | 25         | 151                    |                      |                                      |                            | 83                                   |
| SE03S2415A   |                              | 15                    | 200            | 20         | 151                    |                      |                                      |                            | 83                                   |
| SE03D2405A   |                              | ±5                    | ±300           | ±30        | 158                    |                      |                                      | 180*                       | 79                                   |
| SE03D2412A   |                              | ±12                   | ±125           | ±12.5      | 152                    |                      |                                      |                            | 82                                   |
| SE03D2415A   |                              | ±15                   | ±100           | ±10        | 152                    |                      |                                      |                            | 82                                   |
| SE03S4803A   | 48<br>(36 ~ 75)              | 3.3                   | 700            | 70         | 63                     | 3                    | 10                                   | 4700                       | 76                                   |
| SE03S4805A   |                              | 5                     | 600            | 60         | 78                     |                      |                                      |                            | 80                                   |
| SE03S4812A   |                              | 12                    | 250            | 25         | 75                     |                      |                                      |                            | 83                                   |
| SE03S4815A   |                              | 15                    | 200            | 20         | 75                     |                      |                                      |                            | 83                                   |
| SE03D4805A   |                              | ±5                    | ±300           | ±30        | 79                     |                      |                                      | 180*                       | 79                                   |
| SE03D4812A   |                              | ±12                   | ±125           | ±12.5      | 76                     |                      |                                      |                            | 82                                   |
| SE03D4815A   |                              | ±15                   | ±100           | ±10        | 76                     |                      |                                      |                            | 82                                   |

\* For each output

## Input Characteristics

| Parameter                         | Model            | Min.      | Typ. | Max. | Unit |
|-----------------------------------|------------------|-----------|------|------|------|
| Input Surge Voltage (1 sec. max.) | 12V Input Models | -0.7      | ---  | 25   | VDC  |
|                                   | 24V Input Models | -0.7      | ---  | 50   |      |
|                                   | 48V Input Models | -0.7      | ---  | 100  |      |
| Start-Up Voltage                  | 12V Input Models | 4.5       | 6    | 8    |      |
|                                   | 24V Input Models | 8         | 12   | 18   |      |
|                                   | 48V Input Models | 16        | 24   | 36   |      |
| Under Voltage Shutdown            | 12V Input Models | ---       | ---  | 8    |      |
|                                   | 24V Input Models | ---       | ---  | 16   |      |
|                                   | 48V Input Models | ---       | ---  | 32   |      |
| Reverse Polarity Input Current    | All Models       | ---       | ---  | 0.5  | A    |
| Short Circuit Input Power         |                  | ---       | ---  | 1500 | mW   |
| Input Filter                      |                  | Pi Filter |      |      |      |
| Internal Power Dissipation        |                  | ---       | ---  | 2500 | mW   |

## Output Characteristics

| Parameter                    | Conditions                  | Min.       | Typ.  | Max.  | Unit              |
|------------------------------|-----------------------------|------------|-------|-------|-------------------|
| Output Voltage Accuracy      |                             | ---        | ±0.5  | ±1.0  | %                 |
| Output Voltage Balance       | Dual Output, Balanced Loads | ---        | ±0.5  | ±2.0  | %                 |
| Line Regulation              | Vin=Min. to Max.            | ---        | ±0.1  | ±0.3  | %                 |
| Load Regulation              | Io=10% to 100%              | ---        | ±0.3  | ±1.0  | %                 |
| Ripple & Noise (20MHz)       |                             | ---        | 50    | 75    | mV <sub>P-P</sub> |
| Ripple & Noise (20MHz)       | Over Line, Load & Temp.     | ---        | ---   | 100   | mV <sub>P-P</sub> |
| Ripple & Noise (20MHz)       |                             | ---        | ---   | 10    | mV rms            |
| Transient Recovery Time      | 25% Load Step Change        | ---        | 200   | 500   | uS                |
| Transient Response Deviation |                             | ---        | ±2    | ±6    | %                 |
| Temperature Coefficient      |                             | ---        | ±0.01 | ±0.02 | %/°C              |
| Short Circuit Protection     |                             | Continuous |       |       |                   |

## General Characteristics

| Parameter                        | Conditions                        | Min.      | Typ. | Max. | Unit  |
|----------------------------------|-----------------------------------|-----------|------|------|-------|
| I/O Isolation Voltage (rated)    | 60 Seconds                        | 1500      | ---  | ---  | VDC   |
| I/O Isolation Resistance         | 500 VDC                           | 1000      | ---  | ---  | MΩ    |
| I/O Isolation Capacitance        | 100KHz, 1V                        | ---       | 65   | 100  | pF    |
| Switching Frequency              |                                   | ---       | 300  | ---  | KHz   |
| MTBF (calculated)                | MIL-HDBK-217F@25°C, Ground Benign | 1,000,000 | ---  | ---  | Hours |
| Moisture Sensitivity Level (MSL) | IPC/JEDEC J-STD-020D              | Level 2   |      |      |       |


## Recommended Input Fuse

| 12V Input Models     | 24V Input Models     | 48V Input Models     |
|----------------------|----------------------|----------------------|
| 750mA Slow-Blow Type | 350mA Slow-Blow Type | 200mA Slow-Blow Type |

## Environmental Specifications

| Parameter                                     | Conditions          | Min. | Max. | Unit     |
|---|---------------------|------|------|----------|
| Operating Temperature Range (with Derating)   | Ambient             | -40  | +85  | °C       |
| Case Temperature                              |                     | ---  | +90  | °C       |
| Storage Temperature Range                     |                     | -50  | +125 | °C       |
| Humidity (non condensing)                     |                     | ---  | 95   | % rel. H |
| Cooling                                       | Free-Air convection |      |      |          |
| Lead Temperature (1.5mm from case for 10Sec.) |                     | ---  | 260  | °C       |

## Power Derating Curve



## Notes


- 1 Specifications typical at  $T_a = +25^\circ\text{C}$ , resistive load, nominal input voltage and rated output current unless otherwise noted.
- 2 Transient recovery time is measured to within 1% error band for a step change in output load of 75% to 100%.
- 3 Ripple & Noise measurement bandwidth is 0-20MHz.
- 4 These power converters require a minimum output loading to maintain specified regulation, operation under no-load conditions will not damage these modules; however they may not meet all specifications listed.
- 5 All DC/DC converters should be externally fused at the front end for protection.
- 6 Specifications subject to change without notice.
- 7 It is not recommended to use water-washing process on SMT units.

## Mechanical Drawing

### Mechanical Dimensions



### Connecting Pin Patterns



- ▶ All dimensions in mm (inches)
- ▶ Tolerance:  $X.X \pm 0.25$  ( $X.XX \pm 0.01$ )  
 $X.XX \pm 0.13$  ( $X.XXX \pm 0.005$ )
- ▶ Pins  $\pm 0.05$  ( $\pm 0.002$ )

### Pin Connections

| Pin        | Single Output | Dual Output |
|------------|---------------|-------------|
| 1,2        | -Vin          | -Vin        |
| 3,11,14,22 | NC            | NC          |
| 10         | NC            | Common      |
| 12         | NC            | -Vout       |
| 13         | +Vout         | +Vout       |
| 15         | -Vout         | Common      |
| 23,24      | +Vin          | +Vin        |

NC : No Connection

### Physical Characteristics

|               |  |
|---------------|--|
| Case Size     | : 32.3x14.8x10.2mm (1.27x0.58x0.4 Inches)                          |
| Case Material | : Non-Conductive Black Plastic<br>(flammability to UL 94V-0 rated) |
| Weight        | : 8.8g   |



| Part Numbering System |               |       |                   |               |                |                    |
|-----------------------|---------------|-------|-------------------|---------------|----------------|--------------------|
| S                     | E             | 03    | S                 | 12            | 05             | A                  |
| Form factor           | Family series | Watt  | Number of Outputs | Input Voltage | Output Voltage | Option Code        |
| D-DIP                 | A-Z           | 01:1W | S - Single        | 03:3.3V       | 03:3.3V        | A - Std. Functions |
| P-SIP                 |               | 02:2W | D- Dual           | 05: 5V        | 05: 5V         |                    |
| S-SMD                 |               | 03:3W |                   | 12:12V        | 12:12V         |                    |
|                       |               | 04:4W |                   | 24: 24V       | 15: 15V        |                    |
|                       |               | 06:6W |                   | 48:48V        | 24: 24V        |                    |

### WARRANTY

Delta offers a three(3) years limited warranty. Complete warranty information is listed on our web site or is available upon request from Delta.

Information furnished by Delta is believed to be accurate and reliable. However, no responsibility is assumed by Delta for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Delta. Delta reserves the right to revise these specifications at any time, without notice.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А