

## ISL8488E, ISL8489E, ISL8490E, ISL8491E

±15kV ESD Protected, 5V, Low Power, High Speed and Slew Rate Limited, Full Duplex, RS-485/RS-422 Transceivers

FN6073  
Rev.4.00  
July 26, 2007

The ISL8488E, ISL8489E, ISL8490E, ISL8491E devices are ESD protected, BiCMOS, 5V powered, single transceivers that meet both the RS-485 and RS-422 standards for balanced communication. Each driver output and receiver input is protected against ±15kV ESD strikes, without latch-up. Unlike competitive versions, these Intersil devices are specified for 10% tolerance supplies (4.5V to 5.5V).

These devices are configured for full duplex (separate Rx input and Tx output pins) applications, so they are ideal for RS-422 networks requiring high ESD tolerance on the bus pins. The ISL8488E, ISL8490E are 8 Ld versions without Rx and Tx output enables. The other two versions include Rx and Tx output enable pins in a standard 14 Ld pinout.

The ISL8488E, ISL8489E utilize slew rate limited drivers which reduce EMI, and minimize reflections from improperly terminated transmission lines, or unterminated stubs in multidrop and multipoint applications.

Data rates up to 10Mbps are achievable by using the ISL8490E, ISL8491E, which feature higher slew rates.

The devices present a "single unit load" to the RS-485 bus, which allows a total of 32 transmitters and receivers on the network. For "1/8 unit load" versions (256 devices on the bus), please refer to the ISL4489E, ISL4491E data sheet.

Receiver (Rx) inputs feature a "fail-safe if open" design, which ensures a logic high Rx output if Rx inputs are floating.

Driver (Tx) outputs are short circuit protected, even for voltages exceeding the power supply voltage. Additionally, on-chip thermal shutdown circuitry disables the Tx outputs to prevent damage if power dissipation becomes excessive.

### Features

- RS-485 I/O Pin ESD Protection ..... ±15kV HBM
  - Class 3 ESD Level on all Other Pins ..... >7kV HBM
- High Data Rates (ISL8490E, ISL8491E) . . . up to 10Mbps
- Slew Rate Limited for Error Free Data Transmission (ISL8488E, ISL8489E)
- Single Unit Load Allows up to 32 Devices on the Bus (See ISL4489E, ISL4491E for 256 Devices on Bus)
- Low Quiescent Current:
  - 120µA (ISL8488E)
  - 140µA (ISL8489E)
  - 370µA (ISL8490E, ISL8491E)
- -7V to +12V Common Mode Input Voltage Range
- Three-State Rx and Tx Outputs (Except ISL8488E, ISL8490E)
- Full Duplex Pinout
- Operates from a Single +5V Supply (10% Tolerance)
- Current Limiting and Thermal Shutdown for Driver Overload Protection
- Pb-Free Plus Anneal Available (RoHS Compliant)

### Applications


- Factory Automation
- Security Networks
- Building Environmental Control Systems
- Industrial/Process Control Networks
- Level Translators (e.g., RS-232 to RS-422)
- RS-232 "Extension Cords"

TABLE 1. SUMMARY OF FEATURES


| PART NUMBER | HALF/FULL DUPLEX | HIGH ESD? | NO. OF DEVICES ALLOWED ON BUS | DATA RATE (Mbps) | SLEW-RATE LIMITED? | RECEIVER/ DRIVER ENABLE? | QUIESCENT I <sub>CC</sub> (µA) | PIN COUNT |
|-------------|------------------|-----------|-------------------------------|------------------|--------------------|--------------------------|--------------------------------|-----------|
| ISL8488E    | Full             | Yes       | 32                            | 0.25             | Yes                | No                       | 120                            | 8         |
| ISL8489E    | Full             | Yes       | 32                            | 0.25             | Yes                | Yes                      | 140                            | 14        |
| ISL8490E    | Full             | Yes       | 32                            | 10               | No                 | No                       | 370                            | 8         |
| ISL8491E    | Full             | Yes       | 32                            | 10               | No                 | Yes                      | 370                            | 14        |

## Pinouts

ISL8488E, ISL8490E  
(8 LD SOIC)  
TOP VIEW



ISL8489E, ISL8491E  
(14 LD SOIC)  
TOP VIEW



## Ordering Information

| PART NUMBER<br>(Note 1)  | PART MARKING | TEMP. RANGE (°C) | PACKAGE                 | PKG. DWG. # |
|--------------------------|--------------|------------------|-------------------------|-------------|
| ISL8488EIB               | 8488 EIB     | -40 to +85       | 8 Ld SOIC               | M8.15       |
| ISL8488EIBZA<br>(Note 2) | 8488 EIBZ    | -40 to +85       | 8 Ld SOIC<br>(Pb-free)  | M8.15       |
| ISL8489EIB               | ISL8489EIB   | -40 to +85       | 14 Ld SOIC              | M14.15      |
| ISL8489EIBZ<br>(Note 2)  | 8489EIBZ     | -40 to +85       | 14 Ld SOIC<br>(Pb-free) | M14.15      |
| ISL8490EIBZ<br>(Note 2)  | 8490E IBZ    | -40 to +85       | 8 Ld SOIC<br>(Pb-free)  | M8.15       |
| ISL8491EIB               | ISL8491EIB   | -40 to +85       | 14 Ld SOIC              | M14.15      |
| ISL8491EIBZ<br>(Note 2)  | 8491EIBZ     | -40 to +85       | 14 Ld SOIC<br>(Pb-free) | M14.15      |

### NOTES:

1. Add "-T" suffix for tape and reel. Please refer to TB347 for details on reel specifications.
2. Intersil Pb-free plus anneal products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.

## Truth Tables (For ISL8488E, ISL8490E, only the DE = 1 and $\overline{RE}$ = 0 entries are valid)

| TRANSMITTING    |    |    |         |        |
|-----------------|----|----|---------|--------|
| INPUTS          |    |    | OUTPUTS |        |
| $\overline{RE}$ | DE | DI | Z       | Y      |
| X               | 1  | 1  | 0       | 1      |
| X               | 1  | 0  | 1       | 0      |
| X               | 0  | X  | High-Z  | High-Z |


| RECEIVING       |    |              |        |
|-----------------|----|--------------|--------|
| INPUTS          |    |              | OUTPUT |
| $\overline{RE}$ | DE | A-B          | RO     |
| 0               | X  | $\geq +0.2V$ | 1      |
| 0               | X  | $\leq -0.2V$ | 0      |
| 0               | X  | Inputs Open  | 1      |
| 1               | X  | X            | High-Z |

## Pin Descriptions


| PIN             | FUNCTION                                                                                                                                          |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| RO              | Receiver output: If $A > B$ by at least 0.2V, RO is high; If $A < B$ by 0.2V or more, RO is low; RO = High if A and B are unconnected (floating). |
| $\overline{RE}$ | Receiver output enable. RO is enabled when $\overline{RE}$ is low; RO is high impedance when $\overline{RE}$ is high.                             |
| DE              | Driver output enable. The driver outputs, Y and Z, are enabled by bringing DE high. They are high impedance when DE is low.                       |
| DI              | Driver input. A low on DI forces output Y low and output Z high. Similarly, a high on DI forces output Y high and output Z low.                   |
| GND             | Ground connection.                                                                                                                                |
| A               | $\pm 15kV$ HBM ESD Protected, Non-inverting receiver input.                                                                                       |
| B               | $\pm 15kV$ HBM ESD Protected, Inverting receiver input.                                                                                           |
| Y               | $\pm 15kV$ HBM ESD Protected, Non-inverting driver output.                                                                                        |
| Z               | $\pm 15kV$ HBM ESD Protected, Inverting driver output.                                                                                            |
| VCC             | System power supply input (4.5V to 5.5V).                                                                                                         |
| NC              | No Connection.                                                                                                                                    |

## Typical Operating Circuit

ISL8488E, ISL8490E



ISL8489E, ISL8491E



**Absolute Maximum Ratings**

|                        |                              |
|------------------------|------------------------------|
| $V_{CC}$ to GND        | 7V                           |
| Input Voltages         |                              |
| DI, DE, RE             | -0.5V to ( $V_{CC} + 0.5V$ ) |
| Input/Output Voltages  |                              |
| A, B, Y, Z             | -8V to +12.5V                |
| RO                     | -0.5V to ( $V_{CC} + 0.5V$ ) |
| Short Circuit Duration |                              |
| Y, Z                   | Continuous                   |
| ESD Rating             | See Specification Table      |

**Thermal Information**

|                                                                                                                 |                      |
|-----------------------------------------------------------------------------------------------------------------|----------------------|
| Thermal Resistance (Typical)                                                                                    | $\theta_{JA}$ (°C/W) |
| 8 Ld SOIC Package (Note 3)                                                                                      | 170                  |
| 14 Ld SOIC Package (Note 3)                                                                                     | 128                  |
| Maximum Junction Temperature (Plastic Package)                                                                  | +150°C               |
| Maximum Storage Temperature Range                                                                               | -65°C to +150°C      |
| Pb-free reflow profile                                                                                          | see link below       |
| <a href="http://www.intersil.com/pbfree/Pb-FreeReflow.asp">http://www.intersil.com/pbfree/Pb-FreeReflow.asp</a> |                      |

**Operating Conditions**

|                   |                |
|-------------------|----------------|
| Temperature Range | -40°C to +85°C |
|-------------------|----------------|

**CAUTION:** Do not operate at or near the maximum ratings listed for extended periods of time. Exposure to such conditions may adversely impact product reliability and result in failures not covered by warranty.

**NOTE:**

3.  $\theta_{JA}$  is measured with the component mounted on a low effective thermal conductivity test board in free air. See Tech Brief TB379 for details.

**Electrical Specifications** Test Conditions:  $V_{CC} = 4.5V$  to  $5.5V$ ; Unless Otherwise Specified. Typicals are at  $V_{CC} = 5V$ ,  $T_A = +25^\circ C$ , (Note 4).

| PARAMETER                                                                            | SYMBOL          | TEST CONDITIONS                                               | TEMP (°C) | MIN (NOTE 9) | TYP  | MAX (NOTE 9) | UNITS      |
|--------------------------------------------------------------------------------------|-----------------|---------------------------------------------------------------|-----------|--------------|------|--------------|------------|
| <b>DC CHARACTERISTICS</b>                                                            |                 |                                                               |           |              |      |              |            |
| Driver Differential $V_{OUT}$ (no load)                                              | $V_{OD1}$       |                                                               | Full      | -            | -    | $V_{CC}$     | V          |
| Driver Differential $V_{OUT}$ (with load)                                            | $V_{OD2}$       | $R = 50\Omega$ (RS-422) (Figure 1)                            | Full      | 2            | 3    | -            | V          |
|                                                                                      |                 | $R = 27\Omega$ (RS-485) (Figure 1)                            | Full      | 1.5          | 2.3  | 5            | V          |
| Change in Magnitude of Driver Differential $V_{OUT}$ for Complementary Output States | $\Delta V_{OD}$ | $R = 27\Omega$ or $50\Omega$ (Figure 1)                       | Full      | -            | 0.01 | 0.2          | V          |
| Driver Common-Mode $V_{OUT}$                                                         | $V_{OC}$        | $R = 27\Omega$ or $50\Omega$ (Figure 1)                       | Full      | -            | -    | 3            | V          |
| Change in Magnitude of Driver Common-Mode $V_{OUT}$ for Complementary Output States  | $\Delta V_{OC}$ | $R = 27\Omega$ or $50\Omega$ (Figure 1)                       | Full      | -            | 0.01 | 0.2          | V          |
| Logic Input High Voltage                                                             | $V_{IH}$        | DE, DI, $\overline{RE}$                                       | Full      | 2            | -    | -            | V          |
| Logic Input Low Voltage                                                              | $V_{IL}$        | DE, DI, $\overline{RE}$                                       | Full      | 0.8          | -    | -            | V          |
| Logic Input Current                                                                  | $I_{IN1}$       | DI                                                            | Full      | -2           | -    | 2            | $\mu A$    |
|                                                                                      |                 | DE, $\overline{RE}$ (Note 8)                                  | Full      | -40          | -    | 40           | $\mu A$    |
| Input Current (A, B) (Note 7)                                                        | $I_{IN2}$       | DE = 0V, $V_{CC} = 0V$ or 4.5V to 5.5V<br>$V_{IN} = 12V$      | Full      | -            | -    | 1            | mA         |
|                                                                                      |                 | $V_{IN} = -7V$                                                | Full      | -0.8         | -    | -            | mA         |
| Driver Three-State Output Current (Y, Z)                                             | $I_{OZD}$       | DE = 0V, $-7V \leq V_O \leq 12V$ (Note 8)                     | Full      | -100         | -    | 100          | $\mu A$    |
| Receiver Differential Threshold Voltage                                              | $V_{TH}$        | $-7V \leq V_{CM} \leq 12V$                                    | Full      | -0.2         | -    | 0.2          | V          |
| Receiver Input Hysteresis                                                            | $\Delta V_{TH}$ | $V_{CM} = 0V$                                                 | 25        | -            | 70   | -            | mV         |
| Receiver Output High Voltage                                                         | $V_{OH}$        | $I_O = -4mA$ , $V_{ID} = 200mV$                               | Full      | 3.5          | -    | -            | V          |
| Receiver Output Low Voltage                                                          | $V_{OL}$        | $I_O = 4mA$ , $V_{ID} = 200mV$                                | Full      | -            | -    | 0.4          | V          |
| Receiver Three-State Output Current                                                  | $I_{OZR}$       | $\overline{RE} = V_{CC}$ , $0.4V \leq V_O \leq 2.4V$ (Note 8) | Full      | -            | -    | $\pm 1$      | $\mu A$    |
| Receiver Input Resistance                                                            | $R_{IN}$        | $-7V \leq V_{CM} \leq 12V$                                    | Full      | 12           | -    | -            | k $\Omega$ |
| No-Load Supply Current (Note 5)                                                      | $I_{CC}$        | ISL8488E, DI = 0V or $V_{CC}$                                 | Full      | -            | 120  | 140          | $\mu A$    |
|                                                                                      |                 | ISL8489E, DE, DI, $\overline{RE} = 0V$ or $V_{CC}$            | Full      | -            | 140  | 190          | $\mu A$    |
|                                                                                      |                 | ISL8490E/ISL8491E, DE, DI, $\overline{RE} = 0V$ or $V_{CC}$   | Full      | -            | 370  | 460          | $\mu A$    |
| Driver Short-Circuit Current, $V_O =$ High or Low                                    | $I_{OSD1}$      | DE = $V_{CC}$ , $-7V \leq V_Y$ or $V_Z \leq 12V$ (Note 6)     | Full      | 35           | -    | 250          | mA         |

**Electrical Specifications** Test Conditions:  $V_{CC} = 4.5V$  to  $5.5V$ ; Unless Otherwise Specified. Typical values are at  $V_{CC} = 5V$ ,  $T_A = +25^\circ C$ , (Note 4). **(Continued)**

| PARAMETER                                             | SYMBOL             | TEST CONDITIONS                                  | TEMP<br>(°C) | MIN<br>(NOTE 9) | TYP       | MAX<br>(NOTE 9) | UNITS |
|-------------------------------------------------------|--------------------|--------------------------------------------------|--------------|-----------------|-----------|-----------------|-------|
| Receiver Short-Circuit Current                        | $I_{OSR}$          | $0V \leq V_O \leq V_{CC}$                        | Full         | 7               | -         | 85              | mA    |
| <b>SWITCHING CHARACTERISTICS (ISL8488E, ISL8489E)</b> |                    |                                                  |              |                 |           |                 |       |
| Driver Input to Output Delay                          | $t_{PLH}, t_{PHL}$ | $R_{DIFF} = 54\Omega$ , $C_L = 100pF$ (Figure 2) | Full         | 250             | 400       | 2000            | ns    |
| Driver Output Skew                                    | $t_{SKEW}$         | $R_{DIFF} = 54\Omega$ , $C_L = 100pF$ (Figure 2) | Full         | -               | 160       | 800             | ns    |
| Driver Differential Rise or Fall Time                 | $t_R, t_F$         | $R_{DIFF} = 54\Omega$ , $C_L = 100pF$ (Figure 2) | Full         | 250             | 600       | 2000            | ns    |
| Driver Enable to Output High                          | $t_{ZH}$           | $C_L = 100pF$ , $SW = GND$ (Figure 3, Note 8)    | Full         | 250             | 1000      | 2000            | ns    |
| Driver Enable to Output Low                           | $t_{ZL}$           | $C_L = 100pF$ , $SW = V_{CC}$ (Figure 3, Note 8) | Full         | 250             | 860       | 2000            | ns    |
| Driver Disable from Output High                       | $t_{HZ}$           | $C_L = 15pF$ , $SW = GND$ (Figure 3, Note 8)     | Full         | 300             | 660       | 3000            | ns    |
| Driver Disable from Output Low                        | $t_{LZ}$           | $C_L = 15pF$ , $SW = V_{CC}$ (Figure 3, Note 8)  | Full         | 300             | 640       | 3000            | ns    |
| Receiver Input to Output Delay                        | $t_{PLH}, t_{PHL}$ | (Figure 4)                                       | Full         | 250             | 500       | 2000            | ns    |
| Receiver Skew   $t_{PLH} - t_{PHL}$                   | $t_{SKD}$          | (Figure 4)                                       | 25           | -               | 60        | -               | ns    |
| Receiver Enable to Output High                        | $t_{ZH}$           | $C_L = 15pF$ , $SW = GND$ (Figure 5, Note 8)     | Full         | -               | 10        | 50              | ns    |
| Receiver Enable to Output Low                         | $t_{ZL}$           | $C_L = 15pF$ , $SW = V_{CC}$ (Figure 5, Note 8)  | Full         | -               | 10        | 50              | ns    |
| Receiver Disable from Output High                     | $t_{HZ}$           | $C_L = 15pF$ , $SW = GND$ (Figure 5, Note 8)     | Full         | -               | 10        | 50              | ns    |
| Receiver Disable from Output Low                      | $t_{LZ}$           | $C_L = 15pF$ , $SW = V_{CC}$ (Figure 5, Note 8)  | Full         | -               | 10        | 50              | ns    |
| Maximum Data Rate                                     | $f_{MAX}$          |                                                  | Full         | 250             | -         | -               | kbps  |
| <b>SWITCHING CHARACTERISTICS (ISL8490E, ISL8491E)</b> |                    |                                                  |              |                 |           |                 |       |
| Driver Input to Output Delay                          | $t_{PLH}, t_{PHL}$ | $R_{DIFF} = 54\Omega$ , $C_L = 100pF$ (Figure 2) | Full         | 13              | 24        | 50              | ns    |
| Driver Output Skew                                    | $t_{SKEW}$         | $R_{DIFF} = 54\Omega$ , $C_L = 100pF$ (Figure 2) | Full         | -               | 3         | 10              | ns    |
| Driver Differential Rise or Fall Time                 | $t_R, t_F$         | $R_{DIFF} = 54\Omega$ , $C_L = 100pF$ (Figure 2) | Full         | 5               | 12        | 25              | ns    |
| Driver Enable to Output High                          | $t_{ZH}$           | $C_L = 100pF$ , $SW = GND$ (Figure 3, Note 8)    | Full         | -               | 14        | 70              | ns    |
| Driver Enable to Output Low                           | $t_{ZL}$           | $C_L = 100pF$ , $SW = V_{CC}$ (Figure 3, Note 8) | Full         | -               | 14        | 70              | ns    |
| Driver Disable from Output High                       | $t_{HZ}$           | $C_L = 15pF$ , $SW = GND$ (Figure 3, Note 8)     | Full         | -               | 44        | 70              | ns    |
| Driver Disable from Output Low                        | $t_{LZ}$           | $C_L = 15pF$ , $SW = V_{CC}$ (Figure 3, Note 8)  | Full         | -               | 21        | 70              | ns    |
| Receiver Input to Output Delay                        | $t_{PLH}, t_{PHL}$ | (Figure 4)                                       | Full         | 30              | 90        | 150             | ns    |
| Receiver Skew   $t_{PLH} - t_{PHL}$                   | $t_{SKD}$          | (Figure 4)                                       | 25           | -               | 5         | -               | ns    |
| Receiver Enable to Output High                        | $t_{ZH}$           | $C_L = 15pF$ , $SW = GND$ (Figure 5, Note 8)     | Full         | -               | 9         | 50              | ns    |
| Receiver Enable to Output Low                         | $t_{ZL}$           | $C_L = 15pF$ , $SW = V_{CC}$ (Figure 5, Note 8)  | Full         | -               | 9         | 50              | ns    |
| Receiver Disable from Output High                     | $t_{HZ}$           | $C_L = 15pF$ , $SW = GND$ (Figure 5, Note 8)     | Full         | -               | 9         | 50              | ns    |
| Receiver Disable from Output Low                      | $t_{LZ}$           | $C_L = 15pF$ , $SW = V_{CC}$ (Figure 5, Note 8)  | Full         | -               | 9         | 50              | ns    |
| Maximum Data Rate                                     | $f_{MAX}$          |                                                  | Full         | 10              | -         | -               | Mbps  |
| <b>ESD PERFORMANCE</b>                                |                    |                                                  |              |                 |           |                 |       |
| RS-485 Pins (A, B, Y, Z)                              |                    | Human Body Model                                 | 25           | -               | $\pm 15$  | -               | kV    |
| All Other Pins                                        |                    |                                                  | 25           | -               | $> \pm 7$ | -               | kV    |

**NOTES:**

- All currents into device pins are positive; all currents out of device pins are negative. All voltages are referenced to device ground unless otherwise specified.
- Supply current specification is valid for loaded drivers when  $DE = 0V$ .
- Applies to peak current. See "Typical Performance Curves" on page 9 for more information.
- Devices meeting these limits are denoted as "single unit load (1 UL)" transceivers. The RS-485 standard allows up to 32 Unit Loads on the bus.
- Not applicable to the ISL8488E, ISL8490E.
- Parts are 100% tested at  $+25^\circ C$ . Over-temperature limits established by characterization and are not production tested.

Test Circuits and Waveforms




FIGURE 1. DRIVER  $V_{OD}$  AND  $V_{OC}$





FIGURE 2A. TEST CIRCUIT



$$SKEW = |t_{PLH}(Y \text{ or } Z) - t_{PHL}(Z \text{ or } Y)|$$

FIGURE 2B. MEASUREMENT POINTS

FIGURE 2. DRIVER PROPAGATION DELAY AND DIFFERENTIAL TRANSITION TIMES

Test Circuits and Waveforms (Continued)




FIGURE 3A. TEST CIRCUIT




FIGURE 3B. MEASUREMENT POINTS

FIGURE 3. DRIVER ENABLE AND DISABLE TIMES (EXCLUDING ISL8488E, ISL8490E)




FIGURE 4A. TEST CIRCUIT




FIGURE 4B. MEASUREMENT POINTS

FIGURE 4. RECEIVER PROPAGATION DELAY




FIGURE 5A. TEST CIRCUIT




FIGURE 5B. MEASUREMENT POINTS

FIGURE 5. RECEIVER ENABLE AND DISABLE TIMES (EXCLUDING ISL8488E, ISL8490E)

## Application Information

RS-485 and RS-422 are differential (balanced) data transmission standards for use in long haul or noisy environments. RS-422 is a subset of RS-485, so RS-485 transceivers are also RS-422 compliant. RS-422 is a point-to-multipoint (multidrop) standard, which allows only one driver and up to 10 (assuming one unit load devices) receivers on each bus. RS-485 is a true multipoint standard, which allows up to 32 one unit load devices (any combination of drivers and receivers) on each bus. To allow for multipoint operation, the RS-485 specification requires that drivers must handle bus contention without sustaining any damage.

Another important advantage of RS-485 is the extended common mode range (CMR), which specifies that the driver outputs and receiver inputs withstand signals that range from +12V to -7V. RS-422 and RS-485 are intended for runs as long as 4000', so the wide CMR is necessary to handle ground potential differences, as well as voltages induced in the cable by external fields.

### Receiver Features

These devices utilize a differential input receiver for maximum noise immunity and common mode rejection. Input sensitivity is  $\pm 200\text{mV}$ , as required by the RS-422 and RS-485 specifications.

Receiver input resistance surpasses the RS-422 specification of  $4\text{k}\Omega$ , and meets the RS-485 "Unit Load" requirement of  $12\text{k}\Omega$  minimum.

Receiver inputs function with common mode voltages as great as  $\pm 7\text{V}$  outside the power supplies (i.e., +12V and -7V), making them ideal for long networks where induced voltages are a realistic concern.

All the receivers include a "fail-safe if open" function that guarantees a high level receiver output if the receiver inputs are unconnected (floating).

Receivers easily meet the data rate supported by the corresponding driver. ISL8489E/ISL8491E receiver outputs are three-statable via the active low  $\overline{\text{RE}}$  input.

### Driver Features

The RS-485/RS-422 driver is a differential output device that delivers at least 1.5V across a  $54\Omega$  load (RS-485), and at least 2V across a  $100\Omega$  load (RS-422). The drivers feature low propagation delay skew to maximize bit width, and to minimize EMI. ISL8489E/ISL8491E driver outputs are three-statable via the active high DE input.

The ISL8488E/ISL8489E driver outputs are slew rate limited to further reduce EMI, and to minimize reflections in unterminated or improperly terminated networks. Data rates on these slew rate limited versions are a maximum of 250kbps. Outputs of ISL8490E/ISL8491E drivers are not limited, so faster output transition times allow data rates of at least 10Mbps.

## Data Rate, Cables, and Terminations

Twisted pair is the cable of choice for RS-485/RS-422 networks. Twisted pair cables tend to pick up noise and other electromagnetically induced voltages as common mode signals, which are effectively rejected by the differential receivers in these ICs.

RS-485/RS-422 are intended for network lengths up to 4000', but the maximum system data rate decreases as the transmission length increases. Devices operating at 10Mbps are limited to lengths of a few hundred feet, while the 250kbps versions can operate at full data rates with lengths in excess of 1000'.

Proper termination is imperative, when using the 10Mbps devices, to minimize reflections. Short networks using the 250kbps versions need not be terminated, but, terminations are recommended unless power dissipation is an overriding concern. In point-to-point, or point-to-multipoint (single driver on bus) networks, the main cable should be terminated in its characteristic impedance (typically  $120\Omega$ ) at the end farthest from the driver. In multi-receiver applications, stubs connecting receivers to the main cable should be kept as short as possible. Multipoint (multi-driver) systems require that the main cable be terminated in its characteristic impedance at both ends. Stubs connecting a transceiver to the main cable should be kept as short as possible.

### Built-In Driver Overload Protection

As stated previously, the RS-485 specification requires that drivers survive worst case bus contentions undamaged. The ISL84xxE devices meet this requirement via driver output short circuit current limits, and on-chip thermal shutdown circuitry.

The driver output stages incorporate short circuit current limiting circuitry which ensures that the output current never exceeds the RS-485 specification, even at the common mode voltage range extremes. Additionally, these devices utilize a foldback circuit which reduces the short circuit current, and thus the power dissipation, whenever the contending voltage exceeds either supply.

In the event of a major short circuit condition, ISL84xxE devices also include a thermal shutdown feature that disables the drivers whenever the die temperature becomes excessive. This eliminates the power dissipation, allowing the die to cool. The drivers automatically reenables after the die temperature drops about  $15^\circ$ . If the contention persists, the thermal shutdown/reenable cycle repeats until the fault is cleared. Receivers stay operational during thermal shutdown.

## ESD Protection

All pins on these devices include class 3 Human Body Model (HBM) ESD protection structures, but the RS-485 pins (driver outputs and receiver inputs) incorporate advanced structures allowing them to survive ESD events in excess of

$\pm 15\text{kV}$  HBM. The RS-485 pins are particularly vulnerable to ESD damage because they typically connect to an exposed port on the exterior of the finished product. Simply touching the port pins, or connecting a cable, can cause an ESD event that might destroy unprotected ICs. These new ESD structures protect the device whether or not it is powered up,

protect without allowing any latch-up mechanism to activate, and without degrading the RS-485 common mode range of  $-7\text{V}$  to  $+12\text{V}$ . This built-in ESD protection eliminates the need for board level protection structures (e.g., transient suppression diodes), and the associated, undesirable capacitive load they present.

### Typical Performance Curves $V_{CC} = 5\text{V}$ , $T_A = +25^\circ\text{C}$ ; Unless Otherwise Specified.




FIGURE 6. DRIVER OUTPUT CURRENT vs DIFFERENTIAL OUTPUT VOLTAGE




FIGURE 7. DRIVER DIFFERENTIAL OUTPUT VOLTAGE vs TEMPERATURE




FIGURE 8. DRIVER OUTPUT CURRENT vs SHORT CIRCUIT VOLTAGE




FIGURE 9. SUPPLY CURRENT vs TEMPERATURE

# **Typical Performance Curves** $V_{CC} = 5V$ , $T_A = +25^\circ C$ ; Unless Otherwise Specified.




FIGURE 10. DRIVER PROPAGATION DELAY vs TEMPERATURE (ISL8488E/ISL8489E)




FIGURE 11. DRIVER SKEW vs TEMPERATURE (ISL8488E/ISL8489E)




FIGURE 12. DRIVER PROPAGATION DELAY vs TEMPERATURE (ISL8490E/ISL8491E)




FIGURE 13. DRIVER SKEW vs TEMPERATURE (ISL8490E/ISL8491E)




FIGURE 14. DRIVER AND RECEIVER WAVEFORMS, LOW TO HIGH (ISL8488E/ISL8489E)




FIGURE 15. DRIVER AND RECEIVER WAVEFORMS, HIGH TO LOW (ISL8488E/ISL8489E)

## Typical Performance Curves $V_{CC} = 5V$ , $T_A = +25^\circ C$ ; Unless Otherwise Specified.




FIGURE 16. DRIVER AND RECEIVER WAVEFORMS, LOW TO HIGH (ISL8490E/ISL8491E)




FIGURE 17. DRIVER AND RECEIVER WAVEFORMS, HIGH TO LOW (ISL8490E/ISL8491E)

## Die Characteristics

SUBSTRATE POTENTIAL (POWERED UP):


GND

TRANSISTOR COUNT:

518

PROCESS:

Si Gate BiCMOS

**Small Outline Plastic Packages (SOIC)****NOTES:**


1. Symbols are defined in the "MO Series Symbol List" in Section 2.2 of Publication Number 95.
2. Dimensioning and tolerancing per ANSI Y14.5M-1982.
3. Dimension "D" does not include mold flash, protrusions or gate burrs. Mold flash, protrusion and gate burrs shall not exceed 0.15mm (0.006 inch) per side.
4. Dimension "E" does not include interlead flash or protrusions. Interlead flash and protrusions shall not exceed 0.25mm (0.010 inch) per side.
5. The chamfer on the body is optional. If it is not present, a visual index feature must be located within the crosshatched area.
6. "L" is the length of terminal for soldering to a substrate.
7. "N" is the number of terminal positions.
8. Terminal numbers are shown for reference only.
9. The lead width "B", as measured 0.36mm (0.014 inch) or greater above the seating plane, shall not exceed a maximum value of 0.61mm (0.024 inch).
10. Controlling dimension: MILLIMETER. Converted inch dimensions are not necessarily exact.

**M8.15 (JEDEC MS-012-AA ISSUE C)****8 LEAD NARROW BODY SMALL OUTLINE PLASTIC PACKAGE**

| SYMBOL | INCHES    |        | MILLIMETERS |      | NOTES |
|--------|-----------|--------|-------------|------|-------|
|        | MIN       | MAX    | MIN         | MAX  |       |
| A      | 0.0532    | 0.0688 | 1.35        | 1.75 | -     |
| A1     | 0.0040    | 0.0098 | 0.10        | 0.25 | -     |
| B      | 0.013     | 0.020  | 0.33        | 0.51 | 9     |
| C      | 0.0075    | 0.0098 | 0.19        | 0.25 | -     |
| D      | 0.1890    | 0.1968 | 4.80        | 5.00 | 3     |
| E      | 0.1497    | 0.1574 | 3.80        | 4.00 | 4     |
| e      | 0.050 BSC |        | 1.27 BSC    |      | -     |
| H      | 0.2284    | 0.2440 | 5.80        | 6.20 | -     |
| h      | 0.0099    | 0.0196 | 0.25        | 0.50 | 5     |
| L      | 0.016     | 0.050  | 0.40        | 1.27 | 6     |
| N      | 8         |        | 8           |      | 7     |
| α      | 0°        | 8°     | 0°          | 8°   | -     |

Rev. 1 6/05

## Small Outline Plastic Packages (SOIC)



### NOTES:

1. Symbols are defined in the "MO Series Symbol List" in Section 2.2 of Publication Number 95.
2. Dimensioning and tolerancing per ANSI Y14.5M-1982.
3. Dimension "D" does not include mold flash, protrusions or gate burrs. Mold flash, protrusion and gate burrs shall not exceed 0.15mm (0.006 inch) per side.
4. Dimension "E" does not include interlead flash or protrusions. Interlead flash and protrusions shall not exceed 0.25mm (0.010 inch) per side.
5. The chamfer on the body is optional. If it is not present, a visual index feature must be located within the crosshatched area.
6. "L" is the length of terminal for soldering to a substrate.
7. "N" is the number of terminal positions.
8. Terminal numbers are shown for reference only.
9. The lead width "B", as measured 0.36mm (0.014 inch) or greater above the seating plane, shall not exceed a maximum value of 0.61mm (0.024 inch).
10. Controlling dimension: MILLIMETER. Converted inch dimensions are not necessarily exact.

### M14.15 (JEDEC MS-012-AB ISSUE C) 14 LEAD NARROW BODY SMALL OUTLINE PLASTIC PACKAGE

| SYMBOL   | INCHES    |        | MILLIMETERS |      | NOTES |
|----------|-----------|--------|-------------|------|-------|
|          | MIN       | MAX    | MIN         | MAX  |       |
| A        | 0.0532    | 0.0688 | 1.35        | 1.75 | -     |
| A1       | 0.0040    | 0.0098 | 0.10        | 0.25 | -     |
| B        | 0.013     | 0.020  | 0.33        | 0.51 | 9     |
| C        | 0.0075    | 0.0098 | 0.19        | 0.25 | -     |
| D        | 0.3367    | 0.3444 | 8.55        | 8.75 | 3     |
| E        | 0.1497    | 0.1574 | 3.80        | 4.00 | 4     |
| e        | 0.050 BSC |        | 1.27 BSC    |      | -     |
| H        | 0.2284    | 0.2440 | 5.80        | 6.20 | -     |
| h        | 0.0099    | 0.0196 | 0.25        | 0.50 | 5     |
| L        | 0.016     | 0.050  | 0.40        | 1.27 | 6     |
| N        | 14        |        | 14          |      | 7     |
| $\alpha$ | 0°        | 8°     | 0°          | 8°   | -     |

Rev. 0 12/93

© Copyright Intersil Americas LLC 2004-2007. All Rights Reserved.  
All trademarks and registered trademarks are the property of their respective owners.

For additional products, see [www.intersil.com/en/products.html](http://www.intersil.com/en/products.html)

Intersil products are manufactured, assembled and tested utilizing ISO9001 quality systems as noted in the quality certifications found at [www.intersil.com/en/support/qualandreliability.html](http://www.intersil.com/en/support/qualandreliability.html)

Intersil products are sold by description only. Intersil may modify the circuit design and/or specifications of products at any time without notice, provided that such modification does not, in Intersil's sole judgment, affect the form, fit or function of the product. Accordingly, the reader is cautioned to verify that datasheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А