

# FLIR Exx-Series™

## Advanced Thermal Imaging Cameras for Electrical and Mechanical Applications



reddot award 2017  
best of the best

FLIR E75, E85, and E95 cameras offer the superior resolution and range performance needed to quickly identify hot spots and discover potential points of failure in electrical distribution and mechanical systems. With up to 161,472 pixel resolution and a larger, more vibrant LCD screen than any other pistol-grip thermal camera, the Exx-Series makes it easier than ever to diagnose problems – even at a distance. Avoid costly shutdowns and lost production time through regular predictive maintenance routines with these rugged, intuitive cameras.

### Improve Plant Reliability

*Equipment failures are costly and can impact on-time delivery, so it's important to have the right tools to find potential problems before they happen.*

- High-resolution infrared detectors, up to 464 x 348, for crisp, detailed images
- Wide temperature ranges: -40°C to 120°C, 0°C to 650°C, 300°C up to 1500°C (E95)
- Superior spot-size performance for accurate temperature measurements on smaller, more distant targets
- Laser-assisted autofocus for precise identification of hot spots, even in cluttered scenes

### Increase Plant Safety

*The Exx-Series improves plant safety by helping you diagnose and report electrical problems before they result in fire or damage.*

- Detect temperature differences down to 30 mK for immediate identification of failing components
- Interchangeable lenses, from wide angle to telephoto, offer complete coverage of near and far targets
- Lenses auto-calibrate with camera for the most precise temperature readings
- MSX® image enhancement adds the depth and detail to image

### Designed to Make Your Work Easier

*FLIR designed the E75, E85, and E95 to make your work faster, safer, and more efficient.*

- Rapid-response touch screen with intuitive new user interface
- Convenient menu buttons allow for one-handed operation
- New folder and naming structure that makes finding images easier
- Connect over Wi-Fi to mobile devices or via METERLiNK® to FLIR clamps and multimeters

### Key Features:

- 320 x 240 – 464 x 348 true native resolution
- Laser-assisted autofocus
- Wide temperature ranges, up to 1500°C
- Vibrant, 4" optically-bonded PCAP touchscreen with 160° viewing angle
- Wi-Fi, METERLiNK® connectivity
- Streamlined reporting features
- FLIR's industry-leading 2-5-10 warranty



Find problems quickly and eliminate costly plant shutdowns



Streamlined data collection and sharing speeds analysis and repairs



One-handed operation with convenient buttons helps maintain workplace safety

## Specifications

Features By Camera	E75	E85	E95
IR Resolution	320 x 240	384 x 288	464 x 348
Object Temperature Range	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) Optional 300°C to 1000°C (572°F to 1830°F)	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) 300°C to 1200°C (572°F to 2192°F)	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1200°F) 300°C to 1500°C (572°F to 2732°F)
Time-lapse (Infrared)	No	No	10 sec to 24 hours
Measurement Features by Camera			
Area Measurement Information	No	Yes	Yes
Spotmeter	1 in live mode	3 in live mode	3 in live mode
Area	No	3 in live mode	3 in live mode
Common Features		Exx-Series	
Detector Type and Pitch	Uncooled microbolometer, 17 µm		
Thermal Sensitivity/NETD	< 0.03°C @ 30°C (86°F)		
Spectral Range	7.5 - 14.0 µm		
Image Frequency	30 Hz		
Field of View (FOV)	24° x 18° (17 mm lens), 42° x 32° (10 mm lens), 14° x 10° (29 mm lens)		
F-Number	f/1.3, f/1.1		
Lens Identification	Automatic		
Focus	Continuous, one-shot laser distance meter (LDM), one-shot contrast, manual		
Digital Zoom	1-4x continuous		
Image Presentation and Modes			
Display	4", 640 x 480 optically-bonded PCAP touchscreen, with 400 cd/m <sup>2</sup> surface brightness		
Digital Camera	5 MP, 53° x 41° FOV		
Color Palettes	Iron, Gray, Rainbow, Arctic, Lava, Rainbow HC		
Image Modes	Infrared, visual, MSX®, Picture-in-Picture		
Picture-in-Picture	Resizable and movable		
MSX®	Embosses visual details on full resolution thermal image		
UltraMax™	Super-resolution process quadruples pixel count, activated in FLIR Tools+		
Measurement and Analysis			
Accuracy	±2°C (±3.6°F) or ±2% of reading for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)		
Alarms	Moisture alarm, insulation alarm, measurement alarms		
Color Alarm (Isotherm)	Above/below/interval/condensation/insulation		
Laser Distance Measurement	Yes, on-screen		
Measurement Presets	No measurement, center spot, hot spot, cold spot, User Preset 1, User Preset 2		
Compass, GPS	Yes; automatic GPS image tagging		
METERLiNK®	Yes; several readings		
Image Storage			
Storage Media	Removable SD card (8 GB)		
Image File Format	Standard radiometric JPEG, measurement data included		
Video Recording and Streaming			
Radiometric IR Video Recording	Real-time radiometric recording (.csq)		
Non-Radiometric IR or Visual Video	H.264 to memory card		
Radiometric IR Video Streaming	Yes, over UVC or Wi-Fi		
Non-Radiometric IR Video Streaming	H.264 or MPEG-4 over Wi-Fi MJPEG over UVC or Wi-Fi		
Communication Interfaces	USB 2.0, Bluetooth, Wi-Fi		
Video Out	DisplayPort over USB Type-C		
Additional Data			
Battery Type	Li-ion battery, charged in camera or on separate charger		
Battery Operating Time	Approx. 2.5 hours at 25°C (77°F) ambient temperature and typical use		
Operating Temperature Range	-15°C to 50°C (5°F to 122°F)		
Storage Temperature Range	-40°C to 70°C (-40°F to 158°F)		
Shock/Vibration/Encapsulation; Safety	25 g / IEC 60068-2-27, 2 g / IEC 60068-2-6, IP 54 / IEC 60529; EN/UL/CSA/PSE 60950-1		
Weight/Dimensions w/o Lens	1 kg (2.2 lbs), 27.8 x 11.6 x 11.3 cm (11.0 x 4.6 x 4.4 in)		
Box Contents			
Packaging	Infrared camera with lens, battery (2 ea), battery charger with power supply, front lens and light protection, straps (hand and wrist), lanyards, lens caps (front and rear), lens cleaning cloth, 15 W3 A power supply, printed documentation, 8 GB SD card, Torx screwdriver, cables (USB 2.0 A to USB Type-C, USB Type-C to HDMI, USB Type-C to USB Type-C)		

**PORTLAND**  
Corporate Headquarters  
FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
PH: +1 866.477.3687

**NASHUA**  
FLIR Systems, Inc.  
9 Townsend West  
Nashua, NH 03063  
PH: +1 866.477.3687

**CANADA**  
FLIR Systems, Ltd.  
920 Sheldon Court  
Burlington, ON L7L 5K6  
Canada  
PH: +1 800.613.0507

**LATIN AMERICA**  
FLIR Systems Brasil  
Av. Antonio Bardella,  
320 Sorocaba,  
SP 18085-852  
Brasil  
PH: +55 15 3238 7080

**CHINA**  
FLIR Systems Co., Ltd  
Rm 1613-16, Tower II  
Grand Central Plaza 1  
38 Shatin Rural  
Committee Rd.  
Shatin, New Territories  
Hong Kong  
PH: +852 2792 8955

**BELGIUM**  
FLIR Systems  
Luxemburgstraat 2  
2321 Meer  
Belgium  
PH: +32 (0) 3665 5100

**UNITED KINGDOM**  
FLIR Systems UK  
2 Kings Hill Ave., Kings Hill  
West Malling, Kent  
ME19 4AQ  
United Kingdom  
PH +44 (0)1732 220 011  
www.flir.com  
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. [01/17] 16-1455

Specifications are subject to change without notice.

For the most up-to-date specs, go to [www.support.flir.com](http://www.support.flir.com)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А