

### Standard Recovery Diodes, Generation 2 DO-5 (Stud Version), 80 A

80PF(R)...



DO-203AB (DO-5)

80PF(R)...W



DO-203AB (DO-5)

#### FEATURES

- High surge current capability
- Designed for a wide range of applications
- Stud cathode and stud anode version
- Wire version available
- Low thermal resistance
- UL approval pending
- Compliant to RoHS directive 2002/95/EC
- Designed and qualified for multiple level



**RoHS**  
COMPLIANT

#### TYPICAL APPLICATIONS

- Battery chargers
- Converters
- Power supplies
- Machine tool controls
- Welding

#### PRODUCT SUMMARY

|             |      |
|-------------|------|
| $I_{F(AV)}$ | 80 A |
|-------------|------|

#### MAJOR RATINGS AND CHARACTERISTICS

| PARAMETER    | TEST CONDITIONS | VALUES      | UNITS            |
|--------------|-----------------|-------------|------------------|
| $I_{F(AV)}$  |                 | 80          | A                |
|              | $T_C$           | 140         | °C               |
| $I_{F(RMS)}$ |                 | 126         | A                |
| $I_{FSM}$    | 50 Hz           | 1500        | A                |
|              | 60 Hz           | 1570        |                  |
| $I^2t$       | 50 Hz           | 11 250      | A <sup>2</sup> s |
|              | 60 Hz           | 10 230      |                  |
| $V_{RRM}$    | Range           | 400 to 1200 | V                |
| $T_J$        |                 | - 55 to 180 | °C               |

#### ELECTRICAL SPECIFICATIONS

##### VOLTAGE RATINGS

| TYPE NUMBER   | VOLTAGE CODE | $V_{RRM}$ , MAXIMUM REPETITIVE<br>PEAK REVERSE VOLTAGE<br>V | $V_{RSM}$ , MAXIMUM NON-REPETITIVE<br>PEAK REVERSE VOLTAGE<br>V | $I_{RRM}$ MAXIMUM<br>AT $T_J = 150$ °C<br>mA |
|---------------|--------------|-------------------------------------------------------------|-----------------------------------------------------------------|----------------------------------------------|
| 80PF(R)...(W) | 40           | 400                                                         | 500                                                             | 9                                            |
|               | 80           | 800                                                         | 960                                                             |                                              |
|               | 120          | 1200                                                        | 1440                                                            |                                              |

| FORWARD CONDUCTION                                            |                     |                                                                                                          |                        |                                                       |         |                   |
|---------------------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------|------------------------|-------------------------------------------------------|---------|-------------------|
| PARAMETER                                                     | SYMBOL              | TEST CONDITIONS                                                                                          |                        |                                                       | VALUES  | UNITS             |
| Maximum average forward current at case temperature           | I <sub>F(AV)</sub>  | 180° conduction, half sine wave                                                                          |                        |                                                       | 80      | A                 |
|                                                               |                     |                                                                                                          |                        |                                                       | 140     | °C                |
| Maximum RMS forward current                                   | I <sub>F(RMS)</sub> |                                                                                                          |                        |                                                       | 126     | A                 |
| Maximum peak, one-cycle forward, non-repetitive surge current | I <sub>FSM</sub>    | t = 10 ms                                                                                                | No voltage reappplied  | Sinusoidal half wave, initial T <sub>J</sub> = 150 °C | 1500    | A                 |
|                                                               |                     | t = 8.3 ms                                                                                               |                        |                                                       | 1570    |                   |
|                                                               |                     | t = 10 ms                                                                                                | 100 % V <sub>RRM</sub> |                                                       | 1260    |                   |
|                                                               |                     | t = 8.3 ms                                                                                               | reappplied             |                                                       | 1320    |                   |
| Maximum I <sup>2</sup> t for fusing                           | I <sup>2</sup> t    | t = 10 ms                                                                                                | No voltage reappplied  |                                                       | 11 250  | A <sup>2</sup> s  |
|                                                               |                     | t = 8.3 ms                                                                                               |                        |                                                       | 10 230  |                   |
|                                                               |                     | t = 10 ms                                                                                                | 100 % V <sub>RRM</sub> |                                                       | 7950    |                   |
|                                                               |                     | t = 8.3 ms                                                                                               | reappplied             |                                                       | 7200    |                   |
| Maximum I <sup>2</sup> √t for fusing                          | I <sup>2</sup> √t   | t = 0.1 ms to 10 ms, no voltage reappplied                                                               |                        |                                                       | 112 500 | A <sup>2</sup> √s |
| Low level value of threshold voltage                          | V <sub>F(TO)</sub>  | (16.7 % x π x I <sub>F(AV)</sub> < I < π x I <sub>F(AV)</sub> ), T <sub>J</sub> = T <sub>J</sub> maximum |                        |                                                       | 0.73    | V                 |
| Low level value of forward slope resistance                   | r <sub>f</sub>      | (16.7 % x π x I <sub>F(AV)</sub> < I < π x I <sub>F(AV)</sub> ), T <sub>J</sub> = T <sub>J</sub> maximum |                        |                                                       | 3.0     | mΩ                |
| Maximum forward voltage drop                                  | V <sub>FM</sub>     | I <sub>pk</sub> = 220 A, T <sub>J</sub> = 25 °C, t <sub>p</sub> = 400 μs rectangular wave                |                        |                                                       | 1.40    | V                 |

| THERMAL AND MECHANICAL SPECIFICATIONS                    |                                   |                                                             |                 |                     |
|----------------------------------------------------------|-----------------------------------|-------------------------------------------------------------|-----------------|---------------------|
| PARAMETER                                                | SYMBOL                            | TEST CONDITIONS                                             | VALUES          | UNITS               |
| Maximum junction operating and storage temperature range | T <sub>J</sub> , T <sub>Stg</sub> |                                                             | - 55 to 180     | °C                  |
| Maximum thermal resistance, junction to case             | R <sub>thJC</sub>                 | DC operation                                                | 0.30            | K/W                 |
| Maximum thermal resistance, case to heatsink             | R <sub>thCS</sub>                 | Mounting surface, smooth, flat and greased                  | 0.25            |                     |
| Maximum allowable mounting torque (+ 0 %, - 10 %)        |                                   | Not lubricated thread, tightening on nut <sup>(1)</sup>     | 3.4<br>(30)     | N · m<br>(lbf · in) |
|                                                          |                                   | Lubricated thread, tightening on nut <sup>(1)</sup>         | 2.3<br>(20)     |                     |
|                                                          |                                   | Not lubricated thread, tightening on hexagon <sup>(2)</sup> | 4.2<br>(37)     |                     |
|                                                          |                                   | Lubricated thread, tightening on hexagon <sup>(2)</sup>     | 3.2<br>(28)     |                     |
| Approximate weight                                       |                                   |                                                             | 15.8            | g                   |
|                                                          |                                   |                                                             | 0.56            | oz.                 |
| Case style                                               |                                   | See dimensions - link at the end of datasheet               | DO-203AB (DO-5) |                     |

**Notes**

(1) Recommended for pass-through holes

(2) Torque must be applicable only to hexagon and not to plastic structure, recommended for holed heatsink



## 80PF(R)...(W) Series

Standard Recovery Diodes,  
Generation 2 DO-5 (Stud Version), 80 A

Vishay High Power Products

| $\Delta R_{thJC}$ CONDUCTION |                       |                        |                               |       |
|------------------------------|-----------------------|------------------------|-------------------------------|-------|
| CONDUCTION ANGLE             | SINUSOIDAL CONDUCTION | RECTANGULAR CONDUCTION | TEST CONDITIONS               | UNITS |
| 180°                         | 0.14                  | 0.10                   | $T_J = T_{J \text{ maximum}}$ | K/W   |
| 120°                         | 0.16                  | 0.17                   |                               |       |
| 90°                          | 0.21                  | 0.22                   |                               |       |
| 60°                          | 0.30                  | 0.31                   |                               |       |
| 30°                          | 0.50                  | 0.50                   |                               |       |

### Note

- The table above shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Forward Power Loss Characteristics

# 80PF(R)...(W) Series

Vishay High Power Products

Standard Recovery Diodes,  
Generation 2 DO-5 (Stud Version), 80 A




Fig. 4 - Forward Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristics



## ORDERING INFORMATION TABLE

|             |    |    |   |     |   |
|-------------|----|----|---|-----|---|
| Device code | 80 | PF | R | 120 | W |
|             | 1  | 2  | 3 | 4   | 5 |

- |   |   |                                                                                                                                                                                                                                               |
|---|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | - | <ul style="list-style-type: none"><li>• 80 = Standard device</li><li>• 82 = Isolated lead on standard terminal<br/>with silicone sleeve available for 1200 V only<br/>(red = Reverse polarity)<br/>(blue = Normal polarity)</li></ul>         |
| 2 | - | PF = Plastic package                                                                                                                                                                                                                          |
| 3 | - | <ul style="list-style-type: none"><li>• None = Stud normal polarity (cathode to stud)</li><li>• R = Stud reverse polarity (anode to stud)</li></ul>                                                                                           |
| 4 | - | Voltage code x 10 = $V_{RRM}$ (see Voltage Ratings table)                                                                                                                                                                                     |
| 5 | - | <ul style="list-style-type: none"><li>• None = Standard terminal<br/>(see dimensions for 80PF(R)... - link at the end of datasheet)</li><li>• W = Wire terminal<br/>(see dimensions for 80PF(R)...W - link at the end of datasheet)</li></ul> |

| LINKS TO RELATED DOCUMENTS |                                                                        |
|----------------------------|------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?95345">www.vishay.com/doc?95345</a> |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А