



Is Now Part of



**ON Semiconductor®**

To learn more about ON Semiconductor, please visit our website at  
[www.onsemi.com](http://www.onsemi.com)

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.



## FCH072N60F\_F085

### N-Channel SuperFET II FRFET MOSFET

600 V, 52 A, 72 mΩ


November  
2014

#### Features

- Typical  $R_{DS(on)} = 62 \text{ mΩ}$  at  $V_{GS} = 10 \text{ V}$ ,  $I_D = 26 \text{ A}$
- Typical  $Q_{G(\text{tot})} = 160 \text{ nC}$  at  $V_{GS} = 10 \text{ V}$ ,  $I_D = 26 \text{ A}$
- UIS Capability
- Qualified to AEC Q101
- RoHS Compliant

#### Description

SuperFET® II MOSFET is Fairchild Semiconductor's brand-new high voltage super-junction (SJ) MOSFET family that is utilizing charge balance technology for outstanding low on-resistance and lower gate charge performance. This technology is tailored to minimize conduction loss, provide superior switching performance, dv/dt rate and higher avalanche energy. Consequently SuperFETII is very well suited for the Soft switching and Hard Switching topologies like High Voltage Full Bridge and Half Bridge DC-DC, Interleaved Boost PFC, Boost PFC for HEV-EV automotive. SuperFET II FRFET® MOSFET's optimized body diode reverse recovery performance can remove additional component and improve system reliability.



For current package drawing, please refer to the Fairchild website at <https://www.fairchildsemi.com/package-drawings/TO/TO247A03.pdf>

#### Application

- Automotive On Board Charger
- Automotive DC/DC converter for HEV



#### Maximum Ratings $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol          | Parameter   | Ratings                   | Units                      |
|-----------------|---|---------------------------|----------------------------|
| $V_{DSS}$       | Drain to Source Voltage                                 | 600                       | V                          |
| $V_{GS}$        | Gate to Source Voltage                                  | $\pm 20$                  | V                          |
| $I_D$           | Drain Current - Continuous ( $V_{GS}=10$ ) (Note 1)     | $T_C = 25^\circ\text{C}$  | 52                         |
|                 |   | $T_C = 100^\circ\text{C}$ | 33                         |
| $E_{AS}$        | Single Pulse Avalanche Rating (Note 2)                  | See Fig 4                 | A                          |
|                 |   | 1128                      | mJ                         |
| $dv/dt$         | MOSFET $dv/dt$  | 100                       | V/ns                       |
|                 | Peak Diode Recovery $dv/dt$ (Note 3)                    | 50                        |                            |
| $P_D$           | Power Dissipation                                       | 481                       | W                          |
|                 | Derate Above $25^\circ\text{C}$                         | 3.85                      | $W/\text{ }^\circ\text{C}$ |
| $T_J, T_{STG}$  | Operating and Storage Temperature                       | -55 to + 150              | $^\circ\text{C}$           |
| $R_{\theta JC}$ | Maximum Thermal Resistance Junction to Case             | 0.26                      | $^\circ\text{C}/\text{W}$  |
| $R_{\theta JA}$ | Maximum Thermal Resistance Junction to Ambient (Note 4) | 40                        | $^\circ\text{C}/\text{W}$  |

#### Package Marking and Ordering Information

| Device Marking | Device          | Package | Reel Size | Tape Width | Quantity |
|----------------|-----------------|---------|-----------|------------|----------|
| FCH072N60F     | FCH072N60F_F085 | TO-247  | -         | -          | 30       |

##### Notes:

- 1: Current is limited by bondwire configuration.
- 2: Starting  $T_J = 25^\circ\text{C}$ ,  $L = 25\text{mH}$ ,  $I_{AS} = 9.5\text{A}$ ,  $V_{DD} = 100\text{V}$  during inductor charging and  $V_{DD} = 0\text{V}$  during time in avalanche.
- 3:  $I_{SD} \leq 26\text{A}$ ,  $di/dt \leq 200 \text{ A}/\mu\text{s}$ ,  $V_{DD} \leq 380\text{V}$ , starting  $T_J = 25^\circ\text{C}$ .
- 4:  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance, where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design, while  $R_{\theta JA}$  is determined by the board design. The maximum rating presented here is based on mounting on a 1 in<sup>2</sup> pad of 2oz copper.

## Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--------|-----------|-----------------|-----|-----|-----|-------|
|--------|-----------|-----------------|-----|-----|-----|-------|

### Off Characteristics

|            |                                   |  |     |   |           |               |
|------------|-----------------------------------|--|-----|---|-----------|---------------|
| $B_{VDSS}$ | Drain to Source Breakdown Voltage | $I_D = 250\mu\text{A}, V_{GS} = 0\text{V}$             | 600 | - | -         | V             |
| $I_{DSS}$  | Drain to Source Leakage Current   | $V_{DS} = 600\text{V}, T_J = 25^\circ\text{C}$         | -   | - | 10        | $\mu\text{A}$ |
|            |                                   | $V_{GS} = 0\text{V}, T_J = 150^\circ\text{C}$ (Note 5) | -   | - | 1         | mA            |
| $I_{GSS}$  | Gate to Source Leakage Current    | $V_{GS} = \pm 20\text{V}$                              | -   | - | $\pm 100$ | nA            |

### On Characteristics

|                     |                                  |   |     |     |     |                  |
|---------------------|----------------------------------|---|-----|-----|-----|------------------|
| $V_{GS(\text{th})}$ | Gate to Source Threshold Voltage | $V_{GS} = V_{DS}, I_D = 250\mu\text{A}$                 | 3.0 | 4.0 | 5.0 | V                |
| $r_{DS(\text{on})}$ | Drain to Source On Resistance    | $I_D = 26\text{A}, T_J = 25^\circ\text{C}$              | -   | 62  | 72  | $\text{m}\Omega$ |
|                     |                                  | $V_{GS} = 10\text{V}, T_J = 150^\circ\text{C}$ (Note 5) | -   | 154 | 195 | $\text{m}\Omega$ |

### Dynamic Characteristics

|                     |                               |   |   |      |     |          |
|---------------------|-------------------------------|---|---|------|-----|----------|
| $C_{iss}$           | Input Capacitance             | $V_{DS} = 100\text{V}, V_{GS} = 0\text{V}, f = 1\text{MHz}$ | - | 6330 | -   | pF       |
| $C_{oss}$           | Output Capacitance            |   | - | 199  | -   | pF       |
| $C_{rss}$           | Reverse Transfer Capacitance  |   | - | 1.25 | -   | pF       |
| $R_g$               | Gate Resistance               | $f = 1\text{MHz}$   | - | 0.46 | -   | $\Omega$ |
| $Q_{g(\text{ToT})}$ | Total Gate Charge             |   | - | 160  | 210 | nC       |
| $Q_{g(\text{th})}$  | Threshold Gate Charge         |   | - | 11   | 16  | nC       |
| $Q_{gs}$            | Gate to Source Gate Charge    |   | - | 34   | -   | nC       |
| $Q_{gd}$            | Gate to Drain "Miller" Charge |   | - | 67   | -   | nC       |

### Switching Characteristics

|              |                     |  |   |     |     |    |
|--------------|---------------------|--|---|-----|-----|----|
| $t_{on}$     | Turn-On Time        | $V_{DD} = 380\text{V}, I_D = 26\text{A}, V_{GS} = 10\text{V}, R_G = 4.7\Omega$ | - | 75  | 100 | ns |
| $t_{d(on)}$  | Turn-On Delay Time  |  | - | 44  | -   | ns |
| $t_r$        | Rise Time           |  | - | 31  | -   | ns |
| $t_{d(off)}$ | Turn-Off Delay Time |  | - | 128 | -   | ns |
| $t_f$        | Fall Time           |  | - | 22  | -   | ns |
| $t_{off}$    | Turn-Off Time       |  | - | 150 | 200 | ns |

### Drain-Source Diode Characteristics

|          |                               |  |   |      |     |    |
|----------|-------------------------------|--|---|------|-----|----|
| $V_{SD}$ | Source to Drain Diode Voltage | $I_{SD} = 26\text{A}, V_{GS} = 0\text{V}$                | - | -    | 1.2 | V  |
| $T_{rr}$ | Reverse Recovery Time         | $I_F = 26\text{A}, dI_{SD}/dt = 100\text{A}/\mu\text{s}$ | - | 185  | -   | ns |
|          |                               | $V_{DD} = 480\text{V}$                                   | - | 1515 | -   | nC |

#### Note:

5: The maximum value is specified by design at  $T_J = 150^\circ\text{C}$ . Product is not tested to this condition in production.

## Typical Characteristics




Figure 1. Normalized Power Dissipation vs. Case Temperature




Figure 2. Maximum Continuous Drain Current vs. Case Temperature




Figure 3. Normalized Maximum Transient Thermal Impedance




Figure 4. Peak Current Capability

## Typical Characteristics




Figure 5. Forward Bias Safe Operating Area




Figure 6. Transfer Characteristics




Figure 7. Forward Diode Characteristics




Figure 8. Saturation Characteristics




Figure 9. Saturation Characteristics




Figure 10.  $R_{DSON}$  vs. Gate Voltage

## Typical Characteristics




Figure 11. Normalized  $R_{DS(on)}$  vs. Junction Temperature




Figure 12. Normalized Gate Threshold Voltage vs. Temperature




Figure 13. Normalized Drain to Source Breakdown Voltage vs. Junction Temperature




Figure 14. Capacitance vs. Drain to Source Voltage




Figure 15. Gate Charge vs. Gate to Source Voltage




Figure 16. Eoss vs. Drain to Source Voltage




Figure 17. Gate Charge Test Circuit & Waveform




Figure 18. Resistive Switching Test Circuit & Waveforms




Figure 19. Unclamped Inductive Switching Test Circuit & Waveforms





Figure 20. Peak Diode Recovery  $dv/dt$  Test Circuit & Waveforms



**FAIRCHILD**™

NOTES: UNLESS OTHERWISE SPECIFIED.

- A. PACKAGE REFERENCE: JEDEC TO-247,  
ISSUE E, VARIATION AB, DATED JUNE, 2004.
- B. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD  
FLASH, AND TIE BAR EXTRUSIONS.
- C. ALL DIMENSIONS ARE IN MILLIMETERS.
- D. DRAWING CONFORMS TO ASME Y14.5 - 1994

 DOES NOT COMPLY JEDEC STANDARD VALUE  
F. DRAWING FILENAME: MKT-TO247A03\_REV04

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor](#):

[FCH072N60F\\_F085](#)



# OCEAN CHIPS

## Океан Электроники

### Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибутором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибутором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А