


### Product Overview

The Qorvo QPD1011 is a 7W ( $P_{3dB}$ ),  $50\Omega$ -input matched discrete GaN on SiC HEMT which operates from 30 MHz to 1.2 GHz. The integrated input matching network enables wideband gain and power performance, while the output can be matched on board to optimize power and efficiency for any region within the band.

The device is housed in a 5 x 6 mm leadless SMT package that saves real estate of already space-constrained handheld radios.


Lead-free and ROHS compliant.

Evaluation boards are available upon request.



5 x 6 x 0.85 mm Package

### Functional Block Diagram



### Key Features

- Frequency: 30 to 1200 MHz
  - Output Power ( $P_{3dB}$ )<sup>1</sup>: 8.7 W
  - Linear Gain<sup>1</sup>: 21 dB
  - Typical PAE<sub>3dB</sub><sup>1</sup>: 60 %
  - Operating Voltage: 50 V
  - CW and Pulse capable
- Note 1: @ 1 GHz Load Pull

### Applications

- Military radar
- Civilian radar
- Land mobile and military radio communications
- Test instrumentation
- Wideband or narrowband amplifiers
- Jammers

### Ordering info

Part No.	Description
QPD1011EVB01	30 – 1000 MHz EVB
QPD1011S2	Pack of 2 QPD1011
QPD1011SQ	Pack of 25 QPD1011
QPD1011SR	Pack of 100 QPD1011

### Absolute Maximum Ratings<sup>1</sup>

Parameter	Rating	Units
Breakdown Voltage, $V_{BDG}$	+145	V
Gate Voltage Range, $V_G$	-7 to +2	V
Drain Current, $I_{D_{MAX}}$	1.46	A
Gate Current Range, $I_G$	See page 17.	mA
Power Dissipation, $P_{DISS}$	14.7 <sup>2</sup>	W
RF Input Power, Pulsed, 1.3 GHz, $T = 25\text{ }^\circ\text{C}^2$	+27	dBm
Mounting Temperature (30 Seconds)	320	$^\circ\text{C}$
Storage Temperature	-65 to +150	$^\circ\text{C}$

Notes:

1. Operation of this device outside the parameter ranges given above may cause permanent damage.
2. Pulsed, 100  $\mu\text{S}$  PW, 10% DC

### Recommended Operating Conditions<sup>1</sup>

Parameter	Min	Typ	Max	Units
Operating Temp. Range	-40	+25	+85	$^\circ\text{C}$
Drain Voltage Range, $V_D$	+32	+50	+55	V
Drain Bias Current, $I_{DQ}$		20		mA
Drain Current, $I_D^4$	-	300	-	mA
Gate Voltage, $V_G^3$	-	-2.8	-	V
Power Dissipation ( $P_D$ ) <sup>2,4</sup>	-	-	13	W
Power Dissipation ( $P_D$ ), CW <sup>2</sup>	-	-	10	W

Notes:

1. Electrical performance is measured under conditions noted in the electrical specifications table. Specifications are not guaranteed over all recommended operating conditions.
2. Package base at 85  $^\circ\text{C}$
3. To be adjusted to desired  $I_{DQ}$
4. Pulsed, 100  $\mu\text{S}$  PW, 10% DC

### Measured Load Pull Performance – Power Tuned<sup>1, 2</sup>

Parameter	Typical Values				Units
	0.6	0.8	1.0	1.2	
Frequency, F	0.6	0.8	1.0	1.2	GHz
Drain Voltage, $V_D$	50	50	50	50	V
Drain Bias Current, $I_{DQ}$	20	20	20	20	mA
Output Power at 3dB compression, $P_{3dB}$	39.7	39.4	39.4	39.1	dBm
Power Added Efficiency at 3dB compression, $PAE_{3dB}$	59.4	58.7	49.3	49.1	%
Gain at 3dB compression, $G_{3dB}$	15.7	18	18.3	16.6	dB

Notes:

1. Pulsed, 100  $\mu\text{S}$  Pulse Width, 10% Duty Cycle
2. Characteristic Impedance  $Z_0 = 33.4\ \Omega$ .

### Measured Load Pull Performance – Efficiency Tuned<sup>1, 2</sup>

Parameter	Typical Values				Units
	0.6	0.8	1.0	1.2	
Frequency, F	0.6	0.8	1.0	1.2	GHz
Drain Voltage, $V_D$	50	50	50	50	V
Drain Bias Current, $I_{DQ}$	20	20	20	20	mA
Output Power at 3dB compression, $P_{3dB}$	37.7	38.4	37.3	37.4	dBm
Power Added Efficiency at 3dB compression, $PAE_{3dB}$	71.6	64.1	60.1	55.4	%
Gain at 3dB compression, $G_{3dB}$	17.9	19.2	19.5	19.1	dB

Notes:

1. Pulsed, 100  $\mu\text{S}$  Pulse Width, 10% Duty Cycle
2. Characteristic Impedance  $Z_0 = 33.4\ \Omega$ .

### 50 – 1000 MHz EVB 500 MHz Performance<sup>1</sup>

Parameter	Min	Typ	Max	Units
Linear Gain, $G_{LIN}$	–	17.8	–	dB
Output Power at 3dB compression point, P3dB	–	7.2	–	W
Drain Efficiency at 3dB compression point, DEFF3dB	–	52.6	–	%
Gain at 3dB compression point, G3dB	–	14.8	–	dB

1.  $V_D = +50$  V,  $I_{DQ} = 20$  mA, Temp = +25 °C, CW

### RF Characterization – Mismatch Ruggedness at 1000 MHz<sup>1</sup>

Symbol	Parameter	Input Drive Level	Typical
VSWR	Impedance Mismatch Ruggedness	23 dBm	10:1


1. Test conditions unless otherwise noted:  $T_A = 25$  °C,  $V_D = 50$  V,  $I_{DQ} = 20$  mA, CW

Measured Load-Pull Smith Charts<sup>1, 2</sup>

Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$ , 100  $\mu\text{s}$  Pulse Width, 10% Duty Cycle
2. See page 18 for load pull reference planes where the performance was measured.

0.6GHz, Load-pull




Measured Load-Pull Smith Charts<sup>1, 2</sup>

Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$ , 100 uS Pulse Width, 10% Duty Cycle
2. See page 18 for load pull reference planes where the performance was measured.

0.8GHz, Load-pull




Measured Load-Pull Smith Charts<sup>1, 2</sup>

Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$ , 100 uS Pulse Width, 10% Duty Cycle
2. See page 18 for load pull reference planes where the performance was measured.

1GHz, Load-pull




Measured Load-Pull Smith Charts<sup>1, 2</sup>

Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$ , 100 uS Pulse Width, 10% Duty Cycle
2. See page 18 for load pull reference planes where the performance was measured.





1.2GHz, Load-pull



### Typical Measured Performance – Load-Pull Drive-up<sup>1, 2</sup>

Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$ , 100  $\mu\text{s}$  Pulse Width, 10% Duty Cycle
2. See page 18 for load-pull and source-pull reference planes where the performance was measured.









### Typical Measured Performance – Load-Pull Drive-up<sup>1, 2</sup>

Notes:

1. C Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$ , 100  $\mu\text{s}$  Pulse Width, 10% Duty Cycle
2. See page 18 for load-pull and source-pull reference planes where the performance was measured.




### Power Driveup Performance Over Temperatures Of 50 – 1000 MHz EVB<sup>1,2</sup>


Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$ , CW
2. The dissipation power is calculated at EVB level. The device dissipation power is lower due to input and output matching network losses.


**P3dB Over Temperatures**




**DEFF3dB Over Temperatures**



**G3dB Over Temperatures**



**Pdiss3dB Over Temperatures**




### Power Driveup Performance At 25°C Of 50 – 1000 MHz EVB<sup>1,2</sup>


Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$ , CW
2. The dissipation power is calculated at EVB level. The device dissipation power is lower due to input and output matching network losses.


**P3dB At 25 °C**




**DEFF3dB At 25 °C**



**G3dB At 25 °C**







**Pdiss3dB At 25 °C**



### Power Driveup Performance At 25°C Over Drain Voltage Of 50 – 1000 MHz EVB<sup>1, 2</sup>

Notes:




1. Test Conditions:  $I_{DQ} = 20$  mA, CW
2. The dissipation power limit is conservative because it is specified at DUT only without accounting for the loss of the output matching network..



### 2-Tone Performance At 25°C Of 50 – 1000 MHz EVB<sup>1</sup>

Notes:





1. Test Conditions:  $I_{DQ} = 20 \text{ mA}$ , CW



### S-Parameters At -40°C Of 50 – 1000 MHz EVB<sup>1, 2</sup>


Notes:

1. Test Conditions:  $V_D = 50\text{ V}$ ,  $I_{DQ} = 20\text{ mA}$
2. K-factor > 1 indicates unconditional stability




### Thermal and Reliability Information - CW

**Peak IR Surface Temperature vs. CW Dissipation Power  
Base of DFN Package Fixed at 85 °C**



Parameter	Conditions	Values	Units
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	10.6	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	10.5 W Pdiss, CW	196	°C
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	10.2	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	9.0 W Pdiss, CW	177	°C
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	10.0	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	7.5 W Pdiss, CW	160	°C
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	9.8	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	6.0 W Pdiss, CW	144	°C
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	9.6	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	4.5 W Pdiss, CW	128	°C

<sup>1</sup>Refer to the following document [GaN Device Channel Temperature, Thermal Resistance, and Reliability Estimates](#)

**Thermal and Reliability Information - Pulsed**
**Peak IR Surface Temperature vs. Dissipation Power  
Base of DFN Package Fixed at 85 °C**



Parameter	Conditions	Values	Units
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	7.8	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	10.5 W Pdiss, 100 uS PW, 10% DC	167	°C
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	7.7	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	8.3 W Pdiss, 100 uS PW, 10% DC	149	°C
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	7.5	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	6.0 W Pdiss, 100 uS PW, 10% DC	130	°C
Thermal Resistance, IR <sup>1</sup> ( $\theta_{JC}$ )	85 °C Case	7.0	°C/W
Peak IR Surface Temperature <sup>1</sup> ( $T_{CH}$ )	3.0 W Pdiss, 100 uS PW, 10% DC	106	°C

<sup>1</sup>Refer to the following document [GaN Device Channel Temperature, Thermal Resistance, and Reliability Estimates](#)




**Maximum Gate Current**

---



### Pin Configuration and Description<sup>1</sup>

Note 1: The QPD1011 will be marked with the “QPD1011” designator and a lot code marked below the part designator. The “YY” represents the last two digits of the calendar year the part was manufactured, the “WW” is the work week of the assembly lot start, the MXXX” is the production lot number.




Pin	Symbol	Description
1	$V_G$	Gate Voltage
2, 3	RF INPUT	Gate
6, 7	RF OUTPUT / $V_D$	Drain
4, 5, 8	NC	No connection
9	Source	Source / Ground / Backside of part


### Mechanical Drawing<sup>1, 2, 3, 4</sup>

Note

1. Dimensions are in mm.
2. Dimension tolerance is  $\pm 0.1$  mm, unless noted otherwise.
3. Package leads are gold plated.
4. Part is mold encapsulated.




50 – 1000 MHz Application Circuit - Schematic



Bias-up Procedure	Bias-down Procedure
1. Set $V_G$ to -3.5 V.	1. Turn off RF signal.
2. Set $I_D$ current limit to 30 mA.	2. Turn off $V_D$
3. Apply 50 V $V_D$ .	3. Wait 2 seconds to allow drain capacitor to discharge
4. Slowly adjust $V_G$ until $I_D$ is set to 20 mA.	4. Turn off $V_G$
5. Set $I_D$ current limit to 500 mA (CW operation)	
6. Apply RF.	

50 – 1000 MHz Application Circuit - Layout


Board material is RO4350B 0.020" thickness with 2oz copper cladding. Overall EVB size is 3.98" x 3.98".



**50 – 1000 MHz Application Circuit - Bill Of material**

Description	Ref. Des.	Manufacturer	Part Number
CAP, SMT 0603 10nF	C2	AVX Corporation	0603YC103KAT2A
CAP, CER, SMD 10UF, 10%, 10V, 0805, X7R	C3	Murata	GRM21BR71A106KE51L
CAP MLCC 2400PF TC +/-15% 50V, 0805	C1, C6		C08BL242X-5UN-X0T
CAP CER 4.7UF 100V 10% X7R 2220	C7	Murata	GRM55ER72A475KA01L
CAP, 2.2pF, +/-0.1pF, 250V, HI-Q, 0603	C4	American Technical Ceramics	600S2R2BT250T
CAP, 3.0pF, +/-0.1pF, 250V, HI-Q, 0603	C5	American Technical Ceramics	600S3R0BT250XT
RES 10 OHM 1/10W +/-5% 0603	R1	TTI Inc.	CRCW060310R0JNEA
IND 1000nH 0603 2%	L4	Coilcraft Inc.	0603LS-102XGLC
IND 900nH 1008 5%	L1	Coilcraft Inc.	1008AF-901XJLC
IND, 6.8nH, 5%, W/W, 0603	L5	Coilcraft Inc.	0603HC-6N8XJLW
IND, 12nH, 5%, 0603, HC	L2, L3	Coilcraft Inc.	0603HC-12NXGLW

Recommended Solder Temperature Profile



## Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	Class 1A, 250 V	ANSI/ESD/JEDEC JS-001
ESD – Charged Device Model (CDM)	750 V	ANSI/ESD/JEDEC JS-002
MSL – Moisture Sensitivity Level	Level 3	JESD J-STD-020



Caution!  
ESD-Sensitive Device

## Solderability

Compatible with both lead-free (260°C max. reflow temp.) and tin/lead (245°C max. reflow temp.) soldering processes. Solder profiles available upon request.

Contact plating: NiPdAu

## RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C<sub>15</sub>H<sub>12</sub>Br<sub>4</sub>O<sub>2</sub>) Free
- PFOS Free
- SVHC Free



## Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about Qorvo:

**Web:** [www.qorvo.com](http://www.qorvo.com)      **Tel:** +1.844.890.8163  
**Email:** [customer.support@qorvo.com](mailto:customer.support@qorvo.com)

For technical questions and application information:      **Email:** [info-products@qorvo.com](mailto:info-products@qorvo.com)

## Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2016 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А