
Surface Mountable
Phase Control SCR, 10 A



D²PAK



DESCRIPTION/FEATURES

The 10TTS08S High Voltage Series of silicon controlled rectifiers are specifically designed for medium power switching and phase control applications. The glass passivation technology used has reliable operation up to 125 °C junction temperature.

Typical applications are in input rectification (soft start) and these products are designed to be used with Vishay HPP input diodes, switches and output rectifiers which are available in identical package outlines.

This product has been designed and qualified for industrial level.

PRODUCT SUMMARY	
V_T at 6.5 A	< 1.15 V
I_{TSM}	140 A
V_{RRM}	800 V

OUTPUT CURRENT IN TYPICAL APPLICATIONS			
APPLICATIONS	**SINGLE-PHASE BRIDGE**	**THREE-PHASE BRIDGE**	**UNITS**
NEMA FR-4 or G-10 glass fabric-based epoxy with 4 oz. (140 µm) copper	2.5	3.5	A
Aluminum IMS, R_{thCA} = 15 °C/W	6.3	9.5	
Aluminum IMS with heatsink, R_{thCA} = 5 °C/W	14.0	18.5	

Note

- T_A = 55 °C, T_J = 125 °C, footprint 300 mm²

MAJOR RATINGS AND CHARACTERISTICS			
PARAMETER	**TEST CONDITIONS**	**VALUES**	**UNITS**
$I_{T(AV)}$	Sinusoidal waveform	6.5	A
I_{RMS}		10	
V_{RRM}/V_{DRM}		800	V
I_{TSM}		140	A
V_T	6.5 A, T_J = 25 °C	1.15	V
dV/dt		150	V/µs
dI/dt		100	A/µs
T_J	Range	- 40 to 125	°C

VOLTAGE RATINGS			
PART NUMBER	**V_{RRM}, MAXIMUM PEAK REVERSE VOLTAGE V**	**V_{DRM}, MAXIMUM PEAK DIRECT VOLTAGE V**	**I_{RRM}/I_{DRM} AT 125 °C mA**
10TTS08S	800	800	1.0

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS
Maximum average on-state current	$I_{T(AV)}$	T_C = 112 °C, 180° conduction half sine wave		6.5	A
Maximum RMS on-state current	$I_{T(RMS)}$			10	
Maximum peak, one-cycle, non-repetitive surge current	I_{TSM}	10 ms sine pulse, rated V_{RRM} applied, T_J = 125 °C		120	
		10 ms sine pulse, no voltage reapplied, T_J = 125 °C		140	
Maximum I^2t for fusing	I^2t	10 ms sine pulse, rated V_{RRM} applied, T_J = 125 °C		72	A^2s
		10 ms sine pulse, no voltage reapplied, T_J = 125 °C		100	
Maximum $I^2\sqrt{t}$ for fusing	$I^2\sqrt{t}$	t = 0.1 to 10 ms, no voltage reapplied, T_J = 125 °C		1000	$A^2\sqrt{s}$
Maximum on-state voltage drop	V_{TM}	6.5 A, T_J = 25 °C		1.15	V
On-state slope resistance	r_t	T_J = 125 °C		17.3	mΩ
Threshold voltage	$V_{T(TO)}$			0.85	V
Maximum reverse and direct leakage current	I_{RM}/I_{DM}	T_J = 25 °C	V_R = Rated V_{RRM}/V_{DRM}	0.05	mA
		T_J = 125 °C		1.0	
Typical holding current	I_H	Anode supply = 6 V, resistive load, initial I_T = 1 A		30	
Maximum latching current	I_L	Anode supply = 6 V, resistive load		50	
Maximum rate of rise of off-state voltage	dV/dt	T_J = 25 °C		150	V/µs
Maximum rate of rise of turned-on current	dI/dt			100	A/µs

TRIGGERING

PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
Maximum peak gate power	P_{GM}		8.0	W
Maximum average gate power	$P_{G(AV)}$		2.0	
Maximum peak positive gate current	$+I_{GM}$		1.5	A
Maximum peak negative gate voltage	$-V_{GM}$		10	V
Maximum required DC gate current to trigger	I_{GT}	Anode supply = 6 V, resistive load, T_J = - 65 °C	20	mA
		Anode supply = 6 V, resistive load, T_J = 25 °C	15	
		Anode supply = 6 V, resistive load, T_J = 125 °C	10	
Maximum required DC gate voltage to trigger	V_{GT}	Anode supply = 6 V, resistive load, T_J = - 65 °C	1.2	V
		Anode supply = 6 V, resistive load, T_J = 25 °C	1	
		Anode supply = 6 V, resistive load, T_J = 125 °C	0.7	
Maximum DC gate voltage not to trigger	V_{GD}	T_J = 125 °C, V_{DRM} = Rated value	0.2	
Maximum DC gate current not to trigger	I_{GD}		0.1	mA

SWITCHING

PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
Typical turn-on time	t_{gt}	T_J = 25 °C	0.8	µs
Typical reverse recovery time	t_{rr}	T_J = 125 °C	3	
Typical turn-off time	t_q		100	

THERMAL AND MECHANICAL SPECIFICATIONS				
PARAMETER	**SYMBOL**	**TEST CONDITIONS**	**VALUES**	**UNITS**
Maximum junction and storage temperature range	T_J, T_{Stg}		- 40 to 125	°C
Soldering temperature	T_S	For 10 s (1.6 mm from case)	240	
Maximum thermal resistance, junction to case	R_{thJC}	DC operation	1.5	°C/W
Typical thermal resistance, junction to ambient (PCB mount)	R_{thJA} (1)		40	
Approximate weight			2	g
			0.07	oz.
Marking device		Case style D^2PAK (SMD-220)	10TTS08S	

Note

(1) When mounted on 1" square (650 mm^2) PCB of FR-4 or G-10 material 4 oz. (140 µm) copper 40 °C/W
For recommended footprint and soldering techniques refer to application note #AN-994




Fig. 1 - Current Rating Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 3 - On-State Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Thermal Impedance Z_{thJC} Characteristics

ORDERING INFORMATION TABLE

Device code

10	T	T	S	08	S	TRL	-
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)

- 1 - Current rating, RMS value
- 2 - Circuit configuration:
  - T = Single thyristor
- 3 - Package:
  - T = TO-220AC
- 4 - Type of silicon:
  - S = Converter grade
- 5 - Voltage code x 100 = V_{RRM}
- 6 - S = TO-220 D^2PAK (SMD-220) version
- 7 - Tape and reel option:
  - TRL = Left reel
  - TRR = Right orientation reel
- 8 -
  - None = Standard production
  - PbF = Lead (Pb)-free

LINKS TO RELATED DOCUMENTS	
Dimensions	http://www.vishay.com/doc?95046
Part marking information	http://www.vishay.com/doc?95054
Packaging information	http://www.vishay.com/doc?95032

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А