




SERIES: PBO-5 | **DESCRIPTION:** AC-DC POWER SUPPLY

FEATURES


- up to 5 W continuous power
- ultra-compact SIP package
- wide input voltage range
- over current and short circuit protections
- 4,000 Vac isolation
- UL 62368, CE safety approvals
- efficiency up to 79%



| MODEL | output voltage (Vdc) | output current | | output power max (W) | ripple and noise ¹ max (mVp-p) | efficiency ² typ (%) |
|------------|-------------------------|----------------|-------------|----------------------------|---|---------------------------------------|
| | | min (mA) | max (mA) | | | |
| PBO-5-S3.3 | 3.3 | 0 | 1000 | 3.3 | 150 | 67 |
| PBO-5-S5 | 5 | 0 | 1000 | 5 | 150 | 74 |
| PBO-5-S9 | 9 | 0 | 560 | 5 | 150 | 75 |
| PBO-5-S12 | 12 | 0 | 420 | 5 | 150 | 76 |
| PBO-5-S15 | 15 | 0 | 340 | 5 | 150 | 77 |
| PBO-5-S24 | 24 | 0 | 210 | 5 | 150 | 79 |

Notes: 1. At full load, nominal input, 20 MHz bandwidth oscilloscope, with a 1 μ F ceramic and 10 μ F electrolytic capacitor on the output.
 2. At 230 Vac input.
 3. All specifications are measured at T_a=25°C, humidity <75%, 115 or 230 Vac input voltage, and rated output load unless otherwise specified.

PART NUMBER KEY



INPUT

| parameter | conditions/description | min | typ | max | units |
|---------------------------|------------------------|-----|-----|------|-------|
| voltage | | 85 | | 264 | Vac |
| | | 100 | | 400 | Vdc |
| frequency | | 47 | | 63 | Hz |
| current | at 115 Vac | | | 0.2 | A |
| | at 230 Vac | | | 0.1 | A |
| inrush current | at 115 Vac | | 5 | | A |
| | at 230 Vac | | 10 | | A |
| leakage current | CY0 is 1 nF/400 Vac | | | 0.25 | mA |
| no load power consumption | | | | 0.5 | W |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|----------------------------|------------------------|-----|-------|-------|-------|
| capacitive load | 3.3 Vdc output models | | | 2,200 | μF |
| | 5 Vdc output models | | | 1,500 | μF |
| | 9 Vdc output models | | | 680 | μF |
| | 12 Vdc output models | | | 470 | μF |
| | 15 Vdc output models | | | 330 | μF |
| | 24 Vdc output models | | | 100 | μF |
| initial set point accuracy | 3.3 Vdc output models | | | ±3 | % |
| | all other models | | | ±2 | % |
| line regulation | at full load | | ±0.5 | | % |
| load regulation | from 10~100% load | | | ±1.5 | % |
| hold-up time | at 115 Vac | | 15 | | ms |
| | at 230 Vac | | 75 | | ms |
| switching frequency | | | 100 | | kHz |
| temperature coefficient | | | ±0.02 | | %/°C |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------|---------------------------|-----|-----|-----|-------|
| over voltage protection | output voltage clamp | | | | |
| | 3.3 & 5 Vdc output models | | | 7.5 | Vdc |
| | 9 Vdc output models | | | 15 | Vdc |
| | 12 & 15 Vdc output models | | | 20 | Vdc |
| | 24 Vdc output models | | | 30 | Vdc |
| over current protection | auto recovery | 150 | | | % |
| short circuit protection | continuous, auto recovery | | | | |

SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|---------------------|--|-------|-----|-----|-------|
| isolation voltage | input to output at 5 mA for 1 minute | 4,000 | | | Vac |
| safety approvals | UL 62368, EN 62368 | | | | |
| safety class | class II | | | | |
| conducted emissions | CISPR32/EN55032 Class A, (external circuit required, see figure 1) | | | | |
| | CISPR32/EN55032 Class B, (external circuit required, see figure 2) | | | | |
| radiated emissions | CISPR32/EN55032 Class B, (external circuit required, see figure 1) | | | | |
| ESD | IEC/EN61000-4-2 Class B, ±6 kV | | | | |
| radiated immunity | IEC/EN61000-4-3 Class A, 10V/m | | | | |
| EFT/burst | IEC/EN61000-4-4 Class B, ±2 kV (external circuit required, see figure 1) | | | | |
| | IEC/EN61000-4-4 Class B, ±4 kV (external circuit required, see figure 2) | | | | |

Notes: 1. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

SAFETY & COMPLIANCE (CONTINUED)

| parameter | conditions/description | min | typ | max | units |
|------------------------------|--|---------|-----|-----|-------|
| surge | IEC/EN61000-4-5 Class B, ±1 kV (external circuit required, see figure 1) | | | | |
| | IEC/EN61000-4-5 Class B, ±1 kV/±2 kV | | | | |
| conducted immunity | IEC/EN61000-4-6 Class A, 10 Vr.m.s (external circuit required, see figure 2) | | | | |
| voltage dips & interruptions | IEC/EN61000-4-11 Class B, 0%-70% | | | | |
| MTBF | as per MIL-HDBK-217F at 25 °C | 300,000 | | | hours |
| RoHS | 2011/65/EU | | | | |


Notes: 1. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | see derating curves | -25 | | 85 | °C |
| storage temperature | | -40 | | 105 | °C |
| storage humidity | non-condensing | | | 85 | % |


SOLDERABILITY

| parameter | conditions/description | min | typ | max | units |
|----------------|------------------------|-----|-----|-----|-------|
| hand soldering | for 3~5 seconds | 350 | 360 | 370 | °C |
| wave soldering | for 5~10 seconds | 255 | 260 | 265 | °C |




DERATING CURVES

load vs. ambient temperature
(at 85~264 Vac / 100~400 Vdc input voltage)




load vs. input voltage
(at 25°C)




EFFICIENCY CURVES


PBO-5-S3.3 AC Input Efficiency Curve
(Efficiency vs. Load Current)




PBO-5-S3.3 DC Input Efficiency Curve
(Efficiency vs. Load Current)




PBO-5-S5 AC Input Efficiency Curve
(Efficiency vs. Load Current)




PBO-5-S5 DC Input Efficiency Curve
(Efficiency vs. Load Current)



PBO-5-S9 AC Input Efficiency Curve
(Efficiency vs. Load Current)




PBO-5-S9 DC Input Efficiency Curve
(Efficiency vs. Load Current)




EFFICIENCY CURVES (CONTINUED)


PBO-5-S12 AC Input Efficiency Curve
(Efficiency vs. Load Current)




PBO-5-S12 DC Input Efficiency Curve
(Efficiency vs. Load Current)




PBO-5-S15 AC Input Efficiency Curve
(Efficiency vs. Load Current)




PBO-5-S15 DC Input Efficiency Curve
(Efficiency vs. Load Current)



PBO-5-S24 AC Input Efficiency Curve
(Efficiency vs. Load Current)



PBO-5-S24 DC Input Efficiency Curve
(Efficiency vs. Load Current)



MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|------------|---|-----|-----|-----|----------|
| dimensions | vertical models: 40.00 x 12.80 x 18.50 (1.575 x 0.504 x 0.729 inches) right-angle models: 40.00 x 20.00 x 12.80 (1.575 x 0.787 x 0.504 inches) | | | | mm mm |
| weight | | | 7 | | g |

MECHANICAL DRAWING

Vertical Orientation



units: mm[inch]

tolerance: $\pm 0.50[\pm 0.020]$

pin section tolerance: $\pm 0.10[\pm 0.004]$


| PIN CONNECTIONS | |
|-----------------|----------|
| PIN | Function |
| 1 | AC (N) |
| 3 | AC (L) |
| 5 | +V(CAP) |
| 7 | -V(CAP) |
| 12 | -Vo |
| 14 | +Vo |

Note: 1. It is required to add C1 between pins 5 & 7 (see application circuits).



Note: Grid 2.54*2.54mm

Top View
PCB Layout



MECHANICAL DRAWING (CONTINUED)

Right-angle Orientation


units: mm[inch]

tolerance: $\pm 0.50[\pm 0.020]$


pin section tolerance: $\pm 0.10[\pm 0.004]$

| PIN CONNECTIONS | |
|-----------------|----------|
| PIN | Function |
| 1 | AC (N) |
| 3 | AC (L) |
| 5 | +V(CAP) |
| 7 | -V(CAP) |
| 12 | -Vo |
| 14 | +Vo |


Note: 1. It is required to add C1 between pins 5 & 7 (see application circuits).




Top View



Right View



Front View



Top View
PCB Layout

APPLICATION CIRCUIT




Table 1

| Recommended External Circuit Components | | | | | | | | | | |
|---|-------------------|---------|-------|--------------|--------|-----------------|------------|-----------------|----------|-----------|
| Vo (Vdc) | FUSE ¹ | MOV | NTC | CX1 | R1 | C1 ¹ | CY0 | C2 ¹ | TVS | C3 |
| 3.3 | 1A/250V | S14K350 | 13D-5 | 0.1μF/275Vac | 12Ω/2W | 10μF/400V | 1nF/400Vac | 220μF/35V | SMBJ7.0A | 100nF/50V |
| 5 | 1A/250V | S14K350 | 13D-5 | 0.1μF/275Vac | 12Ω/2W | 10μF/400V | 1nF/400Vac | 220μF/35V | SMBJ7.0A | 100nF/50V |
| 9 | 1A/250V | S14K350 | 13D-5 | 0.1μF/275Vac | 12Ω/2W | 10μF/400V | 1nF/400Vac | 220μF/35V | SMBJ12A | 100nF/50V |
| 12 | 1A/250V | S14K350 | 13D-5 | 0.1μF/275Vac | 12Ω/2W | 10μF/400V | 1nF/400Vac | 150μF/35V | SMBJ20A | 100nF/50V |
| 15 | 1A/250V | S14K350 | 13D-5 | 0.1μF/275Vac | 12Ω/2W | 10μF/400V | 1nF/400Vac | 150μF/35V | SMBJ20A | 100nF/50V |
| 24 | 1A/250V | S14K350 | 13D-5 | 0.1μF/275Vac | 12Ω/2W | 10μF/400V | 1nF/400Vac | 100μF/35V | SMBJ30A | 100nF/50V |

Note: 1. Required components.

EMC RECOMMENDED CIRCUIT




Table 2

| Recommended External Circuit Components | |
|---|----------------------|
| FUSE | 1A/250V, slow fusing |
| MOV2 | S14K320 |
| LCM | 3.5mH |
| LDM | 330μH |
| CX | 0.1μF/275 Vac |
| CY1, CY2 | 1nF/400 Vac |
| R1 | 12Ω/2W |
| C1 | 10μF/400V |
| CY0 | 1nF/400Vac |

Note: Also refer to Table 1.

- Notes:
- C1 is required for both AC and DC inputs. For input voltages greater than 370 Vdc, the recommended value is 10 μF / 450 V.
 - C2 is recommended to be a high frequency and low impedance capacitor. For capacitance and rated ripple current of capacitors, refer to the datasheets provided by the manufacturers. Voltage derating of capacitors should be 80% or above.
 - C3 is a ceramic capacitor used to filter high frequency noise.
 - TVS is a recommended post-component to protect post-circuits (if converter fails).
 - It is required to have a distance ≥ 6.4 mm for safety between external components in primary and secondary circuit.

REVISION HISTORY

| rev. | description | date |
|------|---|------------|
| 1.0 | initial release | 10/18/2016 |
| 1.01 | added right-angle pin versions, updated to 62368 safety approvals, reduced component height to 12.80 mm max | 04/19/2018 |

The revision history provided is for informational purposes only and is believed to be accurate.

**CUI INC[®]****Headquarters**
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А