

MC74AC373, MC74ACT373

Octal Transparent Latch with 3-State Outputs

The MC74AC373/74ACT373 consists of eight latches with 3-state outputs for bus organized system applications. The flip-flops appear transparent to the data when Latch Enable (LE) is HIGH. When LE is LOW, the data that meets the setup time is latched. Data appears on the bus when the Output Enable (\overline{OE}) is LOW. When \overline{OE} is HIGH, the bus output is in the high impedance state.

Features

- Eight Latches in a Single Package
- 3-State Outputs for Bus Interfacing
- Outputs Source/Sink 24 mA
- 'ACT373 Has TTL Compatible Inputs
- Pb-Free Packages are Available





Figure 1. Pinout: 20-Lead Packages Conductors
(Top View)




ON Semiconductor®


<http://onsemi.com>




PDIP-20
N SUFFIX
CASE 738



SOIC-20W
DW SUFFIX
CASE 751D



TSSOP-20
DT SUFFIX
CASE 948E



SOEIAJ-20
M SUFFIX
CASE 967

PIN ASSIGNMENT

| PIN | FUNCTION |
|--------------------------------|-----------------------|
| D ₀ -D ₇ | Data Inputs |
| LE | Latch Enable Input |
| \overline{OE} | Output Enable Input |
| O ₀ -O ₇ | 3-State Latch Outputs |




Figure 2. Logic Symbol

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 8 of this data sheet.

DEVICE MARKING INFORMATION

See general marking information in the device marking section on page 9 of this data sheet.

MC74AC373, MC74ACT373

TRUTH TABLE

| Inputs | | Outputs | |
|-----------------|----|---------|-------|
| \overline{OE} | LE | D_n | O_n |
| H | X | X | Z |
| L | H | L | L |
| L | H | H | H |
| L | L | X | O_0 |

H = HIGH Voltage Level

L = LOW Voltage Level


Z = High Impedance

X = Immaterial

O_0 = Previous O_0 before LOW-to-HIGH Transition of Clock

FUNCTIONAL DESCRIPTION

The MC74AC373/74ACT373 contains eight D-type latches with 3-state standard outputs. When the Latch Enable (LE) input is HIGH, data on the D_n inputs enters the latches. In this condition the latches are transparent, i.e., a latch output will change state each time its D input changes. When LE is LOW, the latches store the information that was present on the D inputs a setup time preceding the HIGH-to-LOW transition of LE. The 3-state standard outputs are controlled by the Output Enable (\overline{OE}) input. When \overline{OE} is LOW, the standard outputs are in the 2-state mode. When \overline{OE} is HIGH, the standard outputs are in the high impedance mode but this does not interfere with entering new data into the latches.



NOTE: This diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Figure 3. Logic Diagram

MC74AC373, MC74ACT373

MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|-----------|---|-----------------------|------|
| V_{CC} | DC Supply Voltage (Referenced to GND) | -0.5 to +7.0 | V |
| V_{IN} | DC Input Voltage (Referenced to GND) | -0.5 to V_{CC} +0.5 | V |
| V_{OUT} | DC Output Voltage (Referenced to GND) | -0.5 to V_{CC} +0.5 | V |
| I_{IN} | DC Input Current, per Pin | ± 20 | mA |
| I_{OUT} | DC Output Sink/Source Current, per Pin | ± 50 | mA |
| I_{CC} | DC V_{CC} or GND Current per Output Pin | ± 50 | mA |
| T_{stg} | Storage Temperature | -65 to +150 | °C |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Min | Typ | Max | Unit |
|-------------------|---|------------------|-----|----------|------|
| V_{CC} | Supply Voltage | 'AC | 2.0 | 5.0 | 6.0 |
| | | 'ACT | 4.5 | 5.0 | 5.5 |
| V_{IN}, V_{OUT} | DC Input Voltage, Output Voltage (Ref. to GND) | 0 | - | V_{CC} | V |
| t_r, t_f | Input Rise and Fall Time (Note 1) 'AC Devices except Schmitt Inputs | V_{CC} @ 3.0 V | - | 150 | - |
| | | V_{CC} @ 4.5 V | - | 40 | - |
| | | V_{CC} @ 5.5 V | - | 25 | - |
| t_r, t_f | Input Rise and Fall Time (Note 2) 'ACT Devices except Schmitt Inputs | V_{CC} @ 4.5 V | - | 10 | - |
| | | V_{CC} @ 5.5 V | - | 8.0 | - |
| T_J | Junction Temperature (PDIP) | - | - | 140 | °C |
| T_A | Operating Ambient Temperature Range | -40 | 25 | 85 | °C |
| I_{OH} | Output Current – High | - | - | -24 | mA |
| I_{OL} | Output Current – Low | - | - | 24 | mA |

1. V_{IN} from 30% to 70% V_{CC} ; see individual Data Sheets for devices that differ from the typical input rise and fall times.

2. V_{IN} from 0.8 V to 2.0 V; see individual Data Sheets for devices that differ from the typical input rise and fall times.

MC74AC373, MC74ACT373

DC CHARACTERISTICS

| Symbol | Parameter | V _{CC} (V) | 74AC | | 74AC | Unit | Conditions |
|------------------|-----------------------------------|------------------------|-------------------------|----------------------|------------------------------------|------|---|
| | | | T _A = +25°C | | T _A = -40°C to +85°C | | |
| | | | Typ | Guaranteed Limits | | | |
| V _{IH} | Minimum High Level Input Voltage | 3.0 4.5 5.5 | 1.5 2.25 2.75 | 2.1 3.15 3.85 | 2.1 3.15 3.85 | V | V _{OUT} = 0.1 V or V _{CC} - 0.1 V |
| V _{IL} | Maximum Low Level Input Voltage | 3.0 4.5 5.5 | 1.5 2.25 2.75 | 0.9 1.35 1.65 | 0.9 1.35 1.65 | V | V _{OUT} = 0.1 V or V _{CC} - 0.1 V |
| V _{OH} | Minimum High Level Output Voltage | 3.0 4.5 5.5 | 2.99 4.49 5.49 | 2.9 4.4 5.4 | 2.9 4.4 5.4 | V | I _{OUT} = -50 μA |
| | | 3.0 4.5 5.5 | — — — | 2.56 3.86 4.86 | 2.46 3.76 4.76 | V | *V _{IN} = V _{IL} or V _{IH} I _{OH} -12 mA -24 mA -24 mA |
| V _{OL} | Maximum Low Level Output Voltage | 3.0 4.5 5.5 | 0.002 0.001 0.001 | 0.1 0.1 0.1 | 0.1 0.1 0.1 | V | I _{OUT} = 50 μA |
| | | 3.0 4.5 5.5 | — — — | 0.36 0.36 0.36 | 0.44 0.44 0.44 | V | *V _{IN} = V _{IL} or V _{IH} I _{OL} 12 mA 24 mA 24 mA |
| I _{IN} | Maximum Input Leakage Current | 5.5 | — | ±0.1 | ±1.0 | μA | V _I = V _{CC} , GND |
| I _{OZ} | Maximum 3-State Current | 5.5 | — | ±0.5 | ±5.0 | μA | V _I (OE) = V _{IL} , V _{IH} V _I = V _{CC} , GND V _O = V _{CC} , GND |
| I _{OLD} | †Minimum Dynamic Output Current | 5.5 | — | — | 75 | mA | V _{OLD} = 1.65 V Max |
| I _{OHD} | | 5.5 | — | — | -75 | mA | V _{OHD} = 3.85 V Min |
| I _{CC} | Maximum Quiescent Supply Current | 5.5 | — | 8.0 | 80 | μA | V _{IN} = V _{CC} or GND |

*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

NOTE: I_{IN} and I_{CC} @ 3.0 V are guaranteed to be less than or equal to the respective limit @ 5.5 V V_{CC}.

MC74AC373, MC74ACT373

AC CHARACTERISTICS (For Figures and Waveforms – See AND8277/D at www.onsemi.com)

| Symbol | Parameter | V_{CC}^* (V) | 74AC | | | 74AC | | Unit | Fig. No. | | |
|-----------|-------------------------------------|-------------------|--|------------|-------------|--|--------------|------|-------------|--|--|
| | | | $T_A = +25^\circ C$ $C_L = 50 \text{ pF}$ | | | $T_A = -40^\circ C$ to $+85^\circ C$ $C_L = 50 \text{ pF}$ | | | | | |
| | | | Min | Typ | Max | Min | Max | | | | |
| t_{PLH} | Propagation Delay D_n to O_n | 3.3 5.0 | 1.5 1.5 | 10 7.0 | 13.5 9.5 | 1.5 1.5 | 15 10.5 | ns | 3-5 | | |
| t_{PHL} | Propagation Delay D_n to O_n | 3.3 5.0 | 1.5 1.5 | 9.5 7.0 | 13 9.5 | 1.5 1.5 | 14.5 10.5 | ns | 3-5 | | |
| t_{PLH} | Propagation Delay LE to O_n | 3.3 5.0 | 1.5 1.5 | 10 7.5 | 13.5 9.5 | 1.5 1.5 | 15 10.5 | ns | 3-6 | | |
| t_{PHL} | Propagation Delay LE to O_n | 3.3 5.0 | 1.5 1.5 | 9.5 7.0 | 12.5 9.5 | 1.5 1.5 | 14 10.5 | ns | 3-6 | | |
| t_{PZH} | Output Enable Time | 3.3 5.0 | 1.5 1.5 | 9.0 7.0 | 11.5 8.5 | 1.0 1.0 | 13 9.5 | ns | 3-7 | | |
| t_{PZL} | Output Enable Time | 3.3 5.0 | 1.5 1.5 | 8.5 6.5 | 11.5 8.5 | 1.0 1.0 | 13 9.5 | ns | 3-8 | | |
| t_{PHZ} | Output Disable Time | 3.3 5.0 | 1.5 1.5 | 10 8.0 | 12.5 11 | 1.0 1.0 | 14.5 12.5 | ns | 3-7 | | |
| t_{PLZ} | Output Disable Time | 3.3 5.0 | 1.5 1.5 | 8.0 6.5 | 11.5 8.5 | 1.0 1.0 | 12.5 10 | ns | 3-8 | | |

*Voltage Range 3.3 V is 3.3 V ± 0.3 V.

Voltage Range 5.0 V is 5.0 V ± 0.5 V.

AC OPERATING REQUIREMENTS

| Symbol | Parameter | V_{CC}^* (V) | 74AC | | 74AC | Unit | Fig. No. |
|--------|--|-------------------|--|--------------------|--|------|-------------|
| | | | $T_A = +25^\circ C$ $C_L = 50 \text{ pF}$ | | $T_A = -40^\circ C$ to $+85^\circ C$ $C_L = 50 \text{ pF}$ | | |
| | | | Typ | Guaranteed Minimum | | | |
| t_s | Setup Time, HIGH or LOW D_n to LE | 3.3 5.0 | 3.5 2.0 | 5.5 4.0 | 6.0 4.5 | ns | 3-9 |
| t_h | Hold Time, HIGH or LOW D_n to LE | 3.3 5.0 | -3.0 -1.5 | 1.0 1.0 | 1.0 1.0 | ns | 3-9 |
| t_w | LE Pulse Width, HIGH | 3.3 5.0 | 4.0 2.0 | 5.5 4.0 | 6.0 4.5 | ns | 3-6 |

*Voltage Range 3.3 V is 3.3 V ± 0.3 V.

Voltage Range 5.0 V is 5.0 V ± 0.5 V.

MC74AC373, MC74ACT373

DC CHARACTERISTICS

| Symbol | Parameter | V _{CC} (V) | 74ACT | | 74ACT | Unit | Conditions |
|-------------------|--|------------------------|------------------------|-------------------|------------------------------------|------|---|
| | | | T _A = +25°C | | T _A = -40°C to +85°C | | |
| | | | Typ | Guaranteed Limits | | | |
| V _{IH} | Minimum High Level Input Voltage | 4.5 5.5 | 1.5 1.5 | 2.0 2.0 | 2.0 2.0 | V | V _{OUT} = 0.1 V or V _{CC} – 0.1 V |
| V _{IL} | Maximum Low Level Input Voltage | 4.5 5.5 | 1.5 1.5 | 0.8 0.8 | 0.8 0.8 | V | V _{OUT} = 0.1 V or V _{CC} – 0.1 V |
| V _{OH} | Minimum High Level Output Voltage | 4.5 5.5 | 4.49 5.49 | 4.4 5.4 | 4.4 5.4 | V | I _{OUT} = -50 µA |
| | | 4.5 5.5 | – – | 3.86 4.86 | 3.76 4.76 | V | *V _{IN} = V _{IL} or V _{IH} I _{OH} –24 mA –24 mA |
| V _{OL} | Maximum Low Level Output Voltage | 4.5 5.5 | 0.001 0.001 | 0.1 0.1 | 0.1 0.1 | V | I _{OUT} = 50 µA |
| | | 4.5 5.5 | – – | 0.36 0.36 | 0.44 0.44 | V | *V _{IN} = V _{IL} or V _{IH} 24 mA I _{OL} 24 mA |
| I _{IN} | Maximum Input Leakage Current | 5.5 | – | ±0.1 | ±1.0 | µA | V _I = V _{CC} , GND |
| ΔI _{CCT} | Additional Max. I _{CC} /Input | 5.5 | 0.6 | – | 1.5 | mA | V _I = V _{CC} – 2.1 V |
| I _{OZ} | Maximum 3-State Current | 5.5 | – | ±0.5 | ±5.0 | µA | V _I (OE) = V _{IL} , V _{IH} V _I = V _{CC} , GND V _O = V _{CC} , GND |
| I _{OLD} | †Minimum Dynamic Output Current | 5.5 | – | – | 75 | mA | V _{OLD} = 1.65 V Max |
| | | 5.5 | – | – | -75 | mA | V _{OHD} = 3.85 V Min |
| I _{CC} | Maximum Quiescent Supply Current | 5.5 | – | 8.0 | 80 | µA | V _{IN} = V _{CC} or GND |

*All outputs loaded; thresholds on input associated with output under test.

†Maximum test duration 2.0 ms, one output loaded at a time.

MC74AC373, MC74ACT373

AC CHARACTERISTICS (For Figures and Waveforms – See AND8277/D at www.onsemi.com)

| Symbol | Parameter | V _{CC} * (V) | 74ACT | | | 74ACT | | Unit | Fig. No. | | |
|------------------|---|--------------------------|--|-----|-----|--|------|------|-------------|--|--|
| | | | T _A = +25°C C _L = 50 pF | | | T _A = -40°C to +85°C C _L = 50 pF | | | | | |
| | | | Min | Typ | Max | Min | Max | | | | |
| t _{PLH} | Propagation Delay D _n to O _n | 5.0 | 2.5 | 8.5 | 10 | 1.5 | 11.5 | ns | 3-5 | | |
| t _{PHL} | Propagation Delay D _n to O _n | 5.0 | 2.0 | 8.0 | 10 | 1.5 | 11.5 | ns | 3-5 | | |
| t _{PLH} | Propagation Delay LE to O _n | 5.0 | 2.5 | 8.5 | 11 | 2.0 | 11.5 | ns | 3-6 | | |
| t _{PHL} | Propagation Delay LE to O _n | 5.0 | 2.0 | 8.0 | 10 | 1.5 | 11.5 | ns | 3-6 | | |
| t _{PZH} | Output Enable Time | 5.0 | 2.0 | 8.0 | 9.5 | 1.5 | 10.5 | ns | 3-7 | | |
| t _{PZL} | Output Enable Time | 5.0 | 2.0 | 7.5 | 9.0 | 1.5 | 10.5 | ns | 3-8 | | |
| t _{PHZ} | Output Disable Time | 5.0 | 2.5 | 9.0 | 11 | 2.5 | 12.5 | ns | 3-7 | | |
| t _{PLZ} | Output Disable Time | 5.0 | 1.5 | 7.5 | 8.5 | 1.0 | 10 | ns | 3-8 | | |

*Voltage Range 5.0 V is 5.0 V ±0.5 V.

AC OPERATING REQUIREMENTS (For Figures and Waveforms – See AND8277/D at www.onsemi.com)

| Symbol | Parameter | V _{CC} * (V) | 74ACT | | 74ACT | Unit | Fig. No. |
|----------------|---|--------------------------|--|--------------------|--|------|-------------|
| | | | T _A = +25°C C _L = 50 pF | | T _A = -40°C to +85°C C _L = 50 pF | | |
| | | | Typ | Guaranteed Minimum | | | |
| t _s | Setup Time, HIGH or LOW D _n to LE | 5.0 | 3.0 | 7.0 | 8.0 | ns | 3-9 |
| t _h | Hold Time, HIGH or LOW D _n to LE | 5.0 | 0 | 0 | 1.0 | ns | 3-9 |
| t _w | LE Pulse Width, HIGH | 5.0 | 2.0 | 7.0 | 8.0 | ns | 3-6 |

*Voltage Range 5.0 V is 5.0 V ±0.5 V.

CAPACITANCE

| Symbol | Parameter | Value Typ | Unit | Test Conditions |
|-----------------|-------------------------------|--------------|------|-------------------------|
| C _{IN} | Input Capacitance | 4.5 | pF | V _{CC} = 5.0 V |
| C _{PD} | Power Dissipation Capacitance | 40 | pF | V _{CC} = 5.0 V |

MC74AC373, MC74ACT373

ORDERING INFORMATION

| Device | Package | Shipping [†] |
|-----------------|------------------------|-----------------------|
| MC74AC373N | PDIP-20 | 18 Units / Rail |
| MC74AC373NG | PDIP-20 (Pb-Free) | |
| MC74ACT373N | PDIP-20 | |
| MC74ACT373NG | PDIP-20 (Pb-Free) | |
| MC74AC373DW | SOIC-20 | 38 Units / Rail |
| MC74AC373DWG | SOIC-20 (Pb-Free) | |
| MC74AC373DWR2 | SOIC-20 | 1000 / Tape & Reel |
| MC74AC373DWR2G | SOIC-20 (Pb-Free) | |
| MC74ACT373DW | SOIC-20 | 38 Units / Rail |
| MC74ACT373DWG | SOIC-20 (Pb-Free) | |
| MC74ACT373DWR2 | SOIC-20 | 1000 / Tape & Reel |
| MC74ACT373DWR2G | SOIC-20 (Pb-Free) | |
| MC74AC373DT | TSSOP-20* | 75 Units / Rail |
| MC74AC373DTG | TSSOP-20* | |
| MC74AC373DTR2 | TSSOP-20* | 2500 / Tape & Reel |
| MC74AC373DTR2G | TSSOP-20* | |
| MC74ACT373DT | TSSOP-20* | 75 Units / Rail |
| MC74ACT373DTG | TSSOP-20* | |
| MC74ACT373DTR2 | TSSOP-20* | 2500 / Tape & Reel |
| MC74ACT373DTR2G | TSSOP-20* | |
| MC74AC373MEL | SOEIAJ-20 | 2000 / Tape & Reel |
| MC74AC373MELG | SOEIAJ-20 (Pb-Free) | |
| MC74ACT373MEL | SOEIAJ-20 | 2000 / Tape & Reel |
| MC74ACT373MELG | SOEIAJ-20 (Pb-Free) | |

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

*These packages are inherently Pb-Free.


MC74AC373, MC74ACT373

MARKING DIAGRAMS


PDIP-20







SOIC-20W



TSSOP-20



SOEIAJ-20



A = Assembly Location

WL, L = Wafer Lot

YY, Y = Year

WW, W = Work Week

G or ▪ = Pb-Free Package

(Note: Microdot may be in either location)

MC74AC373, MC74ACT373

PACKAGE DIMENSIONS


PDIP-20

N SUFFIX

PLASTIC DIP PACKAGE

CASE 738-03

ISSUE E




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.

| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 1.010 | 1.070 | 25.66 | 27.17 |
| B | 0.240 | 0.260 | 6.10 | 6.60 |
| C | 0.150 | 0.180 | 3.81 | 4.57 |
| D | 0.015 | 0.022 | 0.39 | 0.55 |
| E | 0.050 BSC | | 1.27 BSC | |
| F | 0.050 | 0.070 | 1.27 | 1.77 |
| G | 0.100 BSC | | 2.54 BSC | |
| J | 0.008 | 0.015 | 0.21 | 0.38 |
| K | 0.110 | 0.140 | 2.80 | 3.55 |
| L | 0.300 BSC | | 7.62 BSC | |
| M | 0° | 15° | 0° | 15° |
| N | 0.020 | 0.040 | 0.51 | 1.01 |

SOIC-20W
DW SUFFIX
CASE 751D-05
ISSUE G



NOTES:


1. DIMENSIONS ARE IN MILLIMETERS.
2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.
5. DIMENSION B DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.13 TOTAL IN EXCESS OF B DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS | |
|-----|-------------|-------|
| | MIN | MAX |
| A | 2.35 | 2.65 |
| A1 | 0.10 | 0.25 |
| B | 0.35 | 0.49 |
| C | 0.23 | 0.32 |
| D | 12.65 | 12.95 |
| E | 7.40 | 7.60 |
| e | 1.27 BSC | |
| H | 10.05 | 10.55 |
| h | 0.25 | 0.75 |
| L | 0.50 | 0.90 |
| θ | 0° | 7° |

MC74AC373, MC74ACT373

PACKAGE DIMENSIONS

**TSSOP-20
DT SUFFIX
CASE 948E-02
ISSUE C**




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 6.40 | 6.60 | 0.252 | 0.260 |
| B | 4.30 | 4.50 | 0.169 | 0.177 |
| C | --- | 1.20 | --- | 0.047 |
| D | 0.05 | 0.15 | 0.002 | 0.006 |
| F | 0.50 | 0.75 | 0.020 | 0.030 |
| G | 0.65 BSC | | 0.026 BSC | |
| H | 0.27 | 0.37 | 0.011 | 0.015 |
| J | 0.09 | 0.20 | 0.004 | 0.008 |
| J1 | 0.09 | 0.16 | 0.004 | 0.006 |
| K | 0.19 | 0.30 | 0.007 | 0.012 |
| K1 | 0.19 | 0.25 | 0.007 | 0.010 |
| L | 6.40 BSC | | 0.252 BSC | |
| M | 0° | 8° | 0° | 8° |

SOLDERING FOOTPRINT*





*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


MC74AC373, MC74ACT373

PACKAGE DIMENSIONS

**SOEIAJ-20
M SUFFIX
CASE 967-01
ISSUE A**



DETAIL P



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: MILLIMETER.
 3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS AND ARE MEASURED AT THE PARTING LINE. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
 4. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
 5. THE LEAD WIDTH DIMENSION (b) DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSIONS AND ADJACENT LEAD TO BE 0.46 (0.018).

| DIM | MILLIMETERS | | INCHES | |
|----------------|-------------|-------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | --- | 2.05 | --- | 0.081 |
| A ₁ | 0.05 | 0.20 | 0.002 | 0.008 |
| b | 0.35 | 0.50 | 0.014 | 0.020 |
| c | 0.15 | 0.25 | 0.006 | 0.010 |
| D | 12.35 | 12.80 | 0.486 | 0.504 |
| E | 5.10 | 5.45 | 0.201 | 0.215 |
| e | 1.27 BSC | | 0.050 BSC | |
| H _E | 7.40 | 8.20 | 0.291 | 0.323 |
| L | 0.50 | 0.85 | 0.020 | 0.033 |
| L _E | 1.10 | 1.50 | 0.043 | 0.059 |
| M | 0 ° | 10 ° | 0 ° | 10 ° |
| Q ₁ | 0.70 | 0.90 | 0.028 | 0.035 |
| Z | --- | 0.81 | --- | 0.032 |

ON Semiconductor and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free

USA/Canada

Europe, Middle East and Africa Technical Support:

Phone: 421 33 790 2910

Japan Customer Focus Center

Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative



OCEAN CHIPS

Океан Электроники

Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибутором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибутором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А