NLSV4T244

4-Bit Dual-Supply Non-Inverting Level Translator

The NLSV4T244 is a 4−bit configurable dual−supply voltage level translator. The input A_n and output B_n ports are designed to track two different power supply rails, V_{CCA} and V_{CCB} respectively. Both supply rails are configurable from 0.9 V to 4.5 V allowing universal low−voltage translation from the input A_n to the output B_n port.

Features

- Wide V_{CCA} and V_{CCB} Operating Range: 0.9 V to 4.5 V
- High−Speed w/ Balanced Propagation Delay
- Inputs and Outputs have OVT Protection to 4.5 V
- Non−preferential V_{CCA} and V_{CCB} Sequencing
- Outputs at 3−State until Active V_{CC} is Reached
- Power−Off Protection
- Outputs Switch to 3−State with V_{CCB} at GND
- Ultra−Small Packaging: 1.7 mm x 2.0 mm UQFN12
- These are Pb−Free Devices

Typical Applications

- Mobile Phones, PDAs, Other Portable Devices

Important Information

- ESD Protection for All Pins:
  HBM (Human Body Model) > 1500 V

ON Semiconductor®

http://onsemi.com

MARKING DIAGRAMS



UQFN12
MU SUFFIX
CASE 523AE

UR = Specific Device Code
M = Date Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)



SOIC−14
D SUFFIX
CASE 751A





TSSOP−14
DT SUFFIX
CASE 948G



A = Assembly Location
L, WL = Wafer Lot
Y, YY = Year
W, WW = Work Week
G or ▪ = Pb−Free Package
(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
NLSV4T244MUTAG	UQFN12 (Pb−Free)	3000/Tape & Reel
NLSV4T244DR2G	SO−14 (Pb−Free)	2500/Tape & Reel
NLSV4T244DTR2G	TSSOP14 (Pb−Free)	2500/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2012



Figure 1. Pin Assignments



Figure 2. Logic Diagram

PIN ASSIGNMENT

PIN	FUNCTION
V_{CCA}	Input Port DC Power Supply
V_{CCB}	Output Port DC Power Supply
GND	Ground
A_n	Input Port
B_n	Output Port
$\overline{OE}$	Output Enable

TRUTH TABLE

Inputs		Outputs
$\overline{OE}$	A_n	B_n
L	L	L
L	H	H
H	X	3−State

MAXIMUM RATINGS

Symbol	Rating		Value	Condition	Unit
V_{CCA}, V_{CCB}	DC Supply Voltage		−0.5 to +5.5		V
V_I	DC Input Voltage	A_n	−0.5 to +5.5		V
V_C	Control Input	$\overline{OE}$	−0.5 to +5.5		V
V_O	DC Output Voltage (Power Down)	B_n	−0.5 to +5.5	$V_{CCA} = V_{CCB} = 0$	V
	(Active Mode)	B_n	−0.5 to +5.5		V
	(Tri−State Mode)	B_n	−0.5 to +5.5		V
I_{IK}	DC Input Diode Current		−20	V_I < GND	mA
I_{OK}	DC Output Diode Current		−50	V_O < GND	mA
I_O	DC Output Source/Sink Current		±50		mA
I_{CCA}, I_{CCB}	DC Supply Current Per Supply Pin		±100		mA
I_{GND}	DC Ground Current per Ground Pin		±100		mA
T_{STG}	Storage Temperature		−65 to +150		°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter		Min	Max	Unit
V_{CCA}, V_{CCB}	Positive DC Supply Voltage		0.9	4.5	V
V_I	Bus Input Voltage		GND	4.5	V
V_C	Control Input	$\overline{OE}$	GND	4.5	V
V_{IO}	Bus Output Voltage (Power Down Mode)	B_n	GND	4.5	V
	(Active Mode)	B_n	GND	V_{CCB}	V
	(Tri−State Mode)	B_n	GND	4.5	V
T_A	Operating Temperature Range		−40	+85	°C
$\Delta t / \Delta V$	Input Transition Rise or Rate V_I, from 30% to 70% of V_{CC}; V_{CC} = 3.3 V ±0.3 V		0	10	nS

DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Test Conditions	V_{CCA} (V)	V_{CCB} (V)	−40°C to +85°C		Unit
					Min	Max	
V_{IH}	Input HIGH Voltage (An, $\overline{OE}$)		3.6 – 4.5	0.9 – 4.5	2.2	–	V
			2.7 – 3.6		2.0	–	
			2.3 – 2.7		1.6	–	
			1.4 – 2.3		0.65 * V_{CCA}	–	
			0.9 – 1.4		0.9 * V_{CCA}	–	
V_{IL}	Input LOW Voltage (An, $\overline{OE}$)		3.6 – 4.5	0.9 – 4.5	–	0.8	V
			2.7 – 3.6		–	0.8	
			2.3 – 2.7		–	0.7	
			1.4 – 2.3		–	0.35 * V_{CCA}	
			0.9 – 1.4		–	0.1 * V_{CCA}	
V_{OH}	Output HIGH Voltage	I_{OH} = −100 μA; V_I = V_{IH}	0.9 – 4.5	0.9 – 4.5	V_{CCB} – 0.2	–	V
		I_{OH} = −0.5 mA; V_I = V_{IH}	0.9	0.9	0.75 * V_{CCB}	–	
		I_{OH} = −2 mA; V_I = V_{IH}	1.4	1.4	1.05	–	
		I_{OH} = −6 mA; V_I = V_{IH}	1.65	1.65	1.25	–	
			2.3	2.3	2.0	–	
		I_{OH} = −12 mA; V_I = V_{IH}	2.3	2.3	1.8	–	
			2.7	2.7	2.2	–	
		I_{OH} = −18 mA; V_I = V_{IH}	2.3	2.3	1.7	–	
			3.0	3.0	2.4	–	
		I_{OH} = −24 mA; V_I = V_{IH}	3.0	3.0	2.2	–	
V_{OL}	Output LOW Voltage	I_{OL} = 100 μA; V_I = V_{IL}	0.9 – 4.5	0.9 – 4.5	–	0.2	V
		I_{OL} = 0.5 mA; V_I = V_{IL}	1.1	1.1	–	0.3	
		I_{OL} = 2 mA; V_I = V_{IL}	1.4	1.4	–	0.35	
		I_{OL} = 6 mA; V_I = V_{IL}	1.65	1.65	–	0.3	
		I_{OL} = 12 mA; V_I = V_{IL}	2.3	2.3	–	0.4	
			2.7	2.7	–	0.4	
		I_{OL} = 18 mA; V_I = V_{IL}	2.3	2.3	–	0.6	
			3.0	3.0	–	0.45	
		I_{OL} = 24 mA; V_I = V_{IL}	3.0	3.0	–	0.6	
I_I	Input Leakage Current	V_I = V_{CCA} or GND	0.9 – 4.5	0.9 – 4.5	−1.0	1.0	μA
I_{OFF}	Power−Off Leakage Current	$\overline{OE}$ = 0 V	0 0.9 – 4.5	0.9 – 4.5 0	−1.0 −1.0	1.0 1.0	μA
I_{CCA}	Quiescent Supply Current	V_I = V_{CCA} or GND; I_O = 0, V_{CCA} = V_{CCB}	0.9 – 4.5	0.9 – 4.5	–	2.0	μA
I_{CCB}	Quiescent Supply Current	V_I = V_{CCA} or GND; I_O = 0, V_{CCA} = V_{CCB}	0.9 – 4.5	0.9 – 4.5	–	2.0	μA
I_{CCA} + I_{CCB}	Quiescent Supply Current	V_I = V_{CCA} or GND; I_O = 0, V_{CCA} = V_{CCB}	0.9 – 4.5	0.9 – 4.5	–	4.0	μA
ΔI_{CCA}	Increase in I_{CC} per Input Voltage, Other Inputs at V_{CCA} or GND	V_I = V_{CCA} – 0.6 V; V_I = V_{CCA} or GND	4.5 3.6	4.5 3.6	–	10 5.0	μA
ΔI_{CCB}	Increase in I_{CC} per Input Voltage, Other Inputs at V_{CCA} or GND	V_I = V_{CCA} – 0.6 V; V_I = V_{CCA} or GND	4.5 3.6	4.5 3.6	–	10 5.0	μA
I_{OZ}	I/O Tri−State Output Leakage Current	T_A = 25°C, $\overline{OE}$ = 0 V	0.9 – 4.5	0.9 – 4.5	−1.0	1.0	μA

TOTAL STATIC POWER CONSUMPTION (I_{CCA} + I_{CCB})

	−40°C to +85°C										
	V_{CCB} (V)										
	4.5		3.3		2.8		1.8		0.9		
V_{CCA} (V)	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Unit
4.5		2		2		2		2		< 1.5	μA
3.3		2		2		2		2		< 1.5	μA
2.8		< 2		< 1		< 1		< 0.5		< 0.5	μA
1.8		< 1		< 1		< 0.5		< 0.5		< 0.5	μA
0.9		< 0.5		< 0.5		< 0.5		< 0.5		< 0.5	μA

NOTE: Connect ground before applying supply voltage V_{CCA} or V_{CCB}. This device is designed with the feature that the power−up sequence of V_{CCA} and V_{CCB} will not damage the IC.

AC ELECTRICAL CHARACTERISTICS

			−40°C to +85°C										
			V_{CCB} (V)										
			4.5		3.3		2.8		1.8		1.2		
Symbol	Parameter	V_{CCA} (V)	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Unit
t_{PLH}, t_{PHL} (Note 1)	Propagation Delay, A_n to B_n	4.5		1.6		1.8		2.0		2.1		2.3	nS
		3.3		1.7		1.9		2.1		2.3		2.6	
		2.8		1.9		2.1		2.3		2.5		2.8	
		1.8		2.1		2.4		2.5		2.7		3.0	
		1.2		2.4		2.7		2.8		3.0		3.3	
t_{PZH}, t_{PZL} (Note 1)	Output Enable, $\overline{OE}$ to B_n	4.5		2.6		3.8		4.0		4.1		4.3	nS
		3.3		3.7		3.9		4.1		4.3		4.6	
		2.5		3.9		4.1		4.3		4.5		4.8	
		1.8		4.1		4.4		4.5		4.7		5.0	
		1.2		4.4		4.7		4.8		5.0		5.3	
t_{PHZ}, t_{PLZ} (Note 1)	Output Disable, $\overline{OE}$ to B_n	4.5		2.6		3.8		4.0		4.1		4.3	nS
		3.3		3.7		3.9		4.1		4.3		4.6	
		2.5		3.9		4.1		4.3		4.5		4.8	
		1.8		4.1		4.4		4.5		4.7		5.0	
		1.2		4.4		4.7		4.8		5.0		5.3	
t_{OSHL}, t_{OSLH} (Note 1)	Output to Output Skew, Time	4.5		0.15		0.15		0.15		0.15		0.15	nS
		3.3		0.15		0.15		0.15		0.15		0.15	
		2.5		0.15		0.15		0.15		0.15		0.15	
		1.8		0.15		0.15		0.15		0.15		0.15	
		1.2		0.15		0.15		0.15		0.15		0.15	

1. Propagation delays defined per Figure 3.

CAPACITANCE

Symbol	Parameter	Test Conditions	Typ (Note 2)	Unit
C_{IN}	Control Pin Input Capacitance	V_{CCA} = V_{CCB} = 3.3 V, V_I = 0 V or $V_{CCA/B}$	3.5	pF
$C_{I/O}$	I/O Pin Input Capacitance	V_{CCA} = V_{CCB} = 3.3 V, V_I = 0 V or $V_{CCA/B}$	5.0	pF
C_{PD}	Power Dissipation Capacitance	V_{CCA} = V_{CCB} = 3.3 V, V_I = 0 V or V_{CCA}, f = 10 MHz	20	pF

2. Typical values are at T_A = +25°C.
3. C_{PD} is defined as the value of the IC's equivalent capacitance from which the operating current can be calculated from: $I_{CC(operating)} \cong C_{PD} \times V_{CC} \times f_{IN} \times N_{SW}$ where $I_{CC} = I_{CCA} + I_{CCB}$ and N_{SW} = total number of outputs switching.



Figure 3. AC (Propagation Delay) Test Circuit

Test	Switch
t_{PLH}, t_{PHL}	OPEN
t_{PLZ}, t_{PZL}	V_{CCO} x 2
t_{PHZ}, t_{PZH}	GND
C_L = 15 pF or equivalent (includes probe and jig capacitance) R_L = 2 kΩ or equivalent Z_{OUT} of pulse generator = 50 Ω	



Waveform 1 – Propagation Delays
$t_R = t_F$ = 2.0 ns, 10% to 90%; f = 1 MHz; t_W = 500 ns



Waveform 2 – Output Enable and Disable Times
$t_R = t_F$ = 2.0 ns, 10% to 90%; f = 1 MHz; t_W = 500 ns

Figure 4. AC (Propagation Delay) Test Circuit Waveforms

Symbol	V_{CC}				
	3.0 V – 4.5 V	2.3 V – 2.7 V	1.65 V – 1.95 V	1.4 V – 1.6 V	0.9 V – 1.3 V
V_{mA}	V_{CCA}/2	V_{CCA}/2	V_{CCA}/2	V_{CCA}/2	V_{CCA}/2
V_{mB}	V_{CCB}/2	V_{CCB}/2	V_{CCB}/2	V_{CCB}/2	V_{CCB}/2
V_X	V_{OL} x 0.1	V_{OL} x 0.1	V_{OL} x 0.1	V_{OL} x 0.1	V_{OL} x 0.1
V_Y	V_{OH} x 0.9	V_{OH} x 0.9	V_{OH} x 0.9	V_{OH} x 0.9	V_{OH} x 0.9

PACKAGE DIMENSIONS

UQFN12 1.7x2.0, 0.4P
CASE 523AE
ISSUE A











NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM TERMINAL TIP.
4. MOLD FLASH ALLOWED ON TERMINALS ALONG EDGE OF PACKAGE. FLASH 0.03 MAX ON BOTTOM SURFACE OF TERMINALS.
5. DETAIL A SHOWS OPTIONAL CONSTRUCTION FOR TERMINALS.

	MILLIMETERS	
DIM	MIN	MAX
A	0.45	0.55
A1	0.00	0.05
A3	0.127 REF	
b	0.15	0.25
D	1.70 BSC	
E	2.00 BSC	
e	0.40 BSC	
K	0.20	----
L	0.45	0.55
L1	0.00	0.03
L2	0.15 REF	

MOUNTING FOOTPRINT
SOLDERMASK DEFINED



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

PACKAGE DIMENSIONS

SOIC−14
D SUFFIX
CASE 751A−03
ISSUE J



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	8.55	8.75	0.337	0.344
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27 BSC		0.050 BSC	
J	0.19	0.25	0.008	0.009
K	0.10	0.25	0.004	0.009
M	0 °	7 °	0 °	7 °
P	5.80	6.20	0.228	0.244
R	0.25	0.50	0.010	0.019

SOLDERING FOOTPRINT



DIMENSIONS: MILLIMETERS

PACKAGE DIMENSIONS

TSSOP−14
DT SUFFIX
CASE 948G
ISSUE B



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE −W−.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	4.90	5.10	0.193	0.200
B	4.30	4.50	0.169	0.177
C	−−−	1.20	−−−	0.047
D	0.05	0.15	0.002	0.006
F	0.50	0.75	0.020	0.030
G	0.65 BSC		0.026 BSC	
H	0.50	0.60	0.020	0.024
J	0.09	0.20	0.004	0.008
J1	0.09	0.16	0.004	0.006
K	0.19	0.30	0.007	0.012
K1	0.19	0.25	0.007	0.010
L	6.40 BSC		0.252 BSC	
M	0 °	8 °	0 °	8 °

SOLDERING FOOTPRINT



DIMENSIONS: MILLIMETERS

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А