

Operational Amplifiers Series

# Ground Sense

# High Speed Low Voltage CMOS Operational Amplifiers

**BU7485G BU7485SG BU7486xxx BU7486Sxxx BU7487xx BU7487Sxx**

### General Description

BU7485G/BU7486xxx/BU7487xx are CMOS operational amplifiers with input ground sense and full swing output. This series has extended operational amplifiers BU7485SG/BU7486Sxxx/BU7487Sxx which can operate over a wider temperature range (-40°C to +105°C). These ICs have wide band, high slew rate, low voltage operation and low input bias current, making the operational amplifiers suitable for portable equipment and sensor application.

### Features

- High Slew Rate
- Wide Bandwidth
- Low Input Bias Current
- Output Full Swing

### Application

- Battery-powered Equipment
- General Purpose Electronics

### Key Specifications

- Operating Power Supply Voltage Range (Single Supply): +3.0V to +5.5V
- Slew Rate: 10.0V/ $\mu$ s
- Temperature Range:
  - BU7485G -40°C to +85°C
  - BU7486xxx -40°C to +85°C
  - BU7487xx -40°C to +85°C
  - BU7485S -40°C to +105°C
  - BU7486Sxxx -40°C to +105°C
  - BU7487Sxx -40°C to +105°C
- Input Bias Current: 1pA (Typ)
- Input Offset Current: 1pA (Typ)

### Package

| Package  | W(Typ) x D(Typ) x H(Max) |
|----------|--------------------------|
| SSOP5    | 2.90mm x 2.80mm x 1.25mm |
| SOP8     | 5.00mm x 6.20mm x 1.71mm |
| SSOP-B8  | 3.00mm x 6.40mm x 1.35mm |
| MSOP8    | 2.90mm x 4.00mm x 0.90mm |
| SOP14    | 8.70mm x 6.20mm x 1.71mm |
| SSOP-B14 | 5.00mm x 6.40mm x 1.35mm |

### Simplified schematic





Figure 1. Simplified schematic (1 channel only)

○Product structure : Silicon monolithic integrated circuit ○This product is not designed protection against radioactive rays.

**Pin Configuration**

BU7485G, BU7485SG : SSOP5




| Pin No. | Pin Name |
|---------|----------|
| 1       | +IN      |
| 2       | VSS      |
| 3       | -IN      |
| 4       | OUT      |
| 5       | VDD      |

BU7486F, BU7486SF : SOP8

BU7486FV, BU7486SFV : SSOP-B8


BU7486FVM, BU7486SFVM : MSOP8



| Pin No. | Pin Name |
|---------|----------|
| 1       | OUT1     |
| 2       | -IN1     |
| 3       | +IN1     |
| 4       | VSS      |
| 5       | +IN2     |
| 6       | -IN2     |
| 7       | OUT2     |
| 8       | VDD      |

BU7487F, BU7487SF : SOP14

BU7487FV, BU7487SFV : SSOP-B14



| Pin No. | Pin Name |
|---------|----------|
| 1       | OUT1     |
| 2       | -IN1     |
| 3       | +IN1     |
| 4       | VDD      |
| 5       | +IN2     |
| 6       | -IN2     |
| 7       | OUT2     |
| 8       | OUT3     |
| 9       | -IN3     |
| 10      | +IN3     |
| 11      | VSS      |
| 12      | +IN4     |
| 13      | -IN4     |
| 14      | OUT4     |

| Package             |                     |                       |                         |                     |                       |
|---------------------|---------------------|-----------------------|-------------------------|---------------------|-----------------------|
| SSOP5               | SOP8                | SSOP-B8               | MSOP8                   | SOP14               | SSOP-B14              |
| BU7485G<br>BU7485SG | BU7486F<br>BU7486SF | BU7486FV<br>BU7486SFV | BU7486FVM<br>BU7486SFVM | BU7487F<br>BU7487SF | BU7487FV<br>BU7487SFV |

Ordering Information

|   |   |   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| B | U | 7 | 4 | 8 | x | x | x | x | x | - | x | x |
|---|---|---|---|---|---|---|---|---|---|---|---|---|

|             |
|-------------|
| Part Number |
| BU7485G     |
| BU7485SG    |
| BU7486xxx   |
| BU7486Sxxx  |
| BU7487xx    |
| BU7487Sxx   |

|             |          |
|-------------|----------|
| Package     |          |
| G: SSOP5    |          |
| F: SOP8     |          |
|             | SOP14    |
| FV: SSOP-B8 |          |
|             | SSOP-B14 |
| FVM: MSOP8  |          |

|                                     |
|-------------------------------------|
| Packaging and forming specification |
| E2: Embossed tape and reel          |
| (SOP8/SSOP-B8/SOP14/ SSOP-B14)      |
| TR: Embossed tape and reel          |
| (SSOP5/MSOP8)                       |

Line-up

| Topr            | Package  | Operable Part Number |               |
|-----------------|----------|----------------------|---------------|
| -40°C to +85°C  | SSOP5    | Reel of 3000         | BU7485G-TR    |
|                 | SOP8     | Reel of 2500         | BU7486F-E2    |
|                 | SSOP-B8  | Reel of 2500         | BU7486FV-E2   |
|                 | MSOP8    | Reel of 3000         | BU7486FVM-TR  |
|                 | SOP14    | Reel of 2500         | BU7487F-E2    |
|                 | SSOP-B14 | Reel of 2500         | BU7487FV-E2   |
| -40°C to +105°C | SSOP5    | Reel of 3000         | BU7485SG-TR   |
|                 | SOP8     | Reel of 2500         | BU7486SF-E2   |
|                 | SSOP-B8  | Reel of 2500         | BU7486SFV-E2  |
|                 | MSOP8    | Reel of 3000         | BU7486SFVM-TR |
|                 | SOP14    | Reel of 2500         | BU7487SF-E2   |
|                 | SSOP-B14 | Reel of 2500         | BU7487SFV-E2  |

Absolute Maximum Ratings(Ta=25°C)

| Parameter                                | Symbol  | Ratings                     |                                | Unit |
|--|---------|-----------------------------|--------------------------------|------|
|  |         | BU7485G/BU7486xxx /BU7487xx | BU7485Sx/BU7486Sxxx /BU7487Sxx |      |
| Supply Voltage                           | VDD-VSS | +7                          |                                | V    |
| Power dissipation                        | Pd      | SSOP5                       | 0.54 <sup>*1,7</sup>           | W    |
|  |         | SOP8                        | 0.55 <sup>*2,7</sup>           |      |
|  |         | SSOP-B8                     | 0.50 <sup>*3,7</sup>           |      |
|  |         | MSOP8                       | 0.47 <sup>*4,7</sup>           |      |
|  |         | SOP14                       | 0.70 <sup>*5,7</sup>           |      |
|  |         | SSOP-B14                    | 0.45 <sup>*6,7</sup>           |      |
| Differential Input Voltage <sup>*8</sup> | Vid     | VDD – VSS                   |                                | V    |
| Input Common-mode Voltage Range          | Vicm    | (VSS - 0.3) to VDD + 0.3    |                                | V    |
| Input Current <sup>*9</sup>              | Ii      | ±10                         |                                | mA   |
| Operating Supply Voltage                 | Vopr    | +3.0 to +5.5                |                                | V    |
| Operating Temperature                    | Topr    | -40 to +85                  | -40 to +105                    | °C   |
| Storage Temperature                      | Tstg    | -55 to +125                 |                                | °C   |
| Maximum Junction Temperature             | Tjmax   | +125                        |                                | °C   |

Note: Absolute maximum rating item indicates the condition which must not be exceeded. Application of voltage in excess of absolute maximum rating or use out absolute maximum rated temperature environment may cause deterioration of characteristics.

- \*1 To use at temperature above Ta=25°C reduce 5.4mW.
- \*2 To use at temperature above Ta=25°C reduce 5.5mW.
- \*3 To use at temperature above Ta=25°C reduce 5.0mW.
- \*4 To use at temperature above Ta=25°C reduce 4.7mW.
- \*5 To use at temperature above Ta=25°C reduce 7.0mW.
- \*6 To use at temperature above Ta=25°C reduce 4.5mW.
- \*7 Mounted on a FR4 glass epoxy PCB(70mm×70mm×1.6mm).
- \*8 The voltage difference between inverting input and non-inverting input is the differential input voltage. Then input pin voltage is set to more than VSS.
- \*9 An excessive input current will flow when input voltages of more than VDD+0.6V or lesser than VSS-0.6V are applied. The input current can be set to less than the rated current by adding a limiting resistor.

**Electrical Characteristics**

OBU7485G, BU7485SG (Unless otherwise specified VDD=+3V, VSS=0V, Ta=25°C)

| Parameter                            | Symbol         | Temperature Range | Limits  |      |         | Unit | Condition                        |
|--------------------------------------|----------------|-------------------|---------|------|---------|------|----------------------------------|
|                                      |                |                   | Min     | Typ  | Max     |      |                                  |
| Input Offset Voltage <sup>*10</sup>  | Vio            | 25°C              | -       | 1    | 9.5     | mV   | -                                |
| Input Offset Current <sup>*10</sup>  | Iio            | 25°C              | -       | 1    | -       | pA   | -                                |
| Input Bias Current <sup>*10</sup>    | Ib             | 25°C              | -       | 1    | -       | pA   | -                                |
| Supply Current <sup>*11</sup>        | IDD            | 25°C              | -       | 1500 | 2000    | µA   | RL=∞<br>Av=0dB, IN=0.8V          |
|                                      |                | Full range        | -       | -    | 2400    |      |                                  |
| Maximum Output Voltage (High)        | VOH            | 25°C              | VDD-0.1 | -    | -       | V    | RL=10kΩ                          |
| Maximum Output Voltage (Low)         | VOL            | 25°C              | -       | -    | VSS+0.1 | V    | RL=10kΩ                          |
| Large Signal Voltage Gain            | Av             | 25°C              | 70      | 105  | -       | dB   | RL=10kΩ                          |
| Input Common-mode Voltage Range      | Vicm           | 25°C              | 0       | -    | 1.6     | V    | VSS to VDD-1.4V                  |
| Common-mode Rejection Ratio          | CMRR           | 25°C              | 45      | 60   | -       | dB   | -                                |
| Power Supply Rejection Ratio         | PSRR           | 25°C              | 60      | 80   | -       | dB   | -                                |
| Output Source Current <sup>*12</sup> | Isource        | 25°C              | 4       | 8    | -       | mA   | VDD-0.4V                         |
| Output Sink Current <sup>*12</sup>   | Isink          | 25°C              | 7       | 12   | -       | mA   | VSS+0.4V                         |
| Slew Rate                            | SR             | 25°C              | -       | 10   | -       | V/µs | CL=25pF                          |
| Unity Gain Frequency                 | f <sub>T</sub> | 25°C              | -       | 10   | -       | MHz  | CL=25pF, Av=40dB                 |
| Phase Margin                         | θ              | 25°C              | -       | 50   | -       | deg  | CL=25pF, Av=40dB                 |
| Total Harmonic Distortion +Noise     | THD+N          | 25°C              | -       | 0.03 | -       | %    | OUT=0.7V <sub>P-P</sub> , f=1kHz |

<sup>\*10</sup> Absolute value

<sup>\*11</sup> Full range BU7485G: Ta=-40°C to +85°C BU7485SG: Ta=-40°C to +105°C

<sup>\*12</sup> Under the high temperature environment, consider the power dissipation of IC when selecting the output current.  
When the terminal short circuits are continuously output, the output current is reduced to climb to the temperature inside IC.

OBU7486xxx, BU7486Sxxx (Unless otherwise specified VDD=+3V, VSS=0V, Ta=25°C)

| Parameter                            | Symbol              | Temperature Range | Limits               |      |                      | Unit | Condition   |
|--------------------------------------|---------------------|-------------------|----------------------|------|----------------------|------|---|
|                                      |                     |                   | Min                  | Typ  | Max                  |      |   |
| Input Offset Voltage <sup>*13</sup>  | V <sub>io</sub>     | 25°C              | -                    | 1    | 9.5                  | mV   | -   |
| Input Offset Current <sup>*13</sup>  | I <sub>io</sub>     | 25°C              | -                    | 1    | -                    | pA   | -   |
| Input Bias Current <sup>*13</sup>    | I <sub>b</sub>      | 25°C              | -                    | 1    | -                    | pA   | -   |
| Supply Current <sup>*14</sup>        | I <sub>DD</sub>     | 25°C              | -                    | 3000 | 4000                 | μA   | R <sub>L</sub> =∞, All Op-Amps<br>A <sub>v</sub> =0dB, I <sub>N</sub> =0.8V |
|                                      |                     | Full range        | -                    | -    | 4500                 |      |   |
| Maximum Output Voltage (High)        | V <sub>OH</sub>     | 25°C              | V <sub>DD</sub> -0.1 | -    | -                    | V    | R <sub>L</sub> =10kΩ  |
| Maximum Output Voltage (Low)         | V <sub>OL</sub>     | 25°C              | -                    | -    | V <sub>SS</sub> +0.1 | V    | R <sub>L</sub> =10kΩ  |
| Large Signal Voltage Gain            | A <sub>v</sub>      | 25°C              | 70                   | 105  | -                    | dB   | R <sub>L</sub> =10kΩ  |
| Input Common-mode Voltage Range      | V <sub>icm</sub>    | 25°C              | 0                    | -    | 1.6                  | V    | V <sub>SS</sub> to V <sub>DD</sub> -1.4V                                    |
| Common-mode Rejection Ratio          | CMRR                | 25°C              | 45                   | 60   | -                    | dB   | -   |
| Power Supply Rejection Ratio         | PSRR                | 25°C              | 60                   | 80   | -                    | dB   | -   |
| Output Source Current <sup>*15</sup> | I <sub>source</sub> | 25°C              | 4                    | 8    | -                    | mA   | V <sub>DD</sub> -0.4V   |
| Output Sink Current <sup>*15</sup>   | I <sub>sink</sub>   | 25°C              | 7                    | 12   | -                    | mA   | V <sub>SS</sub> +0.4V   |
| Slew Rate                            | SR                  | 25°C              | -                    | 10   | -                    | V/μs | C <sub>L</sub> =25pF  |
| Unity Gain Frequency                 | f <sub>T</sub>      | 25°C              | -                    | 10   | -                    | MHz  | C <sub>L</sub> =25pF, A <sub>v</sub> =40dB                                  |
| Phase Margin                         | θ                   | 25°C              | -                    | 50   | -                    | deg  | C <sub>L</sub> =25pF, A <sub>v</sub> =40dB                                  |
| Total Harmonic Distortion +Noise     | THD+N               | 25°C              | -                    | 0.03 | -                    | %    | OUT=0.7V <sub>P-P</sub> , f=1kHz  |
| Channel Separation                   | CS                  | 25°C              | -                    | 100  | -                    | dB   | A <sub>v</sub> =40dB  |

<sup>\*13</sup> Absolute value

<sup>\*14</sup> Full range BU7486xxx: Ta=-40°C to +85°C BU7486Sxxx: Ta=-40°C to +105°C

<sup>\*15</sup> Under the high temperature environment, consider the power dissipation of IC when selecting the output current.

When the terminal short circuits are continuously output, the output current is reduced to climb to the temperature inside IC.

OBU7487xx, BU7487Sxx (Unless otherwise specified VDD=+3V, VSS=0V, Ta=25°C)

| Parameter                            | Symbol            | Temperature Range | Limits  |      |         | Unit | Condition                            |
|--------------------------------------|-------------------|-------------------|---------|------|---------|------|--------------------------------------|
|                                      |                   |                   | Min     | Typ  | Max     |      |                                      |
| Input Offset Voltage <sup>*16</sup>  | Vio               | 25°C              | -       | 1    | 9.5     | mV   | -                                    |
| Input Offset Current <sup>*16</sup>  | Iio               | 25°C              | -       | 1    | -       | pA   | -                                    |
| Input Bias Current <sup>*16</sup>    | Ib                | 25°C              | -       | 1    | -       | pA   | -                                    |
| Supply Current <sup>*17</sup>        | IDD               | 25°C              | -       | 6000 | 8000    | μA   | RL=∞, All Op-Amps<br>Av=0dB, IN=0.8V |
|                                      |                   | Full range        | -       | -    | 9000    |      |                                      |
| Maximum Output Voltage (High)        | VOH               | 25°C              | VDD-0.1 | -    | -       | V    | RL=10kΩ                              |
| Maximum Output Voltage (Low)         | VOL               | 25°C              | -       | -    | VSS+0.1 | V    | RL=10kΩ                              |
| Large Signal Voltage Gain            | Av                | 25°C              | 70      | 105  | -       | dB   | RL=10kΩ                              |
| Input Common-mode Voltage Range      | Vicm              | 25°C              | 0       | -    | 1.6     | V    | VSS to VDD-1.4V                      |
| Common-mode Rejection Ratio          | CMRR              | 25°C              | 45      | 60   | -       | dB   | -                                    |
| Power Supply Rejection Ratio         | PSRR              | 25°C              | 60      | 80   | -       | dB   | -                                    |
| Output Source Current <sup>*18</sup> | Isource           | 25°C              | 4       | 8    | -       | mA   | VDD-0.4V                             |
| Output Sink Current <sup>*18</sup>   | I <sub>sink</sub> | 25°C              | 7       | 12   | -       | mA   | VSS+0.4V                             |
| Slew Rate                            | SR                | 25°C              | -       | 10   | -       | V/μs | CL=25pF                              |
| Unity Gain Frequency                 | f <sub>T</sub>    | 25°C              | -       | 10   | -       | MHz  | CL=25pF, Av=40dB                     |
| Phase Margin                         | θ                 | 25°C              | -       | 50   | -       | deg  | CL=25pF, Av=40dB                     |
| Total Harmonic Distortion +Noise     | THD+N             | 25°C              | -       | 0.03 | -       | %    | OUT=0.7V <sub>P-P</sub> , f=1kHz     |
| Channel Separation                   | CS                | 25°C              | -       | 100  | -       | dB   | Av=40dB                              |

<sup>\*16</sup> Absolute value

<sup>\*17</sup> Full range BU7487xx: Ta=-40°C to +85°C BU7487Sxx: Ta=-40°C to +105°C

<sup>\*18</sup> Under the high temperature environment, consider the power dissipation of IC when selecting the output current.  
When the terminal short circuits are continuously output, the output current is reduced to climb to the temperature inside IC.

## Description of Electrical Characteristics

Described below are descriptions of the relevant electrical terms used in this datasheet. Items and symbols used are also shown. Note that item name and symbol and their meaning may differ from those on another manufacturer's document or general document.

### 1. Absolute maximum ratings

Absolute maximum rating items indicate the condition which must not be exceeded. Application of voltage in excess of absolute maximum rating or use out of absolute maximum rated temperature environment may cause deterioration of characteristics.

#### 1.1 Supply Voltage (VDD/VSS)

Indicates the maximum voltage that can be applied between the VDD terminal and VSS terminal without deterioration or destruction of characteristics of internal circuit.

#### 1.2 Differential Input Voltage (Vid)

Indicates the maximum voltage that can be applied between non-inverting and inverting terminals without damaging the IC.

#### 1.3 Input Common-mode Voltage Range (Vicm)

Indicates the maximum voltage that can be applied to the non-inverting and inverting terminals without deterioration or destruction of electrical characteristics. Input common-mode voltage range of the maximum ratings does not assure normal operation of IC. For normal operation, use the IC within the input common-mode voltage range characteristics.

#### 1.4 Power dissipation (Pd)

Indicates the power that can be consumed by the IC when mounted on a specific board at the ambient temperature 25°C (normal temperature). As for package product, Pd is determined by the temperature that can be permitted by the IC in the package (maximum junction temperature) and the thermal resistance of the package.

### 2. Electrical characteristics

#### 2.1 Input Offset Voltage (Vio)

Indicates the voltage difference between non-inverting terminal and inverting terminals. It can be translated into the input voltage difference required for setting the output voltage at 0 V.

#### 2.2 Input Offset Current (Iio)

Indicates the difference of input bias current between the non-inverting and inverting terminals.

#### 2.3 Input Bias Current (Ib)

Indicates the current that flows into or out of the input terminal. It is defined by the average of input bias currents at the non-inverting and inverting terminals.

#### 2.4 Supply Current (IDD)

Indicates the current that flows within the IC under specified no-load conditions.

#### 2.5 Maximum Output Voltage(High) / Maximum Output Voltage(Low) (VOH/VOL)

Indicates the voltage range of the output under specified load condition. It is typically divided into maximum output voltage High and low. Maximum output voltage high indicates the upper limit of output voltage. Maximum output voltage low indicates the lower limit.

#### 2.6 Large Signal Voltage Gain (Av)

Indicates the amplifying rate (gain) of output voltage against the voltage difference between non-inverting terminal and inverting terminal. It is normally the amplifying rate (gain) with reference to DC voltage.

$$A_v = (\text{Output voltage}) / (\text{Differential Input voltage})$$

#### 2.7 Input Common-mode Voltage Range (Vicm)

Indicates the input voltage range where IC normally operates.

#### 2.8 Common-mode Rejection Ratio (CMRR)

Indicates the ratio of fluctuation of input offset voltage when the input common mode voltage is changed. It is normally the fluctuation of DC.

$$CMRR = (\text{Change of Input common-mode voltage}) / (\text{Input offset fluctuation})$$

#### 2.9 Power Supply Rejection Ratio (PSRR)

Indicates the ratio of fluctuation of input offset voltage when supply voltage is changed.

It is normally the fluctuation of DC.

$$PSRR = (\text{Change of power supply voltage}) / (\text{Input offset fluctuation})$$

#### 2.10 Output Source Current/ Output Sink Current (Isource / Isink)

The maximum current that can be output from the IC under specific output conditions. The output source current indicates the current flowing out from the IC, and the output sink current indicates the current flowing into the IC.

#### 2.11 Slew Rate (SR)

Indicates the ratio of the change in output voltage with time when a step input signal is applied.

#### 2.12 Unity Gain Frequency (f<sub>T</sub>)

Indicates a frequency where the voltage gain of operational amplifier is 1.

#### 2.13 Phase Margin (θ)

Indicates the margin of phase from 180 degree phase lag at unity gain frequency.

#### 2.14 Total Harmonic Distortion+Noise (THD+N)

Indicates the fluctuation of input offset voltage or that of output voltage with reference to the change of output voltage of driven channel.

#### 2.15 Channel Separation (CS)

Indicates the fluctuation in the output voltage of the driven channel with reference to the change of output voltage of the channel which is not driven.

Typical Performance Curves

OBU7485G, BU7485SG




Figure 2. Derating curve




Figure 3. Derating curve




Figure 4. Supply Current – Supply Voltage




Figure 5. Supply Current – Ambient Temperature

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
 BU7485G: -40°C to +85°C BU7485SG: -40°C to +105°C



Typical Performance Curves - Continued

OBU7485G, BU7485SG




Figure 6.  
Maximum Output Voltage High –  
Supply Voltage  
( $R_L=10k\Omega$ )




Figure 7.  
Maximum Output Voltage High –  
Ambient Temperature  
( $R_L=10k\Omega$ )




Figure 8.  
Maximum Output Voltage Low –  
Supply Voltage  
( $R_L=10k\Omega$ )




Figure 9.  
Maximum Output Voltage Low –  
Ambient Temperature  
( $R_L=10k\Omega$ )

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7485G: -40°C to +85°C BU7485SG: -40°C to +105°C

Typical Performance Curves - Continued

OBU7485G, BU7485SG




Figure 10.  
Output Source Current – Output Voltage  
(VDD=3V)




Figure 11.  
Output Source Current – Ambient Temperature  
(OUT=VDD-0.4V)




Figure 12.  
Output Sink Current – Output Voltage  
(VDD=3V)




Figure 13.  
Output Sink Current – Ambient Temperature  
(OUT=VSS+0.4V)

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7485G: -40°C to +85°C BU7485SG: -40°C to +105°C

Typical Performance Curves - Continued

OBU7485G, BU7485SG




Figure 14.  
Input Offset Voltage – Supply Voltage  
(Vicm=VDD-1.4V, OUT=1.5V)




Figure 15.  
Input Offset Voltage – Ambient Temperature  
(Vicm=VDD-1.4V, OUT=1.5V)




Figure 16.  
Input Offset Voltage – Common Mode  
Input Voltage  
(VDD=3V)




Figure 17.  
Large Signal Voltage Gain – Supply Voltage

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7485G: -40°C to +85°C BU7485SG: -40°C to +105°C

Typical Performance Curves - Continued

OBU7485G, BU7485SG




Figure 18  
Large Signal Voltage Gain – Ambient Temperature




Figure 19.  
Common Mode Rejection Ratio – Supply Voltage




Figure 20.  
Common Mode Rejection Ratio – Ambient Temperature




Figure 21.  
Power Supply Rejection Ratio – Ambient Temperature

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7485G: -40°C to +85°C BU7485SG: -40°C to +105°C

Typical Performance Curves - Continued

OBU7485G, BU7485SG




Figure 22.  
Slew Rate L-H – Ambient Temperature




Figure 23.  
Slew Rate H-L – Ambient Temperature




Figure 24.  
Voltage Gain • Phase – Frequency

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7485G: -40°C to +85°C BU7485SG: -40°C to +105°C

Typical Performance Curves - Continued

OBU7486xxx, BU7486Sxxx




Figure 25.  
Derating curve




Figure 26.  
Derating curve




Figure 27.  
Supply Current – Supply Voltage




Figure 28.  
Supply Current – Ambient Temperature

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7486xxx: -40°C to +85°C BU7486Sxxx: -40°C to +105°C

Typical Performance Curves - Continued

OBU7486xxx, BU7486Sxxx




Figure 29.  
Maximum Output Voltage High –  
Supply Voltage  
(RL=10kΩ)




Figure 30.  
Maximum Output Voltage High –  
Ambient Temperature  
(RL=10kΩ)




Figure 31.  
Maximum Output Voltage Low –  
Supply Voltage  
(RL=10kΩ)




Figure 32.  
Maximum Output Voltage Low –  
Ambient Temperature  
(RL=10kΩ)

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7486xxx: -40°C to +85°C BU7486Sxxx: -40°C to +105°C

Typical Performance Curves - Continued

OBU7486xxx, BU7486Sxxx




Figure 33.  
Output Source Current – Output Voltage  
(VDD=3V)




Figure 34.  
Output Source Current – Ambient Temperature  
(OUT=VDD-0.4V)




Figure 35.  
Output Sink Current – Output Voltage  
(VDD=3V)




Figure 36.  
Output Sink Current – Ambient Temperature  
(OUT=VSS+0.4V)

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7486xxx: -40°C to +85°C BU7486Sxxx: -40°C to +105°C



Typical Performance Curves - Continued

OBU7486xxx, BU7486Sxxx




Figure 37.  
Input Offset Voltage – Supply Voltage




Figure 38.  
Input Offset Voltage – Ambient Temperature




Figure 39.  
Input Offset Voltage – Common Mode  
Input Voltage  
(VDD=3V)




Figure 40.  
Large Signal Voltage Gain – Supply Voltage

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7486xxx: -40°C to +85°C BU7486Sxxx: -40°C to +105°C

Typical Performance Curves - Continued

OBU7486xxx, BU7486Sxxx




Figure 41.  
Large Signal Voltage Gain – Ambient Temperature




Figure 42.  
Common Mode Rejection Ratio – Supply Voltage




Figure 43.  
Common Mode Rejection Ratio – Ambient Temperature




Figure 44.  
Power Supply Rejection Ratio – Ambient Temperature

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7486xxx: -40°C to +85°C BU7486Sxxx: -40°C to +105°C

Typical Performance Curves - Continued

OBU7486xxx, BU7486Sxxx




Figure 45.  
Slew Rate L-H – Ambient Temperature




Figure 46.  
Slew Rate H-L – Ambient Temperature




Figure 47.  
Voltage Gain • Phase—Frequency

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7486xxx: -40°C to +85°C BU7486Sxxx: -40°C to +105°C

Typical Performance Curves

OBU7487xx, BU7487Sxx




Figure 48.  
Derating curve




Figure 49.  
Derating curve




Figure 50.  
Supply Current – Supply Voltage




Figure 51.  
Supply Current – Ambient Temperature

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7487xx: -40°C to +85°C BU7487Sxx: -40°C to +105°C

Typical Performance Curves - Continued

OBU7487xx, BU7487Sxx




Figure 52.  
Maximum Output Voltage High – Supply Voltage  
(RL=10kΩ)




Figure 53.  
Maximum Output Voltage High – Ambient Temperature  
(RL=10kΩ)




Figure 54.  
Maximum Output Voltage Low – Supply Voltage  
(RL=10kΩ)




Figure 55.  
Maximum Output Voltage Low – Ambient Temperature  
(RL=10kΩ)

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7487xx: -40°C to +85°C BU7487Sxx: -40°C to +105°C

Typical Performance Curves - Continued

OBU7487xx, BU7487Sxx




Figure 56.  
Output Source Current – Output Voltage  
(VDD=3V)




Figure 57.  
Output Source Current – Ambient Temperature  
(OUT=VDD-0.4V)




Figure 58.  
Output Sink Current – Output Voltage  
(VDD=3V)




Figure 59.  
Output Sink Current – Ambient Temperature  
(OUT=VSS+0.4V)

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7487xx: -40°C to +85°C BU7487Sxx: -40°C to +105°C

Typical Performance Curves - Continued

OBU7487xx, BU7487Sxx




Figure 60.  
Input Offset Voltage – Supply Voltage




Figure 61.  
Input Offset Voltage – Ambient Temperature




Figure 62.  
Input Offset Voltage –  
Common Mode Input Voltage  
(VDD=3V)




Figure 63.  
Large Signal Voltage Gain – Supply Voltage

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7487xx: -40°C to +85°C BU7487Sxx: -40°C to +105°C

Typical Performance Curves - Continued

OBU7487xx, BU7487Sxx




Figure 64.

Large Signal Voltage Gain – Ambient Temperature




Figure 65.

Common Mode Rejection Ratio – Supply Voltage




Figure 66.

Common Mode Rejection Ratio – Ambient Temperature




Figure 67.

Power Supply Rejection Ratio – Ambient Temperature

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
 BU7487xx: -40°C to +85°C BU7487Sxx: -40°C to +105°C



Typical Performance Curves - Continued

OBU7487xx, BU7487Sxx




Figure 68.  
Slew Rate L-H – Ambient Temperature




Figure 69.  
Slew Rate H-L – Ambient Temperature




Figure 70.  
Voltage Gain · Phase – Frequency

(\*)The above characteristics are measurements of typical sample, they are not guaranteed.  
BU7487xx: -40°C to +85°C BU7487Sxx: -40°C to +105°C

Application Information

NULL method condition for Test circuit1

VDD, VSS, EK, Vicm Unit:V

| Parameter  | VF  | S1 | S2 | S3  | VDD | VSS | EK   | Vicm | Calculation |
|--|-----|----|----|-----|-----|-----|------|------|-------------|
| Input Offset Voltage   | VF1 | ON | ON | OFF | 3   | 0   | -1.5 | 1.8  | 1           |
| Large Signal Voltage Gain  | VF2 | ON | ON | ON  | 3   | 0   | -0.5 | 0.9  | 2           |
|  | VF3 |    |    |     |     |     | -2.5 |      |             |
| Common-mode Rejection Ratio<br>(Input Common-mode Voltage Range) | VF4 | ON | ON | OFF | 3   | 0   | -1.5 | 0    | 3           |
|  | VF5 |    |    |     |     |     | -1.5 | 1.8  |             |
| Power Supply Rejection Ratio                                     | VF6 | ON | ON | OFF | 3   | 0   | -0.9 | 0    | 4           |
|  | VF7 |    |    |     | 5.5 |     |      |      |             |

—Calculation—

1. Input Offset Voltage ( $V_{io}$ ) 
$$V_{io} = \frac{|VF1|}{1+RF/RS} [V]$$
2. Large Signal Voltage Gain ( $A_v$ ) 
$$A_v = 20\text{Log} \frac{2 \times (1+RF/RS)}{|VF2-VF3|} [dB]$$
3. Common-mode Rejection Ratio (CMRR) 
$$\text{CMRR} = 20\text{Log} \frac{1.8 \times (1+RF/RS)}{|VF4 - VF5|} [dB]$$
4. Power Supply Rejection Ratio (PSRR) 
$$\text{PSRR} = 20\text{Log} \frac{2.5 \times (1+ RF/RS)}{|VF6 - VF7|} [dB]$$




Figure 71. Test circuit 1 (one channel only)

Switch Condition for Test circuit2

| SW No.                         | SW1 | SW2 | SW3 | SW4 | SW5 | SW6 | SW7 | SW8 | SW9 | SW10 | SW11 | SW12 |
|--------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|
| Supply Current                 | OFF | OFF | ON  | OFF | ON  | OFF | OFF | OFF | OFF | OFF  | OFF  | OFF  |
| Maximum Output Voltage RL=10kΩ | OFF | ON  | OFF | OFF | ON  | OFF | OFF | ON  | OFF | OFF  | ON   | OFF  |
| Output Current                 | OFF | ON  | OFF | OFF | ON  | OFF | OFF | OFF | OFF | ON   | OFF  | OFF  |
| Slew Rate                      | OFF | OFF | ON  | OFF | OFF | OFF | ON  | OFF | ON  | OFF  | OFF  | ON   |
| Unity Gain Frequency           | ON  | OFF | OFF | ON  | ON  | OFF | OFF | OFF | ON  | OFF  | OFF  | ON   |




Figure 72. Test circuit 2




Figure 73. Slew rate input output wave





Figure 74. Test circuit 3 (Channel Separation)

**Application example**

○Voltage follower




Voltage gain is 0dB.

Using this circuit, the output voltage (OUT) is configured to be equal to the input voltage (IN). This circuit also stabilizes the output voltage (OUT) due to high input impedance and low output impedance. Computation for output voltage (OUT) is shown below.

$$OUT=IN$$

Figure 75. Voltage follower

○Inverting amplifier




For inverting amplifier, input voltage (IN) is amplified by a voltage gain and depends on the ratio of R1 and R2. The out-of-phase output voltage is shown in the next expression

$$OUT=-(R2/R1) \cdot IN$$

This circuit has input impedance equal to R1.

Figure 76. Inverting amplifier circuit

○Non-inverting amplifier



For non-inverting amplifier, input voltage (IN) is amplified by a voltage gain, which depends on the ratio of R1 and R2. The output voltage (OUT) is in-phase with the input voltage (IN) and is shown in the next expression.

$$OUT=(1 + R2/R1) \cdot IN$$

Effectively, this circuit has high input impedance since its input side is the same as that of the operational amplifier.

Figure 77. Non-inverting amplifier circuit

**Power Dissipation**

Power dissipation (total loss) indicates the power that the IC can consume at Ta=25°C (normal temperature). As the IC consumes power, it heats up, causing its temperature to be higher than the ambient temperature. The allowable temperature that the IC can accept is limited. This depends on the circuit configuration, manufacturing process, and consumable power.

Power dissipation is determined by the allowable temperature within the IC (maximum junction temperature) and the thermal resistance of the package used (heat dissipation capability). Maximum junction temperature is typically equal to the maximum storage temperature. The heat generated through the consumption of power by the IC radiates from the mold resin or lead frame of the package. Thermal resistance, represented by the symbol  $\theta_{ja}$ °C/W, indicates this heat dissipation capability. Similarly, the temperature of an IC inside its package can be estimated by thermal resistance.

Figure 78. (a) shows the model of the thermal resistance of a package. The equation below shows how to compute for the Thermal resistance ( $\theta_{ja}$ ), given the ambient temperature (Ta), maximum junction temperature (Tjmax), and power dissipation (Pd).

$$\theta_{ja} = (T_{jmax} - T_a) / P_d \quad \text{°C/W} \quad \dots \quad (I)$$

The Derating curve in Figure 78. (b) indicates the power that the IC can consume with reference to ambient temperature. Power consumption of the IC begins to attenuate at certain temperatures. This gradient is determined by Thermal resistance ( $\theta_{ja}$ ), which depends on the chip size, power consumption, package, ambient temperature, package condition, wind velocity, etc. This may also vary even when the same of package is used. Thermal reduction curve indicates a reference value measured at a specified condition. Figure 79. (c) to (h) shows an example of the derating curve for BU7485G, BU7485SG, BU7486xxx, BU7486Sxxx, BU7487xx, BU7487Sxx.










Figure 78. Thermal resistance and Derating Curve





| (*19) | (*20) | (*21) | (*22) | (*23) | (*24) | Unit  |
|-------|-------|-------|-------|-------|-------|-------|
| 5.4   | 5.5   | 5.0   | 4.7   | 7.0   | 4.5   | mW/°C |

When using the unit above Ta=25°C, subtract the value above per degree °C. Power dissipation is the value when FR4 glass epoxy board 70mm × 70mm × 1.6mm (copper foil area below 3%) is mounted.

Figure 79. Derating Curve

**Operational Notes**

1) Unused circuits

When there are unused circuits, it is recommended that they are connected as in Figure .56, setting the non-inverting input terminal to a potential within the in-phase input voltage range ( $V_{icm}$ ).

2) Input voltage

Applying  $V_{SS}-0.3V$  to  $V_{DD}+0.3V$  to the input terminal is possible without causing deterioration of the electrical characteristics or destruction, regardless of the supply voltage. However, this does not ensure normal circuit operation. Please note that the circuit operates normally only when the input voltage is within the common mode input voltage range of the electric characteristics.

3) Power supply (single / dual)

The op-amp operates when the voltage supplied is between  $V_{DD}$  and  $V_{SS}$ . Therefore, the single supply op-amp can be used as dual supply op-amp as well.

4) Power Dissipation ( $P_d$ )

Using the unit in excess of the rated power dissipation may cause deterioration in electrical characteristics including reduced current capability due to the rise of chip temperature. Therefore, please take into consideration the power dissipation ( $P_d$ ) under actual operating conditions and apply a sufficient margin in thermal design. Refer to the thermal derating curves for more information.

5) Short-circuit between pins and erroneous mounting

Be careful when mounting the IC on printed circuit boards. The IC may be damaged if it is mounted in a wrong orientation or if pins are shorted together. Short circuit may be caused by conductive particles caught between the pins.

6) Operation in a strong electromagnetic field

Operating the IC in the presence of a strong electromagnetic field may cause the IC to malfunction.

7) IC handling

Applying mechanical stress to the IC by deflecting or bending the board may cause fluctuations of the electrical characteristics due to piezo resistance effects.

8) Board Inspection

Connecting a capacitor to a pin with low impedance may stress the IC. Therefore, discharging the capacitor after every process is recommended. In addition, when attaching and detaching the jig during the inspection phase, make sure that the power is turned OFF before inspection and removal. Furthermore, please take measures against ESD in the assembly process as well as during transportation and storage.

9) Output capacitor

If a large capacitor is connected between the output pin and  $V_{SS}$  pin, current from the charged capacitor will flow into the output pin and may destroy the IC when the  $V_{CC}$  pin is shorted to ground or pulled down to 0V. Use a capacitor smaller than 0.1 $\mu$ F between output pin and  $V_{SS}$  pin.

10) Oscillation by output capacitor

Please pay attention to the oscillation by output capacitor and in designing an application of negative feedback loop circuit with these ICs.

11) Latch up

Be careful of input voltage that exceed the  $V_{DD}$  and  $V_{SS}$ . When CMOS device have sometimes occur latch up and protect the IC from abnormaly noise.





Figure 80. Example of application circuit for unused op-amp


Physical Dimensions Tape and Reel Information

|              |       |
|--------------|-------|
| Package Name | SSOP5 |
|--------------|-------|




< Tape and Reel Information >

|                   |   |
|-------------------|---|
| Tape              | Embossed carrier tape   |
| Quantity          | 3000pcs   |
| Direction of feed | TR<br>( The direction is the 1pin of product is at the upper right when you hold )<br>reel on the left hand and you pull out the tape on the right hand |







Package Name SOP8



(UNIT : mm)  
 PKG : SOP8  
 Drawing No. : EX112-5001-1



Package Name SSOP-B8





(UNIT : mm)  
 PKG : SSOP-B8  
 Drawing No. EX151-5002

<Tape and Reel information>




|                   |   |
|-------------------|---|
| Tape              | Embossed carrier tape   |
| Quantity          | 2500pcs   |
| Direction of feed | E2<br>(The direction is the 1pin of product is at the upper left when you hold reel on the left hand and you pull out the tape on the right hand) |

Diagram of a carrier tape showing the direction of feed and the location of pin 1. The tape is shown with multiple packages, and an arrow indicates the 'Direction of feed' from left to right. A specific pin is labeled '1pin'. A note below the diagram states: '\*Order quantity needs to be multiple of the minimum quantity.'

Package Name MSOP8



|              |       |
|--------------|-------|
| Package Name | SOP14 |
|--------------|-------|






(UNIT : mm)  
 PKG : SOP14  
 Drawing No. : EX113-5001

<Tape and Reel information>

|                   |   |
|-------------------|---|
| Tape              | Embossed carrier tape   |
| Quantity          | 2500pcs   |
| Direction of feed | E2<br>( The direction is the 1pin of product is at the upper left when you hold reel on the left hand and you pull out the tape on the right hand ) |

1pin  
 \*Order quantity needs to be multiple of the minimum quantity.

|              |          |
|--------------|----------|
| Package Name | SSOP-B14 |
|--------------|----------|



(UNIT : mm)

PKG : SSOP-B14

Drawing No. EX152-5002

<Tape and Reel information>

|                   |   |
|-------------------|---|
| Tape              | Embossed carrier tape   |
| Quantity          | 2500pcs   |
| Direction of feed | E2<br>( The direction is the 1pin of product is at the upper left when you hold reel on the left hand and you pull out the tape on the right hand ) |







Reel

1 pin

Direction of feed

\*Order quantity needs to be multiple of the minimum quantity.



Marking Diagram



| Product Name |     | Package Type | Marking  |
|--------------|-----|--------------|----------|
| BU7485       | G   | SSOP5        | D5       |
| BU7485S      |     |              | FC       |
| BU7486       | F   | SOP8         | 7486     |
|              | FV  | SSOP-B8      |          |
|              | FVM | MSOP8        |          |
| BU7486S      | F   | SOP8         | 7486S    |
|              | FV  | SSOP-B8      | 486S     |
|              | FVM | MSOP8        | 7486S    |
| BU7487       | F   | SOP14        | BU7487F  |
|              | FV  | SSOP-B14     | 7487     |
| BU7487S      | F   | SOP14        | BU7487SF |
|              | FV  | SSOP-B14     | 7487S    |

Land pattern data

| PKG                 | Land pitch<br>e | Land space<br>MIE | Land length<br>$\geq \ell 2$ | Unit: mm         |
|---------------------|-----------------|-------------------|------------------------------|------------------|
|                     |                 |                   |                              | Land width<br>b2 |
| SSOP5               | 0.95            | 2.4               | 1.0                          | 0.6              |
| SOP8<br>SOP14       | 1.27            | 4.60              | 1.10                         | 0.76             |
| SSOP-B8<br>SSOP-B14 | 0.65            | 4.60              | 1.20                         | 0.35             |
| MSOP8               | 0.65            | 2.62              | 0.99                         | 0.35             |



Revision History

| Date        | Revision | Changes     |
|-------------|----------|-------------|
| 12.JUL.2013 | 001      | New Release |

# Notice

## ●General Precaution

- 1) Before you use our Products, you are requested to carefully read this document and fully understand its contents. ROHM shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any ROHM's Products against warning, caution or note contained in this document.
- 2) All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using ROHM's Products, please confirm the latest information with a ROHM sales representative.

## ●Precaution on using ROHM Products

- 1) Our Products are designed and manufactured for application in ordinary electronic equipments (such as AV equipment, OA equipment, telecommunication equipment, home electronic appliances, amusement equipment, etc.). If you intend to use our Products in devices requiring extremely high reliability (such as medical equipment, transport equipment, traffic equipment, aircraft/spacecraft, nuclear power controllers, fuel controllers, car equipment including car accessories, safety devices, etc.) and whose malfunction or failure may cause loss of human life, bodily injury or serious damage to property ("Specific Applications"), please consult with the ROHM sales representative in advance. Unless otherwise agreed in writing by ROHM in advance, ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties arising from the use of any ROHM's Products for Specific Applications.
- 2) ROHM designs and manufactures its Products subject to strict quality control system. However, semiconductor products can fail or malfunction at a certain rate. Please be sure to implement, at your own responsibilities, adequate safety measures including but not limited to fail-safe design against the physical injury, damage to any property, which a failure or malfunction of our Products may cause. The following are examples of safety measures:
  - [a] Installation of protection circuits or other protective devices to improve system safety
  - [b] Installation of redundant circuits to reduce the impact of single or multiple circuit failure
- 3) Our Products are designed and manufactured for use under standard conditions and not under any special or extraordinary environments or conditions, as exemplified below. Accordingly, ROHM shall not be in any way responsible or liable for any damages, expenses or losses arising from the use of any ROHM's Products under any special or extraordinary environments or conditions. If you intend to use our Products under any special or extraordinary environments or conditions (as exemplified below), your independent verification and confirmation of product performance, reliability, etc. prior to use, must be necessary:
  - [a] Use of our Products in any types of liquid, including water, oils, chemicals, and organic solvents
  - [b] Use of our Products outdoors or in places where the Products are exposed to direct sunlight or dust
  - [c] Use of our Products in places where the Products are exposed to sea wind or corrosive gases, including Cl<sub>2</sub>, H<sub>2</sub>S, NH<sub>3</sub>, SO<sub>2</sub>, and NO<sub>2</sub>
  - [d] Use of our Products in places where the Products are exposed to static electricity or electromagnetic waves
  - [e] Use of our Products in proximity to heat-producing components, plastic cords, or other flammable items
  - [f] Sealing or coating our Products with resin or other coating materials
  - [g] Use of our Products without cleaning residue of flux (even if you use no-clean type fluxes, cleaning residue of flux is recommended); or Washing our Products by using water or water-soluble cleaning agents for cleaning residue after soldering
  - [h] Use of the Products in places subject to dew condensation
- 4) The Products are not subject to radiation-proof design.
- 5) Please verify and confirm characteristics of the final or mounted products in using the Products.
- 6) In particular, if a transient load (a large amount of load applied in a short period of time, such as pulse) is applied, confirmation of performance characteristics after on-board mounting is strongly recommended. Avoid applying power exceeding normal rated power; exceeding the power rating under steady-state loading condition may negatively affect product performance and reliability.
- 7) De-rate Power Dissipation (Pd) depending on Ambient temperature (Ta). When used in sealed area, confirm the actual ambient temperature.
- 8) Confirm that operation temperature is within the specified range described in the product specification.
- 9) ROHM shall not be in any way responsible or liable for failure induced under deviant condition from what is defined in this document.



**●Precaution for Mounting / Circuit board design**

- 1) When a highly active halogenous (chlorine, bromine, etc.) flux is used, the residue of flux may negatively affect product performance and reliability.
- 2) In principle, the reflow soldering method must be used; if flow soldering method is preferred, please consult with the ROHM representative in advance.

For details, please refer to ROHM Mounting specification

**●Precautions Regarding Application Examples and External Circuits**

- 1) If change is made to the constant of an external circuit, please allow a sufficient margin considering variations of the characteristics of the Products and external components, including transient characteristics, as well as static characteristics.
- 2) You agree that application notes, reference designs, and associated data and information contained in this document are presented only as guidance for Products use. Therefore, in case you use such information, you are solely responsible for it and you must exercise your own independent verification and judgment in the use of such information contained in this document. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties arising from the use of such information.

**●Precaution for Electrostatic**

This Product is electrostatic sensitive product, which may be damaged due to electrostatic discharge. Please take proper caution in your manufacturing process and storage so that voltage exceeding the Products maximum rating will not be applied to Products. Please take special care under dry condition (e.g. Grounding of human body / equipment / solder iron, isolation from charged objects, setting of Ionizer, friction prevention and temperature / humidity control).

**●Precaution for Storage / Transportation**

- 1) Product performance and soldered connections may deteriorate if the Products are stored in the places where:
  - [a] the Products are exposed to sea winds or corrosive gases, including Cl<sub>2</sub>, H<sub>2</sub>S, NH<sub>3</sub>, SO<sub>2</sub>, and NO<sub>2</sub>
  - [b] the temperature or humidity exceeds those recommended by ROHM
  - [c] the Products are exposed to direct sunshine or condensation
  - [d] the Products are exposed to high Electrostatic
- 2) Even under ROHM recommended storage condition, solderability of products out of recommended storage time period may be degraded. It is strongly recommended to confirm solderability before using Products of which storage time is exceeding the recommended storage time period.
- 3) Store / transport cartons in the correct direction, which is indicated on a carton with a symbol. Otherwise bent leads may occur due to excessive stress applied when dropping of a carton.
- 4) Use Products within the specified time after opening a humidity barrier bag. Baking is required before using Products of which storage time is exceeding the recommended storage time period.

**●Precaution for Product Label**

QR code printed on ROHM Products label is for ROHM's internal use only.

**●Precaution for Disposition**

When disposing Products please dispose them properly using an authorized industry waste company.

**●Precaution for Foreign Exchange and Foreign Trade act**

Since our Products might fall under controlled goods prescribed by the applicable foreign exchange and foreign trade act, please consult with ROHM representative in case of export.

**●Precaution Regarding Intellectual Property Rights**

- 1) All information and data including but not limited to application example contained in this document is for reference only. ROHM does not warrant that foregoing information or data will not infringe any intellectual property rights or any other rights of any third party regarding such information or data. ROHM shall not be in any way responsible or liable for infringement of any intellectual property rights or other damages arising from use of such information or data.:
- 2) No license, expressly or implied, is granted hereby under any intellectual property rights or other rights of ROHM or any third parties with respect to the information contained in this document.

● **Other Precaution**

- 1) The information contained in this document is provided on an "as is" basis and ROHM does not warrant that all information contained in this document is accurate and/or error-free. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties resulting from inaccuracy or errors of or concerning such information.
- 2) This document may not be reprinted or reproduced, in whole or in part, without prior written consent of ROHM.
- 3) The Products may not be disassembled, converted, modified, reproduced or otherwise changed without prior written consent of ROHM.
- 4) In no event shall you use in any way whatsoever the Products and the related technical information contained in the Products or this document for any military purposes, including but not limited to, the development of mass-destruction weapons.
- 5) The proper names of companies or products described in this document are trademarks or registered trademarks of ROHM, its affiliated companies or third parties.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А