



Thin Film Platinum RTDs
HEL-700 Series



Thin Film Platinum RTDs

The HEL-700 Series Thin Film Platinum RTDs (Resistance Temperature Detectors) are designed to monitor or control critical temperatures in industrial applications. They provide a linear change in resistance versus temperature, combining high linearity, stability, accuracy, and wide temperature range in a small, fast-response package.

The HEL-700 Series is designed to measure temperatures from -75 °C to 540 °C [-100 °F to 1000 °F] with high accuracy. These fully-assembled elements are ready-to-use in probe assemblies, without the need for fragile splices to extension leads.

These products are manufactured using a thin layer of platinum deposited on an alumina substrate and are laser trimmed to a resistance interchangeability of a standard $\pm 0.2\%$ (± 0.5 °C accuracy) or optional $\pm 0.1\%$ (± 0.3 °C accuracy). The sensor chip is then glassed, wired and potted or ceramic fired to result in a cylindrical alumina package with either TFE Teflon®- or fiberglass-insulated lead wires.

Key Features

- Wide temperature range
- Interchangeable
- Accurate
- Linear resistance vs temperature
- Fast response
- Laser trimmed
- Ceramic case material
- TFE Teflon® or fiberglass leadwires
- Multiple small sizes
- Ready-to-use, fully assembled elements

Potential Applications

Temperature sensing for monitoring, compensation and regulation in:

INDUSTRIAL

- HVAC equipment
- Instrument and probe assemblies
- Process control
- Motor windings and bearings
- Battery packs
- Environmental chambers
- Ovens and kilns
- Drill holes in large objects

MEDICAL

- Autoclaves

AEROSPACE/DEFENSE

- Aircraft
- Space vehicles

WIDE TEMPERATURE RANGE • INTERCHANGEABLE • ACCURATE

Thin Film Platinum RTDs, HEL-700 Series

Table 1. Specifications

| Characteristic | Condition | Parameter |
|---|--------------------------------|---|
| Alpha: R ₀ = 1000 Ω R ₀ = 100 Ω | 0 °C | 0.00375 Ω/Ω/°C 0.00385 Ω/Ω/°C |
| Temperature range: TFE Teflon fiberglass | — | -70 °C to 260 °C [-94 °F to 500 °F] -75 °C to 540 °C [-100 °F to 1000 °F] |
| Temperature accuracy: R ₀ ±0.2% trim (standard) R ₀ ±0.1% trim (optional) | — | ±0.5°C or 0.8% of temperature, whichever is greater ±0.3°C or 0.6% of temperature, whichever is greater |
| Base resistance and interchangeability, R ₀ ±ΔR ₀ : R ₀ ±0.2% trim (standard) R ₀ ±0.1% trim (optional) | 0 °C | 1000 Ω ±2 Ω 1000 Ω ±1 Ω |
| Linearity: -40 °C to 125 °C -75 °C to 540 °C | — | ±0.1% of full scale ±2.0% of full scale |
| Time constant | water at 3 ft/s still water | <0.5 s for 0.086 in O.D. <1.0 s for 0.086 in O.D. |
| Operating current | — | 2 mA max. minimal self heating errors of 1 °C; 1 mA recommended |
| Stability | occupied environments | <0.25 °C /year; 0.05 °C /5 years |
| Self heating | — | <15 mW/°C typ. for 0.086 in O.D. |
| Insulation resistance | 50 Vdc at 25 °C | >50 MΩ |
| Construction/material: case Teflon [®] -insulated leads fiberglass-insulated leads | — | high purity alumina nickel-coated stranded copper, epoxy potting nickel-coated stranded copper, ceramic potting |

Table 2. Constant Values (β = 0 and C = 0 for T > 0 °C)

| Constant | 1000 Ω | 100 Ω | Functional Behavior |
|-----------------------------|--------------------------|----------------------------|---|
| Alpha α (°C ⁻¹) | 0.00375 ±0.000029 | 0.003850 ±0.000010 | $R_T = R_0(1 + AT + BT^2 - 100CT^3 + CT^4)$ Where: R _T = Resistance (Ω) at temperature T (°C) R ₀ = Resistance (Ω) at 0 °C T = Temperature (°C) $A = \alpha + \frac{\alpha\delta}{100}$ $B = -\frac{\alpha\delta}{100^2}$ $C_{T<0} = -\frac{\alpha\beta}{100^4}$ |
| Delta δ (°C) | 1.605 ±0.009 | 1.4999 ±0.007 | |
| Beta β (°C) | 0.16 | 0.10863 | |
| A (°C ⁻¹) | 3.81 x 10 ⁻³ | 3.908 x 10 ⁻³ | |
| B (°C ⁻²) | -6.02 x 10 ⁻⁷ | -5.775 x 10 ⁻⁷ | |
| C (°C ⁻⁴) | -6.0 x 10 ⁻¹² | -4.183 x 10 ⁻¹² | |

CAUTION

PRODUCT DAMAGE

- Ensure proper ESD (Electrostatic Discharge) precautions are followed when handling this product.

Failure to comply with these instructions may result in product damage.

Thin Film Platinum RTDs, HEL-700 Series

Table 3. Accuracy vs Temperature

| Temperature (°C) | Tolerance | | | |
|------------------|-----------------------|----------|-----------------------|----------|
| | Standard Trim (±0.2%) | | Optional Trim (±0.1%) | |
| | ±ΔR ¹ (Ω) | ±ΔT (°C) | ±ΔR ¹ (Ω) | ±ΔT (°C) |
| -100 | 2.9 | 0.8 | 2.4 | 0.6 |
| 0 | 2.0 | 0.5 | 1.0 | 0.3 |
| 100 | 2.9 | 0.8 | 2.2 | 0.6 |
| 200 | 5.6 | 1.6 | 4.3 | 1.2 |
| 300 | 8.2 | 2.4 | 6.2 | 1.8 |
| 400 | 11.0 | 3.2 | 8.3 | 2.5 |
| 500 | 12.5 | 4.0 | 9.6 | 3.0 |
| 600 | 15.1 | 4.8 | 10.4 | 3.3 |

¹1000 Ω RTD. Divide Δ by 10 for 100 Ω RTD.

Table 4. NIST Calibration

| Temperature (°C) | Standard Temperature Point (±ΔT (°C)) | | |
|------------------|---------------------------------------|------|------|
| | 1 | 2 | 3 |
| -100 | 0.5 | 0.27 | 0.15 |
| 0 | 0.03 | 0.03 | 0.03 |
| 100 | 0.4 | 0.11 | 0.07 |
| 200 | 0.8 | 0.02 | 0.08 |
| 300 | 1.2 | 0.33 | 6.2 |
| 400 | 1.6 | 0.5 | 8.3 |
| 500 | 2.0 | 0.8 | 9.6 |
| 600 | 2.6 | 1.2 | 10.4 |

¹NIST-traceable calibration provides resistance readings at 1, 2 or 3 standard temperature points to yield a resistance versus temperature curve with 10x better accuracy.

Figure 1. Resistance vs Temperature



Figure 2. Nomenclature and Ordering Guide

For example, a **HEL-705-U-0-12-C1** part number defines an HEL-700 Series Thin Film RTD with two, 28 gauge TFE Teflon[®] insulated leadwires, an alpha of 1000 Ω: 0.00375 Ω/Ω/°C, a standard ±0.2% trim resistance, 12 inch leadwires, and a NIST calibration report at 0 °C.

| HEL- | 705- | U- | 0- | 12- | C1 |
|--|--|---|--------------------------|---------------------|--------------------------------------|
| Product Series | Leadwire Insulation Material, Gauge and Number | Resistance and Alpha | Resistance Trim | Leadwire Length | NIST Calibration Report |
| HEL-700 Series Thin Film Platinum RTDs | 705 TFE Teflon [®] , 28 gauge; 1000 Ω: 2-wire, 100 Ω: 2-wire | U 1000 Ω: 0.00375 Ω/Ω/°C | 0 Standard: ±0.2% | 12 12 inches | 00 none |
| | 707 fiberglass, 28 gauge; 1000 Ω: 2-wire, 100 Ω: 2-wire | T 100 Ω: 0.00385 Ω/Ω/°C (DIN Standard) | 1 Optional: ±0.1% | | C1 at 0 °C |
| | 711 TFE Teflon [®] , 28 gauge; 1000 Ω: 2-wire, 100 Ω: 3-wire | | | | C2 at 0 °C and 100 °C |
| | 712 fiberglass, 28 gauge; 1000 Ω: 2-wire, 100 Ω: 3-wire | | | | C3 at 0 °C, 100 °C and 260 °C |
| | 716 TFE Teflon [®] , 24 gauge; 1000 Ω: 2-wire, 100 Ω: 3-wire | | | | |
| | 717 fiberglass, 24 gauge; 1000 Ω: 2-wire, 100 Ω: 3-wire | | | | |

Thin Film Platinum RTDs, HEL-700 Series

Figure 3. All Available Standard Configurations



Figure 4. Dimensional Drawings (For reference only: mm [in].)



Thin Film Platinum RTDs, HEL-700 Series

Figure 5. Circuits

Wheatstone Bridge 2-Wire Interface



Linear Output Voltage



Adjustable Point (Comparator) Interface



ADDITIONAL INFORMATION

The following associated literature is available at sensing.honeywell.com:

- Temperature Sensors Line Guide
- Thermal Sensors Range Guide

⚠ WARNING **PERSONAL INJURY**

DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

⚠ WARNING **MISUSE OF DOCUMENTATION**

- The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

Sales and Service

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office or email us at info.sc@honeywell.com. Visit us on the Web at sensing.honeywell.com

Phone and Fax:

| | |
|---------------|---|
| Asia Pacific | +65 6355-2828 +65 6445-3033 Fax |
| Europe | +44 (0) 1698 481481 +44 (0) 1698 481676 Fax |
| Latin America | +1-305-805-8188 +1-305-883-8257 Fax |
| USA/Canada | +1-800-537-6945 +1-815-235-6847 +1-815-235-6545 Fax |

Sensing and Control
Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422
honeywell.com

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell website, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

Honeywell

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А