

PRINTING RIBBONS AND INKS TECHNICAL DATASHEET

TTDS-257 Revision 6, March 2016

Section 1, Contents

| SECTION | PAGE | SECTION DESCRIPTION | COLOUR AND TYPE |
|-----------|------------|---|---|
| Section 1 | Page 1 | CONTENTS | |
| Section 2 | Page 2 | 1966-RIBBONS, 2000P-4TT, T300-RIBBON-UV-SCE | BLACK THERMAL TRANSFER |
| Section 3 | Page 3 | TMS-XXX-RIBBON-XXX | BLACK THERMAL TRANSFER |
| Section 4 | Page 4 & 5 | TTB-XXXX/XXX | BLACK THERMAL TRANSFER |
| Section 5 | Page 6 & 7 | 1330-XXXX-XX | BLACK THERMAL TRANSFER |
| Section 6 | Page 8 & 9 | WHITE & SILVER | WHITE & SILVER THERMAL TRANSFER |
| Section 7 | Page 10 | BTT-02 CARD PRINTER | BLUE, RED, BLACK AND WHITE THERMAL TRANSFER |
| Section 8 | Page 11 | DOT MATRIX | BLACK INK CARTRIDGES |

PAGE 1

Section 2, BLACK 1966-RIBBONS, 2000P-4TT, T300-RIBBON-UV-SCE

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|---------------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| 1966-RIBBON | F55931-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 100mm (3.9 inches) | 25.4mm (1 inch) | Ink side out | Black |
| LBF-2000P-RIBBON-1966-MED | 6-1768383-4 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side out | Black |
| T200-RIBBON-1966 | D60849-000 | 3 years, when stored between -5°C (23°F) and 40° (104°F) | 74m (242 feet) | 110mm (4.3 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| 2000P-RIBBON-4TT-MED | 893803-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 2000P-RIBBON-4TT-NAR | 277493-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 40mm (1.57 inches) | 25.4mm (1 inch) | Ink side out | Black |
| T300-UV-SCE-RIBBON | EC8932-000 | 1 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |

Section 3, BLACK TMS THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|-----------------------|-------------|---|---------------------|------------------------|----------------------|--------------|--------|
| TMS-RJS-RIBBON-4DSCE | 311292-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 450m (1476 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TMS-101-RIBBON-4DSCE | 505478-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| TMS-RJS-RIBBON-4RPSCE | 557721-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TMS-101-RIBBON-4RPSCE | 310109-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| TMS-RJS-RIBBON-4HT | 754073-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TMS-101-RIBBON-4HT | 746617-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |

Section 4, BLACK TTB THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|--------------------|-------------|--|---------------------|------------------------|--------------------|--------------|--------|
| TTB-060SC/300 | 2-1768049-6 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-076SC/300 | 3-1768049-0 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 76mm (3 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-084SC/300 | C75514-000 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 84mm (3.3 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-110SC/300 | 3-1768049-6 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-128SC/450 | 4-1768049-1 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 450m (1476 feet) | 128mm (5.04 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TTB-170SC/450 | 4-1768049-7 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 450m (1476 feet) | 170mm (6.70 inches) | 25.4mm (1 inch) | Ink side out | Black |

Section 4, BLACK TTB THERMAL TRANSFER RIBBONS (Continued)

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|---------------------|-------------|--|---------------------|------------------------|--------------------|--------------|--------|
| TTB-110SC/300WH | 3-1768049-8 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 110mm (4.30 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-060SC/450AQ529 | 2-1768049-7 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 450m (1476 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-090SC/360-AQ529 | 3-1768049-4 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 360m (1181 feet) | 90mm (3.54 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-110SC/300AQ529S | 3-1768049-7 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TTB-114SC/360AQ529 | 4-1768049-0 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 360m (984 feet) | 114mm (4.48 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TTB-166SC/360AQ529 | 8-1768402-6 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 360m (1181 feet) | 166mm (6.53 inches) | 25.4mm (1 inch) | Ink side out | Black |

Section 5, BLACK 1330 THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|--------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| 1330-0600-10 | 143060-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0600-T200 | C36369-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| 1330-TTB-T200 | 1-1768384-8 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| 1330-3300-15 | 562492-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 165mm (6.5 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-3300-10 | 980892-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.3 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-3300-08 | 728382-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 80mm (3.15 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-3300-06 | F31906-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 64mm (2.52 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-3300-101TT | C95590-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.3 inches) | 12.7mm (1/2 inch) | Ink side out | Black |

Section 5, BLACK 1330 THERMAL TRANSFER RIBBONS (Continued)

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|--------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| 1330-0607-10 | 742412-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0607-08 | 555080-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 80mm (3.15 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0607-T200 | E45478-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| 1330-0619-10 | 952888-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0619-08 | F65920-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 83mm (3.27 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0619-T200 | C49013-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |

Section 6, WHITE and SILVER THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|----------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| T300-RIBBON-WH-4HT | 154739-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | White |
| T200-RIBBON-WH-4HT | 086961-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | White |
| T300-RIBBON-WH | 650784-000 | 2 year, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | White |
| T200-RIBBON-WH | 117366-000 | 2 year, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | White |
| 2000P-RIBBON-WH-MED | 094514-000 | 2 year, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side out | White |
| 2000P-RIBBON-WH-NAR | 530304-000 | 2 year, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 40mm (1.57 inches) | 25.4mm (1 inch) | Ink side out | White |
| RIB-1976-076360-0L-9 | 1-2186321-1 | 1 years, when stored between -5°C (23°F) and 40°C (104°F) | 360m | 76mm | 25.4mm | Ink side out | White |
| RIB-1976-110300-0L-9 | 1-2186043-1 | 1 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m | 110mm | 25.4mm | Ink side out | White |

Section 6, WHITE and SILVER THERMAL TRANSFER RIBBONS (Continued)

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|----------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| TMS-RJS-RIBBON-4AG | 124503-000 | 5 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Silver |
| TMS-101-RIBBON-4AG | 252557-000 | 5 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Silver |
| 2000P-RIBBON-4AG-MED | 351013-000 | 5 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side out | Silver |
| 2000P-RIBBON-4AG-NAR | 346933-000 | 5 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 40mm (1.57 inches) | 25.4mm (1 inch) | Ink side out | Silver |

Section 7, BTT-02 CARD PRINTER THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|--------------------|-------------|---|--------------------|-----------------------|----------------------|--------------|--------|
| BBB-060BL/200 | 1-1768016-1 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 200m (656 feet) | 60mm (2.36 inches) | 12.7mm (1/2 inch) | Ink side out | Blue |
| BBB-060RT/200 | 1-1768016-3 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 200m (656 feet) | 60mm (2.36 inches) | 12.7mm (1/2 inch) | Ink side out | Red |
| BBB-060SC/200 | 1-1768016-4 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 200m (656 feet) | 60mm (2.36 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| BBB-060WE/200 | 1-1768016-5 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 200m (656 feet) | 60mm (2.36 inches) | 12.7mm (1/2 inch) | Ink side out | White |

Section 8, DOT MATRIX INK CARTRIDGES

| Ribbon Description | Part number | Shelf life and storage conditions | Colour |
|---------------------------|-------------|---|--------|
| LQ590-RIBBON | 1-2186029-1 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| TMS-SYSTEM-SIX-RIBBON-A | 310347-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| TMS-LQ590-RIBBON | CC3130-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| TMS-SYSTEM-SIX-RIBBON-B | 264327-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| 1892BK04-RIBBON | D06106-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| 1892BK03-HIGH-PERF-RIBBON | A72722-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| 18910000-OKI380-RIBBON | 856832-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| 1330-0037-00 | 9-1198202-3 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |

Printer Information

Print quality and print performance can only be guaranteed when specific TE printer and ribbons are used.

The current list of printers and ribbons can be found in TE document 411-121005 'Identification Printer Product Ribbon Matrix'. This document can be found in 'Access Our Tools':

<http://www.te.com/usa-en/utilities/access-product-tools-and-resources.html>

Software

WINTOTAL and PrintEasy label printing software, available from the Identification Printer Software page:

<http://www.te.com/usa-en/products/identification-labeling/printers-software/printing-software.html?tab=pgp-story>

Contact a TE representative for further information

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2014 TE Connectivity Ltd. family of companies All Rights Reserved.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А