

# Thermal Measurement Report

DATE: 5/8/96  
revised 11/18/96

Package Description:      Package: 240 32 x 32 mm QFP  
Die Down  
Flag: 10.6 mm Square  
Leadframe: SIDN 1234625  
Die Attach: JMI 2500AN  
Mold Compound: Sumitomo 7304LC  
Assembled: ANAM  
Die: PST6 - 10.16 mm Square

Junction to Ambient Thermal Resistance or Theta JA ( $R_{\theta JA}$ ) was measured per SEMI Test Method G38-87 at 1.5 watts in a horizontal configuration. The test board conforms to EIA/JESD 51-3; it is a single layer 115x102 mm board designed to test 0.5 mm pitch QFP packages from 208 to 304 leads. The trace width is 0.24 mm, trace thickness is 0.076 mm. Sample size was 5.

| Convection | Theta JA<br>Average<br>°C/watt | Standard<br>Deviation<br>°C/watt | Theta JA<br>Ave + 3 Std. Dev.<br>°C/watt |
|------------|--------------------------------|----------------------------------|------------------------------------------|
| Natural    | 31.0                           | 0.08                             | 31.3                                     |
| 100 ft/min | 27.7                           | 0.18                             | 28.3                                     |
| 200        | 26.1                           | 0.1                              | 26.4                                     |
| 400        | 23.7                           | 0.34                             | 24.7                                     |
| 800        | 19.9                           | 0.11                             | 20.2                                     |

"Thermal resistance" from junction to a thermocouple on top center of case, previously titled Theta J-Ref ( $R_{\theta JR}$ ), was been renamed by the industry standard committee JEDEC JC15.1 as  $\Psi_{JT}$  and defined in EIA/JESD51-2. It is a useful value to use to estimate junction temperature in steady state customer environments.

| Convection | $\Psi_{JT}$<br>Average<br>°C/watt | Standard<br>Deviation<br>°C/watt |
|------------|-----------------------------------|----------------------------------|
| Natural    | 1.9                               | 0.09                             |
| 100 ft/min | 2.3                               | 0.06                             |
| 200        | 2.5                               | 0.04                             |
| 400        | 3.1                               | 0.08                             |
| 800        | 3.9                               | 0.1                              |

Junction to case thermal resistance,  $\Theta_{JC}$  ( $R_{\theta JC}$ ), was measured using the cold plate technique with the cold plate temperature used as the "case" temperature. The reference specifications are MIL-STD 883D, Method 1012.1 and SEMI G30-88. Sample size was 5.

| Theta JC<br>Average<br>°C/watt | Standard<br>Deviation<br>°C/watt | Theta JC<br>Ave + 3 Std. Dev.<br>°C/watt |
|--------------------------------|----------------------------------|------------------------------------------|
| 8.9                            | 0.07                             | 9.1                                      |

Junction to board thermal resistance  $\Theta_{JB}$  ( $R_{\theta JB}$ ) was measured using a cold plate technique with the cold plate in thermal contact with the bottom of the printed circuit board. The board temperature was measured with a thermocouple soldered to a center lead along one side of the package where the lead was soldered to the board. The measurement was taken using the 4 conductor layer printed circuit board described below. Sample size is 5.

| Theta JB<br>Average<br>°C/watt | Standard<br>Deviation<br>°C/watt | Theta JB<br>Ave + 3 Std. Dev.<br>°C/watt |
|--------------------------------|----------------------------------|------------------------------------------|
| 18.8                           | 0.19                             | 19.4                                     |

Junction to Ambient Thermal Resistance ( $\Theta_{JA}$ ) was also measured on a four layer test board. The test board was a 115x102 mm board designed to test 0.5 mm pitch QFP packages from 208 to 304 leads with two solid internal plane of 1 oz nominal thickness (0.033 mm thick). The trace pattern on the component side had a trace width of 0.231 mm, trace thickness of 0.0715 mm. Sample size was 5.

**Do Not Use this data without special footnote indicating that the results were measured on a board with two solid internal planes.**

| Convection | Theta JA<br>Average<br>°C/watt | Standard<br>Deviation<br>°C/watt | Theta JA<br>Ave + 3 Std. Dev.<br>°C/watt |
|------------|--------------------------------|----------------------------------|------------------------------------------|
| Natural    | 26.1                           | 0.11                             | 26.4                                     |
| 100 ft/min | 23.8                           | 0.13                             | 24.2                                     |
| 200        | 22.8                           | 0.13                             | 23.2                                     |
| 400        | 21.3                           | 0.19                             | 21.9                                     |
| 800        | 18.6                           | 0.16                             | 19.1                                     |

SEMI specifications are available from Semiconductor Equipment and Materials International at (415) 964-5111.

MIL-SPEC and EIA/JESD (JEDEC) specifications are available from Global Engineering Documents at 800-854-7179 or 303-397-7956.

|                     |        |              |              |
|---------------------|--------|--------------|--------------|
|                     | EMAIL  | Phone        | FAX          |
| From Bennett Joiner | RXMN60 | 512-933-7597 | 512-933-6344 |
| Ruth Reinhardt      | RBDT20 | 512-933-6407 | 512-933-6344 |

## Home Page:

[www.freescal.com](http://www.freescal.com)

## email:

[support@freescal.com](mailto:support@freescal.com)

## USA/Europe or Locations Not Listed:

Freescal Semiconductor  
Technical Information Center, CH370  
1300 N. Alma School Road  
Chandler, Arizona 85224  
(800) 521-6274  
480-768-2130

[support@freescal.com](mailto:support@freescal.com)

## Europe, Middle East, and Africa:

Freescal Halbleiter Deutschland GmbH  
Technical Information Center  
Schatzbogen 7  
81829 Muenchen, Germany  
+44 1296 380 456 (English)  
+46 8 52200080 (English)  
+49 89 92103 559 (German)  
+33 1 69 35 48 48 (French)  
[support@freescal.com](mailto:support@freescal.com)

## Japan:

Freescal Semiconductor Japan Ltd.  
Headquarters  
ARCO Tower 15F  
1-8-1, Shimo-Meguro, Meguro-ku  
Tokyo 153-0064, Japan  
0120 191014  
+81 2666 8080  
[support.japan@freescal.com](mailto:support.japan@freescal.com)

## Asia/Pacific:

Freescal Semiconductor Hong Kong Ltd.  
Technical Information Center  
2 Dai King Street  
Tai Po Industrial Estate,  
Tai Po, N.T., Hong Kong  
+800 2666 8080  
[support.asia@freescal.com](mailto:support.asia@freescal.com)

## For Literature Requests Only:

Freescal Semiconductor  
Literature Distribution Center  
P.O. Box 5405  
Denver, Colorado 80217  
(800) 441-2447  
303-675-2140  
Fax: 303-675-2150  
[LDCForFreescalSemiconductor@hibbertgroup.com](mailto:LDCForFreescalSemiconductor@hibbertgroup.com)

RoHS-compliant and/or Pb- free versions of Freescal products have the functionality and electrical characteristics of their non-RoHS-compliant and/or non-Pb- free counterparts. For further information, see <http://www.freescal.com> or contact your Freescal sales representative.

For information on Freescal.s Environmental Products program, go to <http://www.freescal.com/epp>.

Information in this document is provided solely to enable system and software implementers to use Freescal Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document. Freescal Semiconductor reserves the right to make changes without further notice to any products herein. Freescal Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescal Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Freescal Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Freescal Semiconductor does not convey any license under its patent rights nor the rights of others. Freescal Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescal Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescal Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescal Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescal Semiconductor was negligent regarding the design or manufacture of the part.



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А