

A

B

C

D

E

F

A


B

C


D

E

F



25Sx10P CONFIGURATION SHOWN
HOLD DOWN TYPE



25Sx10P CONFIGURATION SHOWN
SCREW MOUNT TYPE

NOTES:

1. HOUSING MATERIAL:GF LCP,COLOR: BLACK, UL 94 V-0 RATED
SIGNAL CONTACT MATERIAL: PHOSPHOR BRONZE
SIGNAL PIN OVERMOLD MATERIAL: GF POLYESTER
POWER CONTACT MATERIAL: COPPER ALLOY
2. PLATING ON SIGNAL CONTACTS: 1.27μm MIN Ni UNDERPLATING ALL OVER
WITH 0.76μm MIN GXT IN CONTACT MATING AREA, AND
0.5μm MIN MATTE TIN ON TAIL AREA.




PLATING ON POWER CONTACTS: 1.27μm MIN Ni UNDERPLATING ALL OVER
WITH 0.76μm MIN GXT IN CONTACT MATING AREA, AND
0.5μm MIN MATTE TIN ON TAIL AREA.

PLATING ON HOLD DOWN IF APPLICABLE: 1.27um MIN Ni, UNDERPLATING ALL
OVER WITH 0.76um MIN MATTE TIN OVER.
3. LUBRICATION: LUBRICATE ON CONTACT AREA.
4. RECOMMENDED PCB THICKNESS IS:
FOR PRESS FIT APPLICATION: 1.4mm MIN
FOR SOLDER APPLICATION: 1.40mm THROUGH 2.62mm.
5. FOR SCREW MOUNT APPLICATIONS, A #4-40 UNC PAN SCREW WITH HEX
NUT IS RECOMMENDED (SUPPLIED BY CUSTOMER).
6. FOR PRESS FIT $\varnothing 0.61\pm 0.05\text{mm}$, FOR SOLDER $\varnothing 0.90\pm 0.05\text{mm}$.
7. UNPLATED HOLES.
8. HOLD DOWN APPLICATION NEEDED.
9. SCREW MOUNT APPLICATION NEEDED.
10. PRODUCT SPECIFICATION: GS-12-1064
APPLICATION SPECIFICATION: GS-20-0362

Amphenol
FCI


© 2016 AFCI

spec ref		SEE NOTE 10			dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		1:1	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED			eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1					
ISO 406					chr		Fancy Zhang		2017/05/23						product family		PwrLoPro		rel level		Released	
ISO 1101					appr		Pei-Ming Zheng		2017/05/26													
surface		linear		0.X		±0.30		Amphenol FCI		title		PWR LoPro HEADER ASSEMBLY RA, PASSIVE GUIDE,S+P		dwg no		10122460		rev		H		
ISO 1302				0.XX		±0.20																
				0.XXX		±0.10																
		angular		0°		±2°				cat. no.		-		Product - Customer Drw				sheet 1 of 10				







SCREW MOUNT TYPE AS SHOWN

spec ref		SEE NOTE 10		dr	Zhang Hong-Tu	2012/08/13	projection	MM	size	A2	scale	3:1	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	De-Ming Lu	2017/05/09			ecn no	ELX-DG-18076-1			
ISO 406 ISO 1101				chr	Fancy Zhang	2017/05/23				rel level	Released		
				appr	Pei-Ming Zheng	2017/05/26	product family		PwrLoPro				
surface	linear	0.X	±0.30	Amphenol FCI	title	PWR LoPro HEADER ASSEMBLY				dwg no	10122460		rev
		0.XX	±0.20										
		0.XXX	±0.10										
ISO 1302	angular	0°	±2°		cat. no.	-	Product - Customer Drw				sheet 2 of 10		




10122460-002LF AS SHOWN
RECOMMENDED PRINTED CIRCUIT BOARD LAYOUT SEE NOTE 4
FOR 10122460-XXXLF SCREW MOUNT TYPE
(AS VIEWED FROM COMPONENT SIDE)

spec ref		SEE NOTE 10		dr		Zhang Hong-Tu		2012/08/13		projection  MM		size		A2		scale		3:1	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		De-Ming Lu		2017/05/09				ecn no		ELX-DG-18076-1		rel level		Released	
ISO 406				chr		Fancy Zhang		2017/05/23		product family		PwrLoPro							
ISO 1101				appr		Pei-Ming Zheng		2017/05/26											
surface  ISO 1302		linear		Amphenol FCi		title		PWR LoPro HEADER ASSEMBLY		dwg no		10122460		rev		H			
		0.X		±0.30															
		0.XX		±0.20															
		0.XXX		±0.10															
		angular		0°		±2°													
								cat. no.		-		Product - Customer Drw				sheet 3 of 10			




HOLE DOWN TYPE AS SHOWN

spec ref		SEE NOTE 10		dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		3:1									
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1											
ISO 406						chr		Fancy Zhang		2017/05/23																			
ISO 1101						appr		Pei-Ming Zheng		2017/05/26																			
						product family				PwrLoPro												rel level				Released			
surface		linear		0.X		±0.30		Amphenol FCI		title		PWR LoPro HEADER ASSEMBLY						dwg no		10122460						rev		H	
				0.XX		±0.20																							
				0.XXX		±0.10																							
ISO 1302		angular		0°		±2°				cat. no.		-		Product - Customer Drw						sheet 4 of 10									




10122460-003LF AS SHOWN
RECOMMENDED PRINTED CIRCUIT BOARD LAYOUT SEE NOTE 4
FOR 10122460-XXXLF HOLD DOWN TYPE
(AS VIEWED FROM COMPONENT SIDE)

spec ref	SEE NOTE 10			dr	Zhang Hong-Tu	2012/08/13	projection  MM	size	A2	scale	4:1
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	De-Ming Lu	2017/05/09		ecn no ELX-DG-18076-1			
ISO 406				chr	Fancy Zhang	2017/05/23					
ISO 1101				appr	Pei-Ming Zheng	2017/05/26			product family PwrLoPro		rel level Released
surface ISO 1302	linear ✓	0.X	±0.30	Amphenol FCI	title PWR LoPro HEADER ASSEMBLY RA, PASSIVE GUIDE,S+P	dwg no 10122460	rev H				
		0.XX	±0.20								
		0.XXX	±0.10								
	angular	0°	±2°					cat. no. -	Product - Customer Drw	sheet 5 of 10	

1		2		3		4		5		6		7		8	
A	PART NUMBER	CONFIGURATION	DIM "A"	DIM "B" FOR SCREW MOUNT	DIM "C" FOR HOLD DOWN	"D" SPACES	"E" SPACES	"F" QTY.	"G" QTY.	MOUNTING FEATURE					
	10122460-001LF	35S+18P	77.71	-	72.60	6	17	35	108	HOLD DOWN					
	10122460-003LF	25S+10P	51.71	-	46.6	4	9	25	60	HOLD DOWN					
	10122460-004LF	25S+8P	46.21	-	41.1	4	7	25	48	HOLD DOWN					
	10122460-005LF	25S+10P	51.71	-	46.6	4	9	25	60	HOLD DOWN					
	10122460-006LF	25S+8P	46.21	-	41.1	4	7	25	48	HOLD DOWN					
	10122460-007LF	25S+10P	51.71	47.31	-	4	9	25	60	SCREW MOUNT					
	10122460-008LF	15S+2P	25.71	-	15.1	2	1	15	12	HOLD DOWN					
	10122460-009LF	25S+10P	51.71	-	46.6	4	9	25	60	HOLD DOWN					
	10122460-010LF	35S+20P	83.21	-	78.1	6	19	35	120	HOLD DOWN					
	10122460-011LF	25S+02P	29.71	-	24.6	4	1	25	12	HOLD DOWN					
	10122460-013LF	25S+10P	51.71	47.31	-	4	9	25	60	SCREW MOUNT					
B															
C															
	D														
E															
	F														

Amphenol
FCi

© 2016 AFci

spec ref	SEE NOTE 10			dr	Zhang Hong-Tu	2012/08/13	projection  MM	size	A2	scale	3:1				
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	De-Ming Lu	2017/05/09		ecn no	ELX-DG-18076-1						
chr				Fancy Zhang	2017/05/23										
appr				Pei-Ming Zheng	2017/05/26										
surface	linear	0.X	±0.30	Amphenol FCi	title			PWR LoPro HEADER ASSEMBLY			dwg no	10122460		rev	H
ISO 1302		0.XX	±0.20												
		0.XXX	±0.10												
	angular	0°	±2°	cat. no.			-	Product - Customer Drw			sheet 6 of 10				

Creo File - REV E - 2016-02-12

1

2

3

4

5

PDS: Rev :H

STATUS:Released

Printed: May 26, 2017

CUSTOMER LOADING WORKSHEET FOR SIGNAL & POWER SEQUENCING LEVELS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
PWR LO PRO - MATING FACE OF HEADER CONNECTOR(4)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
E																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															</

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А