

A

B

C

D

E

F

A


B

C


D

E

F



25Sx10P CONFIGURATION SHOWN
HOLD DOWN TYPE



25Sx10P CONFIGURATION SHOWN
SCREW MOUNT TYPE

NOTES:

1. HOUSING MATERIAL:GF LCP,COLOR: BLACK, UL 94 V-0 RATED
SIGNAL CONTACT MATERIAL: PHOSPHOR BRONZE
SIGNAL PIN OVERMOLD MATERIAL: GF POLYESTER
POWER CONTACT MATERIAL: COPPER ALLOY
2. PLATING ON SIGNAL CONTACTS: 1.27µm MIN Ni UNDERPLATING ALL OVER
WITH 0.76µm MIN GXT IN CONTACT MATING AREA, AND
0.5µm MIN MATTE TIN ON TAIL AREA.


PLATING ON POWER CONTACTS: 1.27µm MIN Ni UNDERPLATING ALL OVER
WITH 0.76µm MIN GXT IN CONTACT MATING AREA, AND
0.5µm MIN MATTE TIN ON TAIL AREA.

PLATING ON HOLD DOWN IF APPLICABLE: 1.27um MIN Ni, UNDERPLATING ALL
OVER WITH 0.76um MIN MATTE TIN OVER.
3. LUBRICATION: LUBRICATE ON CONTACT AREA.
4. RECOMMENDED PCB THICKNESS IS:
FOR PRESS FIT APPLICATION: 1.4mm MIN
FOR SOLDER APPLICATION: 1.40mm THROUGH 2.62mm.
5. FOR SCREW MOUNT APPLICATIONS, A #4-40 UNC PAN SCREW WITH HEX
NUT IS RECOMMENDED (SUPPLIED BY CUSTOMER).
6. FOR PRESS FIT $\varnothing 0.61\pm 0.05\text{mm}$, FOR SOLDER $\varnothing 0.90\pm 0.05\text{mm}$.
7. UNPLATED HOLES.
8. HOLD DOWN APPLICATION NEEDED.
9. SCREW MOUNT APPLICATION NEEDED.
10. PRODUCT SPECIFICATION: GS-12-1064
APPLICATION SPECIFICATION: GS-20-0362

Amphenol
FCI


© 2016 AFCI

spec ref		SEE NOTE 10			dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		1:1	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED			eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1					
ISO 406					chr		Fancy Zhang		2017/05/23						product family		PwrLoPro		rel level		Released	
ISO 1101					appr		Pei-Ming Zheng		2017/05/26													
surface					linear		Amphenol FCI		title						PWR LoPro HEADER ASSEMBLY		dwg no		10122460		rev	
		0.X		±0.30																		
		0.XX		±0.20																		
		0.XXX		±0.10																		
ISO 1302		angular		0°		±2°		cat. no.		-		Product - Customer Drw		sheet 1 of 10								






Printed: May 26, 2017

spec ref		SEE NOTE 10		dr		Zhang Hong-Tu		2012/08/13		projection				MM				size		A2		scale		3:1			
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1		rel level		Released							
ISO 406				chr		Fancy Zhang		2017/05/23																			
ISO 1101				appr		Pei-Ming Zheng		2017/05/26						product family		PwLoPro											
surface - ISO 1302		linear		Amphenol FCi		title		PWR LoPro HEADER ASSEMBLY		dwg no		10122460		rev		H											
		0.X ±0.30																									
		0.XX ±0.20																									
		0.XXX ±0.10																									
		angular		0° ±2°		cat. no.		-		Product-		Customer Drw		sheet 2 of 10													




10122460-002LF AS SHOWN
RECOMMENDED PRINTED CIRCUIT BOARD LAYOUT SEE NOTE 4
FOR 10122460-XXXLF SCREW MOUNT TYPE
(AS VIEWED FROM COMPONENT SIDE)

spec ref	SEE NOTE 10		dr	Zhang Hong-Tu	2012/08/13	projection 	MM 	size	A2	scale	3:1			
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	De-Ming Lu	2017/05/09			ecn no	ELX-DG-18076-1					
ISO 406			chr	Fancy Zhang	2017/05/23			rel level	Released					
ISO 1101			appr	Pei-Ming Zheng	2017/05/26	product family		PwrLoPro						
surface		linear	0.X	±0.30	Amphenol FCi	title	PWR LoPro HEADER ASSEMBLY				dwg no	10122460	rev	H
			0.XX	±0.20										
			0.XXX	±0.10										
	ISO 1302	angular	0°	±2°			RA, PASSIVE GUIDE,S+P							
			cat. no.	-	Product - Customer Drw				sheet 3 of 10					




HOLE DOWN TYPE AS SHOWN

spec ref		SEE NOTE 10		dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		3:1																			
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1																					
ISO 406						chr		Fancy Zhang		2017/05/23																													
ISO 1101						appr		Pei-Ming Zheng		2017/05/26																													
										product family										PwrLoPro																			
																				rel level										Released									
surface		-		linear		0.X		±0.30		Amphenol FCI		title		PWR LoPro HEADER ASSEMBLY										dwg no		10122460										rev		H	
ISO 1302		0.XX				±0.20																																	
		0.XXX				±0.10																																	
		angular		0°		±2°						cat. no.		-		Product - Customer Drw										sheet 4 of 10													




spec ref	SEE NOTE 10		dr	Zhang Hong-Tu	2012/08/13		MM	size	A2	scale	4:1
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	De-Ming Lu	2017/05/09			ecn no	ELX-DG-18076-1		
ISO 406 ISO 1101			chr	Fancy Zhang	2017/05/23			product family	PwrLoPro		
ISO 1302			appr	Pei-Ming Zheng	2017/05/26			rel level	Released		
surface	linear	0.X	±0.30		PWR LoPro HEADER ASSEMBLY RA, PASSIVE GUIDE,S+P			dwg no 10122460	rev H		
		0.XX	±0.20								
		0.XXX	±0.10								
	angular	0°	±2°	cat. no.		-	Product-	Customer Drw	sheet 5 of 10		


Printed: May 26, 2017

CUSTOMER LOADING WORKSHEET FOR SIGNAL & POWER SEQUENCING LEVELS																																										
PWR LO PRO - MATING FACE OF HEADER CONNECTOR(4)																																										
E										COLUMNS																																
D																																										
C																																										
B																																										
A																																										
ROWS	MOUNTING FEATURE (3)	1	2	3	4	5	6	7	8		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	MOUNTING FEATURE (3)							
		SIGNAL CONTACTS(2)								POWER CONTACTS(1)																																


- 1). LOAD WITH CHOICE OF 2 POWER CONTACT MATING LEVELS, SEE SECTIONS KM & KR FOR AVAILABLE LEVEL OPTIONS.
- 2). LOAD WITH CHOICE OF 3 SIGNAL CONTACT MATING LEVELS, SEE SECTIONS KA,KB,&KC FOR AVAILABLE LEVEL OPTIONS.
- 3). MOUNTING FEATURE OPTION "X"
- H : HOLD DOWN TYPE
- S : SCREW MOUNT TYPE
- 4). CUSTOMER LOADING WORKSHEET SHOWN AT MAXMUM SIZE CONFIGURATION (40Sx24P), SIGNALS AVAILABLE IN 2,3,4 THRU 8 POSITIONS, POWERS AVAILABLE IN 4,6,8 THRU 24 POSITIONS IN EVEN QUANTITIES ONLY.




POWER
SECTION KM-KM
LEVEL 1:
LONGEST MATING
CONTACTS




POWER
SECTION KR-KR
LEVEL 2:
SHORTEST MATING
CONTACTS




SIGNAL
SECTION KA-KA
LEVEL 2:
ALL LONGEST
CONTACTS



SIGNAL
SECTION KB-KB
LEVEL 32222 (MIXED):
ROW "A", SHORTEST CONTACT
ROW "B" THRU "E", LONGEST CONTACTS



SIGNAL
SECTION KC-KC
LEVEL 3:
ALL SHORTEST
CONTACTS

spec ref		SEE NOTE 10			dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		1:1	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED			eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1					
ISO 406					chr		Fancy Zhang		2017/05/23						rel level		Released					
ISO 1101					appr		Pei-Ming Zheng		2017/05/26						product family		PwrLoPro					
surface		linear		0.X		±0.30		Amphenol FCI		title		PWR LoPro HEADER ASSEMBLY		dwg no		10122460		rev		H		
ISO 1302				0.XX		±0.20																
				0.XXX		±0.10																
		angular		0°		±2°		cat. no.		-		Product - Customer Drw				sheet 7 of 10						

1		2				3				4				5				6				7				8			
A	PART NUMBER	ROWS		SIGNALS							POWERS																		
				1	2	3	4	5	6	7	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	
	10122460-001LF 35S + 18P	E	H																										
		D																											
		C																											
		B																											
A			3	3																									
B	PART NUMBER	ROWS		SIGNALS					POWERS																				
				1	2	3	4	5	1	2	3	4	5	6	7	8	9	10											
	10122460-003LF 25S + 10P	E	H																										
		D																											
		C																											
		B																											
A			2	2																									32222
C	PART NUMBER	ROWS		SIGNALS					POWERS																				
				1	2	3	4	5	1	2	3	4	5	6	7	8													
	10122460-004LF 25S + 8P	E	H																										
		D																											
		C																											
		B																											
A			2	2																									32222
D	PART NUMBER	ROWS		SIGNALS					POWERS																				
				1	2	3	4	5	1	2	3	4	5	6	7	8													
	10122460-005LF 25S + 10P	E	H																										
		D																											
		C																											
		B																											
A			2	2																									2
E	PART NUMBER	ROWS		SIGNALS					POWERS																				
				1	2	3	4	5	1	2	3	4	5	6	7	8	9	10											
	10122460-005LF 25S + 10P	E	H																										
		D																											
		C																											
		B																											
A			2	2																									2
F	PART NUMBER	ROWS		SIGNALS					POWERS																				
				1	2	3	4	5	1	2	3	4	5	6	7	8	9	10											
	10122460-005LF 25S + 10P	E	H																										
		D																											
		C																											
		B																											
A			2	2																									2
VIEWED FROM MATING FACE:																													
</																													

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А