

A

B

C

D

E

F

A


B

C


D

E

F



25Sx10P CONFIGURATION SHOWN
HOLD DOWN TYPE



25Sx10P CONFIGURATION SHOWN
SCREW MOUNT TYPE

NOTES:

- 1. HOUSING MATERIAL:GF LCP,COLOR: BLACK, UL 94 V-0 RATED
SIGNAL CONTACT MATERIAL: PHOSPHOR BRONZE
SIGNAL PIN OVERMOLD MATERIAL: GF POLYESTER
POWER CONTACT MATERIAL: COPPER ALLOY
- 2. PLATING ON SIGNAL CONTACTS: 1.27µm MIN Ni UNDERPLATING ALL OVER WITH 0.76µm MIN GXT IN CONTACT MATING AREA, AND 0.5µm MIN MATTE TIN ON TAIL AREA.




PLATING ON POWER CONTACTS: 1.27µm MIN Ni UNDERPLATING ALL OVER WITH 0.76µm MIN GXT IN CONTACT MATING AREA, AND 0.5µm MIN MATTE TIN ON TAIL AREA.

PLATING ON HOLD DOWN IF APPLICABLE: 1.27um MIN Ni, UNDERPLATING ALL OVER WITH 0.76um MIN MATTE TIN OVER.
- 3. LUBRICATION: LUBRICATE ON CONTACT AREA.
- 4. RECOMMENDED PCB THICKNESS IS:
FOR PRESS FIT APPLICATION: 1.4mm MIN
FOR SOLDER APPLICATION: 1.40mm THROUGH 2.62mm.
- 5. FOR SCREW MOUNT APPLICATIONS, A #4-40 UNC PAN SCREW WITH HEX NUT IS RECOMMENDED (SUPPLIED BY CUSTOMER).
- 6. FOR PRESS FIT Ø0.61±0.05mm, FOR SOLDER Ø0.90±0.05mm.
- 7. UNPLATED HOLES.
- 8. HOLD DOWN APPLICATION NEEDED.
- 9. SCREW MOUNT APPLICATION NEEDED.
- 10. PRODUCT SPECIFICATION: GS-12-1064
APPLICATION SPECIFICATION: GS-20-0362

Amphenol
FCi


© 2016 AFCi

spec ref		SEE NOTE 10			dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		1:1																
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED			eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1																				
ISO 406					chr		Fancy Zhang		2017/05/23						rel level		Released																				
ISO 1101					appr		Pei-Ming Zheng		2017/05/26																												
										product family										PwrLoPro																	
surface		linear		0.X		±0.30		Amphenol FCi		title		PWR LoPro HEADER ASSEMBLY RA, PASSIVE GUIDE,S+P										dwg no		10122460										rev		H	
				0.XX		±0.20																															
				0.XXX		±0.10																															
		ISO 1302		angular		0°																															







SCREW MOUNT TYPE AS SHOWN

spec ref		SEE NOTE 10		dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		3:1			
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1							
ISO 406				chr		Fancy Zhang		2017/05/23						rel level		Released							
ISO 1101				appr		Pei-Ming Zheng		2017/05/26						product family		PwrLoPro							
surface		linear		0.X		±0.30		Amphenol FCi		title		PWR LoPro HEADER ASSEMBLY		dwg no		10122460		rev		H			
ISO 1302				0.XX		±0.20																RA, PASSIVE GUIDE,S+P	
		angular		0°		±2°																	
										cat. no.		-		Product - Customer Drw		sheet 2 of 10							




10122460-002LF AS SHOWN
RECOMMENDED PRINTED CIRCUIT BOARD LAYOUT SEE NOTE 4
FOR 10122460-XXXLF SCREW MOUNT TYPE
(AS VIEWED FROM COMPONENT SIDE)


spec ref		SEE NOTE 10		dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		3:1			
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1							
ISO 406				chr		Fancy Zhang		2017/05/23						rel level		Released							
ISO 1101				appr		Pei-Ming Zheng		2017/05/26						product family		PwrLoPro							
surface		linear		Amphenol FCi		title		PWR LoPro HEADER ASSEMBLY		dwg no		10122460		rev		H							
		0.X																±0.30					
		0.XX																±0.20					



HOLE DOWN TYPE AS SHOWN


spec ref		SEE NOTE 10		dr		Zhang Hong-Tu		2012/08/13		projection		MM		size		A2		scale		3:1																							
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng		De-Ming Lu		2017/05/09						ecn no		ELX-DG-18076-1																									
ISO 406						chr		Fancy Zhang		2017/05/23																																	
ISO 1101						appr		Pei-Ming Zheng		2017/05/26																																	
										product family										PwrLoPro																							
																				rel level										Released													
surface		-		linear		0.X		±0.30		Amphenol FCI		title		PWR LoPro HEADER ASSEMBLY										dwg no		10122460										rev		H					
ISO 1302		0.XX				±0.20																																					
		0.XXX				±0.10																																					
angular		0°		±2°										cat. no.		-		Product - Customer Drw										sheet 4 of 10															




spec ref		SEE NOTE 10		dr		Zhang Hong-Tu		2012/08/13		projection				size		A2		scale		4:1	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		De-Ming Lu		2017/05/09				ecn no		ELX-DG-18076-1		rel level Released		rev H			
ISO 406				chr		Fancy Zhang		2017/05/23				product family		PwLoPro							
ISO 1101				appr		Pei-Ming Zheng		2017/05/26													
surface		linear		Amphenol FCI		title PWR LoPro HEADER ASSEMBLY RA, PASSIVE GUIDE,S+P		dwg no 10122460		cat. no. -		Product- Customer Drw		sheet 5 of 10							
		0.X ±0.30																			
		0.XX ±0.20																			
		0.XXX ±0.10																			
ISO 1302		angular		0° ±2°																	

CUSTOMER LOADING WORKSHEET FOR SIGNAL & POWER SEQUENCING LEVELS																																					
PWR LO PRO - MATING FACE OF HEADER CONNECTOR(4)																																					
E										COLUMNS																											
D																																					
C																																					
B																																					
A																																					
ROWS	MOUNTING FEATURE (3)	1	2	3	4	5	6	7	8		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	MOUNTING FEATURE (3)		
		SIGNAL CONTACTS(2)								POWER CONTACTS(1)																											


- 1). LOAD WITH CHOICE OF 2 POWER CONTACT MATING LEVELS, SEE SECTIONS KM & KR FOR AVAILABLE LEVEL OPTIONS.
- 2). LOAD WITH CHOICE OF 3 SIGNAL CONTACT MATING LEVELS, SEE SECTIONS KA,KB,&KC FOR AVAILABLE LEVEL OPTIONS.
- 3). MOUNTING FEATURE OPTION "X"
- H : HOLD DOWN TYPE
- S : SCREW MOUNT TYPE
- 4). CUSTOMER LOADING WORKSHEET SHOWN AT MAXMUM SIZE CONFIGURATION (40Sx24P), SIGNALS AVAILABLE IN 2,3,4 THRU 8 POSITIONS, POWERS AVAILABLE IN 4,6,8 THRU 24 POSITIONS IN EVEN QUANTITIES ONLY.




POWER
SECTION KM-KM
LEVEL 1:
LONGEST MATING
CONTACTS




POWER
SECTION KR-KR
LEVEL 2:
SHORTEST MATING
CONTACTS




SIGNAL
SECTION KA-KA
LEVEL 2:
ALL LONGEST
CONTACTS



SIGNAL
SECTION KB-KB
LEVEL 32222 (MIXED):
ROW "A", SHORTEST CONTACT
ROW "B" THRU "E", LONGEST CONTACTS



SIGNAL
SECTION KC-KC
LEVEL 3:
ALL SHORTEST
CONTACTS

spec ref	SEE NOTE 10			dr	Zhang Hong-Tu	2012/08/13			size	A2	scale	1:1	
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	De-Ming Lu	2017/05/09			ecn no	ELX-DG-18076-1			
ISO 406				chr	Fancy Zhang	2017/05/23	product family	PwrLoPro	rel level	Released			
ISO 1101				appr	Pei-Ming Zheng	2017/05/26							
surface	linear	0.X	±0.30		title	PWR LoPro HEADER ASSEMBLY RA, PASSIVE GUIDE,S+P			dwg no	10122460		rev	H
		0.XX	±0.20										
		0.XXX	±0.10										
ISO 1302	angular	0°	±2°		cat. no.	-	Product - Customer Drw				sheet 7 of 10		

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А